Fused connection units continued

13A unswitched with flex outlet

	I.	-	
	,		
GN	1C13	SPF	

Product code	Description	Pack qty
GMC13SPF	Grey	10
GMCS13SPF	Silver Grey	10

13A DP unswitched with neon & flex outlet



Product code	Description	Pack qty
GMC13SPNF	Grey	10
GMCS13SPNF	Silver Grey	10

13A double-pole switched

	Product code	Description	Pack qty
e1 e	GMC13SSP	Grey	10
	GMCS13SSP	Silver Grey	10
GMC13SSP			

13A double-pole switched with neon

1	Product code	Description	Pack qty
	GMC13SSPN	Grey	10
	GMCS13SSPN	Silver Grey	10

GMC13SSPN

GMC13SSPF

13A double-pole switched with flex outlet

Product code	Description	Pack qty
GMC13SSPF	Grey	10
GMCS13SSPF	Silver Grey	10

13A double-pole switched with neon & flex outlet

Ĩ	Product code	Description	Pack qty
	GMC13SSPNF	Grey	10
	GMCS13SSPNF	Silver Grey	10

Double-pole 30mA RCD protected - passive control



GMC13SSPNF

Product code	Description	Pack qty
GMCPRCDFCU	Grey	1

GMCPRCDFCU

- Standard of compliance: BS 1363
- Mounting box: 47mm deep (back box supplied)
- Plate dimensions: 79 x 79 x 42mm
- Technical notes: Active control consists of an electronic latch, which will require resetting in the event of a loss of supply. Particularly useful for domestic use.
- Passive control device will only trip in the event of a fault. Suitable for freezers and commercial applications.