

ARGUS Presence Detector system

ARGUS Presence Detector system

Product Code	MTN55101119	MTN55101219	
Description	Presence Master with IR, relay 1-gang	Presence Master with IR, relay 2-gang	
Nominal voltage	AC 220/230V, 50/60Hz	AC 220/230V, 50/60Hz	
Nominal current	max. 10AX, $\cos\varphi = 0.6$	Max. 10AX, $\cos\varphi = 0.6$. The total load on both channels is not allowed to exceed 14A	
Control current	-	-	
Type	-	-	
Load type	-	-	
Outputs	1 x make contacts	2 x make contacts	
Max. switching capacity per channel:			
Incandescent lamps	2200W	2200W	
HV halogen lamps	2000W	2000W	
LV halogen lamps with wound transformer	500VA	500VA	
Electronic transformers	1050W	1050W	
Capacitive load	10A, 140 μ F	10A, 140 μ F	
Energy-saving lamps	100VA	100VA	
Motor load	1000VA	1000VA	
Neutral conductor	Required (3 conductor system)	Required (3 conductor system)	
Cable capacity	max. 2x2.5mm ²	max. 2x2.5mm ²	
Angle of detection	360°	360°	
Number of levels	6	6	
Number of zones	136	136	
Number of movement sensors	4	4	
Recommended installation height	2.5m	2.5m	
Range	A radius of max. 7m (at an installation height of 2.5m)	A radius of max. 7m (at an installation height of 2.5m)	
Sensitivity	Continuously adjustable	Continuously adjustable	
Brightness threshold	Continuously adjustable between approx. 10 and 1000 lux	Continuously adjustable between approx. 10 and 1000 lux	
Overshoot time	Channel 1: continuously adjustable between approx. 10s and approx. 30min	Channel 1: continuously adjustable between approx. 10s and approx. 30min	
		Channel 2: continuously adjustable between approx. 5min and approx. 2h	
Slave	ARGUS Presence Slave MTN55701019	ARGUS Presence Slave MTN55701019	

ARGUS Presence Detector system

MTN55101419	MTN55101519	MTN55701019
Presence Master with IR, 1-10V	Ultimate Screwless	Presence Slave
AC 220/230V, 50/60Hz	230V 50Hz	AC 220/230V, 50/60Hz
max. 10AX, $\cos\varphi = 0.6$	90°	-
max. 50mA	5m at 1.2m height	-
-	Wall (flush)	-
max. 25 controllable EBs (1-10V)	Single	-
1 x make contact, 1 x (1-10V)	X	4 x PlusLink
2200W	-	-
2000W	-	-
500VA	-	-
1050W	-	-
10A, 140 μ F	-	-
-	-	-
-	-	-
Required (3 conductor system)	Required (3 conductor system)	Required (3 conductor system)
max. 2x2.5mm ²	max. 2x2.5mm ²	max. 2x2.5mm ²
360°	360°	360°
6	6	6
136	136	136
4	4	4
2.5m	2.5m	2.5m
A radius of max. 7m (at an installation height of 2.5m)	A radius of max. 7m (at an installation height of 2.5m)	A radius of max. 7m (at an installation height of 2.5m)
Continuously adjustable	Continuously adjustable	Continuously adjustable
Continuously adjustable between approx. 10 and 1000 lux	Continuously adjustable between approx. 10 and 1000 lux	-
Channel 1: continuously adjustable between approx. 10s and approx. 30min	Channel 1: continuously adjustable between approx. 10s and approx. 30min	Channel 1: continuously adjustable between approx. 10s and approx. 30min
ARGUS Presence Slave MTN55701019	ARGUS Presence Slave MTN55701019	-