


## PMA FIXPlus fittings with NPT threads

### Type UNV-N-UL & UAV-N-UL

#### Type UNV-N-UL - Connector straight, NPT thread


	Order no. black	Order no. grey	Thread size NPT	Fits to conduit size NW	Thread length (mm)	Outside Ø (mm)	Overall length (mm)
	BUNV-N027-UL	SUNV-N027-UL	½"	17	13.0	29.5	49.5
	BUNV-N043-UL	SUNV-N043-UL	¾"	23	14.0	37.0	54.0
	BUNV-N069-UL	SUNV-N069-UL	1"	29	15.0	44.0	56.0
	BUNV-N076-UL	SUNV-N076-UL	1¼"	36	18.0	55.0	71.0
	BUNV-N088-UL	SUNV-N088-UL	1½"	48	18.0	69.0	71.5
	BUNV-N098-UL	SUNV-N098-UL	2"	48	18.0	69.0	71.5

#### Approvals



Extremely high impact resistance  
 Vibration-resistant connection to PMA FLEXPlus conduits  
 Easy installation  
 High conduit pull-out strength  
 Very good chemical properties  
 Free from halogens and cadmium  
 Fits conduit profile coarse (G)  
 Lock nuts available on request

#### Type UAV-N-UL - Connector 45° elbow, metric thread

	Order no. black	Order no. grey	Thread size NPT	Fits to conduit size NW	Thread length (mm)	Outside Ø (mm)	Overall length (mm)	Overall height (mm)
	BUAV-N027-UL	SUAV-N027-UL	½"	17	13.0	29.5	57.5	51.5
	BUAV-N043-UL	SUAV-N043-UL	¾"	23	14.0	37.0	67.0	60.0
	BUAV-N069-UL	SUAV-N069-UL	1"	29	15.0	44.0	73.5	67.0
	BUAV-N076-UL	SUAV-N076-UL	1¼"	36	18.0	53.5	91.5	85.5
	BUAV-N088-UL	SUAV-N088-UL	1½"	36	18.0	66.0	99.0	96.0
	BUAV-N098-UL	SUAV-N097-UL	2"	48	18.0	66.0	99.0	101.0

#### Approvals



Extremely high impact resistance  
 Vibration-resistant connection to PMA FLEXPlus conduits  
 Easy installation  
 High conduit pull-out strength  
 Very good chemical properties  
 Free from halogens and cadmium  
 Fits conduit profile coarse (G)  
 Lock nuts available on request