THE BIG UNITRUNK

Product Guide V4



RECORD BREAKING INSTALLATIONS...

UNITRUNK

WELCOME TO YOUR UNITRUNK PRODUCT GUIDE

You've got more choice than ever before and remember, if you need a bespoke product, just give us a call.

Rapid Installation Systems (RIS)	04
Extreme Cable Management Division	12
Quality standards	18
Training & CPD	20
Working with you	22
How to order	24
Finishes	25
Contact us	162

HANDY

Easy to use Product tab system

SECTION 1 - 26
Standard Trunking Systems
Standard Trunking

SECTION 2 - 34
Multi-Compartment Trunking Systems
Multi Compartment Trunking

SECTION 3 - 46
Lighting Trunking Systems
Lighting Trunking

SECTION 4 - 52
Uniklip Cable Tray Systems
Rapid installation system
Uniklip

SECTION 4 - 68
Cable Tray Systems
Cable Tray

SECTION 5 - 82
Speedway Cable Ladder Systems
Speedway Cable Ladder

SECTION 6 - 92
Cable Basket Systems
Cable Basket Systems

SECTION 7 - 104
Channel & Support Systems
Channel & Support

SECTION 8 - 114
Floor Trunking Systems
Floor Trunking

SECTION 9 - 132
Bench Outlet Boxes & Perimeter Trunking
Bench Outlet & Perimeter Trunking

SECTION 10 - 142
Steel Conduit (Class 4)
Steel Conduit (Class 4)

SECTION 11 - 146
Innovative Design Solutions
Innovative Design Solutions

SECTION 12 - 154
Accessories & Supports
Accessories & Supports

Index - 158
Index

UNITRUNK RAPID INSTALLATION SYSTEMS



SAVE TIME AND MONEY WITH UNITRUNK RIS

You can slash the cost and time of installation by looking for our RIS logo. RIS, or Rapid Installation Systems, are designed by Unitrunk to make your life easier. The fast-fitting products let you complete jobs quicker than ever before.

You'll save time on installation, you'll save money on labour costs, and you'll be ready to start your next job well ahead of schedule. And you'll never have to worry about quality – RIS products are engineered to the same exceptional standards as all Unitrunk products.

UNIKLIP®

Forget about the fuss of conventional equipment. You don't need to worry about tools, cutting or filing with our new snap in-and-secure cable tray system.

EASYCONNECT

You can rely on our new EasyConnect cable basket to give you choice, speed and versatility.

UNITRUNK SPEEDLOK QUICKFIT CABLE LADDER

Add extra strength and durability to your ladder installation, while getting rid of joint-hinging and excess couplers.




Look out for the RIS mark on our products

INTRODUCING TWO NEW PRODUCTS TO OUR EXPANDING RANGE:

TRAY TO CHANNEL KLIP

Ref. CHTR25 – KLMR tray Klip to Channel
Ref. CHTR50 – KLHR tray Klip to Channel




This innovative RIS Klip secures the tray onto any channel i.e. UC4121, UC4141 & Channel Cantilever Arms. The klip works best with Unitrunks' Intelok Channel, as the serration on the return flange provides maximum slip resistance under a side load/impact.

Simply slide the klip onto the channel and snap it over the return flange of the tray; this removes fiddly spring nuts and bolts, saving the contractor precious installation time.

NEW!

EASYCONNECT BASKET KLIP

Ref. UFC41M - Basket Klip to Channel



This simple and innovative RIS klip similar to Unitrunks' CHTR klip will secure the basket onto any channel. UC4121, UC4141 & Channel Cantilever Arms. This klip works best with Unitrunks' Intelok Channel, as the serration on the return flange provides maximum slip resistance under a side load/impact.

Removing the need for a hold down plate, spring nuts and bolts, the klip is simple to fit; slot it in over the bar on the basket and using a star head screwdriver simply turn the klip through 90° to secure.

A UNITRUNK INNOVATION

UNIKLIP®

THE PATENTED REVOLUTIONARY KLIP SYSTEM FOR CABLE TRAY

When using conventional systems, installers had to cut, screw and tighten components at every stage of a job. The systems could be awkward and cumbersome, slowing installers down and dragging out installation time. But now it's different.

Uniklip slashes installation time and saves money by being quick, practical and versatile. Installers already love it, they're racing ahead of their competition by finishing jobs three-times faster than normal and saving up to 50% on overall costs.

ADVANTAGES

- 3 TIMES FASTER THAN STANDARD TRAY SYSTEMS
- SAVE TIME AND MONEY
- LOAD TESTED TO BS EN 61537 STANDARDS


CE

bsi. ISO 9001 Quality Management

3X FASTER THAN YOUR STANDARD INSTALLATION

Uniklip's patented snap and secure system makes cable tray so quick and easy to install. You can adjust and secure each section without the need for measuring or cutting. You just snap it securely into place wherever you need it. And it's as strong and reliable as any system.

The future of cable tray installation has changed – now every job can be completed for less and well ahead of schedule. Can you afford to be left behind?



UNITRUNK RIS

UK PATENTED: UK Patent number: GB2476569,
IRELAND PATENT PENDING: application number:2010/0795

DISCOVER WHAT 3X FASTER LOOKS LIKE

UNIKLIP Cheetah Challenge

3X FASTER

THAN YOUR STANDARD INSTALLATION

Discover what happened when Uniklip faced the ultimate test. Two independent teams race to install cable tray, one team using Uniklip, the other using a standard system.

Both teams have two professional installers and both courses are identical (we even threw in some obstacles to push each team to the limit). Everyone was astounded by the results...

visit: **unitrunk.co.uk** to watch Uniklip vs. a standard system in the Cheetah Challenge



“Unitrunk’s new Uniklip Cable Tray System delivered the labour savings it promised, with installation cost at the site reduced by up to 50%. The new system is extremely easy to use and very quick to install.”

Clive Wass, Contracts Supervisor,
BP Electrical Solutions



VANTRUNK



WELCOME TO OUR EXTREME CABLE MANAGEMENT DIVISION

Unitrunk's specialist division Vantrunk is internationally renowned for its extreme cable management products and associated support systems. Its trusted and innovative solutions have been serving the Global Energy, Oil and Gas and Industrial Processing sector for nearly 50 years with cable management systems designed to thrive in extreme environments.

Visit the Vantrunk website to explore our full range of extreme cable mangemnt solutions.

vantrunk.com



VANTRUNK

THRIVING IN EXTREME ENVIRONMENTS

Vantrunk were the first company in the United Kingdom to manufacture and supply cable ladder products and nearly 50 years later we continue to Thrive in Extreme Environments.

Environments such as the North Sea, the Middle East, Kazakhstan, Australia and Brazil's pre-salt fields, where Vantrunk has been selected to supply its cable management and supports systems. Further applications have been in the Petrochemical and Liquefied Natural Gas Industries as an authority on Cable Management in Extreme Environments including the recent Singapore Parallel Trains major LNG installation.

Given the nature of these critical requirements, our team not only supplies but, as an authority in the "extreme environment" consults with the main engineering houses regarding suitable materials and technical design choice that will meet their needs. Since becoming part of the Unitrunk Group in July 2000 and benefiting from Unitrunk's 9300m2 manufacturing facility in Lisburn, Northern Ireland we have continued to 'lead the charge'.

Quality, innovation and a desire to deliver market leading cable management solutions is at the core of our business whilst excellent service is at the heart of our team.

VANTRUNK SPEEDLOK QUICKFIT CABLE LADDER

Quick Assembly Cable Ladder

VANTRUNK FLEXIBLE FS SOLUTIONS

Flexible Solutions

VANTRUNK VXS

Extreme Steel

+50 VANTRUNK -50

Extreme Temperature



VANTRUNK



GLOBAL EXPERTISE

We are commited to adding value with the highest levels of service and support along with an innovative range of standard and bespoke cable management solutions.

Operators, engineers and design houses want to deal with companies that understand the challenge of operating in a global marketplace from consolidating and shipping vast quantities of materials around the world to providing information to product inspectors and having the know how to complete the detailed documents required to support international shipments.

Thanks to our worldwide network of partners in key strategic locations including Brazil, Denmark, Qatar, USA, Singapore, Kazakhstan, Azerbaijan, Dubai, Oman, the Netherlands and Australia, we deliver proven cable management solutions designed to ‘thrive in extreme environments’, on time to major projects located around the world.



QUALITY COMES AS STANDARD

We work hard to make sure our entire range is safe, reliable and manufactured to exceed all relevant quality standard.

We are also delighted to have our **Rail Industry Link-Up** application approved and our certificate awarded (Supplier no. 22992).

British Standards

Ref: Pre-galvanised steel
BS EN 10346: 2009

Ref: Cable trunking and ducting systems
BS EN 50085-1: 2005
BS EN 50085-2-1: 2006

Ref: Under floor flush floor or on floor
BS EN 50085-2-2: 2008

Ref: Cable tray, cable ladder and cable basket
BS EN 61537: 2007

Ref: Stainless steel material
BS EN 10088-2: 2005

Ref: Post galvanised products
BS EN ISO 1461: 2009

Ref: CR4 material
BS EN 10130: 2006

Ref: Weatherproof trunking
BS EN 60529: 1992

Easyway flush floor trunking has been tested in accordance with
BS6399 PART 1: 1996
(public occupancy class)

Unitrunk is an established quality manufacturer of steel cable management systems with 50 years experience and expertise. Our 70,000 sq.ft. production facility, along with the 124,000 sq.ft. manufacturing facility of sister company Vantrunk, are totally dedicated to the manufacture of cable management and support systems with both facilities ISO accredited.

RECOGNITION OF OUR QUALITY

BSI British Standards

bsi. ISO 9001 Quality Management

QUALITY MARKS: PRODUCTS & MATERIALS

CE

Applies to our Wire Basket range

UL E90 LEAD FREE RoHS COMPLIANT

ACCREDITATIONS

CPD CERTIFIED Construction CPD Certification Service
Membership No. 1230

Accreditated to LUL Standards:
Channel and Support Systems
Cable Basket Tray
Cable Ladder
Lighting Trunking
Standard and Multi Compartment Trunking

Link-up empowered by Achilles Registered
APPROVED & CERTIFICATED SINCE 2008

beama

EDA ELECTRICAL DISTRIBUTORS ASSOCIATION
AFFILIATED MANUFACTURER



UNITRUNK



TRAINING
& DEVELOPMENT

Unitrunk is committed to product training and developing product awareness. We don't assume that our customers will appreciate all the benefits the products offer, but we see it as our duty to make sure they do.

Our CPD accredited presentation includes unique visual evidence to show that Unitrunk products offer levels of performance which can provide significant commercial and technical benefits.

Whether presenting the benefits of the products to engineers in the form of a CPD seminar or demonstrating the safe method of cutting and forming cable basket to site operatives - Unitrunk deliver on our commitment.

> **Unitrunk take a thoroughly professional approach to industry education and best practices because we take our training as seriously as our manufacturing.**

CPD CERTIFIED
Construction CPD Certification Service
Membership No. 1230

unitrunk.co.uk/training



UNITRUNK

WORKING WITH YOU...

We could be with you in 3 hours by road, 30 seconds by phone or 1 click online

You're never far away from Unitrunk, so you can always pop in to your nearest depot or we'll deliver to your site. Thanks to our huge delivery network and with our many distribution partners worldwide and several depots across the UK and Ireland, we have an unbeatable delivery service that reaches every part of the globe.

* In accordance with stock availability.
** Standard delivery terms are 48 hours from receipt of order.

Unitrunk are a trusted and valued supplier delivering a great service with fast turnaround

Eddie Quirke, Senior Branch Manager,
Wilts Wholesale, Bristol



ORDERING

CODE SYSTEM EXPLAINED

STEP 1: CHOOSE FINISH

(Please Note) This is only required if the product is NOT pre-galvanised. Choose from the range of finishes available for your product.

STEP 2: CHOOSE PRODUCT

Choose the product and note the 'code prefix'.
(for example in the standard trunking section: Gusset Bend Top Lid = GTB)

STEP 3: CHOOSE SIZE

Choose the size of product you want and note the corresponding 'size code' from the Code Guide at the rear of each section.
(for example: if the product is 50mm x 50mm the size code = 22)

STEP 4: CHOOSE COMPARTMENTS

Choose the number of compartments required; check in the Code Guide if it's available and add this to your code.
(for example: if you require 2 compartments add x2)

PLEASE NOTE: As it is our policy to improve the design of Unitrunk products, goods supplied may vary in detail from those described or illustrated in this catalogue.

AVAILABLE PRODUCT FINISHES

- **PG** — Pre-Galvanised
- **GA** — Galvanised After (Hot Dipped Galvanised)
- **PC** — Powder Coated
- **EZ** — Electro Zinc
- **GX** — Galvanised After Manufacture Corten A Steel
- **SS** — Stainless Steel 316
- **ST** — Stainless Steel 304

HANDY



You can also view our complete product range online at

unitrunk.co.uk

UNITRUNK

Total Cable Management Solutions

SECTION 1

STANDARD TRUNKING SYSTEMS

Unitrunk Cable Trunking is a complete range of trunking and fittings manufactured to standards as described in BS EN 50085-1:2005 and is manufactured throughout in best quality hot dipped galvanised sheet steel to BS EN 10346:2009 giving maximum protection from corrosion. Standard Cable Trunking is manufactured and stocked in 3 metre lengths (other lengths available on request please refer to our code guide at the back of this section).

- The Trunking has machine formed inturned, strengthening flanges.
- The lid incorporates a quick action metal locking device operated by a slotted stud. The slot indicates the position of the locking bar. - (Note lid is secured using turnbuckle type fastener)
- Each length of Standard Trunking is supplied complete with lid, Coupling, Screws and Nuts.
- Fittings are manufactured from galvanised sheet steel to match the Trunking.
- Bends, Elbows, Tees and Intersection Boxes are complete with integral couplings.
- Special fittings such as OffSets, Risers, Unequal Tees and Bends can be made to order.
- All dimensions relate to the inside measurement.

ACCREDITED TO THE FOLLOWING STANDARDS

CE bsi. ISO 9001 Quality Management

LUL ACCREDITATION ID: 1815




Standard Trunking

Ref.TK22 50mm x 50mm
Ref.TK33 75mm x 75mm
Ref.TK42 100mm x 50mm
Ref.TK44 100mm x 100mm
Ref.TK66 150mm x 150mm

We stock a considerable range of sizes, for our full range of dimensions refer to page 31.

Bespoke sizes available on request




FULL SIZE RANGE GO TO PAGE 31

Unitrunk standard trunking is manufactured from pre-galvanised steel and is supplied in 3m lengths.
Other sizes and finishes are available on request (See code guide at the end of this section).

Gusset Bend Top Lid

Ref.GTB


Code	W	H	X
22	50	50	86
33	75	75	115
42	100	50	137
44	100	100	137
66	150	150	190



Gusset Bend Inside Lid

Ref.GIB


Code	W	H	X
22	50	50	30
33	75	75	30
42	100	50	30
44	100	100	30
66	150	150	30



Gusset Bend Outside Lid

Ref.GOB


Code	W	H	X
22	50	50	30
33	75	75	30
42	100	50	30
44	100	100	30
66	150	150	30



Reducer

Ref.RE


Code	W1	H1	W2	H2	X
33-22	75	75	50	50	152
42-22	100	50	50	50	152
44-33	100	100	75	75	152
66-44	150	150	100	100	152



Gusset Tee Top Lid

Ref.GTT


Code	W	H	X	Y
22	50	50	30	120
33	75	75	30	145
42	100	50	30	165
44	100	100	30	170
66	150	150	30	220



Gusset Tee Inside Lid

Ref.GIT


Code	W	H	X	Y
22	50	50	50	150
33	75	75	50	175
42	100	50	50	150
44	100	100	50	200
66	150	150	50	250



Gusset Tee Outside Lid

Ref.GOT


Code	W	H	X	Y
22	50	50	50	150
33	75	75	50	175
42	100	50	50	150
44	100	100	50	200
66	150	150	50	250



Sharp Elbow Inside Lid

Ref.SIE


Code	W	H	X	Y
22	50	50	40	100
33	75	75	40	125
42	100	50	40	95
44	100	100	40	150
66	150	150	40	200



Sharp Elbow Outside Lid

Ref.SOE


Code	W	H	X	Y
22	50	50	50	100
33	75	75	50	130
42	100	50	50	100
44	100	100	50	155
66	150	150	50	205



Sharp Elbow Top Lid

Ref.STE


Code	W	H	X	Y
22	50	50	50	100
33	75	75	50	125
42	100	50	50	155
44	100	100	50	155
66	150	150	50	205



45° Elbow Top Lid

Ref.TE


Code	W	H	X	Y
22	50	50	50	70
33	75	75	50	80
42	100	50	50	90
44	100	100	50	90
66	150	150	50	110



45° Elbow Inside Lid

Ref.IE


Code	W	H	X	Y
22	50	50	50	70
33	75	75	50	80
42	100	50	50	70
44	100	100	50	90
66	150	150	50	110



45° Elbow Outside Lid

Ref.OE


Code	W	H	X	Y
22	50	50	70	50
33	75	75	80	50
42	100	50	70	50
44	100	100	90	50
66	150	150	110	50



Sharp Tee Top Lid

Ref.STT


Code	W	H	X	Y
22	50	50	50	150
33	75	75	50	175
42	100	50	50	200
44	100	100	50	200
66	150	150	50	250



Sharp Tee Inside Lid

Ref.SIT


Code	W	H	X	Y
22	50	50	50	150
33	75	75	50	175
42	100	50	50	150
44	100	100	50	200
66	150	150	50	250



Sharp Tee Outside Lid

Ref.SOT


Code	W	H	X	Y
22	50	50	50	150
33	75	75	50	175
42	100	50	50	150
44	100	100	50	200
66	150	150	50	250



Intersection Box

Ref.ITB


Code	W	H	X
22	50	50	30
33	75	75	30
42	100	50	30
44	100	100	30
66	150	150	50



Flared Flange

Ref.FF


Code	W1	W2	H	X
22	145	50	50	50
33	175	75	75	50
42	200	100	50	50
44	200	100	100	50
66	250	150	150	50



Adjustable Bends (Vertical) 0-35° Angle

VAB/SIZE External lid


BAB/SIZE Internal lid



Can be formed as an internal or external joint.
Code eg: VAB22 (Adjustable Bend 50x50mm)

Adjustable Bends (Horizontal) 0-35° Angle


HAB/SIZE



Code eg: HAB22
(Adjustable Bend 50x50mm)


Adjustable Lengths Coupler 0-15° Angle

Ref.TAC



Blank End

Ref. BE22 50mm x 50mm
Ref. BE33 75mm x 75mm
Ref. BE42 100mm x 50mm
Ref. BE44 100mm x 100mm
Ref. BE66 150mm x 150mm




Socket Outlet Single

Ref.STL1

Code	X	Y
4	230	110
6	230	160


Can be supply with off centre cutouts



Socket Outlet Double

Ref.STL2

Code	X	Y
4	230	110
6	230	160




Cable Support

Ref. CS22 50mm x 50mm
Ref. CS33 75mm x 75mm
Ref. CS42 100mm x 50mm
Ref. CS44 100mm x 100mm
Ref. CS66 150mm x 150mm



Trunking Coupling


Ref. TC22 50mm x 50mm
Ref. TC33 75mm x 75mm
Ref. TC42 100mm x 50mm
Ref. TC44 100mm x 100mm
Ref. TC66 150mm x 150mm



Fire Barrier Clip


Ref.FB

Code	Y
2	41
3	60
4	85
6	137



Earth Link

Ref.CES (Plain Copper)
Ref. TCES (Tinned Copper)



Distribution Board Trunking **Ref.TKDB**




Trunking no longer requires cutting on site. Size manufactured to customer requirements, saving installation time.

Beam Clamp A

Ref.BCA22 50mm x 50mm

Code	X	Y
22	90	60




Window Beam Clamp

Ref.WBC22 50mm x 50mm

Code	X	Y	W
22	90	103	50

C/W M10 x 40 CPB (Bolt).



Galvanised Steel Lid

Ref.GSL2 50mm
Ref.GSL3 75mm
Ref.GSL4 100mm
Ref.GSL6 150mm
Ref.GSL8 200mm
Ref.GSL9 225mm
Ref.GSL12 300mm




Supplied in 3 metre lengths.

Dividing Fillets


Ref.DF2 50mm
Ref.DF3 75mm
Ref.DF4 100mm
Ref.DF6 150mm

Supplied in 3 metre lengths.



Metal Retaining Strap


Ref. CR2 50mm (Width)
Ref. CR3 75mm (Width)
Ref. CR4 100mm (Width)
Ref. CR6 150mm (Width)




Flanged Coupling

Ref.FC

Code
22
33
44
66





Sold in Pairs. Refer to the Trunking sidewall when ordering. (Example TK42 use FC22)

Plastic Cable Retaining Strap

Ref. CR2/3 50mm x 75mm
Ref. CR4/6 100mm x 150mm




Hanger Bracket

Ref.HBL(x)

Code	H	W	X	X
22	85	55	10	20
33	135	85	10	20
44	165	115	10	20
66	245	165	10	20


Other sizes available on request.



Hanger Bracket (with Swing Bar)


Ref.HBL22SP(x) 50mm x 50mm

Code	W	H	X	X
22	55	85	10	20



Lid Fastener

Ref.LCS2 50mm
Ref.LCS3 75mm
Ref.LCS4 100mm



Available to suit 50mm, 75mm or 100mm widths.
Note: For sizes over 100mm use LCS2 x2

Product Finishing Key (See page 24)

PG ST CP

CODE GUIDE

STEP 1 : CHOOSE PRODUCT FINISH

PG — PRE-GALVANISED

ST — STAINLESS STEEL 304

CP — POWDER COATED

STEP 2: CHOOSE PRODUCT

CODE	PRODUCT NAME
TK	Trunking (3m lengths)
GSL	Galvanised Steel Lid (Width Only)
TC	Trunking Coupling
DF	Dividing Fillet (loose) (Height Only)
GTB	Gusset Bend (Top Lid)
GIB	Gusset Bend (Inside Lid)
GOB	Gusset Bend (Outside Lid)
STE	Sharp Elbow (Top Lid)
SIE	Sharp Elbow (Inside Lid)
SOE	Sharp Elbow (Outside Lid)
GTT	Gusset Tee (Top lid)
GIT	Gusset Tee (Inside Lid)
GOT	Gusset Tee (Outside Lid)
STT	Sharp Tee (Top Lid)
SIT	Sharp Tee (Inside Lid)
SOT	Sharp Tee (Outside Lid)
ITB	Intersection Box
TE	45° Elbow (Top Lid)
IE	45° Elbow (Inside Lid)
OE	45° Elbow (Outside Lid)
RE	Reducer
FF	Flared Flange
BE	Blank End
FB	Fire Barrier Clip
LCS	Lid Clips (Strap and Stud)
FC	Flanged Coupling
CS	Cable Support
CES	Earth Link (Copper) x 10
TCES	Earth Link (Tinned Copper) x 10
CR	Cable Retainer Strap x 10
STLI	Socket Outlet (Single)
STL2	Socket Outlet (Double)
PES	PVC Edging Strip - per metre

STEP 3: CHOOSE SIZE

STEP 4: COMPARTMENTS

NO OF COMPARTMENTS POSSIBLE

WIDTH	HEIGHT	CODE	X1	X2	X3	X4
50	50	22	✓	✓		
75	50	32	✓	✓		
75	75	33	✓	✓		
100	50	42	✓	✓	✓	
100	75	43	✓	✓	✓	
100	100	44	✓	✓	✓	
150	50	62	✓	✓	✓	✓
150	75	63	✓	✓	✓	✓
150	100	64	✓	✓	✓	✓
150	150	66	✓	✓	✓	✓
200	50	82	✓	✓	✓	✓
200	75	83	✓	✓	✓	✓
200	100	84	✓	✓	✓	✓
200	150	86	✓	✓	✓	✓
200	200	88	✓	✓	✓	✓
225	50	92	✓	✓	✓	✓
225	75	93	✓	✓	✓	✓
225	100	94	✓	✓	✓	✓
225	150	96	✓	✓	✓	✓
225	225	99	✓	✓	✓	✓
300	50	12X2	✓	✓	✓	✓
300	75	12X3	✓	✓	✓	✓
300	100	12X4	✓	✓	✓	✓
300	150	12X6	✓	✓	✓	✓
300	200	12X8	✓	✓	✓	✓
300	225	12X9	✓	✓	✓	✓
300	300	12X12	✓	✓	✓	✓

STEP 5: GAUGE

Gauges conform to latest specifications. For specialist requirements a range of gauges are available on request.

Need something special or can't find what you're looking for?

If you need specialist or bespoke products or you can't find the product specification you need, just call one of our regional offices or visit our website.

email: **bespoke@unitrunk.co.uk**


ULSTER
Rugby
Memorial End Stand
Entrance For Wheelchair
Users And Companions

SELECTED FOR ULSTER RUGBY

Unitrunk offered us the convenience and reliability

Harvery Group, N. Ireland

Major redevelopment work at Ulster Rugby's Ravenhill Stadium has seen significant construction and enhancement work at the home of Ulster's Rugby Team throughout the past number of years. The phased work that is due to complete imminently has increased capacity at the ground to 18,000 people. Harvey Group Plc. were employed as the main subcontractor on the project in the provision of all M&E services for the three new stands. David Bennett of Harvey Group commented, "In order to ensure that the rugby stadium and games are held without any disruption it is imperative that our works are planned and carried out with minimal disruption and hyper efficiency.

Using Unitrunk offered us the convenience and reliability of working with a cable management solutions manufacturer who offered competitive pricing on both off the shelf and innovative, labour reducing products to meet our demands".



PRODUCTS

- RIS Basket
- Speedway 4 Cable Ladder
- KLMR Tray and Lighting Trunking
- Powder Coated Trunking

UNITRUNK

Total Cable Management Solutions


SECTION 2

MULTI-COMPARTMENT TRUNKING SYSTEMS

With Multi-Compartment Trunking, dividing fillets are normally supplied spot-welded in position, but can also be supplied loose for fixing on site by drilling and screwing. Spot welds can be treated with Norgalv paint as an extra on request. Purpose-made trunking can be supplied with conduit entries at pre-determined regular intervals in sides and in dividing fillets.

When trunking is mounted vertically or in the inverted position it is recommended that Cable Supports should be fitted.

Bends, Tees, Intersections, etc, can be supplied complete with Dividing Fillets In Tees with Top Lids and in Intersection Boxes, Cross-over Bridges are fitted. Several example assemblies in Tees and Bends with unequal compartments are shown in this section.
Three, four or more compartment trunking is available.



ACCREDITED TO THE FOLLOWING STANDARDS

CE

bsi. ISO 9001 Quality Management

HOW TO ORDER (Without going round the bend!)


PLEASE NOTE: This section is to be used as an aid when ordering unequally divided and TOP LID and therefore directional Trunking Fittings. For INSIDE or OUTSIDE LID fittings all we need to know is the size of each compartment, therefore the steps below are only applicable for TOP LID Accessories.

STEP 1: Trunking Direction

Using the four-way diagram shown, decide what scenario best suits your situation. This will enable you to give information about the trunking sizes you are working with and the size of each trunking compartment. This information will then be used to fill in an Order table later in step 3.

PLEASE NOTE: A, B, C and D represent a plan view of trunking in four directions.

The 4-Way Diagram




PLEASE NOTE: MORE SIZES AND COMPARTMENTS ARE AVAILABLE ON REQUEST. CONTACT YOUR LOCAL OFFICE

To work out what you need, you can use the tables provided in this catalogue or download the Multi-Compartment guide from our website

STEP 2: Size of Trunking

Tell us what size of trunking you are using.

(Trunking Direction Example)





STEP 3: Fitting


Select the appropriate fitting you require from the 'Fitting Key' shown at the bottom of this page. Each fitting has a unique number which should then be used to fill in the order table.


Fitting Key CHOOSE FITTING NUMBER BELOW:

TEE:













INTERSECTION:




BEND:









Product Finishing Key (See page 24)

PG ST CP

STEP 4: Compartment Size & Cable Run

State the compartment sizes and where the cabling will run from/to by filling in Table 2. The remaining spaces should be left blank. For example, in this instance: Cable runs: Compartment B2 goes to C1, and B4 goes to C2.

Table 2 Trunking Compartment sizes & Cable runs


(Example)

From... (State Measurements in mm) \ To... (State Measurements in mm)	A1	A2	A3	A4	B1	B2	B3	B4	C1	C2	C3	C4	D1	D2	D3	D4
A1																
A2																
A3																
A4																
B1																
B2									50							
B3																
B4										75						
C1																
C2																
C3																
C4																
D1																
D2																
D3																
D4																

(EXAMPLE: A)

Trunking Size 100 x 50 x 3 Compartments (code: TK42x3)

90° or 45° Top Lid Bend with smaller compartments to the inside.



STEP 1 Trunking Direction



STEP 2 Size of Trunking

	Trunking Size (mm x mm)
A	100 x 50
D	100 x 50

STEP 3 Fitting



STEP 4 Compartment Size & Cable Run

From... (mm) \ To... (mm)	D2	D3	D4
A1			50
A2		25	
A3	25		


Product Finishing Key (See page 24)

PG ST CP

(EXAMPLE: B)

Trunking Size 150 x 50 x 2 Compartments (code: TK62x2)

90° or 45° Top Lid Bend with smaller compartments to the outside.




STEP 1 Trunking Direction




STEP 2 Size of Trunking

	Trunking Size (mm x mm)
A	150 x 50
D	150 x 50

STEP 3 Fitting






STEP 4 Compartment Size & Cable Run

From... (mm)	To... (mm) C2	C3	C4
D2			
D3		100	
D4			50

(EXAMPLE: C)

Trunking Size 150 x 50 x2 Compartments (code: TK62x2)

Top Lid TEE with underpass taking cables from the right hand compartment out from the rear compartment.




STEP 1 Trunking Direction



STEP 2 Size of Trunking

	Trunking Size (mm x mm)
A	150 x 50
D	150 x 50

STEP 3 Fitting



STEP 4 Compartment Size & Cable Run

From... (mm) \ To... (mm)	C1	C2	C3	C4	D1	D2
A1	50					50
A2		100			100	
A3						

Product Finishing Key (See page 24)

PG ST CP

(EXAMPLE: D)

Trunking Size 200 x 100 x 3 Compartments (code: TK84x3)

Top lid Tee with 2 No crossover pieces to allow cables to Tee off in the correct order to suit the branched trunking supply.




STEP 1 Trunking Direction




STEP 2 Size of Trunking

	Trunking Size (mm x mm)
A	200 x 100
D	200 x 100

STEP 3 Fitting





STEP 4 Compartment Size & Cable Run

From... (mm) \ To... (mm)	C1	C2	C3	C4	D1	D2	D3	D4
A1	75							75
A2		75					75	
A3			50			50		

UNITRUNK

ORDER SHEET

Using steps 1 to 4 as outlined in this section, please complete the two specification tables below which we will use to tailor the correct multi-compartment product for your needs.

Please scan and email or fax to your closest depot.

Table 1
Trunking Sizes

	Trunking Size (mm x mm)
A	
B	
C	
D	

Fitting Number:



Table 2 Trunking Compartment sizes & Cable runs

To... (State Measurements in mm)

From... (State Measurements in mm)

	A1	A2	A3	A4	B1	B2	B3	B4	C1	C2	C3	C4	D1	D2	D3	D4
A1																
A2																
A3																
A4																
B1																
B2																
B3																
B4																
C1																
C2																
C3																
C4																
D1																
D2																
D3																
D4																

Fax and Email Details

UNITRUNK (LISBURN)
fax: +44 (0) 2892 625101
email: lisburn@unitrunk.co.uk

UNITRUNK (IRELAND)
fax: +353 (0) 1 8223533
email: dublin@unitrunk.ie

UNITRUNK (SCOTLAND)
fax: +44 (0) 1506 461969
email: livingston@unitrunk.co.uk

UNITRUNK (NORTH EAST)
fax: +44 (0) 191 4108702
email: northeast@unitrunk.co.uk

UNITRUNK (MANCHESTER)
fax: +44 (0) 161 3361188
email: manchester@unitrunk.co.uk

UNITRUNK (WOLVERHAMPTON)
fax: +44 (0) 1902 714105
email: wolverhampton@unitrunk.co.uk

UNITRUNK (HARLOW)
fax: +44 (0) 1279 444405
email: harlow@unitrunk.co.uk

UNITRUNK (BRISTOL)
fax: +44 (0) 1179 382998
email: bristol@unitrunk.co.uk

CODE GUIDE

STEP 1 : CHOOSE PRODUCT FINISH



PRE-GALVANISED



STAINLESS STEEL



POWDER COATED

STEP 2: CHOOSE PRODUCT

CODE	PRODUCT NAME
TK	Trunking (3m lengths)
LT	Lighting Trunking (3/3.5/4.5/6m lengths)
GSL	Galvanised Steel Lid (Width Only)
TC	Trunking Coupling
DF	Dividing Fillet (loose) (Height Only)
GTB	Gusset Bend (Top Lid)
GIB	Gusset Bend (Inside Lid)
GOB	Gusset Bend (Outside Lid)
STE	Sharp Elbow (Top Lid)
SIE	Sharp Elbow (Inside Lid)
SOE	Sharp Elbow (OutsideLid)
GTT	Gusset Tee (Top lid)
GIT	Gusset Tee (Inside Lid)
GOT	Gusset Tee (Outside Lid)
STT	Sharp Tee (Top Lid)
SIT	Sharp Tee (Inside Lid)
SOT	Sharp Tee (Outside Lid)
ITB	Intersection Box
TE	45° Elbow (Top Lid)
IE	45° Elbow (Inside Lid)
OE	45° Elbow (Outside Lid)
RE	Reducer
FF	Flared Flange
BE	Blank End
FB	Fire Barrier Clip
LCS	Lid Clips (Strap and Stud)
FC	Flanged Coupling
CS	Cable Support
CES	Earth Link (Copper) x 10
TCES	Earth Link (Tinned Copper) x 10
CR	Cable Retainer Strap x 10
STL1	Socket Outlet (Single)
STL2	Socket Outlet (Double)
PES	PVC Edging Strip - per metre

STEP 3: CHOOSE SIZE

STEP 4: COMPARTMENTS

NO OF COMPARTMENTS POSSIBLE

WIDTH	HEIGHT	SIZE CODE	X2	X3	X4
50	50	22	✓		
75	50	32	✓		
75	75	33	✓		
100	50	42	✓	✓	
100	75	43	✓	✓	
100	100	44	✓	✓	
150	50	62	✓	✓	✓
150	75	63	✓	✓	✓
150	100	64	✓	✓	✓
150	150	66	✓	✓	✓
200	50	82	✓	✓	✓
200	75	83	✓	✓	✓
200	100	84	✓	✓	✓
200	150	86	✓	✓	✓
200	200	88	✓	✓	✓
225	50	92	✓	✓	✓
225	75	93	✓	✓	✓
225	100	94	✓	✓	✓
225	150	96	✓	✓	✓
225	225	99	✓	✓	✓
300	50	12X2	✓	✓	✓
300	75	12X3	✓	✓	✓
300	100	12X4	✓	✓	✓
300	150	12X6	✓	✓	✓
300	200	12X8	✓	✓	✓
300	225	12X9	✓	✓	✓
300	300	12X12	✓	✓	✓

STEP 5: GAUGE

Gauges conform to latest specifications. For specialist requirements a range of gauges are available on request.

Need something special or can't find what you're looking for?

If you need specialist or bespoke products or you can't find the product specification you need, just call one of our regional offices or visit our website.

email: **bespoke@unitrunk.co.uk**

UNITRUNK CASE STUDY



HEALTHCARE

> Having worked with Unitrunk in the past, we knew they were the only manufacturer who could meet our needs on a project of this size.

Gavin Hanlon, Mercury Engineering

It's great to know you are trusted. So we were delighted when our services were called upon to develop Scotland's biggest ever hospital project.

A new 'super' laboratory, which covers 25,000 square meters, has just been completed at the site of Glasgow's Southern General hospital and will serve the whole of Glasgow's south-side.

The lab is just one part of the £842 million project which will see an integrated children and adults' hospital built on the site of the current Southern General.



PRODUCTS

- Standard Trunking
- Cable Tray
- Speedway SW4 Cable Ladder
- Support Channel & Bracketry

UNITRUNK


Total Cable Management Solutions

SECTION 3

LIGHTING TRUNKING SYSTEMS

Unitrunk Lighting Trunking is manufactured from galvanised sheet steel to BS EN 10346:2009, giving maximum protection from corrosion and excellent earth continuity.


Standard Cable Trunking fittings can be used with Lighting Trunking, which enables the two types to be easily interconnected thus simplifying installation and wiring.



Lighting Trunking

Ref.	Length
LT223 50 x 50mm	3m
LT223.5 50 x 50mm	3.5m
LT224.5 50 x 50mm	4.5m
LT226 50 x 50mm	6m

(Other sizes available on request)




ACCREDITED TO THE FOLLOWING STANDARDS

CE bsi. ISO 9001 Quality Management

LUL ACCREDITATION ID: 1816

Long Coupling

Ref.LCL22 50mm x 50mm
Ref.LCL33 75mm x 75mm




Hanger Bracket

Ref.HBL(x)

Code	H	W	X	X
22	85	55	10	20
33	135	85	10	20
44	165	115	10	20
66	245	165	10	20

Other sizes available on request.




Fitting Suspension

Ref.FSL22 50mm x 50mm
Ref.FSL33 75mm x 75mm

Code	X	Y
22	62	55
33	82	85


With Brass Bush and Steel Lock Nuts.



Hanger Bracket (with Swing Bar)

Ref.HBL22SP(x) 50mm x 50mm


Code	W	H	X	X
22	55	85	10	20



Galvanised Snap-In Lid

Ref.GCL2 50mm x 50mm


Supplied in 2 Metre Lengths.



Galvanised Steel Lid

Ref.GSL2 50mm
Ref.GSL3 75mm


Supplied in 3 Metre Lengths.



Klik Lid Section


Ref.KLS22

Lid Only.



Blank End

Ref.BEL22 50mm x 50mm
Ref.BEL33 75mm x 75mm



White Plastic Snap-in Lid

Ref.WPL22 50mm
Ref.WPL33 75mm


Supplied in 3 Metre Lengths.



Beam Clamp A

Ref.BCA22 50mm x 50mm

Code	X	Y
22	90	60




Window Beam Clamp

Ref.WBC22 50mm x 50mm

Code	X	Y	W
22	90	103	50

C/W M10 x 40 CPB (Bolt).





We're always making

CONTINUED INVESTMENT

We have just installed a brand new automated folding cell. Allowing us to be more versatile, faster and more efficient - meaning that any of your trunking supply chain issues are solved faster than ever before.

With two factories and seven depots in the UK and Ireland, we work around the clock, and we offer an outstanding distribution and delivery service.

WE GUARANTEE

- An even faster service
- The same great quality
- The same high safety standards
- A wider range of products
- Added flexibility

* In accordance with stock availability.
** Standard delivery terms are 48 hours from receipt of order.

CODE GUIDE

STEP 1 : CHOOSE PRODUCT FINISH

PG PRE-GALVANISED

ST STAINLESS STEEL

CP POWDER COATED

STEP 2: CHOOSE PRODUCT

CODE	PRODUCT NAME
LT	Lighting Trunking (3/3.5/4.5/6m lengths)
GSL	Galvanised Steel lid (Width Only)
TC	Trunking Coupling
DF	Dividing Fillet (loose) (Height Only)
GTB	Gusset Bend (Top Lid)
GIB	Gusset Bend (Inside Lid)
GOB	Gusset Bend (Outside Lid)
STE	Sharp Elbow (Top Lid)
SIE	Sharp Elbow (Inside Lid)
SOE	Sharp Elbow (OutsideLid)
GTT	Gusset Tee (Top lid)
GIT	Gusset Tee (Inside Lid)
GOT	Gusset Tee (Outside Lid)
STT	Sharp Tee (Top Lid)
SIT	Sharp Tee (Inside Lid)
SOT	Sharp Tee (Outside Lid)
ITB	Intersection Box
TE	45˚ Elbow (Top Lid)
IE	45˚ Elbow (Inside Lid)
OE	45˚ Elbow (Outside Lid)
RE	Reducer
FF	Flared Flange
BE	Blank End
FB	Fire Barrier Clip
LCS	Lid Clips (Strap and Stud)
FC	Flanged Coupling
CS	Cable Support
CES	Earth Link (Copper) x 10
TCES	Earth Link (Tinned Copper) x 10
CR	Cable Retainer Strap x 10
STLI	Socket Outlet (Single)
STL2	Socket Outlet (Double)
PES	PVC Edging Strip - per metre

STEP 3: CHOOSE SIZE

STEP 4: COMPARTMENTS

NO OF COMPARTMENTS POSSIBLE

WIDTH	HEIGHT	SIZE CODE	X2	X3	X4
50	50	22	✓		
75	50	32	✓		
75	75	33	✓		

STEP 5: GAUGE

Gauges conform to latest specifications. For specialist requirements a range of gauges are available on request.

Need something special or can't find what you're looking for?

If you need specialist or bespoke products or you can't find the product specification you need, just call one of our regional offices or visit our website.

email: **bespoke@unitrunk.co.uk**



UNITRUNK CASE STUDY

PERFECT PARKING

> Unitrunk supplied us with bespoke quality products that met our customer's exact requirements.

JD McGeown



Situated in the heart of Belfast City Centre, Victoria Square is an impressive commercial, residential and leisure development. At approx 800,000ft^2 (75,000m^2) and costing £400m it is the biggest and one of the most expensive property developments ever undertaken in Northern Ireland. With over 17.2 million people expected to visit Victoria Square per year placing it in the top ten shopping centres in the UK.

Unitrunk tailored a total cable management solution for the extensive 1,000 space Q-Park multi-storey car park at Victoria Square. This project also involved the innovation of bespoke products namely trunking designed to house specialist lighting and hanger brackets designed to suspend two different types of trunking from one bracket in order to meet the customers exact requirements.

PRODUCTS

- Powder Coated Cable Trunking and Cable Tray
- RIS Basket
- Bespoke trunking to house specialist lighting
- Bespoke Hanger Brackets

UNITRUNK
Total Cable Management Solutions

A UNITRUNK INNOVATION
UNIKLIP®

SECTION 4
CABLE TRAY SYSTEMS

UNITRUNK'S LATEST INNOVATION...


Uniklip is our patented fast fitting solution for Cable Tray Installation. Based on the same reliable strength and quality of Unitrunk, Uniklip has been engineered with enhanced speed of installation and ease of use to provide a commercial advantage in a market where efficiency of time is imperative.

Considerable investment in research and development, testing and state of the art computerised machinery has developed a revolutionary solution to fast cable tray installation and a production facility capable of responding quickly to the needs of the market.

Unitrunk's Uniklip System for Cable Tray includes light, medium and heavy duty profile with Klip perforations (also compatible with traditional means of install if required). Uniklip range is produced in pre-galvanised mild steel to BS EN 10346:2009.

All our trays conform to BS 61537:2007 and tested in accordance with BS EN 61537. Earth continuity compliant in accordance with the requirements of BS EN 61537.

Uniklip works up to and including size 600mm tray widths.



ACCREDITED TO THE FOLLOWING STANDARDS

CE bsi. ISO 9001 Quality Management


3X FASTER
THAN YOUR STANDARD INSTALLATION


UK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795

Light Duty Cable Tray (in accordance with BS 61537:2007)

All light duty tray lengths up to and including KLLD225T come complete with swaged end for ease of coupling and to eliminate the need for couplers). KLLD300T and above require the use of couplers. A range of gauges are available on request.

Ref.	Tray Width mm
KLLD50T	50
KLLD75T	75
KLLD100T	100
KLLD150T	150
KLLD225T	225
KLLD300T	300
KLLD450T	450
KLLD600T	600





13.5mm on 50-225mm width


21.5mm on 300-900mm width

Available finishes include:
Pre-galvanised to BS EN 10346:2009 (standard references throughout brochure).
Powder coated (Prefix reference with CP).

UNIKLIP

Bag Ref. KLIPPKT
Box Ref. KLIPBOX

Available in bags of 40 or boxes of 200.




Uniklip is supplied with fittings and couplers.

Fish Plate Coupler

Ref. KLLD/FPC 50-600


Length 200mm.



Fish Plate

Ref. FP 150-600


Length =200mm.



Straight Coupler

Ref. KLLD/SC

Length 200mm.
Sold in pairs.




visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Reducer

Ref. KLLD/SR

Assembly space = 250mm.

Please state sizes required.




Flat 90° Bend

Ref. KLLD 50 - 600FB90

Size	50	75	100	150	225	300	450	600
X	125	150	175	225	300	400	550	700
Y	213	238	263	313	388	488	638	788
Z	106	106	106	106	106	142	142	142
R	75	75	75	75	75	100	100	100

R: Radius




Flat 45° Bend

Ref. KLLD 50 - 600FB45

Size	50	75	100	150	225	300	450	600
X	88	106	124	159	212	283	389	495
Y	72	97	122	172	247	329	479	629
Z	58	58	58	58	58	77	77	77
R	75	75	75	75	75	100	100	100

R: Radius




Flat Equal Tee

Ref. KLLD 50 - 600ET

Size	50	75	100	150	225	300	450	600
X	196	221	246	296	371	446	596	746
Y	123	148	173	223	298	373	523	673
Z	106	106	106	106	106	106	106	106
R	75	75	75	75	75	75	75	75

R: Radius




Flat 4 Way Equal Intersection

Ref. KLLD 50 - 600FW

Size	50	75	100	150	225	300	450	600
X	200	225	250	300	375	450	600	750
Z	106	106	106	106	106	106	106	106
R	75	75	75	75	75	75	75	75

R: Radius




Product Finishing Key (See page 24)

UK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795

Variable Riser

Ref.	Tray Width mm
KLLD50VR	50
KLLD75VR	75
KLLD100VR	100
KLLD150VR	150
KLLD225VR	225
KLLD300VR	300
KLLD450VR	450


Standard radius: 300mm.



Outside Riser

Ref. KLLD 600ER

Size	600
X	314




Standard radius: 300mm.

600 will be supplied formed 90 degrees

Inside Riser

Ref. KLLD 600IR

Size	600
X	300



Standard radius: 300mm.

600 will be supplied formed 90 degrees



Medium Duty Cable Tray
(in accordance with BS 61537:2007)

Ref.	Tray Width mm
KLMR50T	50
KLMR75T	75
KLMR100T	100
KLMR150T	150
KLMR225T	225
KLMR300T	300
KLMR450T	450
KLMR600T	600


Available finishes include:
Pre-galvanised to BS EN 10346:2009 (standard references throughout brochure).
Powder coated (prefix reference with CP).



UNIKLIP

Bag Ref. KLIPPKT
Box Ref. KLIPBOX

Available in bags of 40 or boxes of 200.



Uniklip is supplied with fittings and couplers.

Tray Divider


Ref. KLMR/DF

Length = 3000mm.



Tray to Channel Klip


Ref. CHTR 25



Fish Plate

Ref. FP 150-600mm


Length 200mm.



Fish Plate Coupler

Ref. KLMR/FPC 50-600


Length 200mm.



Straight Coupler

Ref. KLMR/SC

Length 200mm.
Sold in pairs.



Product Finishing Key (See page 24)


UK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795

Reducer

Ref. KLMR/SR

Assembly space = 250mm.

Please state sizes required.




Flat 90° Bend

Ref. KLMR 50 - 600FB90

Size	50	75	100	150	225	300	450	600
X	125	150	175	225	300	400	550	700
Y	213	238	263	313	388	488	638	788
Z	106	106	106	106	106	142	142	142
R	75	75	75	75	75	100	100	100

(Fitting widths W. Sizes in mm)

R: Radius




Flat 45° Bend

Ref. KLMR 50 - 600FB45

Size	50	75	100	150	225	300	450	600
X	88	106	124	159	212	283	389	495
Y	72	97	122	172	247	329	479	629
Z	58	58	58	58	58	77	77	77
R	75	75	75	75	75	100	100	100

(Fitting widths W. Sizes in mm)

R: Radius




Flat Equal Tee

Ref. KLMR 50 - 600ET

Size	50	75	100	150	225	300	450	600
X	196	221	246	296	371	446	596	746
Y	123	148	173	223	298	373	523	673
Z	106	106	106	106	106	106	106	106
R	75	75	75	75	75	75	75	75

R: Radius




Flat 4 Way Equal Intersection

Ref. KLMR 50 - 600FW

Size	50	75	100	150	225	300	450	600
X	200	225	250	300	375	450	600	750
Z	106	106	106	106	106	106	106	106
R	75	75	75	75	75	75	75	75


R: Radius



Variable Riser

(Fitting widths W. Sizes in mm)
Standard radius: 300mm.

Ref.	Tray Width mm
KLMR50VR	50
KLMR75VR	75
KLMR100VR	100
KLMR150VR	150
KLMR225VR	225
KLMR300VR	300
KLMR450VR	450




Outside Riser

Ref. KLMR 600ER

Size	600
X	326

Standard radius: 300mm.

600 will be supplied formed 90 degrees




Inside Riser

Ref. KLMR 600IR

Size	600
X	300

Standard radius: 300mm.


600 will be supplied formed 90 degrees




Conduit Take-off Plate

Ref. TRCB20 (20mm)
Ref. TRCB25 (25mm)

Suitable For Light/Medium/Heavy.






Adjustable Tray Extension

Ref. KLMRATE

Size	Adjustable length ranges		
50	300 - 450	500 - 800	750 - 1200
75	300 - 450	500 - 800	750 - 1200
100	300 - 450	500 - 800	750 - 1200
150	300 - 450	500 - 800	750 - 1200
225	300 - 450	500 - 800	750 - 1200
300	300 - 450	500 - 800	750 - 1200
450	300 - 450	500 - 800	750 - 1200
600	300 - 450	500 - 800	750 - 1200

Made to order item. Other lengths available on request.




Product Finishing Key (See page 24)

UK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795

LOADING DATA FOR ALL UNITRUNK MR CABLE TRAY SYSTEMS

Unitrunk MR




Key

- 50 - 150
- 225 - 300
- 450 - 900

Heavy Duty Cable Tray
(in accordance with BS 61537:2007)

Ref.	Tray Width mm
KLHR50T	50
KLHR75T	75
KLHR100T	100
KLHR150T	150
KLHR225T	225
KLHR300T	300
KLHR450T	450
KLHR600T	600


Available finishes include:
Pre-galvanised to BS EN 10346:2009 (standard references throughout brochure).
Powder coated (prefix reference with CP).



UNIKLIP

Bag Ref. KLIPPKT
Box Ref. KLIPBOX

Available in bags of 40 or boxes of 200.



Uniklip is supplied with fittings and couplers.

Tray Divider

Ref. KLHR/DF

Length = 3000mm.



Tray to Channel Klip


Ref. CHTR 50



Fish Plate

Ref. FP 150-600


Length = 200mm.



Fish Plate Coupler

Ref. KLHR/FPC 50-600


Length = 200mm.



Straight Coupler

Ref. KLHR/SC

Length = 200mm.
Sold in pairs.



Product Finishing Key (See page 24)


UK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795

Reducer

Ref. KLHR/SR

Assembly space = 250mm.

Please state sizes required.




Flat 90° Bend

Ref. KLHR 50-600FB90

Size	50	75	100	150	225	300	450	600
X	125	150	175	225	300	400	550	700
Y	213	238	263	313	388	488	638	788
Z	106	106	106	106	106	142	142	142
R	75	75	75	75	75	100	100	100

R: Radius




Flat 45° Bend

Ref. KLHR 50-600FB45

Size	50	75	100	150	225	300	450	600
X	88	106	124	159	212	283	389	495
Y	72	97	122	172	247	329	479	629
Z	58	58	58	58	58	77	77	77
R	75	75	75	75	75	100	100	100

R: Radius




Flat Equal Tee

Ref. KLHR 50-600ET

Size	50	75	100	150	225	300	450	600
X	196	221	246	296	371	446	596	746
Y	123	148	173	223	298	373	523	673
Z	106	106	106	106	106	106	106	106
R	75	75	75	75	75	75	75	75

R: Radius




Flat 4 Way Equal Intersection

Ref. KLHR 50-600FW

Size	50	75	100	150	225	300	450	600
X	200	225	250	300	375	450	600	750
Z	106	106	106	106	106	106	106	106
R	75	75	75	75	75	75	75	75


R: Radius



Variable Riser

Ref.	Tray Width mm
KLHR50VR	50
KLHR75VR	75
KLHR100VR	100
KLHR150VR	150
KLHR225VR	225
KLHR300VR	300
KLHR450VR	450


(Fitting widths W. Sizes in mm)
Standard radius: 300mm.



Outside Riser

Ref. KLHR 600ER

Size	600
X	350




Standard radius: 300mm.

600 will be supplied formed 90 degrees

Inside Riser

Ref. KLHR 600IR

Size	600
X	300




Standard radius: 300mm.


600 will be supplied formed 90 degrees

Conduit Take-off Plate

Ref. TRCB20 (20mm)
Ref. TRCB25 (25mm)

Suitable For Light/Medium/Heavy.






Adjustable Tray Extension

Ref. KLHRATE

Size	Adjustable length ranges		
50	300 - 450	500 - 800	750 - 1200
75	300 - 450	500 - 800	750 - 1200
100	300 - 450	500 - 800	750 - 1200
150	300 - 450	500 - 800	750 - 1200
225	300 - 450	500 - 800	750 - 1200
300	300 - 450	500 - 800	750 - 1200
450	300 - 450	500 - 800	750 - 1200
600	300 - 450	500 - 800	750 - 1200

Made to order. Other lengths available on request.




Product Finishing Key (See page 24)

PAUK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795

LOADING DATA FOR ALL UNITRUNK HR CABLE TRAY SYSTEMS

Unitrunk HR




Key

- 50 - 150
- 225 - 300
- 450 - 900


COVERS & BRACKETS

The Unitrunk cable tray range is complimented by an extensive range of covers. Covers are available to suit the Unitrunk medium duty and Unitrunk heavy duty cable tray systems. Covers are used with cable tray to provide mechanical and environmental protection for cables and other items installed on the cable tray. Covers can be installed as either closed (non-ventilated, close-fitting) or ventilated (plain raised cover) depending on the type of cover fixing kit supplied with each cover.

Covers for straight cable tray are available in non-standard gauges to suit particular site installation requirements, consult our Sales Team for details. Ventilated covers for Unitrunk medium duty return flange cable tray have a ventilation gap of 21mm. Ventilated covers for Unitrunk heavy duty return flange cable tray have a ventilation gap of 24mm.




Straight Cable Tray
Ventilated (Raised) Cover




Straight Cable Tray Closed
(Non-Ventilated) Cover

Heavy Duty Cable Tray Covers




Medium Duty Cable Tray Covers



Cover Fixing Kits

Unitrunk cable tray covers are supplied complete kits with all necessary fixings. Each fixing kit comprises of a component lid, preformed mounting bracket, a corrosion resistant M6 spire nut, two M6 screws and one M6 nut.

The general method of assembly for the Unitrunk cable tray cover is as shown. This method is common to both medium and heavy duty cable trays and to cable tray fittings.



COVER KIT CODE GUIDE

STEP 1 : CHOOSE PRODUCT FINISH PG **PRE-GALVANISED** *has no code prefix

STEP 2: VENTILATION

CODE	COVER TYPE
UC	Unventilated Cover
VC	Ventilated Cover

STEP 3: TRAY SIDE WALL

CODE	SIDEWALL HEIGHT
MR	Medium Duty
HR	Heavy Duty

STEP 4: TRAY WIDTH

CODE	TRAY WIDTH
50	50mm Wide
75	75mm Wide
100	100mm Wide
150	150mm Wide
225	225mm Wide
300	300mm Wide
450	450mm Wide
600	600mm Wide

STEP 5: PRODUCT TYPE

CODE	PRODUCT TYPE
T	Cable Tray
FB90	Flat Bend 90 Degrees
FB45	Flat Bend 45 Degrees
ET	Equal Tee
FW	Fourway Intersection
ER90	External Riser 90 Deg
IR90	Internal Riser 90 Deg
ER45	External Riser 45 Deg
IR45	Internal Riser 45 Deg

EXAMPLE ORDERING:
PREGALV UNVENTILATED MEDIUM DUTY 100MM WIDE EQUAL TEE = **UCMR100ET**

If you need specialist or bespoke products or you can't find the product specification you need, just call one of our regional offices or visit our website.

Product Finishing Key (See page 24)

PG GA SS CP GX

UK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795


Straight Tray Covers

Unitrunk straight tray covers are 3m in length and are available in widths of 50mm to 900mm as standard. Covers are common for both closed and ventilated applications.

Straight Tray Covers - Dimensions & Weights

Ref.	Tray Width (mm)	Cover Width WC (mm)	Height HC (mm)	Weight (kg)
CR50T	50	61	11.9	2.51
CR75T	75	86	11.9	3.17
CR100T	100	111	11.9	3.92
CR150T	150	161	11.9	5.43
CR225T	225	236	11.9	7.70
CR300T	300	311	12.2	9.96
CR450T	450	461	12.5	18.13
CR600T	600	611	12.5	23.78
CR750T	750	761	12.5	29.47
CR900T	900	911	12.5	35.12

Weights shown are for standard pre-galvanised finish .



Cable Tray Fitting Covers

Unitrunk cable tray fitting covers are available in widths of 50mm to 900mm as standard. Covers are common for both closed and ventilated applications.





Cover Fixing Brackets


Covers for straight cable tray and cable tray fittings are supplied with the appropriate number of cover fixing kits as follows:

Cover Fixing Kit Requirements

Tray & Fitting Type	Width (mm)		
	50-150	225-450	600-900
Straight Tray	6	6	6
90° Flat Elbows	3	4	6
60° Flat Elbows	3	4	6
45° Flat Elbows	3	3	3
30° Flat Elbows	3	3	3
Inside Risers	4	4	4
Outside Risers	4	4	4
Equal Tees	3	4	5
Unequal Tees*	3	4	5
Equal Crosses	4	4	4
Reducers	4	4	4

*Based on largest branch size

Each cover fixing kit is supplied with the appropriate cover mounting bracket for either a non-ventilated cover or ventilated cover based on the part number ordered. (For dimensions of the cover mounting brackets please see table).




Cover Fixing Brackets - Dimensions

Ref.	Cover Type	Bracket Height Hb mm
BKT28	Medium duty closed covers	28
BKT53	Medium duty ventilated covers	53
BKT53	Heavy duty closed covers	53
BKT78	Heavy duty ventilated covers	78

Tray Overhead Hangers

Ref. OH50-OH300

Suitable for Light/Medium/Heavy Duty Cable Tray.
50mm to 300mm Tray Width.



Vertical Adjustable Coupler

Medium Ref. KLMRVAC
Heavy Ref. KLHRVAC

Sold in pairs to suit MR and HR Tray.






Stand-off Bracket

Ref. SOB50-SOB600

Size	50	75	100	150	225	300	450	600


Available finishes include: Pre-galvanised to BS EN 10346:2009 (standard references throughout brochure). Powder coated (prefix reference with CP).



Cantilever Arm

Ref. KLCARM

Size	100	150	225	300	450




Fitting to Fitting Adapter

Ref. KLLDFFA, Ref. KLMRFFA, Ref. KLHRFFA

Size	50	75	100	150	225	300	450	600

Used to connect one cable tray fitting directly onto another cable tray fitting.



Product Finishing Key (See page 24)

UK PATENTED: UK Patent number: GB2476569, IRELAND PATENT PENDING: application number:2010/0795

04 CABLE TRAY SYSTEM FINISHES

(EXCLUDING RIS UNIKLIP SYSTEM)

Galvanised After: Products to this finish are manufactured from mild steel and galvanised after manufacture in accordance with BS EN 1461. These products achieve a thicker coating of zinc which enhances the products resistance to corrosion. Products to this finish are suitable for outdoor installations.



Stainless Steel: Used for products to be installed in the harshest of environments and in various process facilities. Unitrunk offers two grades of stainless steel material.

304: Used extensively throughout the industry. This is a tough, corrosion resistant austenitic grade of stainless steel which is popular in the food and pharmaceutical process industries. Unitrunk cable trunkings are as standard supplied in this grade of material.



316: Also referred to as Marine Grade. This austenitic grade of stainless steel through the addition of molybdenum is used mainly for installations which are exposed to high saline content environments such as offshore facilities and coastal environments. Our cable ladders, cable trays and support channels are supplied as standard in this grade of material. These two grades of stainless steel are to BS EN 10088-2:2005.



Powder Coated (Multicoloured): The painted finish is achieved by powder coating the base steel. This process is achieved by electrostatically charging the base material and then applying a free flowing, dry coloured powder to it. Heat is then applied to allow it to flow and form a "skin". The powder coated finish is very tough and durable providing relatively good corrosion protection. It can be applied to any type of steel finish, including post-galvanised.



Galvanised After Manufacture Corten A Steel: This material is used for products to be installed in environments where high levels of humidity and/or where corrosive substances are present. The high silicon content of Corten A substantially increases the zinc coating thickness which adheres to the surface of the steel thereby extending the life cycle of the installation. The typical zinc coating thickness achieved on 2.0mm mild steel, in accordance with BS EN 1461, is 55µ (microns) whereas 2.0mm Corten A steel can comfortably achieve a coating thickness of 140µ, more than doubling the time to first maintenance.



Pre-Galvanised 750 + 900: Mild steel material to BS EN 10346:2009, pre-coated at the steel manufacturers. Good resistance to rust in a dry, indoor environment. Not recommended for humid or outdoor installations.



UNITRUNK CABLE-TRAY

SECTION 4

CABLE TRAY SYSTEMS


The Unitrunk range of Cable Tray Systems has been developed to suit the demands of an ever changing market. Considerable investment in state of the art computerised machinery has developed a production facility which is able to respond quickly to the demands of the market, making Unitrunk one of the most advanced companies in this field.

Customer satisfaction is of paramount importance to Unitrunk and great care is taken to ensure that the highest standards of manufacture are maintained. Unitrunk Cable Tray Systems consist of light, medium and heavy duty pattern with standard perforations. The requirements of a cable tray finish can vary, depending upon the situation, from being purely cosmetic to being capable of providing protection in the most corrosive environments. Unitrunk Cable Tray is produced in pre-galvanised mild steel to BS EN 10346:2009 or galvanized in accordance with BS EN ISO1461. All our trays conform to BS 61537:2007. A wide range of materials and finishes are also available on request.

ACCREDITED TO THE FOLLOWING STANDARDS

CE BSI UKAS QUALITY MANAGEMENT 003

FM11705



04

Light Duty Cable Tray (in accordance with BS 61537:2007)


All light duty tray lengths up to and including LD225T will be supplied with an inwards form on one end (to eliminate the need for couplers). LD300/T and above require the use of couplers. A range of gauges are available on request.




Ref.	Tray Width mm
LD50T	50
LD75T	75
LD100T	100
LD150T	150
LD225T	225
LD300T	300
LD450T	450
LD600T	600
LD750T	750
LD900T	900

Available across this size range (GX, CP, SS, GA)

750 - 900 ONLY (PG)



Swaged joint




13.5mm on 50-225mm width

21.5mm on 300-900mm width

If you require 50 - 600 in (PG) please refer to the UNIKLIP Cable Tray section on page 53

Straight Coupler


Ref.LD/SC



Length 161mm.
Sold in pairs.

Fish Plate


Ref.FP 225-900



Tray width less 58mm


Earth Link

Ref.CES (Plain Copper)
Ref.TCES (Tinned Copper)
Ref.EBS100 (M6 Braid)



Cranked Coupler


Ref.LD/CC



Sold in pairs.

Reducer

Ref.LD-SR



Total length 250mm.
Please state sizes required.

Bolts & Nuts

Ref.M6X12




Order separately.

Flat 90° Bend

Ref.LD 50-900FB90

Size	50	75	100	150	225	300	450	600	750	900
X	126	151	175	225	375	450	600	750	900	1058
Y	166	191	215	265	415	490	640	790	940	1098
Z	107	107	107	107	211	211	211	211	211	211

Available across this size range (GA, SS, CP, GX) — 750 - 900 ONLY (PG)



If you require 50 - 600 in (PG) please refer to the UNIKLIP Cable Tray section on page 54

visit online: uk unitrunk.co.uk ireland unitrunk.ie


Flat 45° Bend

Ref.LD 50-900FB45

Size	50	75	100	150	225	300	450	600	750	900
X	66	93	120	174	268	344	510	673	835	998
Y	52	63	73	94	155	187	249	311	373	435
Z	58	58	58	58	115	115	115	115	115	115

750 - 900 ONLY

Available across this size range | Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 54


Flat 4 Way Equal Intersection

Ref.LD 50-900FW

Size	50	75	100	150	225	300	450	600	750	900
X	177	213	249	320	532	637	850	1062	1274	1486
Y	177	213	249	320	532	637	850	1062	1274	1486
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range | Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 54


Flat Equal Tee

Ref.LD 50-900ET

Size	50	75	100	150	225	300	450	600	750	900
X	204	229	254	304	530	605	755	906	1056	1206
Y	127	152	177	227	377	452	603	752	902	1053
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range | Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 54


Outside Riser

Ref.LD 50-450VR 600-900ER

Size	50	75	100	150	225	300	450	600	750	900
X	297	297	297	297	297	297	297	297	297	297
Y	337	337	337	337	337	337	337	337	337	337

750 - 900 ONLY

Available across this size range | Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 55


Inside Riser

Ref.LD 50-450VR 600-900IR

Size	50	75	100	150	225	300	450	600	750	900
X	297	297	297	297	297	297	297	297	297	297
Y	337	337	337	337	337	337	337	337	337	337

750 - 900 ONLY

Available across this size range | Available across this size range




If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 55

Medium Duty Cable Tray (in accordance with BS 61537:2007)

Ref.	Tray Width mm
MR50T	50
MR75T	75
MR100T	100
MR150T	150
MR225T	225
MR300T	300
MR450T	450
MR600T	600
MR750T	750
MR900T	900

Available across this size range (GX, CP, SS, GA)

750 - 900 ONLY (PG)




If you require 50 - 600 in (PG) please refer to the UNIKLIP Cable Tray section on page 56

Straight Coupler

Ref.MR/SC

Length 225mm.
Sold in pairs.



Tray Divider

Ref.MR/DF


Length 3000mm.



Fish Plate

Ref.FP 100-900mm


Tray width less 58mm



Cranked Coupler


Ref.MR/CC

Sold in pairs.



Tray to Channel Klip

Ref. CHTR 25




visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Reducer

Ref.MR-SR

Total length 250mm.
Please state sizes required.




Flat 90° Bend

Ref.MR 50-900FB90

Size	50	75	100	150	225	300	450	600	750	900
X	126	151	175	225	375	450	600	750	900	1058
Y	166	191	215	265	415	490	640	790	940	1098
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range — GA SS CP GX — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 57


Flat 45° Bend

Ref.MR 50-900FB45

Size	50	75	100	150	225	300	450	600	750	900
X	66	93	120	174	268	344	510	673	835	998
Y	52	63	73	94	155	187	249	311	373	435
Z	58	58	58	58	115	115	115	115	115	115

750 - 900 ONLY

Available across this size range — GA SS CP GX — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 57


Flat 4 Way Equal Intersection

Ref.MR 50-900FW

Size	50	75	100	150	225	300	450	600	750	900
X	177	213	249	320	532	637	850	1062	1274	1486
Y	177	213	249	320	532	637	850	1062	1274	1486
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range — GA SS CP GX — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 57


Flat Equal Tee

Ref.MR 50-900ET

Size	50	75	100	150	225	300	450	600	750	900
X	204	229	254	304	530	605	755	906	1056	1206
Y	127	152	177	227	377	452	603	752	902	1053
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range — GA SS CP GX — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 57

Outside Riser


Ref.MR 50-450VR
Ref.MR 600-900ER

Size	50	75	100	150	225	300	450	600	750	900
X	297	297	297	297	297	297	297	297	297	297
Y	337	337	337	337	337	337	337	337	337	337

750 - 900 ONLY

Available across this size range

Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 58

Inside Riser


Ref.MR 50-450VR
Ref.MR 600-900IR

Size	50	75	100	150	225	300	450	600	750	900
X	297	297	297	297	297	297	297	297	297	297
Y	337	337	337	337	337	337	337	337	337	337

750 - 900 ONLY

Available across this size range

Available across this size range





If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 58

Conduit Take-off Plate

Ref.TRCB20
Ref.TRCB25


Suitable For Light/Medium/Heavy.





Earth Link

Ref.CES (Plain Copper)
Ref.TCES (Tinned Copper)
Ref.EBS100 (M6 Braid)



Bolts & Nuts

Ref.M6X12

Order separately.




Heavy Duty Cable Tray
(in accordance with BS 61537:2007)

Available across this size range (GX, CP, SS, GA)

Ref.	Tray Width mm
HR50T	50
HR75T	75
HR100T	100
HR150T	150
HR225T	225
HR300T	300
HR450T	450
HR600T	600
HR750T	750
HR900T	900

750 - 900 ONLY (PG)




If you require 50 - 600 in (PG) please refer to the UNIKLIP Cable Tray section on page 60

Straight Coupler

Ref.HR/SC


Length 225mm.
Sold in pairs.



Tray Divider

Ref.HR/DF


Length 3000mm.



Fish Plate

Ref.FP 100-900mm


Tray width less 58mm.



Cranked Coupler

Ref.HR/CC

Sold in pairs.



Tray to Channel Klip

Ref. CHTR 50




Product Finishing Key (See page 67)

PG GA SS CP GX

Reducer

Ref.HR-SR

Total length 250mm.
Please state sizes required.




Flat 90° Bend

Ref.HR 50-900FB90

Size	50	75	100	150	225	300	450	600	750	900
X	126	151	175	225	375	450	600	750	900	1058
Y	166	191	215	265	415	490	640	790	940	1098
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 61


Flat 45° Bend

Ref.HR 50-900FB45

Size	50	75	100	150	225	300	450	600	750	900
X	66	93	120	174	268	344	510	673	835	998
Y	52	63	73	94	155	187	249	311	373	435
Z	58	58	58	58	115	115	115	115	115	115

750 - 900 ONLY

Available across this size range — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 61


Flat 4 Way Equal Intersection

Ref.HR 50-900FW

Size	50	75	100	150	225	300	450	600	750	900
X	177	213	249	320	532	637	850	1062	1274	1486
Y	177	213	249	320	532	637	850	1062	1274	1486
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 61


Flat Equal Tee

Ref.HR 50-900ET

Size	50	75	100	150	225	300	450	600	750	900
X	204	229	254	304	530	605	755	906	1056	1206
Y	127	152	177	227	377	452	603	752	902	1053
Z	107	107	107	107	211	211	211	211	211	211

750 - 900 ONLY

Available across this size range — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 61


Outside Riser

Ref.HR 50-450VR
Ref.HR 600-900ER

Size	50	75	100	150	225	300	450	600	750	900
X	297	297	297	297	297	297	297	297	297	297
Y	337	337	337	337	337	337	337	337	337	337

PG 750 - 900 ONLY

Available across this size range — GA SS CP GX — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 62


Inside Riser

Ref.HR 50-450VR
Ref.HR 600-900IR

Size	50	75	100	150	225	300	450	600	750	900
X	297	297	297	297	297	297	297	297	297	297
Y	337	337	337	337	337	337	337	337	337	337

PG 750 - 900 ONLY

Available across this size range — GA SS CP GX — Available across this size range



If you require 50 - 600 in PG please refer to the UNIKLIP Cable Tray section on page 62

DON'T FORGET THE NUTS & BOLTS OF IT...

REMEMBER TO CHECK SECTION 12

For all your Accessories & Supports needs


SEE PAGE 154

PG GA SS CP GX

Tray Overhead Hangers

Ref.OH50-OH300


Suitable for Light/Medium/Heavy Duty Cable Tray.
50mm to 300mm Tray Width.



Vertical Adjustable Coupler

Ref.HR-VAC / MR-VAC

Sold in pairs to suit MR and HR Tray.




Stand-off Bracket

Ref. SOB50-SOB600

Size	50	75	100	150	225	300	450	600
Height	40	40	40	40	40	40	40	40


Order Information
Stainless Steel 316 grade (prefix reference with SS).

Available finishes include: Pre-galvanised to BS EN 10346:2009 (standard references throughout brochure). Post galvanised to BS EN ISO 1461:2009 (prefix reference with GA). Powder coated (prefix reference with CP).



Earth Link


Ref.CES (Plain Copper)
Ref.TCES (Tinned Copper)
Ref.EBS100 (M6 Braid)




COVERS & BRACKETS

The Unitrunk cable tray range is complimented by an extensive range of covers. Covers are available to suit the Unitrunk medium duty and Unitrunk heavy duty cable tray systems. Covers are used with cable tray to provide mechanical and environmental protection for cables and other items installed on the cable tray. Covers can be installed as either closed (non-ventilated, close-fitting) or ventilated (plain raised cover) depending on the type of cover fixing kit supplied with each cover.

Covers for straight cable tray are available in non-standard gauges to suit particular site installation requirements, consult our Sales Team for details. Ventilated covers for Unitrunk medium duty return flange cable tray have a ventilation gap of 21mm. Ventilated covers for Unitrunk heavy duty return flange cable tray have a ventilation gap of 24mm.




Straight Cable Tray
Ventilated (Raised) Cover




Straight Cable Tray Closed
(Non-Ventilated) Cover

Heavy Duty Cable Tray Covers




Medium Duty Cable Tray Covers



Cover Fixing Kits

Unitrunk cable tray covers are supplied complete kits with all necessary fixings. Each fixing kit comprises of a component lid, preformed mounting bracket, a corrosion resistant M6 spire nut, two M6 screws and one M6 nut.

The general method of assembly for the Unitrunk cable tray cover is as shown. This method is common to both medium and heavy duty cable trays and to cable tray fittings.



COVER KIT CODE GUIDE

STEP 1 : CHOOSE PRODUCT FINISH PG GA SS CP GX **PRE-GALVANISED** *has no code prefix

STEP 2: VENTILATION

CODE	COVER TYPE
UC	Unventilated Cover
VC	Ventilated Cover

STEP 3: TRAY SIDE WALL

CODE	SIDEWALL HEIGHT
MR	Medium Duty
HR	Heavy Duty

STEP 4: TRAY WIDTH

CODE	TRAY WIDTH
50	50mm Wide
75	75mm Wide
100	100mm Wide
150	150mm Wide
225	225mm Wide
300	300mm Wide
450	450mm Wide
600	600mm Wide
750	750mm Wide
900	900mm Wide

STEP 5: PRODUCT TYPE

CODE	PRODUCT TYPE
T	Cable Tray
FB90	Flat Bend 90 Degrees
FB45	Flat Bend 45 Degrees
ET	Equal Tee
FW	Fourway Intersection
ER90	External Riser 90 Deg
IR90	Internal Riser 90 Deg
ER45	External Riser 45 Deg
IR45	Internal Riser 45 Deg

EXAMPLE ORDERING:
STAINLESS STEEL UNVENTILATED HEAVY DUTY 100MM WIDE EQUAL TEE = **SSUCHR100ET**

If you need specialist or bespoke products or you can't find the product specification you need, just call one of our regional offices or visit our website.

Product Finishing Key (See page 67)

PG GA SS CP GX


Straight Tray Covers

Unitrunk straight tray covers are 3m in length and are available in widths of 50mm to 900mm as standard. Covers are common for both closed and ventilated applications.

Straight Tray Covers - Dimensions & Weights

Ref.	Tray Width (mm)	Cover Width WC (mm)	Height HC (mm)	Weight (kg)
CR50T	50	61	11.9	2.59
CR75T	75	86	11.9	3.31
CR100T	100	111	11.9	3.99
CR150T	150	161	11.9	5.61
CR225T	225	236	11.9	7.92
CR300T	300	311	12.2	10.01
CR450T	450	461	12.5	18.19
CR600T	600	611	12.5	23.82
CR750T	750	761	12.5	29.63
CR900T	900	911	12.5	35.31

Weights shown are for standard atainless steel finish .



Cable Tray Fitting Covers

Unitrunk cable tray fitting covers are available in widths of 50mm to 900mm as standard. Covers are common for both closed and ventilated applications.





Cover Fixing Brackets


Covers for straight cable tray and cable tray fittings are supplied with the appropriate number of cover fixing kits as follows:

Cover Fixing Kit Requirements

Tray & Fitting Type	Width (mm)		
	50-150	225-450	600-900
Straight Tray	6	6	6
90° Flat Elbows	3	4	6
60° Flat Elbows	3	4	6
45° Flat Elbows	3	3	3
30° Flat Elbows	3	3	3
Inside Risers	4	4	4
Outside Risers	4	4	4
Equal Tees	3	4	5
Unequal Tees*	3	4	5
Equal Crosses	4	4	4
Reducers	4	4	4

*Based on largest branch size

Each cover fixing kit is supplied with the appropriate cover mounting bracket for either a non-ventilated cover or ventilated cover based on the part number ordered. (For dimensions of the cover mounting brackets please see table).



Cover Fixing Brackets - Dimensions

Ref.	Cover Type	Bracket Height Hb mm
BKT28	Medium duty closed covers	28
BKT53	Medium duty ventilated covers	53
BKT53	Heavy duty closed covers	53
BKT78	Heavy duty ventilated covers	78

visit online: uk unitrunk.co.uk ireland unitrunk.ie



UNITRUNK CASE STUDY

A TOWERING SUCCESS

> Innovation is key to this project and with Unitrunk's expertise we worked together to ensure any obstacles were overcome.

Morris Cairns, Director,
Blackbourne Integrated M & E



Costing £85 million and measuring 85 metres in height, the Obel Tower super structure when completed is set to dominate the Belfast skyline and will overtake the current tallest skyscraper in Ireland. The obelisk shaped structure will contain 28 floors of 282 residential apartments with residents set to enjoy stunning views across Belfast.

The project was selected by Constructing Excellence in NI as a demonstration of Design Quality using Modern Methods of Construction. With many innovations being demonstrated, Unitrunk worked closely with the contractor to develop cable trunking and tray that assisted in running cabling through confined spaces. Unitrunk are proud to be part of local history in providing a complete cable management solution for what is set to be one of Belfast's most iconic developments.

PRODUCTS

- RIS Basket
- Speedway SW4 Cable Ladder
- HR and MR Cable Tray
- Lighting Trunking
- Standard Trunking
- Multi-Compartment Trunking

UNITRUNK

SPEEDWAY®

SECTION 5

SPEEDWAY CABLE LADDER SYSTEMS

The Speedway Cable Ladder System represents a major advance in cable ladder design, providing faster and easier installation, a unique coupler locking system and a comprehensive range of accessories.

The Speedway Cable Ladder System is subject to Registered Design, Trade Mark and Patent considerations and conforms to BS EN 61537:2007.

SPEEDWAY – FOR WHEN IT MATTERS

THE LADDER SYSTEMS
are manufactured in 3 heights:
SPEEDWAY 4 (SW4) - 110mm overall height
SPEEDWAY 5 (SW5) - 125mm overall height
SPEEDWAY 6 (SW6) - 150mm overall height

SYSTEM ATTRIBUTES
Special Profiled Side Section:
1. Enhanced structural rigidity.
2. Increased internal width for cables.
3. High performance coupling.
4. Safety edge.

Slotted Side Section:
1. Allows faster installation as the ladder can be cut to any length and coupled without on-site drilling.
2. Fixing to ladder sides.
3. Reduced weight.


Shallow Channel Rungs:
1. The welding of the rungs to the lowest point of the side section ensures maximum loading height.
2. High strength even in the widest ladders.
3. Use of every known type of cleat, tie and bonding with infinite adjustment.
4. Rungs alternately inverted (on lengths)permitting suspension of light fittings etc.from underside.

Speedway Cable Ladder is supplied in various materials and finishes:

LADDER & FITTINGS
GY Hot dip galvanized Vantrunk Extreme Steel (Steel BS EN 10025-2 and Galvanising BS EN 1461:2009)

COVERS & ACCESSORIES
GA Hot dip galvanized Mild Steel (Steel BS EN 10111 and Galvanising BS EN 1461:2009)

LADDER, FITTINGS, COVERS & ACCESSORIES
GX Hot dip deep galvanized after manufacture to BS EN 1461:2009
SS Stainless steel grade 1.4404 (316 marine) to BS EN 10088-2:2005



ACCREDITED TO THE FOLLOWING STANDARDS


CE


05

Speedway SW4 Cable Ladder

Speedway 4 (SW4) Medium Duty Cable Ladder is manufactured in 3.0m lengths as standard with 6.0m lengths to order. The cable ladder is available in standard widths of 150mm, 300mm, 450mm, 600mm, 750mm and 900mm, although other widths up to 1050mm are available to order. Rung spacing is 300mm as standard.

Ref.SW4/SL3/Width/Finish





Part Number	No. of Rungs	Dimensions (mm)				Weight (kg)
		W	W1	L	H	
SW4/SL3/150/○	10	150	200	3000	110	13.93
SW4/SL3/300/○		300	350			15.55
SW4/SL3/450/○		450	500			17.17
SW4/SL3/600/○		600	650			18.79
SW4/SL3/750/○		750	800			23.12
SW4/SL3/900/○		900	950			25.28

Height	H	110mm
Loading Depth	D	85mm
Ladder Width	W	100mm to 1050mm
Maximum Internal Width	W2	W + 14mm
Overall Width	W1	W + 50mm
Flange Width	F	25mm

○= Select a Finish & Material refer to Page 82

Weights shown are for standard hot dip galvanised finish only.

Supplied with:





visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Speedway SW5 Cable Ladder

Speedway 5 (SW5) Heavy Duty Cable Ladder is manufactured in 3.0m lengths as standard with 6.0m lengths supplied to order. The cable ladder is available in standard widths of 150mm, 300mm, 450mm, 600mm, 750mm, 900mm and 1050mm, although other widths up to 1500mm are available to order. Rung spacing is 300mm as standard.

Ref.SW5/SL3/Width/Finish






Part Number	No. of Rungs	Dimensions (mm)				Weight (kg)
		W	W1	L	H	
SW5-SL3-150-○	10	150	200	3000	125	18.53
SW5-SL3-300-○	10	300	350			20.15
SW5-SL3-450-○	10	450	500			21.77
SW5-SL3-600-○	10	600	650			23.40
SW5-SL3-750-○	10	750	800			27.72
SW5-SL3-900-○	10	900	950			29.88
SW5-SL3-1050-○	10	1050	1100			32.05

Height	H	125mm
Loading Depth	D	100mm
Ladder Width	W	100mm to 1500mm
Overall Width	W1	W + 50mm
Maximum Internal Width	W2	W + 14mm
Flange Width	F	25mm

Supplied with:



○= Select a Finish & Material refer to Page 82

Weights shown are for standard hot dip galvanised finish only.


Product Finishing Key (See page 82)


GY SS CP GX

Speedway SW6 Cable Ladder

Speedway 6 (SW6) Extra Heavy Duty Cable Ladder is manufactured in 3.0m lengths as standard with 6.0m lengths supplied to order. The cable ladder is available in standard widths of 150mm, 300mm, 450mm, 600mm, 750mm, 900mm and 1050mm, although other widths up to 1500mm are available to order. Rung spacing is 300mm as standard.

Ref.SW6/SL3/Width/Finish





Part Number	No. of Rungs	Dimensions (mm)				Weight (kg)
		W	W1	L	H	
SW6-SL3-150-○	10	150	200	3000	150	21.63
SW6-SL3-300-○	10	300	350			23.79
SW6-SL3-450-○	10	450	500			25.95
SW6-SL3-600-○	10	600	650			28.11
SW6-SL3-750-○	10	750	800			30.28
SW6-SL3-900-○	10	900	950			32.44
SW6-SL3-1050-○	10	1050	1100			34.60

Height	H	150mm
Loading Depth	D	125mm
Ladder Width	W	100mm to 1500mm
Overall Width	W1	W + 50mm
Maximum Internal Width	W2	W + 14mm
Flange Width	F	25mm

Supplied with:



○= Select a Finish & Material refer to Page 82

Weights shown are for standard hot dip galvanised finish only.


Cable Ladder Fitting with Speedlock Integral Coupler

Fast fit, total cost saving through reduction of the number of couplers and fixings required. The integral coupler has a formed shape which increases strength and rigidity and reduces joint hinging.



Flat Elbow
30°, 45°, 60°, 90°

Ref.SW-/FE Angle/Width /Radius/Finish




Cross

Ref.SW-/C/Width/Radius/Finish



Equal Tee

Ref.SW-/ET/Width/ Radius/Finish




Can also be manufactured unequal.

Ref.SW-/UET/W1/W2/ Radius/Finish

Covers

SW/CC/SL1.5/Width/Finish (Closed)
SW/CL/SL1.5/Width/Finish (Louvered)

Supplied c/w fixings.
Please note straight ladder covers are supplied in 1.5m lengths.



Riser (Outside)
30°, 45°, 60°, 90°


Ref.SW-/OR Angle/Width /Radius/Finish



Short Adjustable Coupler

Ref. SW-/SAC/Finish

Overall length 300mm.
Used as an alternative to Reducers/unequal tees.
Supplied c/w fixings.



Riser (Inside)
30°, 45°, 60°, 90°


Ref.SW-/IR Angle/Width /Radius/Finish



Straight Coupler

Ref.SW-/CS/Finish

Sold in pairs.
Supplied c/w fixings.
1 Pair per ladder.




Product Finishing Key (See page 82)

GY GA SS CP GX

Long Adjustable Coupler

Ref.SW-/LAC/Finish


Overall length 450mm
Used as an alternative to Reducers/ unequal tees.
Supplied c/w fixings.



Adjustable Fixing Bracket

Ref.SW/AFB/Finish


Supplied c/w 1 fixing.




External Flange Clamp

Ref.SW/EFC/Finish

Fixings ordered separately.






Horizontal Adjustable Coupler

Ref.SW-/HAC/Finish

Each c/w fixings.




Hold Down Bracket

Ref.SW-/HDB/Finish

Fixings ordered separately.






Vertical Adjustable Coupler

Ref.SW-/VAC/Finish

Each c/w fixings.


Identical for sw4 & sw5 order as: Sw4/5/vac/finish
for sw6 order as: sw6/vac/finish.



Straight Ladder Divider


Ref.SW-/SL/1.5/Finish

Straight ladder dividers are 1.5m long.
Fixings separate.




Reducer Left Hand

Ref.SW-/RL/W1/W2/Finish




Straight Reducer

Ref.SW-/RS/W1/W2/Finish



Reducer Right Hand

Ref.SW-/RR/W1/W2/Finish



Earth Braid

Ref.EBS01 (M10 BRAID)




The Speedway Earth Bonding Strap (EBS01) is designed for use in installations where an additional means of earthing or electrical bonding is specified. The Speedway Earth Bonding Strap comprises of a 16mm² tinned copper braid crimped into M10 tinned copper end connectors. The Speedway Earth Bonding Strap is common to Speedway SW4, SW5, & SW6.

Pre-punched holes for fixing the earth bonding strap are located at each end of the ladder and fittings.

These illustrated graphs are indicative of the performance of Speedway SW4, SW5 and SW6 Cable Ladder in a typical continuous beam installation. The loading figures have been determined by actual load tests. For detailed loading data please contact our technical department.


Speedway SW4
Load Deflection Data - Continuous Beam



Key

Applicable for full range of standard widths.
Applicable for widths 150-600mm inc.


Speedway SW5
Load Deflection Data - Continuous Beam



Key

Applicable for full range of standard widths.
Applicable for widths 150-750mm inc.

Speedway SW6
Load Deflection Data - Continuous Beam



Key

Applicable for full range of standard widths.
Applicable for widths 150-750mm inc.
Applicable for widths 150, 300 & 450mm inc.

Speedway Cable Ladder System – Standard Material Gauges

Ladder Type	Material & Finish	Side Wall Gauge	Rung Gauge						
			150 mm	300 mm	450 mm	600 mm	750 mm	900 mm	1050 mm
Speedway SW4	GY	1.5mm	1.5mm				2.0mm		
	SS		1.5mm						
	GX								
Speedway SW5	GY	1.5mm	1.5mm				2.0mm		
	SS	2.0mm	2.0mm						
	GX		1.5mm						
Speedway SW6	GY	2.0mm	2.0mm						
	SS								
	GX								

GY - Steel/Hot Dip Galvanized SS - Stainless Steel **GX** - Silicon Rich/Deep Galvanized

Product Finishing Key (See page 82)

LOK DOWN
WITH THE SPEEDLOK INTEGRAL COUPLER

All Speedway fittings are manufactured with the Speedlok Integral Coupler as standard; this represents a major advance in modern cable management design, Speedlok Integral Couplers reduce:

- **The number of fixings required to connect the ladder and fitting, in turn reducing the ladder to fitting connection by 67%**
- **The overall installation time, weight and cost.**

UNITRUNK SPEEDLOK QUICKFIT CABLE LADDER

FAST FITTING & STRONG



UNITRUNK RIS

SEE PAGE 82 FOR DETAILS

UNITRUNK CASE STUDY



SAVING TIME, MONEY AND MOTHER NATURE

The new Uniklip cable tray range was of great benefit - it was very quick and easy to install. It was also good that it could be used in conjunction with the traditional Unitrunk range and that no extra tools were required to install it.

Chris Adams, JBE Building Services Ltd

A UNITRUNK INNOVATION

UNIKLIP®

Unitrunk are always innovative. Not only did our new Uniklip system revolutionise cable installation this year, but it has now been fitted in Tesco's first ever eco superstore in Northern Ireland.

The retail giant picked Newtownards as the site for its ultra-efficient new superstore. The site is designed to be totally sustainable and eco-friendly: it has large windows to boost natural light inside, a timber-steel hybrid frame, 100% sustainable timber cladding, new natural refrigeration technology and even generates its own electricity.

So with forward-thinking and cutting-edge technology a priority, it's no surprise that the new Uniklip system was called in to action. Uniklip makes it possible to install systems three-times faster than normal, saving installers huge amounts of time and money.



PRODUCTS

- Uniklip HR Tray
- Uniklip Accessories
- Standard Trunking
- Support Channel & Bracketry

UNITRUNK
Total Cable Management Solutions

EASYCONNECT

SECTION 6

Cable Basket Systems

UNITRUNK RIS

A strong yet flexible solution is needed to meet the demands of the power, data and systems cabling being installed in modern buildings.

The patented EasyConnect Cable Basket system provides that solution. Adhering to the RIS (Rapid Installation Systems) philosophy, the integral coupler simply pushes together to form a secure joint, no additional couplers or special tools are required.

Manufactured to comply with BS EN 61537, EasyConnect meets all the load test and earth continuity requirements of the standard.



ALL SIDE OR BASE MOUNTED COUPLERS ARE INTEGRAL

EasyConnect has been short circuit tested and has achieved a fire rating of E90, providing further confidence in this quality solution.


Modular Fabrication

The EasyConnect basket product is manufactured with an overall length of 3000mm. When two lengths are joined, the proximity of the joint means that the two lengths have a combined overall length of 6000mm. This makes it perfect for use in Modular (off-site) fabrication as this eliminates "basket creep" that would occur with other basket products. The basket can also be supplied cut to size (multiples of 100mm) to suit the specific demands of any project.

EasyConnect basket tray is patented and manufactured by Valdinox and distributed in the UK & Ireland exclusively through Unitrunk

ACCREDITED TO THE FOLLOWING STANDARDS


CE bsi. ISO 9001 Quality Management UL LUL ACCREDITATION ID: 1820 E90



Product Finishing Key (See page 24)

EasyConnect Wire Basket*

30mm side height



Stock length 3000mm.


***Other lengths, dimensions and finishes are available on request, including Hot Dip Galvanised and Stainless Steel.**

Electro Zinc Plated

Part Number	Width mm	Wire Ømm		Weight kg/m	Cross Section (mm²)
		Length	Beam		
EC 30.060 EZ	60	3.9	3.9	0.500	18.78
EC 30.100 EZ	100	3.9	3.9	0.550	26.87
EC 30.150 EZ	150	3.9	3.9	0.700	42.42
EC 30.200 EZ	200	3.9	3.9	0.820	57.97
EC 30.300 EZ	300	4.3	4.3	1.350	87.43

EasyConnect Wire Basket*

100mm side height



Stock length 3000mm.

***Other lengths, dimensions and finishes are available on request, including Hot Dip Galvanised and Stainless Steel.**


Electro Zinc Plated

Part Number	Width mm	Wire Ømm		Weight kg/m	Cross Section (mm²)
		Length	Beam		
EC 100.150 EZ	150	4.3	4.3	1.350	139.24
EC 100.200 EZ	200	4.3	4.3	1.640	191.04
EC 100.300 EZ	300	4.3	4.8	2.200	292.68
EC 100.400 EZ	400	4.6	4.8	2.800	395.88
EC 100.500 EZ	500	4.6	4.8	3.200	499.08
EC 100.600 EZ	600	4.6	4.8	3.600	602.28

PLEASE NOTE:
EasyConnect is also available in a 155mm side wall on request.
See page 147 for information for special profiles available.

EasyConnect Wire Basket*

60mm side height



Stock length 3000mm.

***Other lengths and dimensions are available on request.**

Electro Zinc Plated

Part Number	Width mm	Wire Ømm		Weight kg/m	Cross Section (mm²)
		Length	Beam		
EC 60.060 EZ	60	3.9	3.9	0.720	25.75
EC 60.100 EZ	100	3.9	3.9	0.770	48.47
EC 60.150 EZ	150	3.9	3.9	0.935	76.52
EC 60.200 EZ	200	3.9	3.9	1.070	104.57
EC 60.300 EZ	300	4.3	4.3	1.643	158.63
EC 60.400 EZ	400	4.3	4.8	2.200	211.86
EC 60.450 EZ	450	4.6	4.8	2.420	238.53
EC 60.500 EZ	500	4.6	4.8	2.800	266.73
EC 60.600 EZ	600	4.6	4.8	3.200	321.93

Hot Dip Galvanised*

Part Number	Width mm	Wire Ømm		Weight kg/m	Cross Section (mm²)
		Length	Beam		
EC 60.060 HDG	60	3.9	3.9	0.800	25.75
EC 60.100 HDG	100	3.9	3.9	0.860	48.47
EC 60.150 HDG	150	3.9	3.9	1.020	76.52
EC 60.200 HDG	200	3.9	3.9	1.200	104.57
EC 60.300 HDG	300	4.3	4.3	1.820	158.63
EC 60.400 HDG	400	4.3	4.8	2.380	211.86
EC 60.450 HDG	450	4.6	4.8	2.660	238.53
EC 60.500 HDG	500	4.6	4.8	3.080	266.73
EC 60.600 HDG	600	4.6	4.8	3.560	321.93

Stainless Steel*

Part Number	Width mm	Wire Ømm		Weight kg/m	Cross Section (mm²)
		Length	Beam		
EC 60.060 IN	60	4.0	4.0	0.740	25.50
EC 60.100 IN	100	4.0	4.0	0.840	48.16
EC 60.150 IN	150	4.0	4.0	0.970	76.16
EC 60.200 IN	200	4.0	4.0	1.140	104.16
EC 60.300 IN	300	4.4	4.4	1.740	158.13
EC 60.400 IN	400	4.4	4.8	2.100	211.75
EC 60.450 IN	450	4.4	4.8	2.300	238.46
EC 60.500 IN	500	4.4	4.8	2.460	266.95
EC 60.600 IN	600	4.4	4.8	2.830	322.15

PLEASE NOTE:
Stainless Steel basket available in 304 & 316 Grades.

Divider Strip

Type	Height mm	Weight kg/pc
SEP30SZ	30	1.410
SEP60SZ	60	1.752
SEP100SZ	100	2.505

Divider Fast Fix Clip


Type	Pack Qty	Weight kg/pc
CSEPSZ	50	0.012

Divider Support

Type	Pack Qty	Weight kg/pc
SEP/DSC	50	0.019




Basket Lid



Type	Width mm (X)	Weight /unit
T060SZ	60	0.545
T100SZ	100	0.665
T150SZ	150	0.905
T200SZ	200	1.145
T300SZ	300	1.905
T400SZ	400	2.465
T500SZ	500	3.465
T600SZ	600	4.105

Clic lid system is supplied in 2M lengths. Finished in Pre Galv. Stainless Steel and Hot Dip Galvanised are also available.

Joint Connector



Type	Pack Qty	Weight kg/pc
UUEZ	100	0.027

Central Hanger - Threaded Rod Type




Type	Pack Qty	Weight kg/pc
SC6CH	25	0.032
SC8CH	25	0.032
SD10CH	25	0.032

Support Clamp




Type	Pack Qty	Weight kg/pc
FASEZ	100	0.084

Hold Down Clamp for EC60.060 Basket



Type	Pack Qty	Weight kg/pc
CPUZF	20	0.013


Slotted Steel Strap



Type	Length mm (x)	Pack Qty	Weight /unit
BKSTP270	270	10	0.108
BKSTP1000	1000	10	0.400

20mm wide strap, used to create bends and tees.

Hold Down Clamp to suit 100mm - 600mm wide basket



Type	Pack Qty	Weight kg/pc
SC6EZ	50	0.016
SC8EZ	50	0.016
SC10EZ	50	0.016


05

Fitting Joint Connector

M-CLIC - Create Bends, Tees & Reducers

Type	Pack Qty	Weight kg/pc	Wire Ø mm
MCLIC-ZF-3.9	100	0.084	3.9mm
MCLIC-ZF-4.3	100	0.087	4.3mm
MCLIC-ZF-4.8	100	0.091	4.6mm to 4.8mm





MCLIC-ZF-3.9


Basket	L	C
EC30.060	✓	✓
EC30.100	✓	✓
EC30.150	✓	✓
EC30.200	✓	✓
EC60.060	✓	✓
EC60.100	✓	✓
EC60.150	✓	✓
EC60.200	✓	✓

MCLIC-ZF-4.3

Basket	L	C
EC30.300	✓	✓
EC60.300	✓	✓
EC60.400	✓	✓
EC100.150	✓	✓
EC100.200	✓	✓
EC100.300	✓	X

MCLIC-ZF-4.8

Basket	L	C
EC60.400	X	✓
EC60.500	✓	✓
EC60.600	✓	✓
EC100.300	X	✓
EC100.400	✓	✓
EC100.500	✓	✓




L - Length Wire
C - Beam Wire


*Wire information based on electro zinc basket finish

M-CLIC CONNECTOR

Fast Bends, Tees & Reducers



DESIGNED FOR FAST ASSEMBLY OF JOINTS, REDUCING TIME AND INSTALLATION COSTS.



FAST, SECURE & FLEXIBLE


visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Side Suspension Hanger




Type	Pack Qty	Weight kg/pc
BKSH	50	0.025

Floor Support Bracket



Type	Length mm (X)	Width mm (Y)	Height mm (Z)	Pack Qty
SASEZ	100	80	60	20

Stand Off Bracket



Type	Length mm (X)	Weight /unit
SOB100	100	0.063
SOB150	150	0.103
SOB225	225	0.156
SOB300	300	0.210
SOB450	450	0.252
SOB600	600	0.291

This is a 40mm high stand for floor mounted mesh basket and cable tray. Which can also be used as a wall stand. Finished in Pre Galvanised Steel to (BS EN ISO 1461). Stainless Steel and Hot Dip Galvanised are also available.

Clic Stand Off Bracket



Type	Length mm (X)	Pack Qty
SD60SZ	60	48
SD100SZ	100	48
SD150SZ	150	32
SD200SZ	200	32
SD300SZ	300	16
SD400SZ	400	16

Support Spacer

Type	Pack Qty	Weight kg/pc
ENTSZ	20	0.027

Support Spacer (ENTSZ) should be used withe the wall bracket (SOC) & ceiling bracket (SOPC)



Product Finishing Key (See page 24)

GA CP ST SS EZ


Ceiling Support Bracket



Type	Length mm (X)	Pack Qty	Weight /unit
SOPC10SZ	100	16	0.517
SOPC15SZ	150	12	0.550
SOPC20SZ	200	8	0.623
SOPC30SZ	300	8	0.714

For fixing to horizontal concrete ceiling and walls. Finished in Pre Galv. Stainless Steel and Hot Dip Galvanised are also available.


Wall Support Bracket



Type	Length mm (X)	Pack Qty	Weight /unit
SOC10SZ	100	10	0.342
SOC15SZ	150	10	0.395
SOC20SZ	200	10	0.447
SOC30SZ	300	10	0.554
SOC40SZ	400	10	0.660

For fixing to walls, use in tandem with Support spacer. Finished in Pre Galv. Stainless Steel and Hot Dip Galvanised are also available.

Suspension Support Bracket




Type	Length mm (X)	Pack Qty	Weight /unit
SOA10SZ	100	10	0.211
SOA15SZ	150	10	0.251
SOA20SZ	200	10	0.386
SOA30SZ	300	10	0.496
SOA40SZ	400	10	0.632
SOA50SZ	500	10	0.713
SOA60SZ	600	10	0.822

Suspension bracket with Clic connection. Finished in Pre Galv. Stainless Steel and Hot Dip Galvanised are also available.




Conduit Take Off Bracket

For Both ø20 & ø25 conduit



Sidewall Mounted *




Base Mounted **

Type	Weight kg/pc
BKCB20-25	0.485

*Fitted on (sidewall EC.60 & EC.105 ranges)
** Fitted on (base EC.30, EC.60 & EC.105 ranges)
Basket shown for illustration purposes only

Wall Support Clic Bracket




Type	Weight kg/pc
SESZ	0.046

Drop Out Plate



Type	Pack Qty
SC-S	50

Wall Mounting Bracket



Type	Length mm (x)	Weight /unit
BKMP65	65	0.840
BKMP90	90	1.056

Plastic End Cap



Type	Pack Qty
INVSO	20


For Supports on Page 99.


Product Finishing Key (See page 24)

GA CP ST SS EZ

05

Basket to Channel clip






Type	Pack Qty	Weight kg/pc
UFC41M	50	0.018


See Page 101, for more information. Basket & Channel shown for illustration purposes only

Wall or Box Support Bracket 30mm



Type	Weight kg/pc
PSA30SZ	0.725

Wall or Box Support Bracket 60mm




Type	Pack Qty	Weight kg/pc
PS60G	20	0.550


Other finished are available on request

Earthing Clamp

Screw fixed Lug to provide earthing point.




Type	Pack Qty
MAT	50



visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Plastic ID tags



Type	Pack Qty	Ref.
Orange	1	BKIDO
Yellow	1	BKIDY
Blue	1	BKIDG
Green	1	BKIDG

To allow contractor to colour code and index cable installations.

Bolt Cutter




Type	Max Wire Ø mm	Weight kg/pc
BFR/CUTTERS	7	1.594

Bolt cutter complete with 30° offset jaw and flush cut.

G Profile Basket


Ref. On Request

Ideal for mounting to a ceiling or even direct to a wall. While maintaining the fast fix easy connect.




Basket Loading Information


SAFE WORKLOAD - EASYCONNECT 30



SAFE WORKLOAD - EASYCONNECT 60



SAFE WORKLOAD - EASYCONNECT 100




Product Finishing Key (See page 24)

GA CP ST SS EZ

BASKET TO CHANNEL RAPID INSTALLATION

Designed for Cable Baskets Systems



FAST & SIMPLE

SECURE & EASY TO INSTALL



The UFC41M clip will secure the basket onto UC4121, UC4141 channel & channel Cantilever Arms. This clip works best with Unitrunks' Intelok Channel, as the serration on the return flange provides maximum slip resistance under a side load/impact.

The clip is simple to fit; slot it in over the bar on the basket and using a star head screwdriver simply turn the clip through 90° to secure.

UNITRUNK CASE STUDY



TOP OF THE CLASS

> Overall this project ran smoothly with both excellent products and services provided by Unitrunk.

John McLain, Contracts Manager,
Blackbourne Integrated M & E



Queen's University Belfast has a record of academic achievement which stretches back more than 150 years with 300 buildings and over 24,000 students. A new addition is The Library which brings together wide-ranging library, computing and media services in a single location, blending the best features of a traditional library with the latest technology. The highest quality services and support are fully integrated within the building, making it an exciting and essential part of the student experience at Queen's. Sustainability was a critical factor in the design and construction of The Library, in keeping with the University's environmental policy with the building meeting the highest environmental standards.

The Unitrunk cable trunking and cable tray act as the main arteries of this spectacular new library and carry cabling to a vast array of state-of-the-art systems present throughout the building. To meet the client design requirements all cable management products were concealed.

PRODUCTS

- Standard Trunking
- MR Cable Tray
- HR Cable Tray

UNITRUNK INTELOK®

SECTION 7

CHANNEL & SUPPORT SYSTEMS

Unitrunk Intelok Channel is a strong, easy to erect support system, ideal for supporting cable trays, cable ladders, pipes and ducting and is adaptable for use in many other applications. The flanges on Intelok channel are serrated to give improved slip resistance over that of conventional 'strut' systems, particularly when Intelok channel nuts are used.

Intelok channels are made in deep, shallow and multiple combination profiles. Standard lengths are either 3 or 6 metres, with other lengths available to order. When used with our extensive range of brackets, an infinite variety of frameworks and structures can be created. Intelok channels conform to BS6946.

Unitrunk Intelok Channels are supplied in the following finishes

STRAIGHT CHANNEL

GM Hot dip galvanized Structural Steel (Steel BS EN 10025-2 and Galvanising BS EN 1461:2009)

QQ Pre-Galvanised Structural Steel (Steel BS EN 10326)

BRACKETS

GA Hot dip galvanized Mild Steel (Steel BS EN 10111 / BS EN 10130 and Galvanising BS EN 1461:2009)

STRAIGHT CHANNEL & BRACKET


SS Stainless steel grade 1.4404 (316 marine) to BS EN 10088-2:2005


ACCREDITED TO THE FOLLOWING STANDARDS

CE LUL ACCREDITATION ID: 1822

The safe loading figures are based on


a) The x-x axis
b) A simply supported beam
c) Pre-galvanised steel - yield 250N/mm2
d) A safety factor of 1.6 against yield






Shallow Channel

Ref.	Length	Finish
UC4121/3	3m	Galvanized to BS EN10346
UC4121/6	6m	Galvanized to BS EN10346
GAUC4121/3	3m	Hot Dipped to BS EN ISO 1461
GAUC4121/6	6m	Hot Dipped to BS EN ISO 1461







Span m	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load*mm	1.70	3.90	6.90	15.60	27.70	43.30	62.30
Safe UDL **kg	259	172	128	84	61	47	38

* Including weight of channel.
** Excluding weight of channel.

Slotted Shallow Channel

Ref.	Length	Finish
UC412IS/3	3m	Galvanized to BS EN10346
UC4121S/6	6m	Galvanized to BS EN10346
GAUC4121S/3	3m	Hot Dipped to BS EN ISO 1461
GAUC4121S/6	6m	Hot Dipped to BS EN ISO 1461







Span m	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load*mm	1.90	4.30	7.70	17.30	30.70	48.00	69.10
Safe UDL **kg	238	158	118	77	56	44	35

Deep Channel

Ref.	Length	Finish
UC4141/3	3m	Galvanized to BS EN10346
UC4141/6	6m	Galvanized to BS EN10346
GAUC4141/3	3m	Hot Dipped to BS EN ISO 1461
GAUC4141/6	6m	Hot Dipped to BS EN ISO 1461







Span m	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load*mm	0.90	2.10	3.70	8.20	14.60	22.80	32.90
Safe UDL **kg	837	557	416	275	204	161	132

Slotted Deep Channel

Ref.	Length	Finish
UC414IS/3	3m	Galvanized to BS EN10346
UC4141S/6	6m	Galvanized to BS EN10346
GAUC4141S/3	3m	Hot Dipped to BS EN ISO 1461
GAUC4141S/6	6m	Hot Dipped to BS EN ISO 1461







Span m	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load*mm	1.00	2.20	4.00	8.90	15.90	24.80	35.70
Safe UDL **kg	776	516	386	255	189	149	122

Back To Back Shallow Channel

Ref.	Length	Finish
UC4142/3	3m	Galvanized to BS EN10346
UC4142/6	6m	Galvanized to BS EN10346
GAUC4142/3	3m	Hot Dipped to BS EN ISO 1461
GAUC4142/6	6m	Hot Dipped to BS EN ISO 1461





Span m	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load*mm	1.00	2.30	4.10	9.20	16.40	25.60	36.80
Safe UDL **kg	736	489	365	240	177	138	112

(Solid Channel in stock, slotted on request)


visit online: uk unitrunk.co.uk ireland unitrunk.ie

UNITRUNK INTELOK® SERRATED CHANNEL

Back To Back Deep Channel

Ref.	Length	Finish
UC4182/3	3m	Galvanized to BS EN10346
UC4182/6	6m	Galvanized to BS EN10346
UC418S/3	3m	Galvanized to BS EN10346 (Slotted)
UC418S/6	6m	Galvanized to BS EN10346 (Slotted)
GAUC4182/3	3m	Hot Dipped to BS EN ISO 1461
GAUC4182/6	6m	Hot Dipped to BS EN ISO 1461

Span m	0.50	0.75	1.00	1.50	2.00	2.50	3.00
Deflection at load*mm	0.50	1.10	2.00	4.60	8.20	12.80	18.40
Safe UDL **kg	2372	1579	1186	784	583	462	380






(Solid Channel in stock, slotted on request)

Tray to Channel Klip


Ref. CHTR 25 (KLMR)

Ref. CHTR 50 (KLHR)



Basket to Channel clip


Ref. UFC41M



GA Standard Finish on Channel Brackets


Square Plate

Ref.	Size
325AJ03	6mm
325AJ05	8mm
325AJ07	10mm
325AJ10	12mm




Two Hole Plate

Ref.325AD11




Three Hole Plate

Ref.325AC11




Four Hole Plate

Ref.325AC13




Five Hole Plate

Ref.325AY10



L Bracket

Ref.325AG10




Right Angle Bracket

Ref.325AS10



T Bracket

Ref.325AF13



Right Angle Bracket

Ref.325AC09



Product Finishing Key (See page 104)


QQ GA CP SS

Standard Finish on Channel Brackets

Right Angle Bracket
Ref.325AD10



Deep 'U' Bracket
Ref.325AJ12



Right Angle Bracket
Ref.325AC10



Right Angle Bracket
Ref.325AE10



Right Angle Bracket
Ref.325AE11



Right Angle Shelf Bracket
Ref.325AE12



Right Angle Bracket
Ref.325AQ10




Right Angle Bracket
Ref.325AQ11




Right Angle Bracket
Ref.325AQ12




Shallow Z Bracket
Ref.325AD28



Deep Z Bracket
Ref.325AC12




Multiple Z Bracket
Ref.325AU10




Back to Back Bracket
Ref.325AT11



'W' Shaped Deep Bracket
Ref.325AU15



Double Channel Bracket
Ref.325AJ11




visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

GA Standard Finish on Channel Brackets

Shallow 'U' Bracket
Ref.325AJ13




Multi-Channel Bracket
Ref.325AJ14




Single Channel Base Plate
Ref.325AR10



Single Channel Base Plate
Ref.325AN10



Double Channel Base Plate
Ref.325AT10



Two Leg Wing Fitting
Ref.325AV10



Three Leg Wing Fitting
Ref.325AV09



Wing Fitting with Gussets
Ref.325AW01



3 Way Corner Bracket
Ref.325AV02




Double Channel Wing Fitting
Ref.325AWO2



Channel Support Bracket R/H
Ref.325AG16



Channel Support Bracket L/H
Ref.325AG15




Channel Support Bracket
Ref.325AF10



L/H Channel Support Bracket
Ref.325AF11



R/H Channel Support Bracket
Ref.325AF12




Product Finishing Key (See page 104)

QQ GA CP SS

Standard Finish on Channel Brackets

45°Angle Bracket

Ref.325AF14



Acute Angle Bracket 45°

Ref.325AH11



Obtuse Angle Bracket 45°

Ref.325AD17

Other angles to Order



Shallow External Connector

Ref.325AK11



Shallow Connector

Ref.336AB07

M10 setscrews supplied separately.



Deep Connector

Ref.336AB08




Deep External Connector

Ref.325AK10



Cross Support Bracket

Ref.325AB10



Beam Clamp

Ref.325AP11




Beam Clamp

Ref.325AX10

Including M12x40 Cone point screw

For Flange thickness up to 18mm.



Beam Clamp

Ref.325AX11

Including M12x40 Cone point screw

For Flange thickness up to 17mm.



Beam Clamp (Deep Back to Back Window)

Ref.325AL09

Including M10x40 Cone point screw

For Flange thickness up to 15mm.




Beam Clamp (Shallow Channel)

Ref.325AL11

Including cone point set screw.


For Flange thickness up to 15mm.



Beam Clamp (Deep Channel)

Ref.325AL10

Including cone point set screw.




Beam Clamp

Ref.325AP10

Including cone point set screw.

For Flange thickness up to 17mm.



visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

GA Standard Finish on Channel Brackets

Beam Clamp
(Back to Back Deep Channel)

Ref.325AM12


Supplied singly with nuts, bolts and washers.



Heavy Duty Beam Clamp
(Back to Back Deep Channel)

Ref. 325AM13*
Ref. 325AM14**

*Up to 25mm flange range.
**25-40mm flange range.




Beam Clamp
(Deep Channel)

Ref.325AM10

25mm flange range.

Also suitable for shallow channel up to 25mm.



'Z' Purlin Clip
(M10 Hole)

Ref.389AH10




Cone Pointed Bolts

Ref.	Thread Size
UCM10/CPB	M10x40




End Cap (Shallow)

Ref.	Finish
325AA11	Black PVC
325AA13	White PVC




End Cap (Deep)

Ref.	Finish
325AA10	Black PVC
325AA12	White PVC




Cover Strip

Ref.	Length	Finish
339AA10	3m long	White PVC (Available in black to special order)
339AB10	3m long	Pre-Galvanised




Single Channel Cantilever Arm

Ref.	Product	Arm Length
CARMSCP150GM	2 Hole	150mm
CARMSCP300GM	2 Hole	300mm
CARMSCP450GM	2 Hole	450mm
CARMSCP600GM	2 Hole	600mm
CARMSCP750GM	2 Hole	750mm
CARMSCP900GM	2 Hole	900mm



Back to Back Cantilever Arm


Ref.	Product	Arm Length
CARMBBP150GM	2 Hole	150mm
CARMBBP300GM	2 Hole	300mm
CARMBBP450GM	2 Hole	450mm
CARMBBP600GM	2 Hole	600mm
CARMBBP750GM	2 Hole	750mm
CARMBBP900GM	2 Hole	900mm



Short Spring Channel Nuts

Ref.	Thread
UCM6/S	M6
UCM8/S	M8
UCM10/S	M10
UCM12/S	M12


Sold in 100's



Long Spring Channel Nuts

Ref.	Thread
UCM6/L	M6
UCM8/L	M8
UCM10/L	M10
UCM12/L	M12


Sold in 100's



Channel Nuts Less Spring

Ref.	Thread
UCM6/N	M6
UCM8/N	M8
UCM10/N	M10
UCM12/N	M12

Sold in 100's




DON'T FORGET THE NUTS & BOLTS OF IT...

REMEMBER TO CHECK SECTION 12

For all your Accessories & Supports needs

SEE PAGE 154



visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

UNITRUNK CASE STUDY



INNOVATION FOR THE PREMIER LEAGUE

> Very visible from the exterior of the building so, for a practical and aesthetic solution, we used risers of Unitrunk's UniKlip perforated steel cable tray with lids

Dale Robinson, Contracts Manager, Direct Technology UK

Newcastle United's St James's Park stadium is one of the city's most iconic structures. Improvement to the stadium's lighting was required, due to new F.A. specifications for television broadcast. By having a glass cantilever roof, restrictions to loading were necessary and the need to protect the stadium's aesthetics were addressed by contractor, Direct Technology UK, by using Unitrunk's Rapid Installation System (RIS), cable tray and cable basket.

The project began at the height of the football season, with work scheduled around fixtures while ensuring that existing floodlights remained operational on match days. Unitrunk's Rapid Installation Systems (RIS) products ensured installation speed and flexibility, helping the contractor complete the installation on schedule.



PRODUCTS

- Cable Basket
- Heavy Duty Galvanised After Tray
- UniKlip Pre Galv Tray
- Tray Lids

UNITRUNK


Total Cable Management Solutions

SECTION 8


FLOOR TRUNKING SYSTEMS

Unitrunk's floor trunking systems have been designed to cater for a wide range of applications and cable management. The range includes the following systems:


EASY-WAY FLUSH FLOOR TRUNKING SYSTEMS: Designed to offer versitility within the trunking layout giving the end user final option as to the position of the service boxes. The Easy-Way system also permits the relocation or addition of the service outlets after completion of the installation.



UNDER FLOOR (IN SCREED) TRUNKING SYSTEMS: Completely buried in-screed, underfloor trunking is used for applications that require access through inspection boxes or service outlets for discrete cable management.



CAVITY FLOOR TRUNKING SYSTEMS: Simple and easy to install, offering efficient cable management with excellent flexibility and providing ease of access to telephone, data and power outlets.



ACCREDITED TO THE FOLLOWING STANDARDS

CE bsi. ISO 9001 Quality Management

EASY-WAY FLUSH FLOOR TRUNKING SYSTEMS



UNITRUNK EASY-WAY FLUSH FLOOR TRUNKING is designed to offer versatility within the trunking layout, giving the end user the final option to ammend the position of the service outlets. The Easy-Way system also permits the relocation or addition of service outlets after the initial installation is complete.

INSTALLATIONS - Easy-way flush floor trunking is 65mm high trunking which can be installed into new builds and existing installations. Here are some installation tips and best practices that should be considered when planning and installing Easyway trunking products:


1. ALLOW ACCESS (EXISTING INSTALLATIONS ONLY) - A level opening for the trunking should be cut in the screed which allows access for tooling.

2. SOLID FOUNDATION - The trunking should be laid on a supporting screed ribbon or a support grout approved by an architect or consultant.

3. LID SUPPORT - The galvanised lids and service outlet boxes should be in position when the screed is poured, otherwise the pressure may distort the trunking sidewalls.

4. NO VOIDS - After final levelling of the trunking and before coupling together, the screed or grout bedding should be fully packed under the trunking to eliminate any voids, which could result In soft spots of the trunking assembly.

5. COMPACT & LEVEL - When applying the screed, the screed layer must be installed with care. The screed should be compacted to provide good static support of the trunking system. Ensure the screed is level with the trunking lid to prevent line shadowing on any final floor finish.



These diagrams are for guidance only. Unitrunk accepts no responsibility for any aspect of product installation.


visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

UNITRUNK EASY-WAY FLUSH FLOOR TRUNKING - Is supplied In two standard widths 310mm wide or 366mm wide. Each 2.4M length comes with four lids to accommodate service outlets. Turnbuckle lid fixings and removable dividers give the end user great flexibility when positioning services.

UNITRUNK EASY-WAY SERVICE OUTLET - Is installed in the trunking length, functioning as the support housing adapter for either service outlet lids or Inspection lids.

UNITRUNK FLOOR SYSTEM OUTLET LIDS - Accessed from finished floor. These lids can be compatible across all floor systems trunking supplied as either service or inspection. Lids are supplied in two widths which should be ordered to match your application.

UNITRUNK SEVICE OUTLET PLATES - The vast range of service outlet plate acts as housing within the trunking for electrical components. They can be compatible across all floor systems trunking, when ordering ensure the outlet plates match your application. (SEE PAGE 124-126 FOR OUTLET PLATES)




WHAT TO ORDER


Type	Service Outlet	Service Outlet Panels	Lid
EWTG3	EWS03	EW755, EW756, EW759, EW763, EW764, EW767	CTI3 (Inspection lid) CTS3 (Service lid)
EWTG43x3	EWS043	EW103, EW105, EW106, EW109, EW113, EW114, EW125	CTI43 (Inspection lid) CTS43 (Service lid)
EWTG43x4		EW755, EW756, EW759, EW763, EW764, EW767	CTI43 (Inspection lid) CTS43 (Service lid)


Product Finishing Key (See page 24)


Easyway Trunking

Ref. EWTG3 - (310mm - 3 Compartment)
Ref. EWTG43x3 - (366mm - 3 Compartment)
Ref. EWTG43x4 - (366mm - 4 Compartment)









Service Outlet Lid

Ref. CT/S3

For use with EWSO3

Ref. CT/S43

For use with EWSO43.



Supplied with a 7mm recess & PVC Trim. Stainess Steel Trim & Deeper recesses are available (Made to order)


Inspection Lid

Ref. CT/I3

For use with EWSO3

Ref. CT/I43

For use with EWSO43.




Supplied with a 7mm recess & PVC Trim. Stainess Steel Trim & Deeper recesses are available (Made to order)

Service Outlet Frame

Ref. EWSO3 - (310mm - 3 Compartment)
Ref. EWSO43 - (366mm - 3 or 4 Compartment)

When ordering PVC Trim:
SERVICE Ref: CT/S 3 or CT/S 43
INSPECTION Ref: CT/I 3 or CT/I 43



Height Adjustable Coupling (18mm Max)

Ref. EWTG3 - (376mm)
Ref. EWTG43 - (432mm)

Supplied in Singles




Riser Bend

Ref.EWRB3
(3 Compartment)

Ref.EWRB43x3
(3 Compartment)


Ref.EWRB43x4
(4 Compartment)



Blank End

Ref. EWBE3

Ref. EWBE43



visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Universal Fitting
Tee/Bend/Intersection

Ref. EWUF3

(3 Compartment) 393mm sq x 65mm sq

Ref. EWUF43x3

(3 Compartment) 449mm sq x 65mm sq

Ref. EWUF43x4

(4 Compartment) 449mm sq x 65mm sq

Note: Not to be used as outlet box when used as tee/bend or intersection.


Ref. EWUF310INSFRAME


Ref. EWUF366INSFRAME

To add an Inspection lid to the universal fitting

Order: EWUF310INSFRAME - CTI3 LID.
Or
IEWUF366INSFRAME - CT143 LID

(CTS3 shown as illustration only)





1 Replace plate with CT/I3, 43 & EWUF***INSFRAME when the universal fitting is to have an inspection point.

2 Corner screws allow fine adjustment to compensate for irregularities in screed levels.

EWUF 3 (3 compartment)

Underpasses: Ⓐ 75 x 25mm
Ⓑ 93 x 25mm
Overall width: 393mm sq. x 65

EWUF 43 (3 compartment)

Underpasses: Ⓐ 98 x 25mm
Ⓑ 109 x 25mm
Overall width: 449mm sq. x 65

EWUF 43 (4 compartment)

Underpasses: Ⓐ 75.5 x 25mm
Ⓑ 75.5 x 25mm
Ⓒ 82 x 25mm
Overall width: 449mm sq. x 65



Product Finishing Key (See page 24)

PG ST CP

In 1876 Alexander Graham Bell invents the first ever telephone...



...In 2010 Unitrunk creates Uniklip, the first klip together system for Cable Tray



UNITRUNK RIS

EVERYTHING CHANGES

DO YOU WANT TO MAKE MORE MONEY & WIN MORE BUSINESS?

THEN YOU NEED **UNIKLIP** THE **FASTEST** CABLE TRAY SYSTEM ON THE MARKET.

UNIKLIP® UNITRUNK

Unitrunk Cavity Floor Trunking is manufactured in a variety of 'standard' formats as indicated in this catalogue but is available as a flexible solution designed to meet the potentially complex cabling and flooring requirements of today's workplace.

The system can be designed and manufactured to suit a wide range of Power, Data and Communications cabling systems. Additionally, the Cavity Floor Outlet Box can be supplied with lids to accommodate a wide variety of flooring finishes from standard carpet tiles through to marble, specialised ceramics and architecturally designed solid wood flooring systems.

SYSTEM ACCESSORIES & SERVICE OUTLETS

To meet the demands of a rapidly growing market, Unitrunk have produced a widely variable package which can be manufactured to fulfil the needs of the most intricate office technology and floor plans.

Our cavity floor trunking is simple and easy to install, offering efficient cable management with excellent flexibility and providing ease of access to telephone, data and power outlets.

CAVITY FLOOR TRUNKING Ref. C.F.T.K.

Manufactured in 3 metre lengths, each length comes complete with lid, connectors, screws and nuts. Lids are held in position by a slotted stud, the stud indicates the position of the locking bar.
Standard size 225 x 38 (mm) x 3 compartment.

Other sizes of trunking may be used provided consideration is given to cable capacity for the size selected.



Ref. CFTOB

Box height 40mm

Ref. TK

Available in 3 metre lengths
Standard size - 3 compartments
225mm x 38mm

Product Finishing Key (See page 24)

THE UNITRUNK 43 SERIES cavity floor service box is manufactured for use with a wide variety of service outlet panels. The cavity floor box can also be used as an inscreed option with conduit


THE BASE BOX is manufactured from galvanised steel and available in 1,2, 3 or 4 compartments (same external dimension). Each compartment has 20mm and 25mm knockouts in each long side to accept flexible conduits. These entries can be replaced with rubber grommets to allow cable access. Dividing fillets are provided to separate services. The base box comes complete with a wide range of interchangeable accessory panels that can be supplied with or without respective accessories. The base box is suitable for mounting in a 335mm x 220mm hole cut into any access floor panel with two fixing holes in each long side or side fixing plates on short sides of box can be screw fixed to bottom of floor tile.

RECESSED LID/TRIM ASSEMBLY The hinged recessed lid is manufactured from 2.5mm galvanised steel, and finished grey epoxy coated to match the polyproplene carpet trim. The lid is fitted with a polyproplene insert which houses cable outlets and a lifting handle. The lid pivots to an angle of 80°. The carpet trim is manufactured from polyproplene and finished grey in colour and supported with a galvanised steel frame. The recessed lid assembly is fixed to the base box by two 5mm screws which are located at each side of the frame. All parts of the lid assembly are replaceable.

TECHNICAL INFORMATION
Floor finish recess in lid: 7mm
Assembled box depth: 75.5mm
Space under outlet panels: 40mm

Variations of Cavity Floor Box Depth can be supplied to order.

Service Outlet Assemblies





SERVICE Ref. CT/S 43 (Shown)
INSPECTION Ref. CT/I 43

SERVICE OUTLET PANELS (See page 124)

Ref. CFSO 43x3 (Shown)
Ref. CFSO 43x4

Overall depth 75.5mm






Cavity Floor Boxes

Single Compartment Cavity Floor Box

Ref. CFSO1C






Made to order

Two Compartment Cavity Floor Box

Ref. CFSO2C






Made to order

Three Compartment Cavity Floor Box

Ref. CFSO43X3






Four Compartment Cavity Floor Box

Ref. CFSO43X4






WHAT TO ORDER

Type	Compartment	Service Outlet Panels	Lid
CFSO1C	1	**EW103, EW105, EW106, EW109, EW113, EW114, EW125, EW166**	**Service Lid included with box**
CFSO2C	2	EW103, EW105, EW106, EW109, EW113, EW114, EW125, EW166	**CTS3 (Service Lid) or CTI3 (Inspection Lid)**
CFSO43X3	3	**EW755, EW756, EW759, EW763, EW764, EW766, EW767**	**CTS43 (Service Lid) or CTI43 (Inspection Lid)**
CFSO43X4	4	EW103, EW105, EW106, EW109, EW113, EW114, EW125, EW166	CTS43 (Service Lid) or CTI43 (Inspection Lid)

Cavity Floor Trunking


Ref. TK

Available in 3 metre lengths. Standard size - 3 compartments 225mm x 38mm.



Gusset Bend


Ref. GTB



Riser Bend


Ref. GIB

Overall height 82mm.




Four-way Intersection

Ref. ITB



Gusset Tee

Ref. GTT



Tap-off Box

Ref. CFTB


Box height 40mm.



Tap-off Lid


Ref. CFTL

Alternative to Tap-off Box Knock-outs (20mm) in each compartment.




Trunking Coupling

Ref. TC



Blank End

Ref. BE



visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Service Outlet Panels


Can be used across a wide range of trunking floor systems. Plates are manufactured as EW7 series (75mm wide) & EW1 series (100mm wide).

Please refer to the product tables for cavity floor service outlet, easyway & underfloor universal fittings to ensure compatibility with your desired product.

****Sockets and RJ45s are available on request.**

EW7 Series Service outlet Panels (75mm x 195mm)

Ref. EW755




Panel to accept 2xLJ2 single telephone outlets (UK only, 50mm centres).

Ref. EW756




Blank Panel.

Ref. EW759




Panel to accept 4 x LJ6/RJ45 snap in connectors cut out size 36.70 x 22.50.

Ref. EW763



Panel to accept 1 twin switched MK2532 WHI panel socket 13A side wired.

Ref. MK2532**




For use with EW763 & EW113, side wired.

Ref. EW766




Wave Panel to accept 4 x LJ6/RJ45 snap in connectors cut out size 36.70 x 22.50.

Ref. EW764



Panel to accept 1 twin switched panel socket 13A rear wired for use in cavity floor box only ref. Volex MC1500.

Ref. MC1500**



For use with EW764 & EW114, Twin Earth.

Ref. EW767



50mm x 25mm Cutouts

Product Finishing Key (See page 24)

PG ST CP

FLOOR SYSTEMS SERVICE PLATES


EW1 Series Service outlet Panels (100mm x 195mm)

Ref. EW103




Panel to accept 3 single unswitched panel sockets 13A side wired e.g. Crabtree 7259 or MK735.

Ref. EW105



Panel to accept 2xLJ3, 2xLJ4, 2xLJ5 single telephone outlets (UK only).

Ref. EW106




Blank panel.

Ref. EW109




Panel to accept 4 x LJ6/RJ45 snap in connectors cut out size 36.70 x 22.50.

Ref. EW113



Panel to accept 1 twin switched MK2532 WHI panel socket 13A side wired.

Ref. MK2532**




For use with EW763 & EW113, side wired.

Ref. EW114



Panel to accept 1 twin switched panel socket 13A rear wired for use in cavity floor box only ref. Volex MC1500.

Ref. MC1500**




For use with EW764 & EW114, Twin Earth.

Ref. EW125



Plate to accept a standard twin socket. To suit 2G outlet.

Ref. EW166



Wave Panel to accept 4 x LJ6/RJ45 snap in connectors cut out size 36.70 x 22.50.

Ref. EW167



50mm x 25mm Cutouts


		EW755	EW756	EW759	EW763	EW764	EW766	EW767	EW103	EW105	EW106	EW109	EW113	EW114	EW125	EW166	EW167
EASYWAY	EWSO3	✓	✓	✓	✓	✓	X	✓	X	X	X	X	X	X	X	X	X
	EWSO43 (when using 3 Compartment)	X	X	X	X	X	X	X	✓	✓	✓	✓	✓	✓	✓	X	✓
	EWSO43 (when using 4 compartment)	✓	✓	✓	✓	✓	X	✓	X	X	X	X	X	X	X	X	X
CAVITY FLOOR	CFSO1C	X	X	X	X	X	X	X	✓	✓	✓	✓	✓	✓	✓	✓	✓
	CFSO2C	X	X	X	X	X	X	X	✓	✓	✓	✓	✓	✓	✓	✓	✓
	CFSO43x3	X	X	X	X	X	X	X	✓	✓	✓	✓	✓	✓	✓	✓	✓
	CFSO43x4	✓	✓	✓	✓	✓	✓	✓	X	X	X	X	X	X	X	X	X
UNDER FLOOR	UFUF9	✓	✓	✓	✓	✓	✓	✓	X	X	X	X	X	X	X	X	X
	UFUF12 (when using 3 Compartment)	X	X	X	X	X	X	X	✓	✓	✓	✓	✓	✓	✓	✓	✓
	UFUF12 (when using 4 Compartment)	✓	✓	✓	✓	✓	✓	✓	X	X	X	X	X	X	X	X	X

visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

SYSTEM ACCESSORIES & SERVICE OUTLETS


	*Single Compartment	*Two Compartment	Three Compartment	*Four Compartment
Sizes (width x depth)	**Ref. UF1**	**Ref. UF2**	**Ref. UF3**	**Ref. UF4**
150x25mm	•	•		
150x38mm	•	•		
225x25mm		•	•	
225x38mm		•	•	
300x25mm			•	•
300x38mm			•	•

*Special Order




Compartment Dimensions

U.F.3



U.F.43x4




Product Finishing Key (See page 24)

Underfloor Trunking


Ref. UF

Supplied in 3m lengths
as per adjacent table



Flange Coupling


Ref. UFFC



Underfloor Coupling

Ref. UFTC

1 off supplied/ 3m length.



Service Outlet (PVC Trim)

Ref. CT/S 3

For use with UFUF9.

Ref. CT/S 43

For use with UFUF12.




Supplied with a 7mm recess & PVC Trim. Stainless Steel Trim & Deeper recesses are available (Made to order)

Riser Bend

Ref.UFRB

Trunking height	URFB height (H)
25mm	130mm
38mm	142mm

Depth of screed should also
be quoted when ordering.



Adjustable Collar

(For Under Floor) Universal Fitting 9 & 12

See Page 129



Height can be manufactured to suit customer requirements.
Please specify screed depth and adjustable range required when ordering.

Riser Bend

(From underfloor into skirting trunking)

Ref.UFST


Depth of screed should also
be quoted when ordering.



Riser Flange

Ref.UFRF


Depth of screed should also
be quoted when ordering.



Underfloor Blank End

Ref. UFBE

For use with UFUF69.




Inspection Lid

Ref. CT/13

For use with UFUF9.

Ref. CT/143

For use with UFUF12.



Supplied with a 7mm recess & PVC Trim. Stainless Steel Trim & Deeper recesses are available (Made to order)

visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

UNITRUNK

Universal Fitting

Ref. UFUF 9X3

For use with UF3 Trunking.

Ref. UFUF 12X4

For use with UF4 Trunking
Supplied with polystyrene block
to prevent screed ingress.


Inspection Trim

Ref. CT/I 3

For use with UFUF69.

Ref. CT/I 43

For use with UFUF12.



Exit panels
Supplied with the Universal Fitting, Exit Panels are fully reversible. When trunking entry is required for 225mmx25mm see diagram (Ref.A). For 225mmx38mm remove plate (Ref.A). Alternatively conduit exits may be created by removing knock-outs (Ref.B).


Universal Fitting

UFUF9 Underpass Layout
Overall dimensions 379mm sq.

Universal Fitting Dimensions


UFUF 9 (3 compartment)

Underpasses: A 75 x 13mm
B 75 x 13mm
Overall width: 350mm sq.
Overall height: 78mm (including base rivet bushes)



UFUF 12 (4 compartment)

Underpasses: A 75 x 13mm
B 75 x 13mm
C 75 x 13mm
Overall width: 452mm sq.
Overall height: 78mm (including base rivet bushes)



Product Finishing Key (See page 24)

PG ST CP


Underfloor Adjustable Collar

(For Under Floor) Universal Fitting 9 & 12


Designed for situations where floor levels are not consistent.

For applications with deeper screed

Also where a deeper void is required within the box to suit larger plug fittings.



Ref. Code 9 Series	Ref. Code 12 Series	Screed Min	Screed Max
UF9ADJCOL-SCREED-92-RANGE-015	UF12ADJCOL-SCREED-92-RANGE-015	85mm	100mm
UF9ADJCOL-SCREED-100-RANGE-020	UF12ADJCOL-SCREED-100-RANGE-020	90mm	110mm
UF9ADJCOL-SCREED-112-RANGE-025	UF12ADJCOL-SCREED-112-RANGE-025	100mm	125mm
UF9ADJCOL-SCREED-135-RANGE-030	UF12ADJCOL-SCREED-135-RANGE-030	120mm	150mm
UF9ADJCOL-SCREED-155-RANGE-030	UF12ADJCOL-SCREED-155-RANGE-030	140mm	170mm
UF9ADJCOL-SCREED-175-RANGE-030	UF12ADJCOL-SCREED-175-RANGE-030	160mm	190mm
UF9ADJCOL-SCREED-200-RANGE-040	UF12ADJCOL-SCREED-200-RANGE-040	180mm	220mm
UF9ADJCOL-SCREED-220-RANGE-020	UF12ADJCOL-SCREED-220-RANGE-020	210mm	230mm



These diagrams are for guidance only. Unitrunk accepts no responsibility for any aspect of product installation.

visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

UNITRUNK CASE STUDY



A TRUE ICON


> Unitrunk are honoured to be part of such a prestigious project. The Signature Building celebrates a true historical icon and we are very proud to be associated with it.

David Morrow, General Manager, Unitrunk

Belfast is gearing up to celebrate a legend. And Unitrunk are right in the thick of it.

2012 marked the centenary of the maiden voyage of the world's most famous ship, the Titanic. As part of the celebrations, the stunning Titanic Signature Building will become the largest man-made tourist attraction in Northern Ireland's history. It will have six floors and nine galleries, telling Titanic's story from its conception to its tragic demise.

As the celebrations take place on the doorstep of Unitrunk HQ in Lisburn, Unitrunk took great pride in supplying a range of products – including trunking and tray – to get the exciting project ready ahead of the big party next year.



PRODUCTS

- Speedway SW4 Cable Ladder
- Cable Tray
- Standard Trunking
- Bespoke Floor Trunking

UNITRUNK


Total Cable Management Solutions


SECTION 9

BENCH OUTLET BOXES & PERIMETER TRUNKING

Bench Trunking


Unitrunk Bench Trunking is manufactured with a galvanised sheet steel body to BS EN 10346:2009 in 3 metre lengths as standard although any length can be supplied to order to suit any application. Each length is provided with coupling and screws. The cover can be supplied punched to accept socket outlets or other accessories.





Skirting Trunking

Unitrunk Skirting Trunking is easily fitted and is available in 3 metre lengths with all the necessary bends etc, to form a complete installation. Trunking is designed for installation after wall and floor surfaces have been completed. Tee Pieces, Pier Sets etc, can be supplied to customer requirements.



ACCREDITED TO THE FOLLOWING STANDARDS

CE bsi. ISO 9001 Quality Management

Dado Trunking

Unitrunk Dado trunking is available in 3 metre lengths with all the necessary bends etc, to form a complete installation.

UNITRUNK SKIRTING TRUNKING is easily fitted and is available with all the necessary bends etc. to form a complete installation. Types S1 and S2 are designed for installation after wall and floor surfaces have been completed. Tee pieces, Threshold Units, Pier Sets etc., can be supplied to customer requirements.

The body and divider of the standard skirting trunking are manufactured from galvanised sheet steel to BS EN 50085-1 :2005 plus BS EN 50085-1-2:2006.

The cover is made from galvanised sheet steel and can be finished in epoxy/polyester coating of any colour on request. All trunking is supplied in 3 metre lengths as standard, complete with joining plates and screws.


S1 and S2 trunking is supplied with compartments as shown and is therefore suitable for carrying mains, telephone and VDU or other low voltage circuits. The dividers have provision every 200mm along the length with 20mm EKOs to al low access between compartments. A Back Box is also available on request for complete segregation.

It is normal practice to run the mains circuit in the larger compartment as the cover can be punched to accept a standard 13 amp socket or other accessory. Alternatively a short section of cover can be supplied c/w a one or two gang socket outlet. Socket plates and accessories are manufactured to overlap at the edges

Standard Skirting Trunking

Ref. S1/2 - 2 Compartment (150mmx43mm)
Ref. S1/3 - 3 Compartment (150mmx43mm)
Ref. S2/2 - 2 Compartment (200mmx43mm)
Ref. S2/3 - 3 Compartment (200mmx43mm)

Other sizes available on request.





Skirting Blank End

Left Hand - Ref. S1BELH
Right Hand - Ref. S1BERH
Left Hand - Ref. S2BELH
Right Hand - Ref. S2BERH




Left Hand



Right Hand

Skirting Outside Bend

Ref. S1OB2C - 2 Compartment (150mmx43mm)
Ref. S1OB3C - 3 Compartment (150mmx43mm)
Ref. S2OB2C - 2 Compartment (200mmx43mm)
Ref. S2OB3C - 3 Compartment (200mmx43mm)






Skirting Inside Bend


Ref. S1IB2C - 2 Compartment (150mmx43mm)
Ref. S1IB3C - 3 Compartment (150mmx43mm)
Ref. S2IB2C - 2 Compartment (200mmx43mm)
Ref. S2IB3C - 3 Compartment (200mmx43mm)






Skirting Tee

Ref. S1T2 - 2 Compartment (150mmx43mm)
Ref. S1T3 - 3 Compartment (150mmx43mm)
Ref. S2T2 - 2 Compartment (200mmx43mm)
Ref. S2T3 - 3Compartment (200mmx43mm)






Product Finishing Key (See page 24)

PG ST CP

Skirting Socket Plate

Ref. S1S1 - Single Socket (150mmx43mm)
Ref. S1S2 - Double Socket (150mmx43mm)
Ref. S2S1 - Single Socket (200mmx43mm)
Ref. S2S2 - Double Socket (200mmx43mm)



Skirting Back Boxes


Ref. S1S1BBX2 - Single Socket - 2 Comp (150mmx43mm)
Ref. S2S1BBX2 - Single Socket - 2 Comp (200mmx43mm)



Ref. S1S1BBX3 - Single Socket - 3 Comp (150mmx43mm)
Ref. S2S1BBX3 - Single Socket - 3 Comp (200mmx43mm)



Ref. S1S2BBX2 - Double Socket - 2 Comp (150mmx43mm)
Ref. S2S2BBX2 - Double Socket - 2 Comp (200mmx43mm)



Ref. S1S2BBX3 - Double Socket - 3 Comp (150mmx43mm)
Ref. S2S2BBX3 - Double Socket - 3 Comp (200mmx43mm)



visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

DADO TRUNKING

UNITRUNK DADO TRUNKING is available with all the necessary bends etc to form a complete installation.
The body and divider of the DAD-TK are manufactured from galvanised sheet steel to BS EN 50085-1 :2005 plus BS EN50085-2-1 :2006. The dividers are provided with 20mm E knockouts for easy access to all compartments at 200mm centres. A Back Box is also available on request for complete segregation. All trunking is supplied in 3 metre lengths as standard, complete with joining plates and screws.

The cover is made from 1.2mm hot dip galvanised sheet steel and can be finished in epoxy polyester coating of any colour on request. The trunking is suitable for carrying mains, telephone and VDU or other low voltage circuits.


It is normal practice to run the mains circuit in the larger compartment as the cover can be punched to accept a standard 13 amp socket or other accessory.

Alternatively a short section of cover can be supplied with a one or two gang socket outlet. Socket plates and accessories are manufactured to overlap at the edges of the trunking cover.

Dado Trunking

Ref. DADTK62 - Single Compartment (152mmx51mm)
Ref. DADTK62x3 - 3 Compartment (152mmx51mm)
Ref: DADTK82 - Single Compartment (202mmx51mm)
Ref: DADTK82x3 - 3 Compartment (202mmx51mm)


Other sizes available on request.





Dado Blank End

Ref. DADBE62 - (152mmx51mm)
Ref. DADBE82 - (202mmx51mm)



Dado Tee

Ref. DADT62 - Single Comp.
Ref. DADT62x3 - 3 Comp.
Ref: DADT82 - Single Comp.
Ref: DADT82x3 - 3 Comp.







Product Finishing Key (See page 24)

Dado Outside Bend


Ref. DADOB62 - Single Compartment (152mmx51mm)
Ref. DADOB62x3 - 3 Compartment (152mmx51mm)
Ref: DADOB82 - Single Compartment (202mmx51mm)
Ref: DADOB82x3 - 3 Compartment (202mmx51mm)






Dado Inside Bend


Ref. DADIB62 - Single Compartment (152mmx51 mm)
Ref. DADIB62x3 - 3 Compartment (152mmx51mm)
Ref: DADIB82 - Single Compartment (202mmx51mm)
Ref: DADIB82x3 - 3 Compartment (202mmx51mm)






Dado Socket Plate

FULL RANGE OF DADO SOCKET PLATE ARE AVAILABLE
EXAMPLE -Ref. DAS282 - Twin Socket - (202mmx51mm)



Dado Back Boxes

FULL RANGE OF DADO BACK BOXES ARE AVAILABLE
EXAMPLE -Ref. DAS2BB - Double Back Box- Twin Socket





BENCH TRUNKING

UNITRUNK BENCH TRUNKING is manufactured with a galvanised sheet steel body to BS EN 10142 and a 'Zintec' sheet steel cover in 3 metre lengths as standard although any length can be supplied to order to suit any application. Each length is provided with coupling and screws. The cover can be supplied punched to accept socket outlets or other accessories. If required, a dividing fillet, 25mm high, can be supplied in position. The trunking cover can also be supplied with epoxy/polyester finish in any colour to order.

Bench Trunking


Ref. BTTK - (90mmx90 mm) Other sizes available on request.






Bench Blank End

Ref. BTBE




Bench Outside Bend

Ref. BTOB




Bench Inside Bend

Ref. BTIB



Bench Tee


Ref. BTT



PLEASE NOTE:
All outlet boxes are factory finished white (Ral 9010).
(Other colours are available on request)

Bench Outlet Box

Ref.BS1







1 Gang
Single Sided

Bench Outlet Box

Ref.BS2






1 Gang
Back to Back

Bench Outlet Box

Ref.BS3







Twin
Single Sided

Bench Outlet Box

Ref.BS4







Twin
Back to Back

Bench Outlet Box

Ref.BS5







2 x 1 Gang
Single Sided

Bench Outlet Box

Ref.BS6





2 x 1 Gang
Back to Back


Data Outlet Box

Box to accept 20, 25 or 32mm conduit.
c/w 5 No Plates to accept: RJ45snap in connector standard sizes.

Ref.	Length mm	Width mm	Height mm
DB65	300	62	65
DB80	300	62	80

Extra height options available to accomodate CAT 6 cables.
Width, length and height are variable and can be adjusted on request.

5 individual plates are supplied with each 300mm box.



visit online: uk unitrunk.co.uk ireland unitrunk.ie



UNITRUNK CASE STUDY


TUNNEL VISION

> This project was challenging due to the sheer range of bespoke products required; a challenge we rose to and a job we are proud of.

Unitrunk Innovation Department

With 270 stations and about 400 km (250 miles) of track, the London Underground is the longest metro system in the world by route length and has one of the highest number of stations. In 2007, more than one billion passenger journeys were recorded, making it the third busiest metro system in Europe.

Unitrunk completed a large scale cable management contract with a wide range of projects carried out on communications, tannoy and fire systems. To date over 480 bespoke fittings have been created for this project with all parts manufactured to the London Underground's own stringent standards including multi-compartment flexible trunking which was pioneered for the first time.



PRODUCTS

- Dedicated Onsite Unitrunk Engineer
- Strict Quality Controls
- Multi-Compartment Flexible Trunking
- Over 480 Bespoke Fittings
- Specialist Project Management

UNITRUNK


Total Cable Management Solutions

SECTION 10

STEEL CONDUIT (CLASS 4)

Rigid steel conduit conforms to the following specification relating to cable management systems: BS4568 part 1: 1970 Clauses 4, 5.1, 5.4, 6.1, 7.1, 7.2, 8 and 9 BS EN 61386-21:2004 Clauses 7.1, 7.5, 8.1, 8.2, 9.1, 10.3, 10.4, and 14.2.2.3 (high protection). The base structure is 20mm (or 25mm or 32mm) seam welded steel tube processed from hot rolled steel strip.

BS4568 heavy protection is achieved by the hot dipped galvanising method to the thickness required under BS 4568 and EN 50086.



CE


FM11705

BSI British Standards

Steel Conduit (Class 4)

Galvanised

Sold in bundles of 8



IMPORTANT - Supplied in 3000mm &3750mm lengths as standard and is threaded both ends with a coupler attached at one end.

Available in 20 - 25mm diameter and 32mm diameter on request

Steel Conduit

Black Enamel

Sold in bundles of 10



IMPORTANT - Supplied in 3000mm lengths as standard and is threaded both ends with a coupler attached at one end.

Available in 20 - 25mm diameter

Black enamel conduit in 3000mm lengths is available from stock in 20mm and 25mm.


UNITRUNK CASE STUDY



MODERN SCIENCE

> The scale of this project meant that a close working relationship was paramount to its success with Unitrunk meeting our every need.

Mercury Engineering



Peterborough Edith Cavell Hospital is part of the £335 million Greater Peterborough Health Investment Plan. The high-tech hospital includes 612 inpatient beds, emergency care centre, diagnostics unit, cancer unit, specialist rehabilitation unit and renal dialysis.

Unitrunk developed a close working relationship with the contractor meeting their every requirement to supply this large scale cable management contract with a wide variety of products. Due to the complex nature of this project, Unitrunk supplied bespoke size floor trunking to suit the customer's exact requirements.

PRODUCTS

- Cable Tray
- Speedway SW4 Cable Ladder
- Support Channel & Bracketry
- Standard Trunking
- Bespoke Sized Trunking


UNITRUNK


Total Cable Management Solutions

SECTION 11

INNOVATIVE DESIGN SOLUTIONS

Our industry experience over many years has secured our position as the leader in bespoke made to order solutions. The products profiled in this section are unique to Unitrunk and have been designed by our Innovation Department who work closely with our customers to overcome any challenges providing the ideal solution to their needs in any given situation. We work harder and faster than our competitors to help you overcome any problems you may encounter, just give us a call and we can work it out.





ACCREDITED TO THE FOLLOWING STANDARDS

CE bsi. ISO 9001 Quality Management

3X FASTER

THAN YOUR STANDARD INSTALLATION

Change of Face Trunking 90° Angle

Ref. COF

Used in situations where a trunking lid changes face, e.g. top lid to front lid.

No more cutting trunking on site saving installation time.




Adjustable Bends (Vertical) 0-35° Angle

VAB/SIZE External lid



BAB/SIZE Internal lid




Gives the flexibility on site to manage any unforeseen problems, where angles cannot be determined before going to installation.

Can be formed as an internal or external joint.
Code eg: VAB22 (Adjustable Bend 50x50mm)

Adjustable Bends (Horizontal) 0-35° Angle

Ref. HAB

Gives the flexibility on site to manage any unforeseen problems, where angles cannot be determined before going to installation.



Fireproof Trunking

Ref.FPTK

The system comprises of a pre-galvanised inner trunking system surrounded by thermal insulation board all contained within a pre-galvanised outer trunking.


The trunking size can be supplied to customer requirements.



G Profile Basket

Ref. On Request

Ideal for mounting to a ceiling or even direct to a wall. While maintaining the fast fix easy connect.




visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

Floor Box - Metal Trim

Special

This metal trim can be Polyester Powder Coated or manufactured in Stainless Steel for installation into standard inspection and service outlets, across the full floor system ranges.


Available with 7mm, 9mm, 15mm, 20mm & 25mm tile recess.



Cavity Floor Access Hatch

Ref.CAVHATCH

This bespoke hatch, fitted at finished floor level, allows access to services within a cavity floor system. Cutouts to allow cables can be supplied to your specification.



Shallow Flush Floor

Ref.SSF

Shallow flush floor trunking is designed for a minimal screed application. It is also available for wooden floors were the same principle applies.

Width and height to customer specification.




Floor Trunking Tray Cover

Ref.FFR

The trunking body and tray type cover are formed from galvanised sheet steel. The standard depth of the tray cover is 8mm but deeper sections for wood block flooring etc are available. Dividing fillets are fitted to 150mm and wider in order to support cover.

When ordering multi-compartment floor trunking the width of each compartment should be specified. Any sizes available to order.




Floor Trunking Chequer Plate Cover

Ref.FFC

The trunking body is similar to tray type. A self adhesive gasket is fitted under the chequer plate cover which can be supplied either galvanised or in grey enamel finish also available with chequer plate lid.

When ordering multi-compartment floor trunking, the width of each compartment should be specified. Any sizes available to order.



Industrial Floor Box

Special

3 compartment floor box is available in 100mm deep to suit 15mm floor tile. The box has chain link fixing for lid.

Please contact Unitrunks technical department for bespoke configuration.

2000kg load




Cable Ladder Fitting Integral Coupler

Special

Fast fit, cost saving system reducing the number of couplers required. The coupler has a formed shape to increase strength and rigidity and reduces joint hinging.


UNITRUNK SPEEDLOK QUICKFIT CABLE LADDER



Cable Guard

Ref: CG


Available in all sizes and finishes to customers requirements manufactured to any length up to 3 metres.



Weatherproof Trunking

Ref.WPTK

The IP65 trunking is constructed with out-wardly turned flanges and provided with an internal sleeve coupling which allows it to be cut as necessary on site. Bonded gaskets are fitted throughout. The flange covers are secured by bolts and both the trunking and cover are manufactured from hot-dip galvanised sheet steel to either BSEN10346 or BS1461. A complete range of weatherproof trunking fittings are available.




Distribution Board Trunking

Ref.TKDB

Trunking no longer requires cutting on site.

Size manufactured to customer requirements, saving installation time.



Screw Fixed Lid Trunking

REF: SFL/TK/SIZE/SCREW TYPE

Available with a complete range of fittings and supplied in various finishes i.e. galvanised steel, stainless steel and epoxy/polyester coated. Also available with tamper proof Lid fixings.

Code eg: SFL/TK/22/TORQ
Screwfix Lid/Trunking/50x50mm/Torq Screw



- Standard (Slot)


Security Screws:

- Torq (Resistorx)
- Snake Eye
- Socket Button Head

Flexible Bend Trunking

Special


Ease of installation, perfect for navigating those awkward areas whilst maintaining the installations symmetric appearance. Manufactured to customer requirements.



Dado Anti Ligature

Special

Installed in a custodial environment, supplied with security fixings with a special design to eliminate ligature points. Manufactured to customer requirements.



Power Posts

Ref. PP

This versatile system provides services from floor voids to desk height work stations.


Size manufactured to customers requirements, saving installation time.



Double Depth Tee

Ref.DDT


Can be manufactured to enter at bottom or lid level. Gives full compartmental depth from trunking to Tee underpass.



UNITRUNK

RIGHT ON YOUR DOORSTEP

FOR OVER 35 YEARS, WE HAVE BEEN PARTNERING WITH WHOLESALERS, CONTRACTORS, ARCHITECTS AND SPECIFIERS TO PROVIDE THE RIGHT **CABLE MANAGEMENT SOLUTIONS**



OUR SERVICES:

- High Quality Products
- National Coverage with Local Stock & Service
- A Flexible Personable Approach
- Unrivalled Technical Support
- Design Service
- Innovative Product Development
- Bespoke Systems Capability

OUR PRODUCTS:

- Standard Trunking
- Multi-Compartment Trunking
- Lighting Trunking
- Weatherproof Trunking
- Cable Tray Systems
- Cable Supports
- Speedway Ladders
- Mesh Cable Trays
- Channel Systems
- Floor Trunking
- Skirting Trunking
- Dado & Bench Trunking
- Special Trunking
- Steel Conduit
- Erico Caddy



UNITRUNK CASE STUDY

SAFETY FIRST

> Safety and reliability are vital to us; Unitrunk always provide products we can rely on.

Billy Robson, Project Manager, Emcor

Unitrunk are helping to secure the UK's safest road tunnels with the refurbishment of the original Tyne Vehicle Tunnel. After the new tunnel opened earlier this year, the original one is undergoing an upgrade, featuring Unitrunk's ultra-reliable trunking, tray and ladder products.

Construction of the original vehicle tunnel began in 1961 and was opened by HM the Queen in October 1967. The new tunnel opened to traffic in February 2011, with the original closing, as work started on creating a separate emergency escape passage. The upgrade will see them become the safest road tunnels in the UK.



PRODUCTS

- Speedway SW4 Cable Ladder
- Cable Tray
- Standard Trunking

UNITRUNK

Total Cable Management Solutions

SECTION 12


ACCESSORIES & SUPPORTS

Cable Management installations often require a wide range of ancillary items such as fixings and accessories. Unitrunk branches carry, in stock, a vast range of these items to ensure that installers have a reliable ‘single source’ supply of components to meet their site requirements.

Although fixings and accessories are often small value parts, they can be important components in the overall installation therefore, breadth of range and product quality are important factors when choosing a supplier.

It’s impossible to feature every product from this wide ranging product area in one catalogue so whilst you’ll find many industry standard items in the following pages, if you have specific requirements that aren’t shown then please call your local branch for expert support and assistance.

Finishes are available in zinc plated (EZ), hot dip galvanised (GA) and stainless steel finishes (SS) and when ordering please specify the finish required



ACCREDITED TO THE FOLLOWING STANDARDS

CE bsi. ISO 9001 Quality Management


Single Channel Cantilever Arm

Ref.	Product	Arm Length
340AH10	2 Hole	150mm
340AH11	2 Hole	300mm
340AH12	2 Hole	450mm
340AH13	2 Hole	600mm
340AH14	2 Hole	750mm
340AH15	2 Hole	900mm




Short Spring Channel Nuts

Ref.	Thread Size
UCM6/S	M6
UCM8/S	M8
UCM10/S	M10
UCM12/S	M12




Back to Back Cantilever Arm

Ref.	Product	Arm Length
CARMBBP150GM	2 Hole	150mm
CARMBBP300GM	2 Hole	300mm
CARMBBP450GM	2 Hole	450mm
CARMBBP600GM	2 Hole	600mm
CARMBBP750GM	2 Hole	750mm
CARMBBP900GM	2 Hole	900mm




Channel Nuts No Spring

Ref.	Thread Size
UCM6/N	M6
UCM8/N	M8
UCM10/N	M10
UCM12/N	M12




Cone Pointed Bolts

Ref.	Thread Size
UCM10/CPB	M10x40



Long Spring Channel Nuts

Ref.	Thread Size
UCM6/L	M6
UCM8/L	M8
UCM10/L	M10
UCM12/L	M12



Threaded Rod

Ref.	Thread Size	Length
M6R3	M6	3m long
M8R3	M8	3m long
M10R3	M10	3m long
M12R3	M12	3m long



Drop in Anchors

Ref.	Thread Size
M6A	M6
M8A	M8
M10A	M10
M12A	M12

Sold in 100's.



Roofing Bolts & Nuts

Ref.	Thread Size
M6X12RNB	M6 x 12mm
M6X16RNB	M6 x 16mm
M6X20RNB	M6 x 20mm
M6X25RNB	M6 x 25mm
M6X30RNB	M6 x 30mm
M6X35RNB	M6 x 35mm
M6X40RNB	M6 x 40mm

Sold in 100's.
Other sizes available on request.



Rod Joiners

Ref.	Thread Size
M6RJ	M6
M8RJ	M8
M10RJ	M10
M12RJ	M12

Sold in 100's.




visit online: uk unitrunk.co.uk ireland unitrunk.ie

Wedge Nut

Ref.	Thread Size
M6WN	M6
M8WN	M8
M10WN	M10
M12WN	M12


Sold in 100's.



Flat Washers

Ref.	Thread Size
M6FW	M6
M8FW	M8
M10FW	M10
M12FW	M12

Sold in 100's.



Anchor Setting Tool

Ref.M6ST
Ref.M8ST
Ref.M10ST
Ref.M12ST



Beam Clamp

Ref.	Thread/Hole Size
FC6T	M6 Threaded
FC8T	M8 Threaded
FC10T	M10 Threaded
FC11	11mm Plain Hole Max girder width for bolting 19mm
FC13	13mm Plain Hole Max girder width for bolting 23mm



Hex Head Set Screws

	Thread Size						Pack Qty	Ref.
M6	20	25	30	35	40	-	100	M6 X SIZE HS
M8	20	25	30	35	40	-	100	M8 X SIZE HS
M10	20	25	30	35	40	50	100	M10 X SIZE HS
M12	20	25	30	35	40	50	100	M12 X SIZE HS


Unitrunk stock a large range of set screws in thread sizes M6, M8, M10 and M12. Popular lengths range from 20mm to 40mm long and are stocked at all our distribution centres.



Mudguard Washers

Ref.	Size
M6MW	M6
M8MW	M8
M10MW	M10
M12MW	M12


Sold in 100's.



Full Hexagonal Nuts


Ref.	Thread Size
M6HN	M6
M8HN	M8
M10HN	M10
M12HN	M12

Sold in 100's.



Tray to Channel Klip

Ref. CHTR 25 (KLMR)
Ref. CHTR 50 (KLHR)



Basket to Channel Klip

Ref. UFC41M



Product Finishing Key (See page 24)


REMEMBER


UNITRUNK STOCK A GIANT RANGE OF ERICO CADDY PRODUCTS...

COMPREHENSIVE RANGE OF

ERICO CADDY PRODUCTS

Unitrunk are an appointed super stockist of the erico caddy range of spring steel products and maintain a large stock profile of the popular caddy products at all the Unitrunk distribution centres.





visit online: uk **unitrunk.co.uk** ireland **unitrunk.ie**

NEW

SPEEDWAY®

SECTION 5.1

SPEEDWAY® CABLE LADDER SYSTEMS

The Speedway® family is growing.

Speedway® Cable Ladder is now available in Pre-Galvanised Steel. The newly added material choice offers greater flexibility, enabling contractors to choose the most suitable material based on the specific requirements of each project.

The **Speedway® Pre-Galvanised Cable Ladder** is ideally suited for areas with low levels of atmospheric corrosion and is tested in accordance with BS EN 61537.

RELIABLE SPEEDWAY® ATTRIBUTES

Special Profiled Side Section:

1. Enhanced structural rigidity.
2. Increased internal width for cables.
3. High performance coupling.
4. Safety edge.

Slotted Side Section:

1. Allows faster installation as the ladder can be cut to any length and coupled without on-site drilling.
2. Flexibility to mount ancillary items such as light fittings.
3. Reduced weight.

Shallow Channel Rungs:

1. The fixing of the rungs to the lowest point of the side section ensures maximum loading height.
2. High strength even in the widest ladders.
3. Use of every known type of cleat, tie and bonding with infinite adjustment.
4. Rungs alternately inverted (on lengths) permitting suspension of light fittings etc.from underside.

PRE. GALV. LADDER SYSTEM HEIGHTS

SPEEDWAY® 4 (SW4) PRE-GALV. - 100mm overall height
SPEEDWAY® 5 (SW5) PRE-GALV. - 125mm overall height
SPEEDWAY® 6 (SW6) PRE-GALV. - 150mm overall height

LADDER, FITTINGS, COVERS & ACCESSORIES

Pre-Galvanised Structural Steel (BS EN 10346)




ACCREDITED TO THE FOLLOWING STANDARDS


CE

Speedway® SW4 Pre-Galvanised Cable Ladder

Speedway® 4 SW4 Pre-Galv. Medium Duty Cable Ladder is manufactured in 3.0m lengths as standard with 6.0m lengths to order. The cable ladder is available in standard widths of 150mm, 300mm, 450mm, 600mm, 750mm, 900mm and 1050mm, although other widths up to 1500mm are available to order. Rung spacing is 300mm as standard.

Ref. SW4-SL3-Width-QQ





Part Number	No. of Rungs	Dimensions (mm)				Weight (kg)
		W	W1	L	H	
SW4-SL3-150-QQ	10	150	200	3000	100	12.39
SW4-SL3-300-QQ		300	350			13.89
SW4-SL3-450-QQ		450	500			15.38
SW4-SL3-600-QQ		600	650			16.88
SW4-SL3-750-QQ		750	800			18.38
SW4-SL3-900-QQ		900	950			19.88
SW4-SL3-1050-QQ		1050	1100			21.38

Height	H	100mm
Loading Depth	D	75mm
Ladder Width	W	100mm to 1050mm
Maximum Internal Width	W2	W + 14mm
Overall Width	W1	W + 50mm
Flange Width	F	25mm


Supplied with:




Speedway® SW5 Pre-Galvanised Cable Ladder

Speedway® 5 (SW5) Pre-Galv. Heavy Duty Cable Ladder is manufactured in 3.0m lengths as standard with 6.0m lengths supplied to order. The cable ladder is available in standard widths of 150mm, 300mm, 450mm, 600mm, 750mm, 900mm and 1050mm, although other widths up to 1500mm are available to order. Rung spacing is 300mm as standard.

Ref. SW5-SL3-Width-QQ






Part Number	No. of Rungs	Dimensions (mm)				Weight (kg)
		W	W1	L	H	
SW5-SL3-150-QQ	10	150	200	3000	125	13.86
SW5-SL3-300-QQ	10	300	350			15.36
SW5-SL3-450-QQ	10	450	500			16.86
SW5-SL3-600-QQ	10	600	650			18.36
SW5-SL3-750-QQ	10	750	800			19.86
SW5-SL3-900-QQ	10	900	950			21.36
SW5-SL3-1050-QQ	10	1050	1100			22.85

Height	H	125mm
Loading Depth	D	100mm
Ladder Width	W	100mm to 1500mm
Overall Width	W1	W + 50mm
Maximum Internal Width	W2	W + 14mm
Flange Width	F	25mm


Supplied with:




Speedway® SW6 Pre-Galvanised Cable Ladder

Speedway® 6 (SW6) Pre-Galv. Extra Heavy Duty Cable Ladder is manufactured in 3.0m lengths as standard with 6.0m lengths supplied to order. The cable ladder is available in standard widths of 150mm, 300mm, 450mm, 600mm, 750mm, 900mm and 1050mm, although other widths up to 1500mm are available to order. Rung spacing is 300mm as standard.

Ref. SW6-SL3-Width-QQ





Part Number	No. of Rungs	Dimensions (mm)				Weight (kg)
		W	W1	L	H	
SW6-SL3-150-QQ	10	150	200	3000	150	15.63
SW6-SL3-300-QQ	10	300	350			17.13
SW6-SL3-450-QQ	10	450	500			18.63
SW6-SL3-600-QQ	10	600	650			20.12
SW6-SL3-750-QQ	10	750	800			21.62
SW6-SL3-900-QQ	10	900	950			23.12
SW6-SL3-1050-QQ	10	1050	1100			24.62

Height	H	150mm
Loading Depth	D	125mm
Ladder Width	W	100mm to 1500mm
Overall Width	W1	W + 50mm
Maximum Internal Width	W2	W + 14mm
Flange Width	F	25mm

Supplied with:



Pre-Galvanised Cable Ladder Fitting with Integral Coupler


Fast fit, total cost saving through reduction of the number of couplers and fixings required (67% installation time reduction).

The integral coupler has a formed shape which increases strength and rigidity and reduces joint hinging.



Flat Elbow 30˚, 45˚, 60˚, 90˚

Ref. SW-FE Angle-Width -Radius-QQ



Equal Cross

Ref. SW-EC-Width-Radius-QQ




Equal Tee

Ref. SW-ET-Width-Radius-QQ

Can also be manufactured unequal.

Ref. SW-UET-W1-W2-Radius-QQ



Covers


SW-CC-SL1.5-Width-QQ (Closed)
SW-CL-SL1.5-Width-QQ (Louvered)

Supplied c-w fixings.
Please note straight ladder covers are supplied in 1.5m lengths.



Riser (Outside) 30˚, 45˚, 60˚, 90˚


Ref. SW-OR Angle-Width -Radius-QQ



Short Adjustable Coupler


Ref. SW-SAC-QQ

Overall length 300mm.
Used as an alternative to Reducers-unequal tees.
Supplied c-w fixings.



Riser (Inside) 30˚, 45˚, 60˚, 90˚


Ref. SW-IR Angle-Width -Radius-QQ



Straight Coupler

Ref. SW-CS-QQ


Sold in pairs.
Supplied c-w fixings.
1 Pair per ladder.



Long Adjustable Coupler

Ref. SW-LAC-QQ


Overall length 450mm
Used as an alternative to Reducers- unequal tees.
Supplied c-w fixings.



Adjustable Fixing Bracket

Ref. AFB-QQ


Supplied c-w 1 fixing.




External Flange Clamp

Ref. SW-EFC-QQ

Fixings ordered separately.






Horizontal Adjustable Coupler

Ref. SW-HAC-QQ

Each c-w fixings.




Hold Down Bracket

Ref. SW-HDB-QQ

Fixings ordered separately.





Vertical Adjustable Coupler

Ref. SW-VAC-QQ

Each c-w fixings.

Identical for sw4 & sw5 order as: Sw4-5-vac-finish
for sw6 order as: sw6-vac-finish.



Straight Ladder Divider


Ref. SW-SL-1.5-QQ

Straight ladder dividers are 1.5m long.
Fixings separate.




Reducer Left Hand

Ref. SW-RL-W1-W2-QQ




Straight Reducer

Ref. SW-RS-W1-W2-QQ



Reducer Right Hand

Ref. SW-RR-W1-W2-QQ



Earth Braid

Ref. EBS01 (M10 BRAID)



The Speedway® Earth Bonding Strap (EBS01) is designed for use in installations where an additional means of earthing or electrical bonding is specified. The Speedway® Earth Bonding Strap comprises of a 16mm² tinned copper braid crimped into M10 tinned copper end connectors. The Speedway® Earth Bonding Strap is common to Speedway® SW4, SW5, & SW6.

Pre-punched holes for fixing the earth bonding strap are located at each end of the ladder and fittings.

Speedway® Pre.Galv. Cable Ladder System - Standard Material Gauges & Loading Data

Ladder Type	Material Configuration	Side Wall Gauge (mm)	Rung Gauge (mm)						Loading Capacity (kg/m)				
			150	300	450	600	750	900	1.0m span	1.5m span	2.0m span	2.5m span	3.0m span
SW4	QQ	1.5	1.5						233	233	233	233	233
SW5	QQ	1.5	1.5						234	234	234	234	234
SW6	QQ	1.5	1.5						235	235	235	235	235

QQ - Pre-Galvanised Steel

Loading data in accordance with BS EN IEC 61537

The Speedway® cable ladder system is also available in a combination of side wall gauges (1.5mm & 2.0mm) and rung gauges (1.5mm, 2.0mm, 2.5mm) to suit specific installation requirements.

Consult our Design Team for guidance on the correct selection of material gauge combinations.

QuickFix

THE REVOLUTIONARY TRUNKING SYSTEM


DISCOVER UP TO 6X FASTER INSTALLATION



UNITRUNK

UP TO 6X FASTER CABLE MANAGEMENT INSTALLATION

Introducing QuickFix, the innovative trunking range designed to save time onsite thanks to its quick and easy to install design.



UNIBOLT FIXINGS UP TO 6X FASTER INSTALL

UniBolt Fixings

Fast fitting UniBolt reduces installation times by up to 80%

IP4X COMPLIANT IP4X AS STANDARD

IP4X Compliant


Compliant as standard with the easy to assemble system

COMPLETE RANGE OF FAST FITTING SYSTEMS

Complete Range


Innovative, rapid installation cable management systems

SCAN HERE
to check out the time saving simplicity for yourself



QuickFix


Rapid Installation Product Range




EASYCONNECT®



UNIKLIP®



INTELOK®




SPEEDWAY®

Known for our market leading engineering and product design for over 50 years, our new QuickFix range completes an already extensive offering of cable management solutions which focus primarily on reducing installation time on site using quality assured products.


Quickfix is a complete range of trunking and fittings manufactured to standards as described in BS EN 50085-1:2005, in best quality, hot dipped galvanised sheet steel to BS EN 10346:2015.

Length to Fitting



- Slide the fitting's integrated coupler into the trunking length.
- Secure into place with the UniBolts supplied.
- Thanks to its engineered design once the lids are secured into place IP4X compliance is standard, meaning no extra components are required.

Length to Length



- Cover straps are only required on length to length joins.
- Simply snap the cover strap into place to ensure IP4X compliance.
- Cover straps are supplied with QuickFix lengths as standard. Cover straps can be ordered separately using code - TS.

UniBolt



- The UniBolt's simple, yet effective design, enables cable management system installation times to be reduced by as much as 80%.
- Universal head
- Bespoke thread
- Serration and domed safety end

SCS ISO 14001 CERTIFIED

SCS ISO 9001 CERTIFIED

SCS OHSAS 18001 CERTIFIED


CE

QuickFix Trunking

Ref.TK22 50mm x 50mm
Ref.TK33 75mm x 75mm
Ref.TK42 100mm x 50mm
Ref.TK44 100mm x 100mm
Ref.TK66 150mm x 150mm

Bespoke sizes available on request

*Cover straps for length to length assembly are supplied with lengths as standard.




QuickFix trunking is manufactured from pre-galvanised steel and is supplied in 3m lengths.
Other sizes and finishes are available on request (See code guide at the end of this section).

Gusset Bend Top Lid

Ref.GTB


Code	W	H	X
22	50	50	91
33	75	75	115
42	100	50	140
44	100	100	140
66	150	150	193



Gusset Bend Inside Lid

Ref.GIB


Code	W	H	X
22	50	50	25
33	75	75	25
42	100	50	25
44	100	100	25
66	150	150	25



Gusset Bend Outside Lid

Ref.GOB


Code	W	H	X
22	50	50	25
33	75	75	25
42	100	50	25
44	100	100	25
66	150	150	25



Reducer

Ref.RE


Code	W1	H1	W2	H2	X
33-22	75	75	50	50	60
42-22	100	50	50	50	60
44-33	100	100	75	75	60
66-44	150	150	100	100	60



Gusset Tee Top Lid

Ref.GTT


Code	W	H	X	Y
22	50	50	25	129
33	75	75	25	154
42	100	50	25	180
44	100	100	25	180
66	150	150	25	230



Gusset Tee Inside Lid

Ref.GIT


Code	W	H	X	Y
22	50	50	25	115
33	75	75	25	140
42	100	50	25	115
44	100	100	25	165
66	150	150	25	215



Gusset Tee Outside Lid

Ref.GOT


Code	W	H	X	Y
22	50	50	25	115
33	75	75	25	140
42	100	50	25	115
44	100	100	25	165
66	150	150	25	215



Sharp Elbow Inside Lid

Ref.SIE


Code	W	H	X	Y
22	50	50	30	85
33	75	75	30	110
42	100	50	30	85
44	100	100	30	135
66	150	150	30	187



Sharp Elbow Outside Lid

Ref.SOE


Code	W	H	X	Y
22	50	50	30	85
33	75	75	30	110
42	100	50	30	85
44	100	100	30	135
66	150	150	30	187



Sharp Elbow Top Lid

Ref.STE


Code	W	H	X	Y
22	50	50	30	85
33	75	75	30	110
42	100	50	30	130
44	100	100	30	130
66	150	150	30	185



45° Elbow Top Lid

Ref.TE


Code	W	H	X	Y
22	50	50	20	43
33	75	75	20	53
42	100	50	20	63
44	100	100	20	63
66	150	150	20	83



45° Elbow Inside Lid

Ref.IE


Code	W	H	X	Y
22	50	50	30	53
33	75	75	30	63
42	100	50	30	53
44	100	100	30	83
66	150	150	30	103



45° Elbow Outside Lid

Ref.OE


Code	W	H	X	Y
22	50	50	53	30
33	75	75	63	30
42	100	50	53	30
44	100	100	83	30
66	150	150	103	30



Sharp Tee Top Lid

Ref.STT


Code	W	H	X	Y
22	50	50	30	115
33	75	75	30	140
42	100	50	30	165
44	100	100	30	165
66	150	150	30	215



Sharp Tee Inside Lid

Ref.SIT


Code	W	H	X	Y
22	50	50	30	112
33	75	75	30	137
42	100	50	30	112
44	100	100	30	162
66	150	150	30	212



Sharp Tee Outside Lid

Ref.SOT


Code	W	H	X	Y
22	50	50	30	112
33	75	75	30	137
42	100	50	30	112
44	100	100	30	162
66	150	150	30	212



Intersection Box

Ref.ITB


Code	W	H	X
22	50	50	25
33	75	75	25
42	100	50	25
44	100	100	25
66	150	150	25



Flared Flange

Ref.FF

Code	W1	W2	H	X
22	145	50	50	50
33	175	75	75	50
42	200	100	50	50
44	200	100	100	50
66	250	150	150	50




Cover Strap

Ref.TS

Code	W
2	50
3	75
4	100
6	150


NB. Cover Straps for length to length assembly are supplied with lengths as standard.



Trunking to Channel Bracket

Ref.TKHDB


Code	H
2	50
3	75
4	100
6	150



Trunking Coupler

Ref.TC


Code	W	H
22	50	50
33	75	75
42	100	50
44	100	100
66	150	150



Blank End

Ref.BE

Code	W	H
22	50	50
33	75	75
42	100	50
44	100	100
66	150	150




Socket Outlet Single

Ref.STL1

Code	X	Y
4	230	110
6	230	160


Can be supplied with off centre cutouts.



Socket Outlet Double

Ref.STL2

Code	X	Y
4	230	110
6	230	160



Cable Support

Ref.CS


Code	W	H
22	50	50
33	75	75
42	100	50
44	100	100
66	150	150



Fire Barrier Clip

Ref.FB

Code	Y
2	41
3	60
4	85
6	137




Earth Link

Ref.CES (Plain Copper)
Ref. TCES (Tinned Copper)



Distribution Board Trunking

Ref.TKDB




Save on installation time
Sizes manufactured to customer requirements, no cutting onsite required.

Beam Clamp A

Ref.BCA22 50mm x 50mm

Code	X	Y
22	90	60




Window Beam Clamp

Ref.WBC22 50mm x 50mm

Code	X	Y	W
22	90	103	50

C/W M10 x 40 CPB (Bolt).



Galvanised Steel Lid

Ref.GSL

Code	W
2	50
3	75
4	100
6	150
8	200
9	225
12	300




Supplied in 3 metre lengths.

Dividing Fillets

Ref.DF

Code	W
2	50
3	75
4	100
6	150




Supplied in 3 metre lengths.

Metal Retaining Strap

Ref.CR


Code	W
2	50
3	75
4	100
6	150




Flanged Coupling

Ref.FC

Code
22
33
44
66





Sold in Pairs. Refer to the Trunking sidewall when ordering.
(Example TK42 use FC22)

Plastic Cable Retaining Strap

Ref. CR2/3 50mm x 75mm
Ref. CR4/6 100mm x 150mm




Hanger Bracket

Ref.HBL(x)

Code	H	W	X	X
22	85	55	10	20
33	135	85	10	20
44	165	115	10	20
66	245	165	10	20


Other sizes available on request.



Hanger Bracket (with Swing Bar)


Ref.HBL22SP(x) 50mm x 50mm

Code	W	H	X	X
22	55	85	10	20



Lid Fastener

Ref.LCS2 50mm
Ref.LCS3 75mm
Ref.LCS4 100mm



Available to suit 50mm, 75mm or 100mm widths.
Note: For sizes over 100mm use LCS2 x2.

Long Coupler

Ref.LCL22 50mm x 50mm
Ref.LCL33 75mm x 75mm




Our entire range of Lighting Trunking and Accessories may be used in conjunction with QuickFix trunking.
They will be IP4X compliant as standard.

Visit our website for full details of our Lighting Trunking Accessory Range.

Visit our website to view our complete product guide, including our standard trunking range, which features additional sizes, alternative lid options and various material configurations.

Adjustable Bends & Adjustable Length Couplers

Ref.TAC



BAB/SIZE



Our range of Adjustable Bends and Adjustable Length Couplers may be used in conjunction with QuickFix trunking.
They will not be IP4X compliant as standard and will be supplied with standard screw fixings.

Visit our website for details of our full Standard Trunking range and accessories.

Need something special or can't find what you're looking for?

Get in touch with our Design Team to discuss bespoke products or advice on choosing the best solution for a specialist project.

email: bespoke@unitrunk.co.uk

CODE GUIDE

STEP 1: CHOOSE FINISH

PRE-GALVANISED

POWDER COATED

STEP 2: CHOOSE PRODUCT

CODE	PRODUCT NAME
TK	Trunking (3m lengths)*
TS	Cover Strap (Width Only)
TKHDB	Trunking to Channel Bracket (Height Only)
GSL	Galvanised Steel Lid (Width Only)
TC	Trunking Coupling
DF	Dividing Fillet (loose) (Height Only)
GTB	Gusset Bend (Top Lid)
GIB	Gusset Bend (Inside Lid)
GOB	Gusset Bend (Outside Lid)
STE	Sharp Elbow (Top Lid)
SIE	Sharp Elbow (Inside Lid)
SOE	Sharp Elbow (Outside Lid)
GTT	Gusset Tee (Top lid)
GIT	Gusset Tee (Inside Lid)
GOT	Gusset Tee (Outside Lid)
STT	Sharp Tee (Top Lid)
SIT	Sharp Tee (Inside Lid)
SOT	Sharp Tee (Outside Lid)
ITB	Intersection Box
TE	45° Elbow (Top Lid)
IE	45° Elbow (Inside Lid)
OE	45° Elbow (Outside Lid)
RE	Reducer
FF	Flared Flange
BE	Blank End
FB	Fire Barrier Clip
LCS	Lid Clips (Strap and Stud)
FC	Flanged Coupling
CS	Cable Support
CES	Earth Link (Copper) x 10
TCES	Earth Link (Tinned Copper) x 10
CR	Cable Retainer Strap x 10
STL1	Socket Outlet (Single)
STL2	Socket Outlet (Double)
PES	PVC Edging Strip - per metre

STEP 3: CHOOSE SIZE

STEP 4: COMPARTMENTS

NO. OF COMPARTMENTS POSSIBLE

WIDTH	HEIGHT	CODE	X1	X2	X3	X4
50	50	22	✓	✓		
75	50	32	✓	✓		
75	75	33	✓	✓		
100	50	42	✓	✓	✓	
100	75	43	✓	✓	✓	
100	100	44	✓	✓	✓	
150	50	62	✓	✓	✓	✓
150	75	63	✓	✓	✓	✓
150	100	64	✓	✓	✓	✓
150	150	66	✓	✓	✓	✓
200	50	82	✓	✓	✓	✓
200	75	83	✓	✓	✓	✓
200	100	84	✓	✓	✓	✓
200	150	86	✓	✓	✓	✓
200	200	88	✓	✓	✓	✓
225	50	92	✓	✓	✓	✓
225	75	93	✓	✓	✓	✓
225	100	94	✓	✓	✓	✓
225	150	96	✓	✓	✓	✓
225	225	99	✓	✓	✓	✓

STEP 5: GAUGE


Gauges conform to latest specifications.
For specialist requirements a range of gauges are available on request.

For trunking sizes greater than 9"x9", alternative lid options, and/or multiple material configurations, please see our Standard Trunking range.


*Trunking lengths are supplied with Cover Straps to ensure IP4X compliance.
Cover Straps are ONLY required on length to length joins.


NEW TRUNKING ACCESSORY

The small bracket making a BIG impact!



Introducing the latest addition to our cable trunking accessories range. The simple, innovative bracket secures trunking length to channel in seconds.







- ✓ **UP TO X7 FASTER**
- ✓ **REDUCED LABOUR**
- ✓ **ZERO DRILLING**

ORDER CODE: TKHBD

IP4X COMPLIANT
IP4X
AS STANDARD

UNITRUNK

Delivering world class products and service via our local distribution network



MANUFACTURING SITES:

Lisburn (Head Office)
Tel: +44 (0) 28 9262 5100
Email: lisburn@unitrunk.co.uk

Warrington (Vantrunk)
Tel: +44 (0) 1928 564 211
Email: sales@vantrunk.co.uk

DEPOT LOCATIONS:

Dublin
Tel: +353 (0) 8200 292
Email: dublin@unitrunk.ie

Manchester
Tel: +44 (0) 161 336 1177
Email: manchester@unitrunk.co.uk

Harlow
Tel: +44 (0) 1279 444 481
Email: harlow@unitrunk.co.uk

Livingston
Tel: +44 (0) 1506 461 964
Email: livingston@unitrunk.co.uk

Yorkshire
Tel: +44 (0) 113 512 2910
Email: yorkshire@unitrunk.co.uk

Bristol
Tel: +44 (0) 1179 823 720
Email: bristol@unitrunk.co.uk

North East
Tel: +44 (0) 1914 921 470
Email: northeast@unitrunk.co.uk

Wolverhampton
Tel: +44 (0) 1902 717 786
Email: wolverhampton@unitrunk.co.uk

THE BIG UNITRUNK Product Guide

INDEX

Standard Trunking Systems - 01

45° Elbow Inside Lid 28
45° Elbow Outside Lid 28
45° Elbow Top Lid 28
Adjustable Bends (Horizontal) 29
Adjustable Bends (Vertical) 29
Adjustable Lengths Coupler 29
Beam Clamp A 30
Blank End 29
Cable Support 29
Distribution Board Trunking 29
Dividing Fillets 30
Earth Link 29
Fire Barrier Clip 29
Flanged Coupling 30
Flared Flange 28
Galvanised Steel Lid 30
Gusset Bend Inside Lid 27
Gusset Bend Outside Lid 27
Gusset Bend Top Lid 27
Gusset Tee Inside Lid 27
Gusset Tee Outside Lid 27
Gusset Tee Top Lid 27
Hanger Bracket 30
Hanger Bracket (With Swing Bar) 30
Intersection Box 28
Lid Fastener 30
Metal Retaining Strap 30
Plastic Cable Retaining Strap 30
Reducer 27
Sharp Elbow Inside Lid 27
Sharp Elbow Outside Lid 28
Sharp Elbow Top Lid 28
Sharp Tee Inside Lid 28
Sharp Tee Outside Lid 28
Sharp Tee Top Lid 28
Socket Outlet Double 29
Socket Outlet Single 29
Standard Trunking 27
Trunking Coupling 29
Window Beam Clamp 30

Multi-Compartment Trunking Systems - 02

Order Sheet 42

Lighting Trunking Systems - 03

Beam Clamp A 47
Blank End 47
Fitting Suspension 47
Galvanised Snap-In Lid 47
Galvanised Steel Lid 47
Hanger Bracket 47
Hanger Bracket (With Swing Bar) 47
Klilk Lid Section 47
Long Coupling 47
White Plastic Snap-In Lid 47
Window Beam Clamp 47

Cable Tray Systems - 04

Adjustable Tray Extension 58, 62
Bolts and Nuts 69, 73
Cable Tray Fitting Covers 64, 78
Cantilever Arm 66
Conduit Take-Off Plate 58, 62, 73
Cover Fixing Kit 64, 78
Covers and Brackets 64, 78
Cranked Coupler 69, 71, 73
Earth Link 69, 73, 77
Fish Plate 53, 56, 60, 69, 71, 74
Fish Plate Coupler 53, 56, 60
Fitting to Fitting Adapter 66
Flat 4 Way Equal Intersection 54, 57, 61, 69, 72, 75
Flat 45° Bend 54, 57, 61, 70, 72, 75
Flat 90° Bend 54, 57, 61, 69, 72, 75
Flat Equal Tee 54, 57, 61, 70, 72, 75
Heavy Duty Cable Tray 60, 74
Inside Riser 55, 58, 62, 70, 73, 76
Light Duty Cable Tray 53, 69
Medium Duty Cable Tray 56, 71
Outside Riser 55, 58, 62, 70, 73, 76
Reducer 54, 57, 61, 69, 72, 75
Stand-Off Bracket 66, 77
Straight Coupler 53, 56, 60, 69, 71, 74
Straight Tray Covers 79
Tray Overhead Hangers 66, 77
Tray to Channel Klip 56, 60, 71, 74, 77, 106
Uniklip 53, 56, 60
Variable Riser 55, 58, 62
Vertical Adjustable Coupler 66, 77

Speedway Cable Systems - 05

Adjustable Fixing Bracket 87
Cable Ladder Fitting with Integral Coupler 86
Covers 86
Cross 86
Earth Braid 88
Equal Tee 86
External Flange Clamp 87
Flat Elbow 30°, 45°, 60°, 90° 86
Hold Down Bracket 87
Horizontal Adjustable Coupler 87
Long Adjustable Coupler 87
Reducer Left Hand 87
Reducer Right Hand 87
Riser (Inside) 86
Riser (Outside) 86
Short Adjustable Coupler 86
Speedway SW4 Cable Ladder 83
Speedway SW5 Cable Ladder 84
Speedway SW6 Cable Ladder 85
Straight Coupler 86
Straight Ladder Divider 87
Straight Reducer 87
Vertical Adjustable Coupler 87

Cable Basket Systems - 06

Barrier Strip 94
Basket 30mm Sidewall Basket 93
Basket 60mm Sidewall Basket 93
Basket 100mm Sidewall Basket 93
Basket Lid 94
Basket to Channel Clip 99
Bolt Cutter 100
Carrier Support Clamp 94
Ceiling Support Bracket 98
Central Hanger - Threaded Rod Type 98
Conduit Take Off Bracket 98
Drop Out Plate 98
Earthing Clamp 99
Fitting Joint Connector 96
Floor Support Bracket 96
G Profile Basket 100
Hold Down Clamp 94
Plastic End Cap 98
Plastic ID Tags 98
Side Suspension Hanger 96
Slotted Steel Strap 94
Stand Off Bracket 96
Support Clamp 94
Support Spacer 96
Suspension Support Bracket 97
Wall Mounting Bracket 98
Wall or Box Support Bracket 99
Wall Support Bracket 97
Wall Support Clic Bracket 98

THE BIG UNITRUNK Product Guide

INDEX

Channel & Support Systems - 07

W Shaped Deep Bracket 107
Z Purlin Clip 109
3 Way Corner Bracket 108
45° Angle Bracket 109
Acute Angle Bracket 45° 109
Back to Back Bracket 107
Back to Back Deep Channel 106
Back to Back Shallow Channel 105
Basket to Channel Clip 106
Beam Clamp 109, 110
Cantilever Arm 110
Channel Nuts Less Spring 110
Channel Support Bracket 108
Channel Support Bracket L/H 108
Channel Support Bracket R/H 108
Cone Pointed Bolts 110
Cover Strip 110
Cross Support Bracket 109
Deep "U" Bracket 107
Deep Channel 105
Deep Connector 109
Deep External Connector 109
Deep Z Bracket 107
Double Channel Base Plate 108
Double Channel Bracket 107
Double Channel Wing Fitting 108
End Cap (Deep) 110
End Cap (Shallow) 110
Five Hole Plate 106
Four Hole Plate 106
Heavy Duty Beam Clamp 110
L Bracket 106
L/H Channel Support Bracket 108
Long Spring Channel Nuts 110
Multi-Channel Bracket 108
Multiple Z Bracket 107
Obtuse Angle Bracket 45° 109
R/H Channel Support Bracket 108
Right Angle Bracket 106, 107
Right Angle Shelf Bracket 107
Shallow "U" Bracket 108
Shallow Channel 105
Shallow Connector 109
Shallow External Connector 109
Shallow Z Bracket 107
Short Spring Channel Nuts 110
Single Channel Base Plate 108
Slotted Deep Channel 105
Slotted Shallow Channel 105
Square Plate 106
T Bracket 106
Three Hole Plate 106
Three Leg Wing Fitting 108
Tray to Channel Klip 106
Two Hole Plate 106
Two Leg Wing Fitting 108
Wing Fitting with Gussets 108

Floor Trunking Systems - 08

Cavity Floor Blank End 123
Cavity Floor Box 122
Cavity Floor Fourway Intersection 123
Cavity Floor Gusset Tee 123
Cavity Floor Gussett Bend 123
Cavity Floor Riser Bend 123
Cavity Floor Tap-Off Box 123
Cavity Floor Trunking 123
Cavity Floor Trunking Coupling 123
Easyway Blank End 117
Easyway Height Adjustable Coupling 117
Easyway Riser Bend 117
Easyway Service Outlet Frame 117
Easyway Trunking 117
Easyway Universal Fitting 118
Inspection Lid 117, 127
Service Outlet Lid 117, 127
Service Outlet Panels 124, 125
Underfloor Adjustable Collar 127, 129
Underfloor Blank End 127
Underfloor Coupling 127
Underfloor Flange Coupling 127
Underfloor Riser Bend 127
Underfloor Riser Flange 127
Underfloor Trunking 127
Underfloor Universal Fitting 128
Underfloor Blank End 127

Bench Outlet & Perimeter Trunking - 09

Bench Outlet Boxes 139
Bench Trunking 138
Bench Trunking Fittings 138
Dado Trunking 136
Dado Trunking Fittings 136, 137
Skirting Trunking 133
Skirting Trunking Fittings 133-135

Steel Conduit (Class 4) - 10

Steel Conduit 143
Steel Conduit (Class 4) 143

Innovative Design Solutions - 11

Adjustable Bends (Horizontal) 147
Adjustable Bends (Vertical) 147
Cable Guard 149
Cable Ladder Fitting Integral Coupler 149
Cavity Floor Access Hatch 148
Change of Face Trunking 147
Dado Anti Ligature 150
Distribution Board Trunking 149
Double Depth Tee 150
Fireproof Trunking 147
Flexible Bend Trunking 150
Floor Box - Metal Trim 148
Floor Trunking Chequer Plate Cover 148
Floor Trunking Tray Cover 148
G Profile Basket 147
Industrial Floor Box 149
Power Posts 150
Screw Fixed Lid Trunking 150
Shallow Flush Floor 148
Weather Proof Trunking 149

Accessories & Supports - 12

Anchor Setting Tool 156
Basket to Channel Clip 156
Beam Clamp 156
Cantilever Arm 155
Channel Nuts No Spring 155
Cone Pointed Bolts 155
Drop in Anchors 155
Flat Washers 156
Full Hexagonal Nuts 155
Hex Head Set Screws 156
Long Spring Channel Nuts 155
Mudguard Washers 156
Rod Joiners 155
Roofing Bolts & Nuts 156
Short Sprint Channel Nuts 155
Tray to Channel Klip 156
Treaded Rod 155
Wedge Nut 156

FOR ANY SPECIALIST REQUIREMENTS PLEASE CONTACT ONE OF OUR LOCAL BRANCHES.

WE'RE NEVER TOO FAR AWAY...

NO MORE THAN 3 HOURS BY ROAD, 30 SECONDS BY PHONE AND 1 CLICK ON LINE

Unitrunk is truly international, with partners and distributors strategically located around the world. But we are never too far away. Across the UK and Ireland, we work smart, fast and reliably. With 2 factories and 7 depots strategically positioned, our branch network has the ability to offer an unsurpassed service to our customers.

We pride ourselves on our wide range of steel cable management products made right here in the UK and Ireland, complemented by our regional distribution network. With impressive manufacturing capabilities, our product range just gets bigger, better and stronger. You can rely on our supply and stock system to service your needs from bespoke solutions to full scale contracts.



"Local distribution centres enable same day & next day delivery and collections."

* In accordance with stock availability.
** Standard delivery terms are 48 hours from receipt of order.

OUR DEPOTS

N. IRELAND (Head Office)
Unitrunk Head Office, Blaris Industrial Estate,
Altona Road, Lisburn, BT27 5QB, Antrim, N.Ireland.

T: +44 (0) 2892 625100
F: +44 (0) 2892 625101
E: lisburn@unitrunk.co.uk

IRELAND
Unitrunk Ireland, Unit 17 Rosemount Park Drive,
Rosemount Business Park, Ballycoolin Road, Dublin 11, Ireland.

T: +353 (0) 1 8200292
F: +353 (0) 1 8223533
E: dublin@unitrunk.ie

SCOTLAND
Unitrunk Scotland, Caputhall Road, Deans Industrial Estate,
Livingston, EH54 8AS, West Lothian, Scotland.

T: +44 (0) 1506 461964
F: +44 (0) 1506 461969
E: livingston@unitrunk.co.uk

NORTH EAST
Unitrunk North East, Unit 1, Angel Park, Drum Industrial
Estate, Chester-le-Street, DH2 1AQ, Durham, England.

T: +44 (0) 191 4921470
F: +44 (0) 191 4108702
E: northeast@unitrunk.co.uk

MANCHESTER
Unitrunk Manchester, Unit 2 Orbital Way,
Windmill Lane, Denton, Manchester, M34 3QA, England.

T: +44 (0) 161 3361177
F: +44 (0) 161 3361188
E: manchester@unitrunk.co.uk

WOLVERHAMPTON
Unitrunk Wolverhampton, Titan 2, Coxwell Avenue,
Wolverhampton Science Park, Stafford Road,
Wolverhampton, WV10 9RT, England.

T: +44 (0) 1902 717786
F: +44 (0) 1902 714105
E: wolverhampton@unitrunk.co.uk

HARLOW
Unitrunk Harlow, Unit G Flex Meadow, Merring Way,
The Pinnicles, Harlow, CM19 5SR, Essex, England

T: +44 (0) 1279 444481
F: +44 (0) 1279 444405
E: harlow@unitrunk.co.uk

BRISTOL
Unitrunk Bristol, Poplar Way East, Cabot Park,
Avonmouth, Bristol, BS11 0YH, England

T: +44 (0) 1179 823720
F: +44 (0) 1179 382998
E: bristol@unitrunk.co.uk

VANTRUNK
Vantrunk, Swineyard Lane, Appleton,
Warrington, Cheshire, WA16 0SD, England
T: +44 (0) 1928 564211
F: +44 (0) 1928 580157
E: sales@vantrunk.co.uk




View our complete
product range online at

unitrunk.co.uk

UK'S LARGEST DISTRIBUTION NETWORK...

NO MORE THAN
3 HOURS BY ROAD,
30 SECONDS BY
PHONE AND 1 CLICK
ON LINE



UNITRUNK

N. IRELAND (Head Office)
T: +44 (0) 2892 625100

IRELAND
T: +353 (0) 1 8200292

SCOTLAND
T: +44 (0) 1506 461964

NORTH EAST
T: +44 (0) 191 4921470

MANCHESTER
T: +44 (0) 161 3361177

WOLVERHAMPTON
T: +44 (0) 1902 717786

HARLOW
T: +44 (0) 1279 444481

BRISTOL
T: +44 (0) 1179 823720

VANTRUNK
T: +44 (0) 1928 564211

unitrunk.co.uk **unitrunk.ie**

See page 162 for more contact details