

Panel Product Range



Click on a **better solution**

Value Added Assembly

IMO Value Added Assembly Division will help you to:

- **Reduce your stock level**
- **Reduce cost**
- **Ensure quality**
- **Increase productivity**

Are you looking for a supplier for your assemblies who can offer:

- Access to a wide range of products
- Extended range of DIN terminals and accessories
- Relay and sockets, MCBs, power supplies, timers, contactors, signal interface units.
- Standard or custom marker solutions for DIN terminals
- Flexible packing facilities for individual or volume packing


IMO through its Assembly Division can provide Value Added Assembly solutions built to customer specification whether you are looking for prototypes, one-off projects, or small to large volume requirements with regular deliveries, IMO can offer you a solution.


As a world recognised manufacturer of electrical components, IMO have a wide range of connection, power, control and interface products readily available from stock and are always looking forward to the next challenge.

Your assembly can be as simple as 2 DIN terminals on a small piece of rail, to multiple products on DIN rail lengths up to 2m; and if required IMO have a range of standard enclosures which are available to accommodate your units, or we can design a custom solution with you.

Challenge us and tell us about your assembly needs and see what solution we can propose.

To save time and money call us today with your drawings, photos and specifications.



Push Buttons	Cam Switches	Enclosures	Power Supplies	DIN Rail Timers	Timers	Contactors
						

The Complete Panel Solution

IMO's range of Panel products continues to deliver innovation and efficiency worldwide, and is where technology and engineering excellence come together.

IMO's Panel range has been specifically designed to meet the demanding needs of today's panel builders and engineers whose requirements can range from a simple DIN Terminal through to a complete panel solution.


IMO's products allow panel builders globally to deliver significant advances through greater efficiency, reliability and performance, thereby increasing their competitive advantage and delivering the optimum panel solution.

When purchasing from IMO you can be confident that over 40 years experience servicing the Panel Builder market has gone into the design and development of the IMO range.


Listed in this brochure are just some of the most popular products from the IMO Panel range. If you can't find what you are looking for, please contact the IMO Sales Desk on +44 (0)20 8452 6444. We will be happy to assist you with your enquiry.



Power Supplies



Relays & Sockets



DIN Rail Terminals

Enclosed Starters	Switch Fuses	Isolators	Motor Protection Circuit Breakers	Miniature Circuit Breakers	DIN Rail Terminals	Relays & Sockets

Push Buttons



- IP67/IP65 Protection
- Opaque or Illuminated
- Aluminium, Black or Chrome Bezel
- Snap-On Contact Blocks
- Colour Coded Contacts
- International Approvals Including UL Approved Products
- Maintained or Spring Return
- Assembled Control Stations
- 1/2/3 Hole Push Button Enclosure
- Key Operated Switch
- Labelling Accessories

Emergency Stop Buttons

Part Number	Description
BS3P3RED-0	Emergency Stop Push Button 28mm, Red With White "0", Twist To Release, Black Bezel
BS3P45RED	Emergency Stop Push Button 38mm, Red, Pull To Release
BS3P44S3	Emergency Stop Push Button 40mm, Red Key Release
BC3P34RED-0	Emergency Stop Push Button 40mm, Red With White "0", Twist To Release, Chrome Bezel
BS3P34RED-0	Emergency Stop Push Button 40mm, Red With White "0", Twist To Release, Black Bezel
BS3P44RED	Emergency Stop Push Button 30mm, Red, Pull To Release
B3-SK-YELLOW	Emergency Stop Shroud for 40mm Max Diameter Button
BG10P45-11	Emergency Stop Station 40mm Red Button, Yellow Face, Pull To Release, 1N/O And 1N/C Contacts
BG10P34P-02	Emergency Stop Station 70mm Twist To Release Red Button, Yellow Enclosure Face, 2N/C Contacts
BG10P34P-11	Emergency Stop Station 70mm Twist To Release Red Button, Yellow Enclosure Face, 1N/O + 1N/C Contacts

Push Buttons / Rotary Knobs

Part Number	Description
BS3P14RED-0	Mushroom Head Push Button 40mm, Red With White "0"
BS3DBLA-ARROW	Push Button Spring Return Black With White Arrow Black Bezel
B3DBLACK	Push Button Spring Return Black, Aluminium Bezel
BS3DBLACK	Push Button Spring Return Black, Black Bezel
B3DBLUE	Push Button Spring Return Blue, Aluminium Bezel
BS3DBLUE	Push Button Spring Return Blue, Black Bezel
BS3DGRE-I	Push Button Spring Return Green With White "I" Black Bezel
BS3DGREEN	Push Button Spring Return Green, Black Bezel
BS3DRED	Push Button Spring Return Red, Black Bezel
B3DRED	Push Button Spring Return Red, Aluminium Bezel
B3P1RED	Push Button Spring Return 28mm Red, Aluminium Bezel
BS3DYELLOW	Push Button Spring Return Yellow, Black Bezel
B3KN2	Rotary Knob, 2 Position Maintained 60deg, Aluminium Bezel
BC3KN2	Rotary Knob, 2 Position Maintained 60deg, Chrome Bezel
BS3KN2	Rotary Knob, 2 Position Maintained 60deg, Black Bezel
B3KN3	Rotary Knob, 3 Position Maintained 60deg, Aluminium Bezel
BS3KN3	Rotary Knob, 3 Position Maintained 60deg, Black Bezel
BS3KN9	Rotary Knob, 2 Position Maintained 120deg, Black Bezel
BS3KN10	Rotary Knob, 2 Position Maintained 90deg, Black Bezel

Illuminated Push Buttons

Part Number	Description
B3DLRED	Illuminated Push Button Spring Return Red, Aluminium Bezel
B3DLGREEN	Illuminated Push Button Spring Return Green, Aluminium Bezel
B3DLYELLOW	Illuminated Push Button Spring Return Yellow, Aluminium Bezel
B3DLBLUE	Illuminated Push Button Spring Return Blue, Aluminium Bezel
BS3KL2	Illuminated Rotary Knob 2 Position Maintained, Black Bezel
BS3DT-GRE/RED	Double Actuation Push Button Green - Red, Black Bezel
BC3DT-GRE/RED	Double Actuation Push Button Green - Red, Chrome Bezel
B3DT-GRE/RED	Double Actuation Push Button Green - Aluminium Bezel

Transparent Lens Caps

Part Number	Description
B3RFGREEN	Lens Cap, Green
B3RFRED	Lens Cap, Red
B3RGREEN	Lens Cap, Green, Fresnel Lens
B3RRRED	Lens Cap, Red, Fresnel Lens



Contact Blocks




Part Number	Description
B3T01	1N/C Clips Onto B3S/B3M
B3T10	1N/O Clips Onto B3S/B3M
B4TU11	1N/O And 1N/C, for BG... Enclosures
B4TU10F	1N/O With Lamp Holder, for BG... Enclosures
B4TU10	1N/O, for BG... Enclosures
B4TU02	2N/C, for BG... Enclosures
B4TU20	2N/O, for BG... Enclosures
BG1	Pushbutton Enclosure 1 Hole Grey
BG1YEL	Pushbutton Enclosure 1 Hole Yellow
BG2	Pushbutton Enclosure 2 Hole Grey
BG3	Pushbutton Enclosure 3 Hole Grey
J7049	Pushbutton Collar tightening tool

LED Pilot Lights



Part Number	Description
LMB-110-GREEN	LED Pilot Light 110VAC Green
LMB-110-RED	LED Pilot Light 110VAC Red
LMB-110-WHITE	LED Pilot Light 110VAC White
LMB-110-YELLOW	LED Pilot Light 110VAC Yellow
LMB-230-GREEN	LED Pilot Light 230VAC Green
LMB-230-RED	LED Pilot Light 230VAC Red
LMB-230-WHITE	LED Pilot Light 230VAC White
LMB-230-YELLOW	LED Pilot Light 230VAC Yellow
LMB-24-BLUE	LED Pilot Light 24V AC/DC Blue
LMB-24-GREEN	LED Pilot Light 24V AC/DC Green
LMB-24-RED	LED Pilot Light 24V AC/DC Red
LMB-24-WHITE	LED Pilot Light 24V AC/DC White
LMB-24-YELLOW	LED Pilot Light 24V AC/DC Yellow

Quick Chart Selection



This is just a selection of our most popular Push Buttons. For the entire range, please go to www.imopc.com and download the dedicated Push Button brochure.



B3RF..	B3P34RED-0	BS3P44RED	BS3P44S3	B3DL..	B3-SK-YELLOW	BG1	B4TU11.. Contact Block

Cam Switches



IMO's range of Cam Switches incorporates a unique building block system that allows for any number of switch variants to be built and supplied to the customer. Such is the flexibility of the Cam Switches, that they can be utilised in countless applications including mains/motor switching and control and instrumentation circuits.


The standard contact rating is 20A, although higher ratings are available on request and these switches have double interruption per pole and two contacts per cell. Standard units incorporate a 22.5mm central fixing for panel mounting. The switch body and actuators are supplied separately to provide a choice of four different set up configurations. Connection from actuator to switch body is made through a solid aluminium shaft.

Manufactured in accordance with IEC 60947-3, the new Cam Switches carry an IP65 rating appropriately when mounted in a suitably rated enclosure and have 'finger proof' screw terminals. The switch body is supplied complete with legend plate and all units are UL/cUL approved.




Part Number	Description
CS20A-A1	1 Pole 2 Position 20A, On/Off With Legend Plate
CS20A-A2	2 Pole 2 Position 20A, On/Off With Legend Plate
CS20A-A4	4 Pole 2 Position 20A, On/Off With Legend Plate
CS20A-A8	8 Pole 2 Position 20A, On/Off With Legend Plate
CS20A-ST31	1 Pole 3 Position 20A, Step With Legend Plate
CS20A-ST33	3 Pole 3 Position 20A, Step With Legend Plate
CS20A-ST42	2 Pole 4 Position 20A, Step With Legend Plate
CS20A-ST45	5 Pole 4 Position 20A, Step With Legend Plate
CS20A-ST51	1 Pole 5 Position 20A, Step With Legend Plate
CS20A-ST52	2 Pole 5 Position 20A, Step With Legend Plate
CS20A-ST61	1 Pole 6 Position 20A, Step With Legend Plate
CS20A-U1	1 Pole 3 Position 20A, Changeover With Legend Plate
CS20A-U2	2 Pole 3 Position 20A, Changeover With Legend Plate
CS20A-U3	3 Pole 3 Position 20A, Changeover With Legend Plate
CS20A-U4	4 Pole 3 Position 20A, Changeover With Legend Plate
CS20A-U6	6 Pole 3 Position 20A, Changeover With Legend Plate
CS20A-W2	2 Pole 2 Position 20A, Changeover Without Off With Legend Plate
CS20A-W3	3 Pole 2 Position 20A, Changeover Without Off With Legend Plate
CS20A-W4	4 Pole 2 Position 20A, Changeover Without Off With Legend Plate
CS20A-W8	8 Pole 2 Position 20A, Changeover Without Off With Legend Plate
RB2	Cam Switch Handle, Round Bezel Lever
RBK2	Cam Switch Handle, Round Bezel, Key Operated
SP2	Cam Switch Handle, Escutcheon Plate Lever
SPK2	Cam Switch Handle, Escutcheon Plate, Key Operated

Off-On Switch




CS20A-A..




For 1-4 Poles

Changeover Switch With Off




CS20A-U..




For 1-4 Poles


Changeover Switch Without Off



CS20A-W..



For 1-4 Poles



Enclosures



- ABS / Polycarbonate Body
- Plain Sided Walls
- Colour RAL 7035 – Light Grey
- Circuit Board Slots in Base
- IP67 / IP66
- Plastic Screws Captive Once Fitted
- Pre-Moulded Fixing Points in Base
- Suitable for Housing Electronic Terminal Blocks, Electro-Mechanical Components & Industrial Equipment
- Polycarbonate Versions (144EP Range) are UL & cUL Approved



ABS / Polycarbonate Enclosures

Part Number	Description
144E0001	Enclosure, ABS (75 X 125 X 75)
144E0002	Enclosure, ABS (125 X 125 X 75)
144E0003	Enclosure, ABS (125 X 125 X 100)
144E0004	Enclosure, ABS (125 X 175 X 75)
144E0005	Enclosure, ABS (125 X 175 X 100)
144E0006	Enclosure, ABS (125 X 175 X 125)
144E0007	Enclosure, ABS (175 X 175 X 100)
144E0008	Enclosure, ABS (175 X 175 X 125)
144E0009	Enclosure, ABS (175 X 175 X 150)
144E0010	Enclosure, ABS (175 X 250 X 100)
144E0011	Enclosure, ABS (175 X 250 X 150)
144E1008	Enclosure, ABS (120 X 200 X 86)
144E1010	Enclosure, ABS (230 X 300 X 111)
144E2002	Transparent Lid Enclosure, ABS (125 X 125 X 75)
144E2003	Transparent Lid Enclosure, ABS (125 X 175 X 100)
144E2004	Transparent Lid Enclosure, ABS (125 X 175 X 150)
144EP0002	Enclosure, Polycarbonate (125 X 125 X 75)
144EP0004	Enclosure, Polycarbonate (125 X 175 X 75)
144EP0005	Enclosure, Polycarbonate (125 X 175 X 100)
144EP0006	Enclosure, Polycarbonate (125 X 175 X 125)
144EP0008	Enclosure, Polycarbonate (175 X 175 X 125)
144EP0010	Enclosure, Polycarbonate (175 X 250 X 100)
144EP0011	Enclosure, Polycarbonate (175 X 250 X 150)

Distribution Boxes

Part Number	Description
E-04W	4 Way IP65 Enclosure, 127x200x120, Transparent Door
E-08W	8 Way IP65 Enclosure, 200x200x120, Transparent Door
E-12W	12Way IP65 Enclosure 318x258x142, Transparent Door
E-24W	24Way IP65 Enclosure 318x383x142, Transparent Door
E-36W	36Way IP65 Enclosure 507x383x142, Transparent Door

Accessories

Part Number	Description
144A0001	Hinge Pair
144A0002	Fastening lug, 4 off
144A0003	Inspection window 2 mod.
144A0004	Inspection window 4 mod.
144A0005	Inspection window 6 mod.
144A0006	Inspection window 8 mod.
144A0007	Inspection window 10 mod.
144A0008	Inspection window 12 mod.
144A0009	Vent device IP34
144A0010	Vent device IP44
144R0001	DIN Rail For 144E0001
144R0002	DIN Rail For 144E0002, 0003
144R0004	DIN Rail For 144E0004, 0005, 0006, 0007, 0008 & 0009
144R0010	DIN Rail For 144E0010, 0011
E-Lock	Enclosure Lock To Suit E-xxW Enclosures

144E0003



144E2003



E-08W



E-24W



Power Supplies



- Single & Three Phase Versions
- Universal Input
- AC/DC Operation
- High Efficiency up to 93%
- Class 2 Types
- Up to 960W
- Plastic & Metal Enclosures
- Short Circuit Protection
- DIN Rail Mountable



DPS-1 Single Phase

Part Number	Description
DPS-1-015-5DC	90-264VAC Input, 5VDC Output, 15W 3A, Plastic Body
DPS-1-018-12DC	90-264VAC Input, 12VDC Output, 18W 1.5A, Plastic Body
DPS-1-018-24DC	90-264VAC Input, 24VDC Output, 18W 0.75A, Plastic Body
DPS-1-030-5DC	85-264VAC Input, 5VDC Output, 30W 6A, Plastic Body
DPS-1-030-12DC	85-264VAC Input, 12VDC Output, 30W 2.5A, Plastic Body
DPS-1-030-24DC	85-264VAC Input, 24VDC Output, 30W 1.25A, Plastic Body
DPS-1-030-48DC	85-264VAC Input, 48VDC Output, 30W 0.625A, Plastic Body
DPS-1-050-5DC	85-264VAC Input, 5VDC Output, 50W 10A, Plastic Body
DPS-1-060-12DC	85-264VAC Input, 12VDC Output, 60W 5A, Plastic Body
DPS-1-060-24DC	85-264VAC Input, 24VDC Output, 60W 2.5A, Plastic Body
DPS-1-060-48DC	85-264VAC Input, 48VDC Output, 60W 1.25A, Plastic Body
DPS-1-100-12DC	115/230VAC Input, 12VDC Output, 100W 8.4A, Plastic Body
DPS-1-100-24DC	115/230VAC Input, 24VDC Output, 100W 4.2A, Plastic Body
DPS-1-100-48DC	115/230VAC Input, 48VDC Output, 100W 2.1A, Plastic Body
DPS-1-120-12DC	115/230VAC Input, 12VDC Output, 120W 10A, Metal Body
DPS-1-120-24DC	115/230VAC Input, 24VDC Output, 120W 5A, Metal Body
DPS-1-120-48DC	115/230VAC Input, 48VDC Output, 120W 2.5A, Metal Body
DPS-1-240-24DC	115/230VAC Input, 24VDC Output, 240W 10A, Metal Body
DPS-1-240-48DC	115/230VAC Input, 48VDC Output, 240W 5A, Metal Body
DPS-1-300-24DC	115/230VAC Input, 24VDC Output, 300W 12.5A, Metal Body
DPS-1-300-48DC	115/230VAC Input, 48VDC Output, 300W 6.25A, Metal Body
DPS-1-480-24DC	115/230VAC Input, 24VDC Output, 480W 20A, Metal Body
DPS-1-480-48DC	115/230VAC Input, 48VDC Output, 480W 10A, Metal Body

DPS-3 Three Phase

Part Number	Description
DPS-3-120-12DC	340-575VAC Input, 12VDC Output, 120W 10A, Metal Body
DPS-3-120-24DC	340-575VAC Input, 24VDC Output, 120W 5A, Metal Body
DPS-3-240-24DC	340-575VAC Input, 24VDC Output, 240W 10A, Metal Body
DPS-3-240-48DC	340-575VAC Input, 48VDC Output, 240W 5A, Metal Body
DPS-3-480-24DC	340-575VAC Input, 24VDC Output, 480W 20A, Metal Body
DPS-3-480-48DC	340-575VAC Input, 48VDC Output, 480W 20A, Metal Body
DPS-3-960-24DC	340-575VAC Input, 24VDC Output, 960W 40A, Metal Body
DPS-3-960-48DC	340-575VAC Input, 48VDC Output, 960W 20A, Metal Body

MPS-1 Single Phase

Part Number	Description
MPS-1-007-5DC	90-264VAC Input, 5VDC Output, 7.5W 1.5A, Plastic Body
MPS-1-015-5DC	90-264VAC Input, 5VDC Output, 15W 3A, Plastic Body
MPS-1-022-5DC	90-264VAC Input, 5VDC Output, 22W 4.5A, Plastic Body
MPS-1-035-5DC	90-264VAC Input, 5VDC Output, 35W 7A, Plastic Body
MPS-1-060-5DC	90-264VAC Input, 5VDC Output, 60W 12A, Plastic Body
MPS-1-010-12DC	90-264VAC Input, 12VDC Output, 10W 0.83A, Plastic Body
MPS-1-024-12DC	90-264VAC Input, 12VDC Output, 24W 2A, Plastic Body
MPS-1-033-12DC	90-264VAC Input, 12VDC Output, 33W 2.75A, Plastic Body
MPS-1-054-12DC	90-264VAC Input, 12VDC Output, 54W 4.5A, Plastic Body
MPS-1-072-12DC	90-264VAC Input, 12VDC Output, 72W 6A, Plastic Body
MPS-1-010-24DC	90-264VAC Input, 24VDC Output, 10W 0.42A, Plastic Body
MPS-1-024-24DC	90-264VAC Input, 24VDC Output, 24W 1A, Plastic Body
MPS-1-036-24DC	90-264VAC Input, 24VDC Output, 36W 1.5A, Plastic Body
MPS-1-060-24DC	90-264VAC Input, 24VDC Output, 60W 2.5A, Plastic Body
MPS-1-100-24DC	90-264VAC Input, 24VDC Output, 100W 4.8A, Plastic Body



Timers



- 17.5mm DIN Rail Mount Range
- 48 DIN Panel Mount/Plug-In Range
- Multifunction
- On / Off / True Off Delay
- Asymmetrical
- Star Delta
- 24 -240VAC/DC, 400VAC (TDSD1)
- Wide Input Voltage Range

IMO's comprehensive range of DIN Rail mountable Timers delivers up-to-the-minute technology. Ranging from the simple single-function through to the multi-function timer with display, these timers are being used daily in all types of applications and industries. The ultra compact design and top-mounted terminals make installation easy, even in the tightest of panels, providing customers with a solution at minimal cost. Wide input voltage capability allow these products to be installed in applications across the world.

IMO's range of Panel Mount / Plug-In Timers provide users with a range of settings and functionality and timing ranges between 0.1sec and 100hrs. Other key features include indication of time range, time up and power on timing. IMO Sockets are available to complement the panel mounting facility thereby giving the installer the option of DIN rail mounting, surface mounting or printed-circuit board mounting.


IMO Timers are always of the highest quality, and are backed with a Three Year Warranty. If you require a timer that is not listed here please contact IMO to receive information on the full range.

Panel Mount / Plug-In

Part Number	Description
TA11-A100-230AC	Timer 0.05s-60hr 2C/O Multi/F 5A, 11pin octal, 100-230VAC
TA11-A24AC/DC	Timer 0.05s-60hr 2C/O Multi/F 5A, 11pin octal, 24VAC/DC
TA8-A100-230AC	Timer 0.05s-60hr 2C/O On-DELAY 5A, 8pin octal, 100-230VAC
TA8-A24AC/DC	Timer 0.05s-60hr 2C/O On-DELAY 5A, 8pin octal, 24VAC/DC
TA8-DA100-230AC	Timer 0.1m-12m 2C/O True Off-DELAY 5A, 8pin octal, 100-230VAC
TA8-SA100-230AC	Timer 0.05s-60hr 1C/O On-DELAY 5A, 8pin octal, 100-230VAC
TA8-TA100-230AC	Timer 0.05s-60hr 2C/O Asymmetrical 5A, 8pin octal, 100-230VAC
TY4-12DC	14 Pin Plug-In On Delay Timer, 0.1s-100h, 12VDC 4C/O
TY4-24DC	14 Pin Plug-In On Delay Timer, 0.1s-100h, 24VDC 4C/O
TY4-24AC	14 Pin Plug-In On Delay Timer, 0.1s-100h, 24VAC 4C/O
TY4-115AC	14 Pin Plug-In On Delay Timer, 0.1s-100h, 115VAC 4C/O
TY4-230AC	14 Pin Plug-In On Delay Timer, 0.1s-100h, 230VAC 4C/O

DIN Rail Mountable

Part Number	Description
TDM10	Multifunction DIN Timer 10 Func, 1C/O, 24-230V AC/DC
TDAS	Multifunction Asymmetrical DIN Timer, 1C/O, 24-230V AC/DC
TDSD1	Star/Delta DIN Timer 20-500ms, 2C/O, 230-400VAC



Contactors 4 - 400kW



- 10A up to 1200A 400V AC3
- Minimum Size & Maximum Performance
- AC & DC Operated
- Ambient Temperature -40°C to +90°C
- DIN Rail Mounting up to 115A AC3
- Bifurcated Aux. Contacts
- High Contact Reliability
- 4 Pole Full Rated Version Available
- Coil Connection Top & Bottom (MC10N to MC22N)



Micro Contactors (MA04, MA05)

Part Number	Description
MA04-S-22230AC	Micro Relay Cont 4P (2N/O+2N/C), 3A AC15, 230VAC coil
MA05-S-01110AC	Micro Cont 3P Open 2.2kW 5A AC3, 1N/C Aux. 110VAC coil
MA05-S-0124AC	Micro Cont 3P Open 2.2kW 5A AC3, 1N/C Aux. 24VAC coil
MA05-S-10110AC	Micro Cont 3P Open 2.2kW 5A AC3, 1N/O Aux. 110VAC coil
MA05-S-10230AC	Micro Cont 3P Open 2.2kW 5A AC3, 1N/O Aux. 230VAC coil
MA05-S-1024DC	Micro Cont 3P Open 2.2kW 5A AC3, 1N/O Aux. 24VDC coil
MA05-R-S-0124AC	Micro Rev Cont 3P Open 2.2kW 5A AC3, 1N/C Aux. 24VAC coil
MA05-P-0124AC	Micro Cont PCB 3P Open 2.2kW 5A AC3, 1N/C Aux. 24VAC coil

Miniature Contactors (MR07, MB09, MB12)

Part Number	Description
MR07-S-22230	Mini Relay 4P (2N/O+2N/C), 3A AC15, 230VAC coil
MB09-S-10=24	Mini Cont 3P Open 4kW 9A AC3, 1N/O Aux, 24VDC coil
MB09-S-1048	Mini Cont 3P Open 4kW 9A AC3, 1N/O Aux, 48VAC coil
MB09-S-10110	Mini Cont 3P Open 4kW 9A AC3, 1N/O Aux, 110VAC coil
MB09-S-01230	Mini Cont 3P Open 4kW 9A AC3, 1N/C Aux, 230VAC coil
MB09-S-10230	Mini Cont 3P Open 4kW 9A AC3, 1N/O Aux, 230VAC coil
MB09-P-10=24	Mini Cont 3P Open 4kW 9A AC3, 1N/C Aux, PCB mount, 24VDC coil
MB12-S-10=24	Mini Cont 3P Open 5.5kW 12A AC3, 1N/O Aux, 24VDC coil

Standard Contactors (MC10N - MC22N)

Part Number	Description
MC10N-S-1024DC	Contactors 3P Open 4kW 10A AC3, 1N/O Aux, 24VDC coil
MC10N-S-10110AC	Contactors 3P Open 4kW 10A AC3, 1N/O Aux, 110VAC coil
MC10N-S-10230AC	Contactors 3P Open 4kW 10A AC3, 1N/O Aux, 230VAC coil
MC14N-S-1024AC	Contactors 3P Open 5.5kW 14A AC3, 1N/O Aux, 24VAC coil
MC14N-S-10230AC	Contactors 3P Open 5.5kW 14A AC3, 1N/O Aux, 230VAC coil
MC14N-S-10400AC	Contactors 3P Open 5.5kW 14A AC3, 1N/O Aux, 400VAC coil
MC18N-S-1024DC	Contactors 3P Open 7.5kW 18A AC3, 1N/O Aux, 24VDC coil
MC18N-S-10230AC	Contactors 3P Open 7.5kW 18A AC3, 1N/O Aux, 230VAC coil
MC22N-S-10110AC	Contactors 3P Open 11kW 22A AC3, 1N/O Aux, 110VAC coil
MC22N-S-10230AC	Contactors 3P Open 11kW 22A AC3, 1N/O Aux, 230VAC coil
MC10N-S-00-22110AC	Contactors 4P (2N/O+2N/C) 4kW 10A AC3, 110VAC coil
MC10N-S-00-31110AC	Contactors 4P (3N/O+1N/C) 4kW 10A AC3, 110VAC coil
MC10N-S-00-40230AC	Contactors 4P Open 4kW 10A AC3, 230VAC coil
MC18N-S-00-40110AC	Contactors 4P Open 7.5kW 18A AC3, 110VAC coil

Standard Contactors (MC24 - MC115)

Part Number	Description
MC24-S-00110	Contactors 3P Open 11kW 24A AC3, 110VAC coil
MC24-S-00230	Contactors 3P Open 11kW 24A AC3, 230VAC coil
MC24-S-00=24	Contactors 3P Open 11kW 24A AC3, 24VDC coil
MC32-S-00110	Contactors 3P Open 15kW 32A AC3, 110VAC coil
MC32-S-00230	Contactors 3P Open 15kW 32A AC3, 230VAC coil
MC32-S-0024	Contactors 3P Open 15kW 32A AC3, 24VAC coil
MC40-S-00230	Contactors 3P Open 18.5kW 40A AC3, 230VAC coil
MC50-S-00400	Contactors 3P Open 22kW 50A AC3, 400VAC coil
MC62-S-00110	Contactors 3P Open 30kW 62A AC3, 110VAC coil
MC74-S-00230	Contactors 3P Open 37kW 74A AC3, 230VAC coil
MC90-S-00230	Contactors 3P Open 45kW 90A AC3, 230VAC/DC coil
MC90-S-00110	Contactors 3P Open 45kW 90A AC3, 110VAC/DC coil
MC115-S-00230	Contactors 3P Open 55kW 115A AC3, 230VAC/DC coil



Capacitor Switching Contactors for reactive or non-reactive capacitor banks

Part Number	Description
MC18N-K-10400AC	12.5kVar Cap. Sw. Contactor 3P, 1N/O Aux. 4000VAC coil
MC18N-K-10230AC	12.5kVar Cap. Sw. Contactor 3P, 1N/O Aux. 230VAC coil
MC32-K-00110	25kVar Cap. Sw. Contactor, 3P, 110VAC coil
MC32-K-00230	25kVar Cap. Sw. Contactor, 3P, 230VAC coil
MC32-K-00400	25kVar Cap. Sw. Contactor, 3P, 400VAC coil
MC50-K-00400	33.3kVar Cap. Sw. Contactor, 3P, 400VAC coil
MC62-K-00110	50kVar Cap. Sw. Contactor, 3P, 110VAC coil
MC62-K-00230	50kVar Cap. Sw. Contactor, 3P, 230VAC coil
MC62-K-00400	50kVar Cap. Sw. Contactor, 3P, 400VAC coil
MC74-K-00230	75kVar Cap. Sw. Contactor, 3P, 230VAC coil
MC74-K-00400	75kVar Cap. Sw. Contactor, 3P, 400VAC coil
MC115-K-00230	100kVar Cap. Sw. Contactor, 3P, 230VAC coil
MC115-K-00400	100kVar Cap. Sw. Contactor, 3P, 400VAC coil

DC Operated Contactor low power consumption 3W inrush-sealed

Part Number	Description
MCD10-S-10=24	Contactors 4kW 10A 3P, 1 N/O Aux. 24VDC coil
MCD14-S-10=24	Contactors 5.5kW 14A 3P, 1 N/O Aux. 24VDC coil
MCD18-S-10=24	Contactors 7.5kW 18A 3P, 1 N/O Aux. 24VDC coil
MCD22-S-10=24	Contactors 11kW 22A 3P, 1 N/O Aux. 24VDC coil
MCD32-S-00=24	Contactors 15kW 32A 3P, 24VDC coil
MCD40-S-00=24	Contactors 18.5kW 40A 3P, 24VDC coil

Accessories


Part Number	Description
MBA-11	1N/O + 1N/C for MB09-MB12 contactors - top mount
MBA-22	2N/O + 2N/C for MB09-MB12 contactors - top mount
MCA01	1N/C Contact, For MC10 to MC115 Contactors, Top Mount
MCA10	1N/O Contact, For MC10 to MC115 Contactors, Top Mount
MCAH01	High Switching Capacity 25A AC1, 1N/C Contact, Top Mount
MCAH10	High Switching Capacity 25A AC1, 1N/O Contact, Top Mount
MCAS-11	1N/O + 1N/C, For MC24 to MC115 Contactors, Side Mount
MCAT11	1N/O + 1N/C, For MC151 to MC316 Contactors, Top Mount
MC-I-W	Interlock for MC(D)10 to MC(D)40 Contactors
MC-I-X	Interlock for MC50 to MC74 Contactors
MC-I-Y	Interlock for MC90 to MC115 Contactors

Thermal Overload Relays

Part Number	Description
U12/16E0.9-MC	Manual reset Overload 0.6-0.9A, MC10N-MC22N
U12/16E1.2-MC	Manual reset Overload 0.8-1.2A, MC10N-MC22N
U12/16E1.8-MC	Manual reset Overload 1.2-1.8A, MC10N-MC22N
U12/16E2.7-MC	Manual reset Overload 1.8-2.7A, MC10N-MC22N
U12/16E4-MC	Manual reset Overload 2.7-4A, MC10N-MC22N
U12/16E6-MC	Manual reset Overload 4-6A, MC10N-MC22N
U12/16E9-MC	Manual reset Overload 6-9A, MC10N-MC22N
U12/16E11-MC	Manual reset Overload 8-11A, MC10N-MC22N
U12/16E14-MC	Manual reset Overload 10-14A, MC10N-MC22N
U12/16E18-MC	Manual reset Overload 13-18A, MC10N-MC22N
U12/16E23-MC	Manual reset Overload 17-23A, MC10N-MC22N
U12/16E30-MC	Manual reset Overload 22-30A, MC10N-MC22N
MCOR-1-0.18	Man./Auto reset Overload 0.12-0.18A, MC10N-MC32
MCOR-1-0.27	Man./Auto reset Overload 0.18-0.27A, MC10N-MC32
MCOR-1-0.4	Man./Auto reset Overload 0.27-0.4A, MC10N-MC32
MCOR-1-0.6	Man./Auto reset Overload 0.4-0.6A, MC10N-MC32
MCOR-1-0.9	Man./Auto reset Overload 0.6-0.9A, MC10N-MC32
MCOR-1-1.2	Man./Auto reset Overload 0.8-1.2A, MC10N-MC32
MCOR-1-1.8	Man./Auto reset Overload 1.2-1.8A, MC10N-MC32
MCOR-1-2.7	Man./Auto reset Overload 1.8-2.7A, MC10N-MC32
MCOR-1-4	Man./Auto reset Overload 2.7-4A, MC10N-MC32
MCOR-1-6	Man./Auto reset Overload 4-6A, MC10N-MC32
MCOR-1-9	Man./Auto reset Overload 6-9A, MC10N-MC32
MCOR-1-11	Man./Auto reset Overload 8-11A, MC10N-MC32
MCOR-1-14	Man./Auto reset Overload 10-14A, MC10N-MC32
MCOR-1-18	Man./Auto reset Overload 13-18A, MC10N-MC32
MCOR-1-24	Man./Auto reset Overload 17-24A, MC10N-MC32
MCOR-1-32	Man./Auto reset Overload 23-32A, MC10N-MC32
MCOR-2-14	Manual reset Overload 10-14A, MC24-MC40
MCOR-2-20	Manual reset Overload 14-20A, MC24-MC40
MCOR-2-28	Manual reset Overload 20-28A, MC24-MC40
MCOR-2-42	Manual reset Overload 28-42A, MC24-MC40



This is just a selection of our most popular Contactors. For the entire range, please go to www.imopc.com or scan this QR code with your smartphone.



Modular Heating & Lighting Contactors



- Suitable for Control of Lamps, Heating, Air-Conditioning & Motor Control
- 2 or 4 Pole Version
- 20A up to 63A 400V AC1
- Multiple Pole Configuration Available
- Space Saving Design
- Low Switching Noise
- Low Power Consumption
- Coil Voltage 230VAC or 24VAC



Part Number	Description
HC20-20230	20A 2 Pole N/O 230VAC coil
HC20-02230	20A 2 Pole N/C 230VAC coil
HC20-2024	20A 2 Pole N/O 24VAC coil
HC25-20230	25A 2 Pole N/O 230VAC coil
HC25-40230	25A 4 Pole N/O 230VAC coil

Part Number	Description
HC25-04230	25A 4 Pole N/C 230VAC coil
HC40-20230	40A 2 Pole N/O 230VAC coil
HC40-40230	40A 4 Pole N/O 230VAC coil
HC63-20230	63A 2 Pole N/O 230VAC coil
HC63-40230	63A 4 Pole N/O 230VAC coil

Istart Enclosed Starters

Starters with Metal Enclosures

- Push button stop/start
- IP55 metal enclosure
- Prewired to accept overload
- Available with 3 phase and neutral isolator



Part Number	Description
DOLI-7.5230	DOL & Isolator 7.5kW 230VAC Supply
DOLI-7.5400	DOL & Isolator 7.5kW 400VAC Supply
SDSI-7.5230	Star Delta Starter 7.5kW 16A + Isolator, 230VAC Control, IP55
SDSI-7.5400	Star Delta Starter 7.5kW 16A + Isolator, 400VAC Control, IP55
SDSI-15230	Star Delta Starter 15kW 30A + Isolator, 230VAC Control, IP55
SDSI-15400	Star Delta Starter 15kW 30A + Isolator, 400VAC Control, IP55

Starters with Plastic Enclosures

- Push button stop/start
- IP65 ABS enclosure
- Prewired to accept overload (U12/16E..)



Part Number	Description
DOL10110	DOL Starter 4kW 10A Start and Stop, 110VAC coil
DOL10230	DOL Starter 4kW 10A Start and Stop, 230VAC coil
DOL10400	DOL Starter 4kW 10A Start and Stop, 400VAC coil
DOL18110	DOL Starter 7.5kW 18A Start and Stop, 110VAC coil
DOL18230	DOL Starter 7.5kW 18A Start and Stop, 230VAC coil
DOL18400	DOL Starter 7.5kW 18A Start and Stop, 400VAC coil

SDSI15-230



DOLI7.5-400



DOL10-230



U12/16E..-MC



HC25..





Switch 79/89 Isolator Series

Isolators

- On-Load Isolators
- 3 & 4 Pole as Standard
- Up to 8 Pole Versions
- Ratings from 63A to 630A
- Rotary Door Interlocked Handles
- Shaft Extensions from 120mm to 500mm
- Full Range of Accessories
- DIN Rail & Chassis Mount Versions



Base Mount Isolator - MS Series

Part Number	Description
MS793160	3 Pole 160 Amps
MS793200	3 Pole 200 Amps
MS793250	3 Pole 250 Amps
MS793400	3 Pole 400 Amps
MS793630	3 Pole 630 Amps
MS794200	4 Pole 200 Amps
MS794315	4 Pole 315 Amps
MS794630	4 Pole 630 Amps

Base Mount Compact Isolator - CM Series

Part Number	Description
CM793063	3 Pole 63A
CM793100	3 Pole 100A
CM793125	3 Pole 125A
CM794100	4 Pole 100A
CM794125	4 Pole 125A
CM794160	4 Pole 160A
CM794200	4 Pole 200A

Accessories - MS Series

Part Number	Description
79E1010	200mm Extension Shaft For MS & SF Series 32-630A Pistol Type
79E1011	250mm Extension Shaft For MS & SF Series 32-630A Pistol Type
79E1012	320mm Extension Shaft For MS79 Range & SF79 32-400 Amp Pistol Type
79E1013	500mm Extension Shaft For MS79 Range & SF79 32-400 Amp Pistol Type
79H1008	Pistol Black Handle To Suit MS Series and SF Series 100- 400 Amps
79H1009	Pistol Red/Yellow Handle To Suit MS Series and SF Series 100-400 Amps

Accessories - CM Series

Part Number	Description
79E1005	200mm Extension Shaft For CM79 Series 63-200A Rotary Type
79E1008	400mm Extension Shaft For CM79 Series 63-200A Rotary Type
79H1005	Rotary Black Handle To Suit CM Series, 63-200 Amps
79H1006	Rotary Red/Yellow Handle To Suit CM Series, 63-200 Amps

Switch Fuses

- On-Load Fuse Switches & Isolators
- 3 & 4 Pole Versions to 800 Amps
- Door Interlocked Handles:
 - ➔ Rotary & Pistol
 - ➔ 3 Padlocking Positions
- Shaft Extensions from 120mm to 500mm
- Auxiliary Contacts - Various Options
- Terminal Shrouds - Various Options
- Full Range of Neutral Terminals

Switch Fuses - CF Series

Part Number	Description
CF793020	Compact fuse switch 3 pole 20A
CF793N20	Compact fuse switch 3 P + Neutral 20A
CF793032	Compact fuse switch 3 pole 32A
CF793N32	Compact fuse switch 3 P + Neutral 32A
79H1006	Red/Yellow Handle, Pistol type, IP65
79E1017	Shaft Extension 320mm

Switch Fuses - SF Series

Part Number	Description
SF893032	Fuse switch 3 pole 32A, BS88 fuse size A1
SF893063	Fuse switch 3 pole 63A, BS88 fuse size A2
SF893100	Fuse switch 3 pole 100A, BS88 fuse size A4
SF893250	Fuse switch 3 pole 250A, BS88 fuse size B1-B3
SF893400	Fuse switch 3 pole 400A, BS88 fuse size B1-B4
SF894160	Fuse switch 4 pole 160A, BS88 fuse size A4
79H1006	Red/Yellow Handle, Pistol type, IP65, 32-63A
79H1009	Red/Yellow Handle, Pistol type, IP65, 100-400A
79E1012	Shaft Extension 320mm, 32-400A



AC Isolators



Enclosed - PE Series

- 3 to 8 Pole
- On-Load 20Amps to 125Amps
- Interlocked Enclosure Lid
- Padlocking Positions
- IP65 Enclosed Type
- Side Mounted Auxiliary Contacts
1 N/O + 1 N/C

Part Number	Description
PE69-3020	3 Pole 20 Amps
PE69-3025	3 Pole 25 Amps
PE69-3032	3 Pole 32 Amps
PE69-3040	3 Pole 40 Amps
PE69-3063	3 Pole 63 Amps
PE69-3080	3 Pole 80 Amps
PE69-4020	4 Pole 20 Amps
PE69-4025	4 Pole 25 Amps
PE69-4032	4 Pole 32 Amps
PE69-4040	4 Pole 40 Amps
PE69-4063	4 Pole 63 Amps
PE69-4080	4 Pole 80 Amps
PE69-6020	6 Pole 20 Amps
PE69-6025	6 Pole 25 Amps
PE69-6032	6 Pole 32 Amps
PE69-6040	6 Pole 40 Amps
PE69-6063	6 Pole 63 Amps
PE69-8020	8 Pole 20 Amps
PE69-8025	8 Pole 25 Amps
PE69-8032	8 Pole 32 Amps
PE69-8040	8 Pole 40 Amps
PE69-8063	8 Pole 63 Amps
PE69-8080	8 Pole 80 Amps
PE69-30100	3 Pole 100 Amps
PE69-30125	3 Pole 125 Amps
PE69-40100	4 Pole 100 Amps
PE69-40125	4 Pole 125 Amps

Base Mount - LB Series

- 3 & 4 pole
- On-Load 20Amps to 80Amps
- Door Interlocked Handles:
 - ⇒ Red/Yellow & Black, 64 x 64mm, 48 x 48mm
 - ⇒ 1 Padlocking Position on 48 x 48mm Version
 - ⇒ 3 Padlocking Positions on 64 x 64mm Version

Part Number	Description
LB69-3020	3 Pole 20 Amps
LB69-3025	3 Pole 25 Amps
LB69-3032	3 Pole 32 Amps
LB69-3040	3 Pole 40 Amps
LB69-3063	3 Pole 63 Amps
LB69-3080	3 Pole 80 Amps
LB69-4020	4 Pole 20 Amps
LB69-4025	4 Pole 25 Amps
LB69-4032	4 Pole 32 Amps
LB69-4040	4 Pole 40 Amps
LB69-4063	4 Pole 63 Amps
LB69-4080	4 Pole 80 Amps

PE & LB Accessories

Part Number	Description
H69-0001	Red/Yellow handle 64 x 64mm
H69-0001-B	Black handle 64 x 64mm
H69-0003	Red/Yellow handle 48 x 48mm
H69-0004	Black handle 48 x 48mm
J7049	Door handle mounting tool
E69-0001	Extension shaft – 100mm
E69-0002	Extension shaft – 200mm
E69-0003	Extension shaft – 300mm
E69-0004	Extension shaft – 400mm
A69-0001	Auxiliary contacts 1 N/O + 1 N/C
A69-0002	Auxiliary contacts 2 N/O
SN69-0001	Solid neutral block
SP69-0001	Add on neutral switching pole 20-40A

Front Panel Mount - PM Series


- 3 & 4 Pole
- On-Load 20Amps to 80Amps
- Door Handles:
 - ⇒ Red/Yellow & Black, 64 x 64mm, 48 x 48mm
 - ⇒ 1 Padlocking Position on 48 x 48mm Version
 - ⇒ 3 Padlocking Positions on 64 x 64mm Version

Part Number	Description
PM69-3020-B64	3P 20A Black Handle 64x64mm
PM69-3020-RY48	3P 20A Red/Yellow Handle 48x48mm
PM69-3020-RY64	3P 20A Red/Yellow Handle 64x64mm
PM69-3025-RY64	3P 25A Red/Yellow Handle 64x64mm
PM69-3032-RY64	3P 32A Red/Yellow Handle 64x64mm
PM69-3040-RY64	3P 40A Red/Yellow Handle 64x64mm
PM69-3063-RY64	3P 63A Red/Yellow Handle 64x64mm
PM69-3080-RY64	3P 80A Red/Yellow Handle 64x64mm
PM69-4020-RY64	4P 20A Red/Yellow Handle 64x64mm
PM69-4032-RY48	4P 32A Red/Yellow Handle 48x48mm
PM69-4040-RY64	4P 40A Red/Yellow Handle 64x64mm
PM69-4063-RY64	4P 63A Red/Yellow Handle 64x64mm

Direct Handle Base Mounted - DM Series

- 3 to 8 Pole
- On-Load 20Amps to 80Amps
- 1 Padlocking Position
- 48x48 Handle Black or Red/Yellow
- To Suit Distribution Boxes

Part Number	Description
DM69-3020-RY48	3 Pole 20 Amps Red/Yellow Handle
DM69-3032-RY48	3 Pole 32 Amps Red/Yellow Handle
DM69-3063-RY48	3 Pole 63 Amps Red/Yellow Handle
DM69-4032-RY48	4 Pole 32 Amps Red/Yellow Handle
DM69-4063-RY48	4 Pole 63 Amps Red/Yellow Handle
DM69-8032-RY48	8 Pole 32 Amps Red/Yellow Handle



DC Isolators



Solar Isolators “SI..” are switchgears for interrupting the DC/AC-Inverter from the solar-panels. Photovoltaic installations have to be equipped with DC-isolators in accordance to IEC 60364-7-712.

- TRUE DC Isolator to UL508i
- Available in 2,4,6,8 Pole Versions
- Max. Rated Current 58A @ 1000VDC (Acc. To DC21B for SI32)
- Max. Rated Current 80A @ 600VDC (Acc. To DC21B for SI55)
- High Reliability Self-Cleaning & Vibration Resistant Knife Contacts
- Arc Suppression Chamber
- Operator Independent High Speed Switching (Typically 3ms)
- Additional Security with Patented “Safelock” Function
- Compact & Space Saving Design
- Maximum Operator Torque of 1Nm for Easy Operation (SI16-32)
- Poles can be Wired in Series to Increase Rating (DC21B & DC22B)
- Large Box Terminals with up to 25mm² Cross Sectional Area for Wiring
- Different Mounting Versions Available (DIN / Base / Panel)
- Solar Connectors are Available (Plug / Socket / Branch)

Part Number	Description	Rating
SI16-PEL64R-2	Enclosed IP66 2 pole - 1 String	16A @ 800VDC
SI16-PEL64R-4	Enclosed IP66 4 pole - 2 Strings	16A @ 800VDC
SI16-PEL64R-4S	Enclosed IP66 4 pole linked - 1 String	16A @ 1500VDC
SI25-PEL64R-2	Enclosed IP66 2 pole - 1 String	25A @ 600VDC
SI25-PEL64R-4	Enclosed IP66 4 pole - 2 Strings	25A @ 600VDC
SI25-PEL64R-4S	Enclosed IP66 4 pole linked - 1 String	25A @ 1200VDC
SI32-PEL64R-2	Enclosed IP66 2 pole - 1 String	32A @ 600VDC
SI32-PEL64R-4	Enclosed IP66 4 pole - 2 Strings	32A @ 600VDC
SI32-PEL64R-4S	Enclosed IP66 4 pole linked - 1 String	32A @ 1200VDC
SI40-PEL64R-4	Enclosed IP66 4 pole - 2 Strings	40A @ 600VDC
SI55-PEL64R-4	Enclosed IP66 4 pole - 2 Strings	55A @ 600VDC
SI25-PM64-4	Panel Mount Lever Handle 64mm 4 pole - 2 Strings	25A @ 600VDC
SI32-PM64-4	Panel Mount Lever Handle 64mm 4 pole - 2 Strings	32A @ 600VDC
SI16-PM64R-2	Panel Mount Rotary Handle 64mm 2 pole - 1 String	16A @ 800VDC
SI25-PM64R-4	Panel Mount Rotary Handle 64mm 4 pole - 2 Strings	25A @ 600VDC
SI40-PM64R-4	Panel Mount Rotary Handle 64mm 4 pole - 2 Strings	40A @ 600VDC
SI55-PM64R-4	Panel Mount Rotary Handle 64mm 4 pole - 2 Strings	55A @ 600VDC
SI16-BMDC64-2	Base Mount Door Interlock Lever Handle 64mm 2 pole - 1 String	16A @ 800VDC
SI16-BMDC64R-2	Base Mount Door Interlock Rotary Handle 64mm 2 pole - 1 String	16A @ 800VDC
SI25-BMDC64R-2	Base Mount Door Interlock Rotary Handle 64mm 2 pole - 1 String	25A @ 600VDC
SI40-BMDC64R-4	Base Mount Door Interlock Rotary Handle 64mm 4 pole - 2 Strings	40A @ 600VDC
SI55-BMDC64R-4	Base Mount Door Interlock Rotary Handle 64mm 4 pole - 2 Strings	55A @ 600VDC
SI16-DB-4	Distribution Board Mount 4 pole - 2 Strings	16A @ 800VDC
SI25-DB-2	Distribution Board Mount 2 pole - 1 String	25A @ 600VDC
SI16-DBL-4	Distribution Board Mount Lockable 4 pole - 2 Strings	16A @ 800VDC
SI16-DBL-8	Distribution Board Mount Lockable 8 pole - 4 Strings	16A @ 800VDC
SI32-DBL-4	Distribution Board Mount Lockable 4 pole - 2 Strings	32A @ 600VDC
SI25-SHM-2	Single Hole Mounting 2 pole - 1 String	25A @ 600VDC
SI25-SHM-4	Single Hole Mounting 4 pole - 2 Strings	25A @ 600VDC



SAFE-LOCK

To read about our entire Solar Product Range, go to www.imopc.com or scan this QR code



Motor Protection Circuit Breakers C4



- Motor protection rating up to 100 Amps
- Short circuit breaking capacity up to 100kA
- Phase failure protection
- DIN rail mounting
- Wide range of accessories

IMO C4 Motor Protection Circuit Breakers are designed to be a compact reliable unit that offers high protection for 3 phase induction motors but can also be used as a motor starter, and for line protection. Integrating the functions of a circuit breaker and thermal overload relay in single unit so they significantly reduce the space requirements and wiring necessary for an installation that would have traditionally used a three component starter assembly.

With ratings from 0.16A to 100A in 3 frame sizes the IMO C4 has a short circuit breaking capacity of 100kA (Icu) and incorporates both thermal overload functionality and phase failure protection for phase-to-phase faults thereby offering comprehensive protection of the motor and controlling electrical circuitry.

The C4 is available with either rocker or rotary control and is complemented with a wide range of accessories that enable it to be connected to supplementary products, such as an IMO contactor, to give greater versatility. The design flexibility of the C4 ensures its convenience for installers, with the availability of auxiliary contacts that can be front or side mounted, to busbar systems available for the interconnection of up to 5 units; the C4 can be wired from either the top or bottom supply terminals without any reduction in ratings.

DIN rail and panel mount models are designed in accordance with IEC 60947-1, IEC 60947-2, IEC 60947-4-1, VDE 660 and UL approved (E223201) ensure that the IMO C4 circuit breakers are ideal for installation and OEM applications.



Part Number	Description
C4/32R-0,63	0.4 - 0.63A Instantaneous Release 8,2A
C4/32R-1	0.63 - 1.0A Instantaneous Release 13A
C4/32R-1,6	1.0 - 1.6A Instantaneous Release 20,8A
C4/32R-2,5	1.6 - 2.5A Instantaneous Release 32,5A
C4/32R-4	2.5 - 4A Instantaneous Release 52A
C4/32R-6	4 - 6A Instantaneous Release 78A
C4/32R-8	5 - 8A Instantaneous Release 104A
C4/32R-10	6 - 10A Instantaneous Release 130A
C4/32R-13	9 - 13A Instantaneous Release 169A
C4/32R-17	11 - 17A Instantaneous Release 221A
C4/32R-22	14 - 22A Instantaneous Release 286A
C4/32T-1,6	1.0 - 1.6A Instantaneous Release 20,8A
C4/32T-4	2.5 - 4A Instantaneous Release 52A
C4/32T-6	4 - 6A Instantaneous Release 78A
C4/32T-8	5 - 8A Instantaneous Release 104A
C4/32T-13	9 - 13A Instantaneous Release 169A
C432VK1	Link Module for the C4/32... MCB's to MB Contactors
C432VK3	Link Module for the C4/32... MCB's to MC10N & MC22N Contactors
C4HQ11	Auxiliary Contact Block Top Mount, 1N/O+1N/C
C4HS11	Auxiliary Contact Block Side Mount, 1N/O+1N/C



This is just a small selection of our range. For the entire range, please go to www.imopc.com or scan this QR code with your smartphone.

C4/32T	C4/32R	C4/63R	C4/100R

Miniature Circuit Breakers B10



The IMO range of Miniature Circuit Breakers has been designed for protection of electrical installations against overload and short circuits and is manufactured in accordance with EN60898.

Ordering Code & Examples

B10		C		10		04A <small>Rated Current Amps (A)</small>	
MCB 4.5kA	B4			10	Single Pole		
MCB 6kA	B6			1N	Single Pole + Neutral		
MCB 10kA	B10			20	Two Pole		
				30	Three Pole		
				3N	Three Pole + Neutral		
Operating Characteristic		B					
Operating Characteristic		C					
Operating Characteristic		D					

Current ratings (A): 2/4/6/10/16/20/25/32/40/50/63
 B6 range standard supply in B curve
 B4 range only available in 1P+N



Residual Current Circuit Breaker (RCCB AC Type)

Part Number	Description
B10R2025-30	RCCB 10kA 30mA 1 Pole + Neutral 25A
B10R2032-30	RCCB 10kA 30mA 1 Pole + Neutral 32A
B10R2040-30	RCCB 10kA 30mA 1 Pole + Neutral 40A
B10R2063-30	RCCB 10kA 30mA 1 Pole + Neutral 63A
B10R4025-30	RCCB 10kA 30mA 3 Pole + Neutral 25A
B10R4032-30	RCCB 10kA 30mA 3 Pole + Neutral 32A
B10R4040-30	RCCB 10kA 30mA 3 Pole + Neutral 40A
B10R4063-30	RCCB 10kA 30mA 3 Pole + Neutral 63A

Miniature Circuit Breakers

Part Number	Description
B4C1N10A	MCB 4.5kA C Curve 1 Pole + Neutral 10A
B6B1010A	MCB 6kA B Curve 1 Pole 10A
B10C1002A	MCB 10kA C Curve 1 Pole 2A
B10C1006A	MCB 10kA C Curve 1 Pole 6A
B10C2010A	MCB 10kA C Curve 2 Pole 10A
B10D1002A	MCB 10kA D Curve 1 Pole 2A
B10D3010A	MCB 10kA D Curve 3 Pole 10A

Residual Circuit Breaker with Overload (RCBO A Type)

Part Number	Description
B6CR1N06-30-A	RCBO 6kA 30mA 1 Pole + Neutral 6A
B6CR1N10-30-A	RCBO 6kA 30mA 1 Pole + Neutral 10A
B6CR1N16-30-A	RCBO 6kA 30mA 1 Pole + Neutral 16A
B6CR1N20-30-A	RCBO 6kA 30mA 1 Pole + Neutral 20A
B6CR1N25-30-A	RCBO 6kA 30mA 1 Pole + Neutral 25A
B6CR1N32-30-A	RCBO 6kA 30mA 1 Pole + Neutral 32A

Isolating Switch

Part Number	Description
BIS1063A	1 Pole 63A 230/400VAC
BIS2063A	2 Pole 63A 230/400VAC
BIS2100C	2 Pole 100A 230/400VAC
BIS2125A	2 Pole 125A 230/400VAC
BIS3063A	3 Pole 63A 230/400VAC
BIS4063A	4 Pole 63A 230/400VAC
BIS4125A	4 Pole 125A 230/400VAC

Accessories

Part Number	Description
B10-F3	Auxiliary contact side mounting 1C/O 6A
B10-S3	Shunt trip side mounting 230VAC
B10-LOCK	Lever locking device (padlock not included)
B10BB1P100-1M	Busbar Pin type 1P 1m
B10BB1F100-1M	Busbar Fork type 1P 1m
B10BB3P100-1M	Busbar Pin type 3P 1m
B10BB3F100-1M	Busbar Fork type 3P 1m
B10BBCAP1	End cap for 1P busbar
B10BBCAP3	End cap for 3P busbar

This is just a small selection of our range. A dedicated MCB catalogue is available at www.imopc.com which includes all options for IMO MCBs.



Screw Clamp Terminals

Part Number	Description
ER2.5BEIGE	2.5mm Beige Terminal
ER2.5PBEIGE	2.5mm Beige Terminal (35mm/32mm DIN Rail version)
ER4BEIGE	4mm Beige Terminal
ER4PBEIGE	4mm Beige Terminal (35mm/32mm DIN Rail version)
ER6BEIGE	6mm Beige Terminal
ER10BEIGE	10mm Beige Terminal
ER16BEIGE	16mm Beige Terminal
ER35PBEIGE	35mm Beige Terminal (35mm/32mm DIN Rail version)
ER70BEIGE	70mm High Current Terminal
ER95BEIGE	95mm High Current Terminal
ERPE2.5/4	2.5 to 4mm Earth Terminal
ERPE2.5P	2.5mm Earth Terminal (35mm/32mm DIN Rail version)
ERPE6/10	6 to 10mm Earth Terminal
ERPE16P	16mm Earth Terminal (35mm/32mm DIN Rail version)
ERPE35P	35mm Earth Terminal (35mm/32mm DIN Rail version)
ERB95	95mm Bolt Connection High Current Terminal
ERB150	150mm Bolt Connection High Current Terminal
ERD2.5BEIGE	2.5mm Double Deck Terminal
ERD4BEIGE	4mm Double Deck Terminal
ERT3BEIGE	2.5mm Triple Deck Terminal
ERTD4	4mm Disconnect Terminal
ERF2BEIGE	6mm Pull-Out Fuse Module Terminal
ERF3BEIGE	4mm Pull-Out Fuse Module Terminal
ERWT2NBEIGE	10mm Test/Disconnect Terminal
ERDT10/16	10/16mm Distribution Terminal

Spring Clamp Terminals


Part Number	Description
SC2.5	2.5mm Beige Spring Clamp Terminal
SC4	4mm Beige Spring Clamp Terminal
SC6	6mm Beige Spring Clamp Terminal
SC10	10mm Beige Spring Clamp Terminal
SCPE2.5	2.5mm Spring Clamp Earth Terminal
SCPE4	4mm Spring Clamp Earth Terminal
SCPE6	6mm Spring Clamp Earth Terminal
SCPE10	10mm Spring Clamp Earth Terminal
SCD2.5BEIGE	2.5mm Beige Double Deck Spring Clamp Terminal
SCD4BEIGE	4mm Beige Double Deck Spring Clamp Terminal
SCT3BEIGE	2.5mm Beige Triple Deck Spring Clamp Terminal
SCTD4	2.5mm Beige Spring Clamp Disconnect Terminal
SCF3BEIGE	4mm Beige Spring Clamp Fuse Terminal
SCS2.5BEIGE	2.5mm Beige Spring Clamp Plug Terminal
SCD2.5EBEIGE	2.5mm Beige Spring Clamp Terminal 2 In 1 Out
SCD2.5CBEIGE	2.5mm Beige Spring Clamp Terminal 2 In 2 Out

Push Fit Terminals


Part Number	Description
PF1.5BEIGE	1.5mm Beige Terminal
PF2.5BEIGE	2.5mm Beige Terminal
PF4BEIGE	4mm Beige Terminal
PF6BEIGE	6mm Beige Terminal
PF10BEIGE	10mm Beige Terminal
PFPE2.5P	2.5mm Earth Terminal (35mm/32mm DIN Rail version)
PFPE4P	4mm Earth Terminal (35mm/32mm DIN Rail version)
PFPE6P	6mm Earth Terminal (35mm/32mm DIN Rail version)
PFPE10P	10mm Earth Terminal (35mm/32mm DIN Rail version)
PFD2.5BEIGE	2.5mm Double Deck Beige Terminal
PFD4BEIGE	4mm Double Deck Beige Terminal
PFT3BEIGE	2.5mm Triple Deck Beige Terminal
PFTD2.5	2.5mm Disconnect Terminal
PFF3BEIGE	2.5mm Fuse Beige Terminal
PFD2.5E	1 In / 2 Out 2.5mm Feedthrough Terminal
PFD4E	1 In / 2 Out 4mm Feedthrough Terminal
PFD2.5C	2 In / 2 Out 2.5mm Feedthrough Terminal
PFD2.5PE	1 In / 2 Out 2.5mm Earth Terminal
PFD2.5CPE	2 In / 2 Out 2.5mm Earth Terminal
PFD3S	2.5mm Triple Decker Sensor Terminal

IMO Push Fit Terminals

SAVE up to 75% on wiring time
when compared to screw clamp connection



To read about our entire DIN Rail Terminal Product Range, go to www.imopc.com or scan this QR code for the latest catalogue.




Industrial Power Relays



IMO's range of Relays include Signal Relays, Power Relays, Automotive Relays and Solar Relays, and range of compatible sockets. IMO's relay manufacturing goes back as far as 1970, and over the years we have strived to innovate and produce new types of relays for developing technologies. In 1984 we developed the first BT Type 47 Telecom Relay, and again in 1990 we launched the first BABT compliant isolation relay for data transfer, confirming our place as one of the leading global relay manufacturers.

As part of our innovative nature we have manufactured a range of Slimline DIN Rail Mount Relays at just 6mm wide, which provide substantial space savings in a panel when compared to traditional plug-in style relays. The range with plug-in relays rated at 6 Amps allows easy maintenance without the need for complete rewiring of the socket. The sockets are available in wide operating voltages for both AC and DC circuits within the same unit, providing greater flexibility for the user and reducing the number of stock items required.

Below are some of the most popular products in the IMO Relay range. A full catalogue is available online at www.imopc.com detailing all products and accessories.



High Capacity Relays

Part Number	Description
HY1A112AC	1N/O, 30A, 12VAC Coil, Solder Lug Or Push On, Coil Resistance 75Ω
HY1A112DC	1N/O, 30A, 12VDC Coil, Solder Lug Or Push On, Coil Resistance 75Ω
HY1A124AC	1N/O, 30A, 24VAC Coil, Solder Lug Or Push On, Coil Resistance 300Ω
HY1A124DC	1N/O, 30A, 24VDC Coil, Solder Lug Or Push On, Coil Resistance 300Ω
HY1A148DC	1N/O, 30A, 48VDC Coil, Solder Lug Or Push On, Coil Resistance 1200Ω
HY1A110AC	1N/O, 30A, 110VAC Coil, Solder Lug Or Push On, Coil Resistance 5200Ω
HY1A110DC	1N/O, 30A, 110VDC Coil, Solder Lug Or Push On, Coil Resistance 6300Ω
HY1A1230AC	1N/O, 30A, 230VAC Coil, Solder Lug Or Push On, Coil Resistance 20800Ω
HY2A112AC	2N/O, 25A, 12VAC Coil, Solder Lug Or Push On, Coil Resistance 75Ω
HY2A112DC	2N/O, 25A, 12VDC Coil, Solder Lug Or Push On, Coil Resistance 75Ω
HY2A124AC	2N/O, 25A, 24VAC Coil, Solder Lug Or Push On, Coil Resistance 300Ω
HY2A124DC	2N/O, 25A, 24VDC Coil, Solder Lug Or Push On, Coil Resistance 300Ω
HY1A1110AC	2N/O, 25A, 110VAC Coil, Solder Lug Or Push On, Coil Resistance 5200Ω
HY2A1230AC	2N/O, 25A, 230VAC Coil, Solder Lug Or Push On, Coil Resistance 20800Ω
HY2A212DC	2N/O, 25A, 12VDC Coil, PCB Mount, Coil Resistance 75Ω
HY2A312DC	2N/O, 25A, 12VDC Coil, PCB Mount Alternative Layout, Coil Resistance 75Ω
HY2A224DC	2N/O, 25A, 24VDC Coil, PCB Mount, Coil Resistance 300Ω

QY Relays

Part Number	Description
QY21XN12AC	2C/O, 10A, 12VAC Coil, LED, Plug-in
QY21XN12DC	2C/O, 10A, 12VDC Coil, LED, Plug-in
QY21XN24AC	2C/O, 10A, 24VAC Coil, LED, Plug-in
QY21XN24DC	2C/O, 10A, 24VDC Coil, LED, Plug-in
QY21XN120AC	2C/O, 10A, 120VAC Coil, LED, Plug-in
QY21XN230AC	2C/O, 10A, 230VAC Coil, LED, Plug-in
QY21XX12DC	2C/O, 10A, 12VDC Coil, Plug-in
QY21XX24AC	2C/O, 10A, 24VAC Coil, Plug-in
QY21XX24DC	2C/O, 10A, 24VDC Coil, Plug-in
QY21XX120AC	2C/O, 10A, 120VAC Coil, Plug-in
QY21XX240AC	2C/O, 10A, 240VAC Coil, Plug-in
QY21XF12DC	2C/O, 10A, 12VDC Coil, Plug-in, Flanged
QY21XF240AC	2C/O, 10A, 240VAC Coil, Plug-in, Flanged
QY22XX12DC	2C/O, 10A, 12VDC Coil, PCB Mount
QY22XX24DC	2C/O, 10A, 24VDC Coil, PCB Mount
QY22XX240AC	2C/O, 10A, 240VAC Coil, PCB Mount



HY Relays


Part Number	Description
2 Pole	
HY21PN12DC	2C/O, 7A, 12VDC Coil, Plug-in, LED & Manual Test/Latch
HY21PN24AC	2C/O, 7A, 24VAC Coil, Plug-in, LED & Manual Test/Latch
HY21PN24DC	2C/O, 7A, 24VDC Coil, Plug-in, LED & Manual Test/Latch
HY21PN120AC	2C/O, 7A, 120VAC Coil, Plug-in, LED & Manual Test/Latch
HY21PN240AC	2C/O, 7A, 240VAC Coil, Plug-in, LED & Manual Test/Latch
HY21XX12DC	2C/O, 7A, 12VDC Coil, Plug-in
HY21XX24AC	2C/O, 7A, 24VAC Coil, Plug-in
HY21XX24DC	2C/O, 7A, 24VDC Coil, Plug-in
HY21XX120AC	2C/O, 7A, 120VAC Coil, Plug-in
HY21XX240AC	2C/O, 7A, 240VAC Coil, Plug-in
3 Pole	
HY31PN24AC	3C/O, 7A, 24VAC Coil, Plug-in, LED & Manual Test/Latch
HY31PN24DC	3C/O, 7A, 24VDC Coil, Plug-in, LED & Manual Test/Latch
HY31PN230AC	3C/O, 7A, 230VAC Coil, Plug-in, LED & Manual Test/Latch
4 Pole	
HY41PN12AC	4C/O, 5A, 12VAC Coil, Plug-in, LED & Manual Test/Latch
HY41PN12DC	4C/O, 5A, 12VDC Coil, Plug-in, LED & Manual Test/Latch
HY41PN24AC	4C/O, 5A, 24VAC Coil, Plug-in, LED & Manual Test/Latch
HY41PN24DC	4C/O, 5A, 24VDC Coil, Plug-in, LED & Manual Test/Latch
HY41PN48AC	4C/O, 5A, 48VAC Coil, Plug-in, LED & Manual Test/Latch
HY41PN48DC	4C/O, 5A, 48VDC Coil, Plug-in, LED & Manual Test/Latch
HY41PN120AC	4C/O, 5A, 120VAC Coil, Plug-in, LED & Manual Test/Latch
HY41PN110DC	4C/O, 5A, 110VDC Coil, Plug-in, LED & Manual Test/Latch
HY41PN240AC	4C/O, 5A, 240VAC Coil, Plug-in, LED & Manual Test/Latch
HY41PX12DC	4C/O, 5A, 12VDC Coil, Plug-in, Manual Test/Latch
HY41PX24DC	4C/O, 5A, 24VDC Coil, Plug-in, Manual Test/Latch
HY41PX48DC	4C/O, 5A, 48VDC Coil, Plug-in, Manual Test/Latch
HY41PX120AC	4C/O, 5A, 120VAC Coil, Plug-in, Manual Test/Latch
HY41PX240AC	4C/O, 5A, 240VAC Coil, Plug-in, Manual Test/Latch
HY41XX12AC	4C/O, 5A, 12VAC Coil, Plug-in
HY41XX12DC	4C/O, 5A, 12VDC Coil, Plug-in
HY41XX24AC	4C/O, 5A, 24VAC Coil, Plug-in
HY41XX24DC	4C/O, 5A, 24VDC Coil, Plug-in
HY41XX48AC	4C/O, 5A, 48VAC Coil, Plug-in
HY41XX120AC	4C/O, 5A, 120VAC Coil, Plug-in
HY41XX240AC	4C/O, 5A, 240VAC Coil, Plug-in
HY42XX12DC	4C/O, 5A, 12VDC Coil, PCB Mount
HY42XX24AC	4C/O, 5A, 24VAC Coil, PCB Mount
HY42XX24DC	4C/O, 5A, 24VDC Coil, PCB Mount
HY42XX120AC	4C/O, 5A, 120VAC Coil, PCB Mount
HY42XX240AC	4C/O, 5A, 240VAC Coil, PCB Mount

RS Relays

Part Number	Description
RS2PN12AC	8 pins, 2C/O, 10A, 12VAC Coil, Plug-in, LED & Manual Test/Latch
RS2PN12DC	8 pins, 2C/O, 10A, 12VDC Coil, Plug-in, LED & Manual Test/Latch
RS2PN24AC	8 pins, 2C/O, 10A, 24VAC Coil, Plug-in, LED & Manual Test/Latch
RS2PN24DC	8 pins, 2C/O, 10A, 24VDC Coil, Plug-in, LED & Manual Test/Latch
RS2PN48DC	8 pins, 2C/O, 10A, 48VDC Coil, Plug-in, LED & Manual Test/Latch
RS2PN110AC	8 pins, 2C/O, 10A, 110VAC Coil, Plug-in, LED & Manual Test/Latch
RS2PN110DC	8 pins, 2C/O, 10A, 110VDC Coil, Plug-in, LED & Manual Test/Latch
RS2PN230AC	8 pins, 2C/O, 10A, 230VAC Coil, Plug-in, LED & Manual Test/Latch
RS3PN12AC	11 pins, 3C/O, 10A, 12VAC Coil, Plug-in, LED & Manual Test/Latch
RS3PN12DC	11 pins, 3C/O, 10A, 12VDC Coil, Plug-in, LED & Manual Test/Latch
RS3PN24AC	11 pins, 3C/O, 10A, 24VAC Coil, Plug-in, LED & Manual Test/Latch
RS3PN24DC	11 pins, 3C/O, 10A, 24VDC Coil, Plug-in, LED & Manual Test/Latch
RS3PN48DC	11 pins, 3C/O, 10A, 48VDC Coil, Plug-in, LED & Manual Test/Latch
RS3PN110AC	11 pins, 3C/O, 10A, 110VAC Coil, Plug-in, LED & Manual Test/Latch
RS3PN110DC	11 pins, 3C/O, 10A, 110VDC Coil, Plug-in, LED & Manual Test/Latch
RS3PN230AC	11 pins, 3C/O, 10A, 230VAC Coil, Plug-in, LED & Manual Test/Latch


Slimline Plug-In Power Relays

Part Number	Description
ETS-1AN-SL-5VDC	Power Relay, 6A, 1N/O, 5VDC, AgNi, Sealed
ETS-1AN-SL-6VDC	Power Relay, 6A, 1N/O, 6VDC, AgNi, Sealed
ETS-1AN-SL-9VDC	Power Relay, 6A, 1N/O, 9VDC, AgNi, Sealed
ETS-1AN-SL-12VDC	Power Relay, 6A, 1N/O, 12VDC, AgNi, Sealed
ETS-1AN-SL-24VDC	Power Relay, 6A, 1N/O, 24VDC, AgNi, Sealed
ETS-1AN-SL-60VDC	Power Relay, 6A, 1N/O, 60VDC, AgNi, Sealed
ETS-1CN-SL-5VDC	Power Relay, 6A, 1C/O, 5VDC, AgNi, Sealed
ETS-1CN-SL-6VDC	Power Relay, 6A, 1C/O, 6VDC, AgNi, Sealed
ETS-1CN-SL-9VDC	Power Relay, 6A, 1C/O, 9VDC, AgNi, Sealed
ETS-1CN-SL-12VDC	Power Relay, 6A, 1C/O, 12VDC, AgNi, Sealed
ETS-1CN-SL-24VDC	Power Relay, 6A, 1C/O, 24VDC, AgNi, Sealed
ETS-1CN-SL-48VDC	Power Relay, 6A, 1C/O, 48VDC, AgNi, Sealed
ETS-1CN-SL-60VDC	Power Relay, 6A, 1C/O, 60VDC, AgNi, Sealed



To read about our entire Relay Product Range, go to www.imopc.com or scan this QR code for the latest catalogue.

RS



Sockets for Relays overleaf

Relay Sockets



Sockets for Standard Plug-In Power Relays

Part Number	For Relay...
SRN2-D, SRN2-S	HY21PN110AC
SRN2-D, SRN2-S	HY21PN230AC
SRN2-D, SRN2-S	HY21PN24AC
SRN2-D, SRN2-S	HY21PN24DC
SRN2-D, SRN2-S	HY21XX12DC
SRN2-D, SRN2-S	HY21XX230AC
SRN2-D, SRN2-S	HY21XX24AC
SRN2-D, SRN2-S	HY21XX24DC
SRN3-D, SRN3-S, SRN3-C	HY31PN230AC
SRN3-D, SRN3-S, SRN3-C	HY31PN24DC
SRN4-D, SRN4-S, SRN4-C	HY41PN110AC
SRN4-D, SRN4-S, SRN4-C	HY41PN110DC
SRN4-D, SRN4-S, SRN4-C	HY41PN12AC
SRN4-D, SRN4-S, SRN4-C	HY41PN12DC
SRN4-D, SRN4-S, SRN4-C	HY41PN230AC
SRN4-D, SRN4-S, SRN4-C	HY41PN24AC
SRN4-D, SRN4-S, SRN4-C	HY41PN24DC
SRN4-D, SRN4-S, SRN4-C	HY41PN48AC
SRN4-D, SRN4-S, SRN4-C	HY41PN48DC
SRN4-D, SRN4-S, SRN4-C	HY41PX12DC
SRN4-D, SRN4-S, SRN4-C	HY41PX24DC
SRN4-D, SRN4-S, SRN4-C	HY41XX110AC
SRN4-D, SRN4-S, SRN4-C	HY41XX12AC
SRN4-D, SRN4-S, SRN4-C	HY41XX12DC
SRN4-D, SRN4-S, SRN4-C	HY41XX230AC
SRN4-D, SRN4-S, SRN4-C	HY41XX24AC
SRN4-D, SRN4-S, SRN4-C	HY41XX24DC
SRN4-D, SRN4-S, SRN4-C	HY41XX48AC

Sockets for 8 Pin Plug-In Power Relays

Part Number	For Relay...
SRR8, SRR8-M	RS2PN110AC
SRR8, SRR8-M	RS2PN110DC
SRR8, SRR8-M	RS2PN12AC
SRR8, SRR8-M	RS2PN12DC
SRR8, SRR8-M	RS2PN230AC
SRR8, SRR8-M	RS2PN24AC
SRR8, SRR8-M	RS2PN24DC
SRR8, SRR8-M	RS2PN48DC

Sockets for Standard Plug-In Power Relays

Part Number	For Relay...
SRH2-C, SRP2-0	QY21PR24AC
SRH2-C, SRP2-0	QY21XN110AC
SRH2-C, SRP2-0	QY21XN12DC
SRH2-C, SRP2-0	QY21XN230AC
SRH2-C, SRP2-0	QY21XN24DC
SRH2-C, SRP2-0	QY21XX110AC
SRH2-C, SRP2-0	QY21XX12DC
SRH2-C, SRP2-0	QY21XX230AC
SRH2-C, SRP2-0	QY21XX24AC
SRH2-C, SRP2-0	QY21XX24DC
SRH2-C, SRP2-0	QY22XX12DC
SRH2-C, SRP2-0	QY22XX24DC



Sockets for 11 Pin Plug-In Power Relays

Part Number	For Relay...
SRR11, SRR11-M	RS3PN110AC
SRR11, SRR11-M	RS3PN110DC
SRR11, SRR11-M	RS3PN12AC
SRR11, SRR11-M	RS3PN12DC
SRR11, SRR11-M	RS3PN230AC
SRR11, SRR11-M	RS3PN24AC
SRR11, SRR11-M	RS3PN24DC

Sockets for Slimline Plug-In Power Relays

Part Number	For Relay...
SRSI-24AC/DC	ETS-1AN-SL-24VDC
SRSI-24DC	ETS-1AN-SL-5VDC
SRSI-60AC/DC	ETS-1AN-SL-60VDC
SRSI-24AC/DC	ETS-1AN-SL-6VDC
SRSI-24AC/DC	ETS-1AN-SL-9VDC
SRSI-24AC/DC	ETS-1CN-SL-12VDC
SRSI-24AC/DC	ETS-1CN-SL-24VDC
SRSI-60AC/DC	ETS-1CN-SL-48VDC
SRSI-24DC	ETS-1CN-SL-5VDC
SRSI-60AC/DC	ETS-1CN-SL-60VDC
SRSI-24AC/DC	ETS-1CN-SL-6VDC
SRSI-24AC/DC	ETS-1CN-SL-9VDC
SRSI-24AC/DC	ETS-1CN1-SL-12VDC
SRSI-60AC/DC	ETS-1CN1-SL-48VDC
SRSI-24DC	ETS-1CN1-SL-5VDC
SRSI-60AC/DC	ETS-1CN1-SL-60VDC
SRSI-24AC/DC	ETS-1CN1-SL-6VDC
SRSI-24AC/DC	ETS-1CN1-SL-9VDC


Sockets for Miniature Plug-In Power Relays

Part Number	For Relay...
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CN-SL-115VAC
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CN-SL-230VAC
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CN-SL-24VAC
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CN-SL-24VDC
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CT-SL-110VDC
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CT-SL-24VAC
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CT-SL-24VDC
SRN3-T, SRN3-S, SRS1-0	SRRHN-1CT-SL-48VDC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CN-SL-115VAC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CN-SL-230VAC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CN-SL-24VAC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CN-SL-24VDC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CT-SL-115VAC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CT-SL-110VDC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CT-SL-230VAC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CT-SL-24VAC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CT-SL-24VDC
SRN5-T, SRN5-S, SRS1-1	SRRHN-2CT-SL-48VDC
SRN5-T, SRN5-S, SRS1-1	SRP-1C1N-SL-230VAC



Also Available From IMO


From a single product to a complete application solution, IMO has the product range and knowledge to meet today's most demanding application requirements...




Solar Product Range



iDrive2 Low-Cost Drives



Miniature Circuit Breakers




Automation Product Range




Relays



PCB Terminal Blocks




DIN Rail Terminals



Solar Cube



iView Advanced HMI



AC Variable Speed Drives



iConnect (Remote M2M)



...visit www.imopc.com for a full range of products and downloadable brochures

IMO Worldwide Offices

IMO Precision Controls Limited

1000 North Circular Road
Staples Corner
London NW2 7JP
United Kingdom

Tel: +44(0)20 8452 6444
Fax: 020 8450 2274
Email: imo@imopc.com
Web: www.imopc.com

IMO Jeambrun Automation SAS

Centre D'Affaires Rocroy
30, Rue de Rocroy
94100 Saint-Maur-Des-Fosses
France

Tel: 0800 912 712 (n° gratuit)
Fax: 0145 134 737
Email: imo-fr@imopc.com
Web: www.imojeambrun.fr

IMO Automazione


Via Ponte alle Mosse, 61
50144 Firenze (FI)
Italia

Tel: 800 930 872 (toll free)
Fax: 8000 452 6445
Email: imo-it@imopc.com
Web: www.imopc.it

IMO Canada

Unit 32 - B - North
18 Stratheam Avenue, Brampton
Ontario L6T 4Y2
Canada

Tel: 905 799 9237 (local)
Fax: 905 799 0450
Email: imo-ca@imopc.com
Web: www.imopc.com



IMO Automation LLC

101 Colony Park Drive, Suite 300
Cumming
Georgia 30040
USA

Tel: 678 679 7110
Fax: 678 679 7112
Email: imo-usa@imopc.com
Web: www.imoautomation.com

IMO South Africa (Pty) Ltd

G16 Centurion Business Park
Montague Gardens
Cape Town 7441
South Africa

Tel: 021 551 1787
Fax: 021 555 0676
Email: info@imopc.co.za
Web: www.imopc.co.za

IMO Pacific Pty Ltd

1/6 Dillington Pass
Landsdale
Perth WA 6065
Australia

Tel: 08 9302 5246 (local)
Fax: 08 9303 9908
Email: sales@imopacific.com.au
Web: www.imopacific.com.au