Nimbus

Disk shaped LED circular high bay

- High efficiency up to 140lm/W
- Diecast aluminum body
- IP65
- Vandal resistant (IK10)
- Flicker free
- Fixed with water-proof junction box for easy wiring
- Optional microwave motion sensor (1-10V dimming)
- Optional wall-mount bracket





Aluminium Shade
KPT-NIM-AS1



PMMA Shade
KPT-NIM-PS1



PMMA Shade
KPT-NIM-PS2

NEW Available June 2018

Order Code	Type	Power	Beam Angle	CCT	Lumen	Trade Price
KMHD150CHB	Standard	150W	90°	5000K	21000lm	**£532.18**
KMHD150CHB/D	Dimmable	150W	90°	5000K	21000lm	**£537.91**
KMHD200CHB/D	Dimmable	200W	90°	5000K	28000lm	**£634.21**
KMHD240CHB/D	Dimmable	240W	60°	5000K	31200lm	**£780.95**

Accessories

Type	Order Code	Description	Trade Price
Sensor	KPT-MWS-UFO	IP65 Merrytek motion sensor	**£101.31**
Remote Control	KPT-MWS-CON	For remotely altering sensor settings or manual override	**£83.61**
Bracket	KPT-BKT1-UFO	Small bracket used on KMHD240	**£26.49**
Bracket	KPT-BKT2-UFO	Large bracket used on KMHD150&200	**£32.24**
Aluminium Shade	KPT-NIM-AS1	Opaque shade used on KMHD150&200	**£49.07**
PMMA Shade	KPT-NIM-PS1	Translucent shade used on KMHD150&200	**£105.54**
PMMA Shade	KPT-NIM-PS2	Translucent shade used on KMHD240	**£133.34**

3 Years Standard Warranty

5 Years Extended Warranty

Sensor Microwave sensor



Bracket



Sensor



Remote Control

General Specification

Voltage	220-240Vac 50-60Hz
CRI	>80
Life Time	40,000h
Power Factor	0.95
Ambient Temp	-20°C to 50°C
Housing	Diecast aluminum
IK Rating	10
Protection	Class I, IP65

Order Code

KMHD150CHB-W50
KMHD150CHB/D-W50

KMHD200CHB/D-W50

KMHD240CHB/D-F50

Dimensions



KPT-NIM-AS1



KPT-NIM-PS1



KPT-NIM-PS2