

3 3 Years
Standard Warranty

5 5 Years
Extended Warranty

1000V
Surge Protection



YouTube

Unboxing of
Mulu - Scan QR
code to watch
video

General Specification

Housing Polycarbonate
Emergency
Operation Time >3h
Emergency
Conversion Time 1s
Charging Time 12h



↔ P284
Spacing table

Order Code

EESN0105S65
EESN0105S65/S

Dimensions



Mulu

Standard/Self-test
IP65 LED emergency exit sign bulkhead

- All legends included
- Maintained and non-maintained option
- 20mm Conduit entry
- IP65 and IK10 (vandal resistant) for internal & external uses.
- Dual entry push-wire terminal block for easy loop-in loop-out wiring
- Available in self-test version



Battery warranty



LED Indicator (Self-test version)

- | | | | |
|----------------------------|-------------------------|--------------------------|-------------------------|
| • Green | System Healthy | • Red | Battery Charging Fault |
| • Green Flash 1 per second | Duration Test Pending | • Red Flash 2 per second | Battery Duration Fault |
| • Green Flash 2 per second | Duration Test Running | • Red Flash 4 per second | Lamp or Luminaire Fault |
| • Green Flash 4 per second | Functional Test Running | | |

Standard Emergency

Self-test Emergency

Standard (All exit legends included)

Order Code	Power	CCT	Lumen	Trade Price
EESN0105S65	5W	6500K	190lm (without graphics) 70lm (with graphics)	£45.22

Self-test (All exit legends included)

Order Code	Power	CCT	Lumen	Trade Price
EESN0105S65/S	5W	6500K	200lm (without graphics) 120lm (with graphics)	£105.94

Battery

Order Code	Type	Capacity	Trade Price
KBAT1500NC9 (for standard)	Nickel Cadmium	1500mAh	£14.30
KBAT2200LI2 (for self-test)	Li-Ion	2200mAh	£42.40