

# Standard/Self-test 3W universal emergency module

• Built-in self-test function according to BS-EN-62034-2012

· Designed for use with all LED luminaires (class III) with external driver

· Easy Plug & Play installation

• For maintained or non-maintained emergency lighting systems

• Internal Li-ion battery with improved lifespan

· Easy battery replacement



#### **LED Indicator (Self-test version)**

- Green
- System Healthy
- Green Flash 1 Duration Test per second
- Pending Green Flash 2 **Duration Test** per second Running
- ★ Green Flash 4 Functional Test per second Running
- - Red
    - Red Flash 2 Battery Duration per second

Battery Charging Fault

Fault

Red Flash 4 Red Flash 4 per second Luminaire Fault





## **Standard**

Order Code	Output Wattage (Max)	Output Voltage	Battery	Battery Capacity	Output Current	Trade Price
CEW03LIL/N	3W	9-58Vdc	Li-ion	2600mAh	50-130mA	£96.73

## Self-test

<u> </u>						
Order Code	Output Wattage (Max)	Output Voltage	Battery	Battery Capacity	Output Current	Trade Price
CEW03LIL/S	3W	20-58Vdc	Li-ion	2600mAh	50-130mA	£119.23

## **Battery**

Order Code	Туре	Capacity	Voltage	Trade Price
KBAT2600	Li-ion	2600mAh	7.2V	£49.12

**Patent** 







#### General Specification

220-240Vac Voltage 50-60Hz Input Current (max) 35mA Emergency Conversion Time Emergency Operation Time >3hCharging Time 12h Battery Life 4 Years **Ambient** Temp  $0^{\circ}\text{C}$  to  $45^{\circ}\text{C}$ Maximum Case Temp 75°C







## **Order Code** CEW03LIL/N

CEW03LIL/S



