

Alden

Backlit LED panel with emergency option

Plug-in emergency 

Flicker free 

- Save up to 50% energy usage compared to traditional fluorescent fittings
 - TP(a) rated diffuser

- Square edge tray with robust structure to allow even light distribution around the edge
- DALI, 1-10V (0-10V) and PUSH alternative driver available
 - IP44 when ceiling recess mounted
 - Flicker free
 - UGR<19



Order Code	Power	Dimension	CCT	Lumen	Trade Price
KPNL30BL1	30W	595x595	3000K 4000K 6500K	3200lm	£72.33

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	CYC030TDC30-90	Configurable DALI & 1-10V (0-10V) Dimmable Driver	£68.46
Emergency module	CEW03LIL/N	UEM, 3W, Li-ion battery	£96.73
Self-test emergency module	CEW03LIL/S	Self-test UEM, 3W, Li-ion battery	£119.23

Accessories

Type	Order Code	Description	Trade Price
Surface mount frame	KTPNL/SMT-WHT0606	595x595mm surface-mount frame, white	£43.65
Suspension kits	KTPNL/SUS0606	595*595mm Suspension set	£10.81
Connector	KCON3FM	Junction Box Connector - 3 Pin + Loop	£7.12

3 Years
Standard Warranty

5 Years
Extended Warranty

1000V
Surge Protection

DALI & 1-10V (0-10V)
Dimmable Options

New Optional Gear



Standard/Self-test universal emergency module
UEM II ⇨ P37



Optional Connector
KCON3FM

General Specification

Voltage	220-240Vac 50-60Hz
CRI	>83
Life Time	40,000h
Power Factor	>0.95
Ambient Temp	-20°C to 40°C
Housing	Powder coated aluminum
Diffuser	Polystyrene TP(a)



Order Code

KPNL30BL1-W30
KPNL30BL1-W40
KPNL30BL1-W65

Dimensions

