

Kurve

Direct / indirect LED modular Luminaire

- Stylish & elegant aesthetic appearance
- Flicker free
- Ultra-low glare, UGR < 17.4*
- Optional DALI, 1-10V (0-10V) driver
- Colour temperature switchable 3000K/4000K/5000K

Plug-in emergency 

Wattage switching 

CCT switching 

Flicker free 

5 **5 Years**
Standard Warranty

7 **7 Years**
Extended Warranty

1000V
Surge Protection

DALI & 1-10V (0-10V)
Dimmable Options



General Specification

Voltage	220-240Vac 50-60Hz
CRI	>80
Life Time	40,000h
Power Factor	>0.93
Ambient Temp	-20°C to 40°C
Housing	Zinc coated sheet steel
Diffuser	Acrylic



Order Code	Default Power	Alternative Power	Dimension	CCT	Lumen	Trade Price
KMRC4030L2A	40W	-	595x595mm	Switchable**	3600lm	£381.74
	-	30W	595x595mm	Switchable**	2800lm	

Optional Gears

Type	Order Code	Description	Trade Price
Dimmable driver	CYC050TDC70-140	Configurable DALI & 1-10V (0-10V) Dimmable Driver	£82.92
Emergency module	CEW03LIL/N	UEM, 3W, Li-ion battery	£96.73
Self-test emergency module	CEW03LIL/S	Self-test UEM, 3W, Li-ion battery	£119.23

* With room size of 4h x 2h, where h is the height of the room

** When CCT switchable, colour temperature switches between 3000K, 4000K & 5000K

Order Code

KMRC4030L2A/SCT

Dimensions

