

5 5 Years
Standard Warranty

7 7 Years
Extended Warranty

2000V
Surge Protection
(L to GND)



Microwave Sensor
(Mounting height ≤8.5m)
KBTNLS1-MWS2

General Specification

Voltage 220-240Vac
50-60Hz
CRI >80
Life Time 40,000h
Power Factor 0.95
Ambient Temp -20°C to 40°C
Housing Polycarbonate



Order Code

KBTN30LS12/SCT
KBTN30LS12/SCT/D

KBTN48LS12/SCT
KBTN48LS12/SCT/D

KBTN65LS12/SCT
KBTN65LS12/SCT/D

Dimensions



Kennet

Interior surface mount slim profile batten

- Ideal replacement for twin T8 surface mount battens
- 20mm conduit entries
- Switchable CCT (3000K/4000K/6000K)
- Flicker free
- Plug & play microwave sensor module with corridor function, for standard version only
- Plug & play emergency module
- BESA box fitting points

E Plug-in emergency

S Plug-in corridor sensor

CCT CCT switching

Flicker free

ECO Modular design



Order Code	Type	Power	Length	CCT	Lumen	Trade Price
KBTN30LS12/SCT	Standard	30W	4ft	Switchable*	3000lm (3000K) 3300lm (4000K) 3300lm (6000K)	£186.58
KBTN30LS12/SCT/D	DALI	30W	4ft	Switchable*	3000lm (3000K) 3300lm (4000K) 3300lm (6000K)	£185.93
KBTN48LS12/SCT	Standard	48W	5ft	Switchable*	4800lm (3000K) 5200lm (4000K) 5200lm (6000K)	£221.69
KBTN48LS12/SCT/D	DALI	48W	5ft	Switchable*	4800lm (3000K) 5200lm (4000K) 5200lm (6000K)	£225.46
KBTN65LS12/SCT	Standard	65W	6ft	Switchable*	6500lm (3000K) 7100lm (4000K) 7100lm (6000K)	£262.50
KBTN65LS12/SCT/D	DALI	65W	6ft	Switchable*	6500lm (3000K) 7100lm (4000K) 7100lm (6000K)	£250.18

* When CCT switchable, colour temperature switches 3000K, 4000K & 6000K

Optional Gears

Type	Order code	Description	Trade Price
Emergency module	CEW05LBL/N	Emergency, with Li-ion battery	£97.05
Self-Test emergency module	CEW05LBL/S	Self-test emergency, with Li-ion battery	£115.25
Microwave Sensor*	KBTNLS1-MWS2	Microwave motion and daylight sensor	£25.06

* Microwave sensor does not work with DALI version