





Project

The Kirkfield - Newton-le-Willows, UK



Beam AC LED

p266

Amenity



Decorative Wall



Architectural Die-Cast Wall



Directional Wall



Decorative Ceiling / Wall



Polycarbonate Ceiling / Wall



Bulkheads

294



Recessed Wall

304



Lanterns and Half Lanterns

313



Bollards

338



Portable Lanterns

341



Feature Landscape Illumination

345





Inground Uplights and Controllers



Designed to
Deliver...



- AISI 316L grade stainless steel wall light with opal polycarbonate diffuser
- Integral E27 PIR option
- Suitable for internal and external applications



Code	Lamp	Description
AACQE27WL/SS	E27	75W E27
AACQE27WL/PIR/SS	E27	75W E27 PIR

Callisto AC LED Low Level

No Driver Required




ACLPWLED/W



ACLPWLED/GR

- Modern surface mounted ultra-slim low level light
- Die-cast aluminium construction with choice of white or graphite paint finish
- Dupont paint finish
- Tamper-proof stainless steel allen key screws
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	4W
Lumens Delivered	121lm
Lm/W	31lm
Beam Angle	51°
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50Hz
Operating Temp	-40°C to 80°C

Code	Lamp	Description
ACLPWLED/W	LED	4W - Warm White - White
ACLPWLED/GR	LED	4W - Warm White - Graphite





Project - Private Residence
Newton-le-Willows, UK

Callisto AC LED Wall/Ceiling

No Driver Required




ACLED/W



ACLED/GR

- Modern surface mounted ultra-slim wall/ceiling light
- Die-cast aluminium construction with choice of white or graphite paint finish
- Dupont paint finish
- Tamper-proof stainless steel allen key screws
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	4W
Lumens Delivered	181lm
Lm/W	45lm
Beam Angle	65°
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50Hz
Operating Temp	-40°C to 80°C

Code	Lamp	Description
ACLED/W	LED	4W - Warm White - White
ACLED/GR	LED	4W - Warm White - Graphite




Furia AC LED

No Driver Required



231

- Shallow AC LED die-cast surface downlight
- Modern aesthetic appearance
- Exceeds performance of 1x26W PL
- 37° beam angle
- LED lifespan L70 30,000 hours
- Triac dimmable as standard



AFULED/W



AFULED/GR

LED Information

Total (Watts)	10W
Lumens Delivered	719lm
Lm/W	74lm
Beam Angle	37°
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C



Code	Lamp	Description
AFULED/W	LED	10W - Warm White - White
AFULED/GR	LED	10W - Warm White - Graphite

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750




Galia LED

Supplied c/w Integral Driver



- Surface mounting ultra-slim low level square pathway light with downward light-spill
- Die-cast aluminium construction with graphite paint finish
- Comparable performance to 26W PLC
- Screwless front cover with concealed allen key access
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	10W
Lumens Delivered	300lm
Lm/W	30lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
AGALSQLED	LED	10W - Cool White




Matala LED

Supplied c/w Integral Driver



233

- Surface mounting ultra-slim low level circular pathway light with downward light-spill
- Die-cast aluminium construction with graphite paint finish
- Comparable performance to 26W PLC
- Screwless front cover with concealed allen key access
- Pre-wired with 1 metre of rubber insulated cable for ease of installation
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	10W
Lumens Delivered	360lm
Lm/W	36lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C



Code Lamp Description

AMATROLED LED 10W - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Kappa LED

Supplied c/w Integral Driver




AKLED/B



AKLED/SG

- Compact wall light with integral driver
- Downward light spill ideal for pathway illumination
- Die-cast aluminium construction
- LED lifespan L70 40,000 hours
- Non-dimmable



LED Information


Total (Watts)	4.5W
Lumens Delivered	270lm
Lm/W	60lm
CRI	Ra 70
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 25°C

Code	Lamp	Description
AKLED/B	LED	4.5W Cool White - Black
AKLED/SG	LED	4.5W Cool White - Silver Grey





- Contemporary die-cast aluminium LED wall light
- Standard and PIR options
- Graphite textured powder coat paint finish
- LED lifespan
L70 36,000 hours
- Non-dimmable



LED Information

Total (Watts)	6.5W
Lumens Delivered	366lm
Lm/W	52lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C



ASELED/WL



ASELED/WL/PIR

	Code	Lamp	Description
Standard	ASELED/WL	LED	6.5W Cool White
PIR	ASELED/WL/PIR	LED	6.5W - PIR - Cool White

Arco LED

Supplied c/w Integral Driver




AARLED/WL



AARLED/WL/PIR

- Ultra modern LED wall light
- Standard and PIR options
- Graphite textured powder coat paint finish
- LED lifespan
L70 36,000 hours
- Non-dimmable



PIR



6 to 10 metres
8 seconds to 8 minutes
5 to 200 LUX

LED Information

Total (Watts)	11W
Lumens Delivered	643lm
Lm/W	58lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C

	Code	Lamp	Description
Standard	AARLED/WL	LED	11W Cool White
PIR	AARLED/WL/PIR	LED	11W - PIR - Cool White





Tempo LED

Supplied c/w Integral Driver



237

- Contemporary die-cast aluminium LED wall light
- Adjustable head to 90° for variable direction of light
- Standard and PIR options
- Graphite textured powder coat paint finish
- LED lifespan L70 36,000 hours
- Non-dimmable



6 to 10 metres
8 seconds to 8 minutes
5 to 200 LUX

LED Information


Total (Watts)	10W
Lumens Delivered	738lm
Lm/W	73lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C



ATLED/WL



ATLED/WL/PIR



	Code	Lamp	Description
Standard	ATLED/WL	LED	10W Cool White
PIR	ATLED/WL/PIR	LED	10W - PIR - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Dolce LED

Supplied c/w Integral Driver




ADOCLED/WL



ADOCLED/WL/PIR

- Ultra modern LED wall light
- Standard and PIR options
- Graphite textured powder coat paint finish
- LED lifespan
L70 36,000 hours
- Non-dimmable



6 to 10 metres
8 seconds to 8 minutes
5 to 200 LUX

LED Information

Total (Watts)	10W
Lumens Delivered	690lm
Lm/W	76lm
CRI	Ra 80
CCT	4000K
Input	100/240V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C



PIR

	Code	Lamp	Description
Standard	ADOCLED/WL	LED	10W Cool White
PIR	ADOCLED/WL/PIR	LED	10W - PIR - Cool White


Pavia Solar LED

Supplied c/w Integral Driver



239

- Ultra modern die-cast solar powered aluminium LED wall light
- PIR motion sensor as standard
- Automatic day/night mode switching
- 2 operation modes:-
 - 1) 15% output after sunset, motion detected 100% output, no motion 15% for 20 hours
 - 2) Motion detected 100% output, no motion off
- Graphite textured powder coat paint finish
- LED lifespan
L70 36,000 hours



LED Information

Lumens Delivered	230lm
CRI	Ra 80
CCT	4000K
Operating Temp	-20°C to 45°C



Code	Lamp	Description
APAVLED/WL	LED	Cool White
Accessories ASBP/17		7.4V 1500mAh Replacement Li-ION Battery

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750





Project - Private Residence
Newton-le-Willows, UK


Talana Solar LED

Supplied c/w Integral Driver

- Ultra modern die-cast solar powered aluminium LED wall light
- PIR motion sensor as standard
- 2 operation modes:-
1) 11% output after sunset, motion detected 100% output, no motion 11% for 20 hours
2) Motion detected 100% output, no motion off
- Graphite textured powder coat paint finish
- LED lifespan
L70 36,000 hours



241



6 to 10 metres
1 minute
10 to 45 LUX

LED Information

Lumens Delivered	210lm
CRI	Ra 80
CCT	4000K
Operating Temp	-20°C to 45°C



Code	Lamp	Description
ATASLED/WL	LED	Cool White

Accessories	ASBP/17	7.4V 1500mAh Replacement Li-ION Battery
-------------	---------	-----------------------------------------

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Uno LED

Supplied c/w Integral Driver




AUNLED/SG



AUNLED

- Die-cast aluminium construction with tamper-proof stainless steel allen key screws and opal polycarbonate diffuser
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	12W
Lumens Delivered	442lm
Lm/W	37lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 25°C

Code	Lamp	Description
AUNLED	LED	12W - Cool White - Black
AUNLED/SG	LED	12W - Cool White - Silver Grey




Tridon LED CCT

Supplied c/w Integral Driver



243

- Die-cast aluminium construction with opal polycarbonate diffuser
- Exceeds performance of 16W TC-DD
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K at the point of installation
- Rear fixing points allowing the option for BESA box mounting
- Horizontal side pilot holes accepting 20mm surface conduit entries
- Tamper-proof stainless steel allen key screws
- Microwave sensor and Photocell options available
- LED lifespan L70 60,000 hours
- Non-dimmable



ATRILED/B
Warm White



ATRILED/G
Warm White

LED Information

Total (Watts)	7.5W
Lumens Delivered	
Cool White	701lm
Warm White	695lm
Lm/W	
Cool White	88lm
Warm White	87lm
CRI	Ra 80
CCT	3000K 4000K
Input	220-240V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
ATRILED/B	LED	7.5W - Cool White/ Warm White - Black
ATRILED/G	LED	7.5W - Cool White/ Warm White - Graphite

Options	/PC	Electronic Photocell
	/MWS	Integral Microwave Sensor



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Lucca LED CCT

Supplied c/w Integral Driver




ALUCLED/B



ALUCLED/G




Integral switches for multi-wattage and selectable CCT options



- Die-cast aluminium construction with tamper-proof stainless steel allen key screws to retain opal polycarbonate diffuser and frame
- One product with integral switches for multi-wattage and selectable CCT options
- 18W exceeds performance of 38W TC-DD
- 27W exceeds performance of 2x26W PL-C
- LED lifespan L70 60,000 hours
- Non-dimmable



Removable 20mm conduit entry cover for ease of installation



LED Information

Total (Watts)	18W/27W	
Lumens Delivered	4000K	3000K
18W	1149lm	1091lm
27W	1622lm	1563lm
Lm/W 18W	64lm	61lm
Lm/W 27W	60lm	58lm
CRI	Ra 80	
CCT	4000K	3000K
Input	220-240V	
Hertz	50/60Hz	
Operating Temp	-20°C to 25°C	

Code	Lamp	Description
ALUCLED/B	LED	18W/27W - Cool White/ Warm White - Black
ALUCLED/G	LED	18W/27W - Cool White/ Warm White - Graphite


Options	/PC	Electronic Photocell
	/M3	Emergency
	/SM3	Self-Test Emergency
	/DM3	DALI Emergency
	/MWS	Integral Microwave Sensor



Nappa LED CCT

Supplied c/w Integral Driver


- Die-cast aluminium construction with tamper-proof stainless steel allen key screws to retain opal polycarbonate diffuser and frame
- One product with integral switches for multi-wattage and selectable CCT options
- 18W exceeds performance of 38W TC-DD
- 28W exceeds performance of 2x26W PL-C
- LED lifespan L70 60,000 hours
- Non-dimmable



245



Removable 20mm conduit entry cover for ease of installation




ANAPLED/B



ANAPLED/G



Integral switches for multi-wattage and selectable CCT options



LED Information

Total (Watts)	18W/28W	
Lumens Delivered	4000K	3000K
18W	2104lm	2012lm
28W	3065lm	2924lm
Lm/W 18W	117lm	112lm
Lm/W 28W	110lm	105lm
CRI	Ra 80	
CCT	4000K	3000K
Input	220-240V	
Hertz	50/60Hz	
Operating Temp	-20°C to 25°C	

Code	Lamp	Description
ANAPLED/B	LED	18W/28W - Cool White/ Warm White - Black
ANAPLED/G	LED	18W/28W - Cool White/ Warm White - Graphite

Options	/PC	Electronic Photocell
	/M3	Emergency
	/SM3	Self-Test Emergency
	/DM3	DALI Emergency
	/MWS	Integral Microwave Sensor



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750





Dugas

Supplied Less Lamp



- Compact die-cast aluminium wall light
- Installation in either upward or downward orientation
- Luminaire design allows for installation of GU10 LED lamps
- Graphite textured paint finish




Code	Lamp	Description
ADU50	GU10	50W





- Bi-directional wall light with housing in die-cast aluminium with a textured paint finish
- Large diameter housing to provide heat dissipation



ADM50GU10

ADM50GU10/SG



Code	Lamp	Description
ADM50GU10	GU10	2 x 50W - Black
ADM50GU10/SG	GU10	2 x 50W - Silver Grey

Tandem

Supplied Less Lamp



- Bi-directional wall light
- Ideal for GU10 LED or GU10 mains halogen options
- Aluminium construction with graphite textured paint finish



Code	Lamp	Description
ATA2X50	GU10	2 x 50W







Project - Private Residence
Abersoch, UK

Riola

Supplied Less Lamp



- Modern wall light with adjustable 180° head in vertical plane
- For use in both internal and external applications
- Brushed aluminium finish
- Suitable for GU10 LED or GU10 Mains halogen





Code	Lamp	Description
ARGU10	GU10	35W





- Modern bi-directional wall light with brushed aluminium finish
- For use in both internal and external applications
- Suitable for GU10 LED or GU10 Mains halogen




Code	Lamp	Description
ACO2X35	GU10	2 x 35W

Antila LED

Supplied c/w Integral Driver



- Die-cast aluminium bi-directional LED wall light
- Die-cast aluminium construction with graphite paint finish
- 90° Beam Angle
- LED lifespan L70 30,000 hours
- Non-Dimmable



LED Information


Total (Watts)	12W
Lumens Delivered	406lm
Lm/W	37lm
Beam Angle	90°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 50°C

Code	Lamp	Description
ANTIALED	LED	12W - Cool White





- Bi-directional LED wall light
- Die-cast aluminium construction with graphite paint finish
- 105° Beam Angle
- LED lifespan
L70 30,000 hours
- Non-dimmable



LED Information

Total (Watts)	12W
Lumens Delivered	491lm
Lm/W	41lm
Beam Angle	105°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 50°C




Code	Lamp	Description
AZATLED	LED	12W - Cool White

Segano LED

Supplied c/w Integral Driver



- Bi-directional LED wall light
- Die-cast aluminium construction with polycarbonate diffuser
- 90° Beam Angle
- LED lifespan L70 30,000 hours
- Non-dimmable



LED Information

Total (Watts)	13W
Lumens Delivered	610lm
Lm/W	47lm
Beam Angle	90°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 50°C

Code	Lamp	Description
ASEGLED	LED	13W - Cool White




Gila LED

Supplied c/w Integral Driver

255

- Modern bi-directional wall light providing vivid angled light distribution
- Exceeds performance of 100W halogen
- Die-cast aluminium body with a graphite powder coated anodized paint finish for enhanced durability
- LED lifespan L70 30,000 hours
- Non-dimmable



LED Information

Total (Watts)	11W
Lumens Delivered	202lm
Lm/W	18lm
Beam Angle	117°
CRI	Ra 90
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C



Code	Lamp	Description
AGLED/WL	LED	11W - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750




Brock LED Wall Light

Supplied c/w Integral Driver



- Modern bi-directional wall light providing vivid angled light distribution
- Die-cast aluminium body with a graphite powder coated anodized paint finish for enhanced durability
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	7.7W
Lumens Delivered	
Cool White	452lm
Warm White	448lm
Lm/W	
Cool White	57lm
Warm White	56lm
Beam Angle	90°
CRI	Ra 80
CCT	4000K
	3000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
ABRLED/WL/CW	LED	7.7W - Cool White
ABRLED/WL/WW	LED	7.7W - Warm White







Project - Private Residence
Chorley, UK


Duo Midi LED

Supplied c/w Integral Driver



259

- Bi-directional LED wall light
- 19W exceeds performance of 70W CDM-T
- 42W exceeds performance of 150W CDM-T
- Die-cast aluminium construction with graphite paint finish
- 34° beam angle
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	19W
	42W
Lumens Delivered	
19W	1752lm
42W	3582lm
Lm/W 19W	92lm
Lm/W 42W	85lm
Beam Angle	34°
CRI	Ra 80
CCT	4000K
Input	220V-240V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C



ADMLED1/GR/CW

Code	Lamp	Description
ADMLED1/GR/CW	LED	19W - Cool White - Graphite
ADMLED2/GR/CW	LED	42W - Cool White - Graphite


Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750






Doppio LED

Supplied c/w Integral Driver



261

- Powerful architectural bi-directional wall light
- Exceeds performance of 50W HQI
- Die-cast aluminium construction with graphite paint finish
- 20° beam angle
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	34W
Lumens Delivered	2 x 848lm
Lm/W	50lm
Beam Angle	20°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C



Code	Lamp	Description
ADOLEDWL	LED	34W - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750




Doppio HP LED

Supplied c/w Integral Driver



- High performance architectural bi-directional wall light
- Exceeds performance of 150W Metal Halide
- Die-cast aluminium construction with graphite paint finish
- 20° beam angle
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	56.3W
Lumens Delivered	2x2573lm
Lm/W	91lm
Beam Angle	20°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C

Code	Lamp	Description
ADOLEDWL/HP	LED	56.3W - Cool White






Project - Aintree University Hospital
Liverpool, UK

Alto LED

Supplied c/w Integral Driver




- Surface bi-directional die-cast wall light providing adjustable beam angle
- Independent beam angle adjustment between up and down distribution
- Minimum beam angle 0°, maximum beam angle 90°
- Die-cast aluminium body with graphite powder coated anodized paint finish for enhanced durability
- LED lifespan L70 30,000 hours
- Non-dimmable




30° Beam Angle



Full Open Beam Angle



Independent beam angle Adjustment



LED Information

Total (Watts)	6W
Lumens Delivered	205lm
Lm/W	34lm
Beam Angle	0° - 90°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 50°C

Code	Lamp	Description
ALTOLED	LED	6W - Cool White





Aero LED

Supplied c/w Integral Driver



265

- Dual purpose design allows installation as either a canopy light or as an uplight
- Comparable performance to 20W HQL
- Aluminium housing is manufactured from high purity marine grade aluminium and treated with a six stage chrome plating treatment and dry polyester powder coating ensuring excellent corrosion resistance
- Screws manufactured from marine grade stainless steel
- LED lifespan L70 50,000 hours
- Tempered glass cover
- Non-dimmable



Top View

LED Information

Total (Watts)	12W
Lumens Delivered	900lm
Lm/W	75lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 50°C



Code	Lamp	Description
AAROLED	LED	12W - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750





Beam AC LED

No Driver Required



- Compact and powerful die-cast aluminium wall light
- Dual purpose design allows installation as either a canopy downlight or as an uplight
- Exceeds performance of 70W HQI
- Allen key screws manufactured from marine grade stainless steel
- LED lifespan L70 70,000 hours
- Non-dimmable



LED Information

Total (Watts)	20W
Lumens Delivered	1624lm
Lm/W	81lm
Beam Angle	60°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 25°C

Code	Lamp	Description
ABEAMLED	LED	20W - Cool White





Project - The Kirkfield
Newton-le-Willows, UK

Eclipse MultiLED

Supplied c/w Integral Driver




AECLED/CH




AECLED/W



AECLED/SC



- LED wall/ceiling luminaire with adjustable power and light output option
- One product with integral driver dip-switch
- Lumen package options allow retrofit of 28W, 38W or 55W CFL luminaires
- Flexibility of performance allows suitability for multiple applications
- Spun aluminium base with dished opal Visiluxe diffuser
- BESA box fixing versatile mounting options
- Option of White, Chrome or Satin Chrome housing
- LED lifespan L70 54,000 hours



Code	Lamp	Description
AECLED/W	LED	10W/13W/26W - White
AECLED/CH	LED	10W/13W/26W - Chrome
AECLED/SC	LED	10W/13W/26W - Satin Chrome

AECLED/WW/W	LED	10W/13W/26W - White - Warm White
AECLED/WW/CH	LED	10W/13W/26W - Chrome - Warm White
AECLED/WW/SC	LED	10W/13W/26W - Satin Chrome - Warm White

Options	/M3	Self-Test Emergency
	/DD	Digital Dimming (DD1/DD2/DD3/DD4 - 26W only)
	/MWS	Integral Microwave Sensor

LED Information

Total (Watts) 10W/13W/26W		
Lumens Delivered	4000K	3000K
10W	1107lm	1041lm
13W	1400lm	1315lm
26W	2695lm	2521lm
Lm/W 10W	111lm	104lm
Lm/W 13W	108lm	101lm
Lm/W 26W	104lm	97lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50/60Hz	
Operating Temp	-10°C to 40°C	





Mercury CCT LED

Supplied c/w Integral Driver




- IP44 polycarbonate wall/ceiling light for corridors, stairwells and general amenity applications
- High output option allows for a range of installation applications
- LED performance significantly exceeds CFL equivalents
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K at the point of installation (**19W only**)
- BESA box fixing facility
- Integral laminated board heatsink provides high performance thermal management
- Digital dimming, self-test emergency, DALI emergency and microwave sensor options
- Chrome bezel accessory
- LED lifespan L70 56,000 hours



Powered by
TRIDONIC
▼ enlightening your ideas



Chrome Trim Ring Fitted



Code Lamp Description

AMERLED/CCT	LED	19W - Matt White - Cool White/Warm White
AMERLED/HP	LED	33W - Matt White - Warm White Only

Options	/M3	Emergency
	/OCTO	OCTO Smart Control
	/DD	Digital Dimming (DD1/DD2/DD3)
	/MWS	Integral Microwave Sensor

Accessories **AMERLEDBZ/CH** Chrome Trim Ring

LED Information

Total (Watts)	19W	33W
Lumens Delivered	4000K	3500K
19W	1655lm	1420lm
33W	N/A	2702lm
Lm/W 19W	87lm	71lm
Lm/W 33W	N/A	82lm
CRI	Ra 80	
CCT	4000K	3500K
Input	230V	
Hertz	50/60Hz	
Operating Temp	-10°C to 40°C	




Beta LED

Supplied c/w Integral Driver

- Multi-purpose compact surface LED bulkhead
- IP44 rating and suitable for bathroom use
- All polycarbonate construction
- Comparable performance to 100W GLS and outperforms 16W CFL equivalents
- Instant light output and unlimited switching
- LED lifespan
L70 56,000 hours
- Non-dimmable



271



LED Information

Total (Watts)	5W
Lumens Delivered	436lm
Lm/W	87lm
CRI	Ra 70
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	0°C to 25°C



Code	Lamp	Description
ABELED/WV	LED	5W - Cool White - White Base, Opal Visiluxe Diffuser

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Gamma Mini LED

Supplied c/w Integral Driver



AMGAMLED




Chrome Trim Ring Fitted



Ultra slim profile

- Ultra slim modern polycarbonate wall/ceiling light
- Matt white finish to body and diffuser
- Rear fixing bracket and terminal housing for ease of installation
- Performance comparable to 28W TC-DD
- IP54 rating and suitable for bathroom use
- Microwave sensor set to 15 minutes (non-adjustable)
- /MWS and /MWS/M3 versions Masters as standard
- /MWS and MWS/M3 has integral photocell isolation switch
- LED lifespan L70 54,000 hours
- Non-dimmable



Code	Lamp	Description
AMGAMLED	LED	11W - Cool White
AMGAMLED/WW	LED	11W - Warm White

Options	/M3	Emergency
	/MWS	Internal Microwave Sensor

Accessories	AMGAMLEDBZ/CH	Chrome Trim Ring
--------------------	----------------------	------------------


LED Information

Total (Watts)	11W
Lumens Delivered	
Cool White	1031lm
Warm White	971lm
Lm/W Cool White	94lm
Lm/W Warm White	88lm
CRI	Ra 80
CCT	4000K
	3000K
Input	230V
Hertz	50Hz
Operating Temp	-5°C to 35°C





- Ultra slim modern polycarbonate wall/ceiling light
- Matt white finish to body and diffuser
- Rear fixing bracket and terminal housing for ease of installation
- Outperforms 38W CFL with opal diffuser by 25% and prismatic diffuser by 52%
- IP54 rating and suitable for bathroom use
- Microwave sensor set to 15 minutes (non-adjustable)
- /MWS and /MWS/M3 versions Masters as standard
- /MWS and MWS/M3 has integral photocell isolation switch
- LED lifespan L70 54,000 hours
- Non-dimmable



AGAMLED



Chrome Trim Ring Fitted



Ultra slim profile


LED Information

Total (Watts)	18W
Lumens Delivered	
Cool White	1675lm
Warm White	1551lm
Lm/W Cool White	93lm
Lm/W Warm White	86lm
CRI	Ra 80
CCT	4000K
	3000K
Input	230V
Hertz	50Hz
Operating Temp	-5°C to 35°C

Code	Lamp	Description
AGAMLED	LED	18W - Cool White
AGAMLED/WW	LED	18W - Warm White

Options	/M3	Emergency
	/MWS	Internal Microwave Sensor

Accessories	AGAMLEDBZ/CH	Chrome Trim Ring
--------------------	---------------------	------------------



Jazz LED

Supplied c/w Integral Driver




IP65

AJALED



Chrome Trim Ring Fitted

- Contemporary all polycarbonate fixture for wall/ceiling mounting
- LED performance exceeds CFL equivalents
- /MWS/M3/CF provides CorridorFUNCTION with Tridonic control gear
- Optional chrome trim ring
- LED lifespan L70 56,000 hours



Code	Lamp	Description
AJALED	LED	14W - Cool White

Options		
/M3	Emergency	
/MWS	Internal Microwave Sensor	
/MWS/M3/CF	Integral Microwave Sensor and Emergency CorridorFUNCTION	

Accessories		
AJALEDDBZ/CH	Chrome Trim Ring	

LED Information


Total (Watts)	14W
Lumens Delivered	993lm
Lm/W	66lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 25°C



Disco Slim LED CCT

Supplied c/w Integral Driver

- Slim modern design with all polycarbonate construction with opal diffuser and white trim ring
- 7W exceeds performance of 16W TC-DD
- 13W exceeds performance of 38W TC-DD
- Internal CCT selector switch allows the installer to choose the CCT between 3000K and 4000K at the point of installation
- Two options of microwave sensor emergency
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours





275





ADSILED1/CCT

IP65



ADSILED1/CCT



ADSILED2/CCT



fitted with chrome trim ring



fitted with graphite trim ring

LED Information

	Cool White	Warm White
Total (Watts)	7W	13W
Lumens Delivered	643lm	575lm
	1083lm	1027lm
Lm/W	92lm	82lm
	83lm	79lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 25°C	

Code Lamp Description

ADSILED1/CCT	LED	7W - Cool White/Warm White
ADSILED2/CCT	LED	13W - Cool White/Warm White

Options	/M3	Emergency (13W only)
	/MWS	Integral Microwave Sensor (13W only)

Accessories	ADSILED1BZ/CH	Chrome Trim Ring (8W)
	ADSILED1BZ/GR	Graphite Trim Ring (8W)
	ADSILED2BZ/CH	Chrome Trim Ring (13W)
	ADSILED2BZ/GR	Graphite Trim Ring (13W)



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Disco Slim LED

Supplied c/w Integral Driver



ADSILED1

IP65




fitted with chrome trim ring




fitted with graphite trim ring

- Slim modern design with all polycarbonate construction with opal diffuser and white trim ring
- 8W exceeds performance of 16W TC-DD
- 13W exceeds performance of 38W CFL
- Two options of microwave sensor emergency
- /MWS/M3/CF provides CorridorFUNCTION with Tridonic control gear
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours



ADSILED1



ADSILED2

Code	Lamp	Description
ADSILED1	LED	8W - Cool White
ADSILED1/WW	LED	8W - Warm White
ADSILED2	LED	13W - Cool White
ADSILED2/WW	LED	13W - Warm White

Options	/M3	Emergency (13W only)
	/MWS	Integral Microwave Sensor (13W only)
	/MWS/M3/CF	Integral Microwave Sensor and Emergency CorridorFUNCTION (13W only)


Accessories	ADSILED/1BZ/CH	Chrome Trim Ring (8W)
	ADSILED/1BZ/GR	Graphite Trim Ring (8W)
	ADSILED/2BZ/CH	Chrome Trim Ring (13W)
	ADSILED/2BZ/GR	Graphite Trim Ring (13W)

LED Information


	Cool White	Warm White
Total (Watts)	8W	13W
Lumens Delivered	584lm	547lm
	1021lm	979lm
Lm/W	73lm	68lm
	79lm	75lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 25°C	



- Slim modern design with all polycarbonate construction with opal diffuser and white trim ring
- Unique design creates halo light spill effect
- 8W exceeds performance of 28W TC-DD
- 13W comparable performance to 40W TC-DD
- Two options of microwave sensor emergency
- /MWS/M3/CF provides CorridorFUNCTION with Tridonic control gear
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours



ADSIHLED1



ADSIHLED2

LED Information

	Cool White	Warm White
Total (Watts)	8W	13W
Lumens Delivered	687lm	605lm
	1198lm	1064lm
Lm/W	86lm	87lm
	92lm	82lm
CRI	Ra 80	
CCT	4000K	
	3000K	
Input	230V	
Hertz	50Hz	
Operating Temp	-10°C to 25°C	



Disco Slim Halo LED

Supplied c/w Integral Driver



277



ADSIHLED1

IP65



Halo light spill effect



fitted with chrome trim ring



fitted with graphite trim ring

Code	Lamp	Description
ADSIHLED1	LED	8W - Cool White
ADSIHLED1/WW	LED	8W - Warm White

ADSIHLED2	LED	13W - Cool White
ADSIHLED2/WW	LED	13W - Warm White

Options	/M3	Emergency (13W only)
	/MWS	Integral Microwave Sensor (13W only)
	/MWS/M3/CF	Integral Microwave Sensor and Emergency CorridorFUNCTION (13W only)

Accessories	ADSILED/1BZ/CH	Chrome Trim Ring (8W)
	ADSILED/1BZ/GR	Graphite Trim Ring (8W)
	ADSILED/2BZ/CH	Chrome Trim Ring (13W)
	ADSILED/2BZ/GR	Graphite Trim Ring (13W)

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Disco LED

Supplied c/w Integral Driver



ADILED1


IP65



ADILED2

IP65

- All polycarbonate construction with opal diffuser and white trim ring
- LED performance exceeds CFL equivalents
- Two options of microwave sensor emergency
- /MWS/M3/CF provides CorridorFUNCTION with Tridonic control gear
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours



Code	Lamp	Description
ADILED1	LED	8W - Cool White
ADILED2	LED	14W - Cool White

Options	/M3	Emergency (14W only)
	/MWS	Integral Microwave Sensor (14W only)
	/MWS/M3/CF	Integral Microwave Sensor and Emergency CorridorFUNCTION (14W only)

Accessories	ADI28BZ/BR	Brass Trim Ring (14W)
	ADI28BZ/CH	Chrome Trim Ring (14W)
	ADI28BZ/SG	Silver Grey Trim Ring (14W)

LED Information


Total (Watts)	8W
	14W
Lumens Delivered	539lm
	860lm
Lm/W	67lm
	61lm
CRI	Ra 70
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 25°C



- All polycarbonate construction with opal diffuser and white trim ring
- Optional trim rings available in brass, chrome and silver grey finishes
- Suitable for bathrooms



IP65



ADI28/HF



fitted with brass trim ring



fitted with chrome trim ring



fitted with silver grey trim ring

Code	Lamp	Description
ADI28/HF	TC-DD	28W

Options	/M3	Emergency
---------	-----	-----------

Accessories	ADI28BZ/BR	Brass Trim Ring (28W)
	ADI28BZ/CH	Chrome Trim Ring (28W)
	ADI28BZ/SG	Silver Grey Trim Ring (28W)



Astro LED

Supplied c/w Integral Driver and Trim Accessory



AALED1/BV
(Fitted with Trim Attachment)




AALED1/WV




AALED2/WV
(Fitted with Trim Attachment)

- All polycarbonate multi-purpose LED square bulkhead
- LED performance exceeds CFL equivalents
- Push fit feed-in, feed-out terminals for speed and ease of installation
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours



AALED1



AALED2

LED Information

Total (Watts)	7W
	14W
Lumens Delivered	
7W	628lm
14W	1220lm
Lm/W	89lm
	87lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 25°C

Code	Lamp	Description
AALED1/BV	LED	7W - Cool White - Black Base, Visiluxe Cover
AALED1/WV	LED	7W - Cool White - White Base, Visiluxe Cover
AALED2/BV	LED	14W - Cool White - Black Base, Visiluxe Cover
AALED2/WV	LED	14W - Cool White - White Base, Visiluxe Cover
Options	/PC	Electronic Photocell
	/M3	Emergency (14W only)
	/MWS	Integral Microwave Sensor (14W only)




- All polycarbonate multi-purpose LED round bulkhead
- LED performance exceeds CFL equivalents
- Push fit feed-in, feed-out terminals for speed and ease of installation
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours




ADLED1/BV



ADLED1/WV
(Fitted with Trim Attachment)



ADLED1



ADLED2



ADLED2/BV
(Fitted with Louvred Bezel Trim)

LED Information

Total (Watts)	6W
	14W
Lumens Delivered	
6W	661lm
14W	1208lm
Lm/W	110lm
	86lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 25°C



Code	Lamp	Description
ADLED1/BV	LED	6W - Cool White - Black Base, Visiluxe Cover
ADLED1/WV	LED	6W -Cool White - White Base, Visiluxe Cover

ADLED2/BV	LED	14W - Cool White - Black Base, Visiluxe Cover
ADLED2/WV	LED	14W - Cool White - White Base, Visiluxe Cover

Options	/PC	Electronic Photocell
	/M3	Emergency (14W only)
	/MWS	Integral Microwave Sensor (14W only)

Accessories	ADLED2/BZ/EYE/B	Black Eyelid Bezel Trim (14W Only)
	ADLED2/BZ/EYEW	White Eyelid Bezel Trim (14W Only)
	ADLED2/BZ/GRILL/B	Black Louvred Bezel Trim (14W Only)
	ADLED2/BZ/GRILLW	White Louvred Bezel Trim (14W Only)

Delta CFL

Supplied c/w Lamp




AD16/WP/HF




AD28/BP/HF

- Multi-purpose range of circular bulkhead fittings for both internal and external installations
- All polycarbonate construction
- Body options of black or white base with diffuser options of clear prismatic or opal



AD16



AD28


Code	Lamp	Description
AD16/BP/HF	TC-DD	16W - Black Base / Prismatic Cover
AD16/WO/HF	TC-DD	16W - White Base / Opal Cover
AD16/WP/HF	TC-DD	16W - White Base / Prismatic Cover
AD28/BP/HF	TC-DD	28W - Black Base / Prismatic Cover
AD28/WO/HF	TC-DD	28W - White Base / Opal Cover
AD28/WP/HF	TC-DD	28W - White Base / Prismatic Cover

Options	/M3	Emergency (28W only)
----------------	------------	----------------------




Mini Vision 3 LED

Supplied c/w Integral Driver and 3 Trim Designs



283

- IP65 polycarbonate LED luminaire for external applications
- Each fitting supplied with plain, louvred eyelid and plain eyelid covers
- Exceeds performance of 28W TC-DD
- LED lifespan L70 36,000 hours
- Non-dimmable
- PIR provides tri-level dimming option with 100%-10% output and manual override



Max 8 metres
8 seconds to 5 minutes
2 to 2000 LUX

LED Information

Total (Watts)	9W
Lumens Delivered	797lm
Lm/W	89lm*
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 50°C

* Please note that Lm/W rating reduces for eyelid versions



AVIMLED/GR/PIR



Discrete integral PIR



AVIMLED/SG/PIR - Fitted with Louvred Eyelid



AVIMLED/W - Fitted with Plain Eyelid

	Code	Lamp	Description
Standard	AVIMLED/GR	LED	9W - Graphite
	AVIMLED/SG	LED	9W - Silver Grey
	AVIMLED/W	LED	9W - White
PIR	AVIMLED/GR/PIR	LED	9W - PIR - Graphite
	AVIMLED/SG/PIR	LED	9W - PIR - Silver Grey
	AVIMLED/W/PIR	LED	9W - PIR - White

Option	/PC	Electronic Photocell
--------	-----	----------------------

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Vision 3 CCT LED

Supplied c/w Integral Driver and 3 Trim Designs



Discrete integral PIR



Fitted with Plain Eyelid

Powered by
TRIDONIC
▼ enlightening your ideas





Fitted with Louvred Eyelid

- IP65 CCT polycarbonate 3-In-1 LED luminaire for external applications
- Each fitting supplied with plain, louvred eyelid and plain eyelid covers
- CCT selectable between 3000K and 4000K
- Exceeds performance of 38W TC-DD
- LED lifespan L70 56,000 hours
- PIR provides tri-level dimming option with 100%-10% output and manual override



Max 8 metres
8 seconds to 5 minutes
2 to 2000 LUX



LED Information

Total (Watts)	17W
Lumens Delivered	
Cool White	1420lm
Warm White	1324lm
Lm/W Cool White	84lm*
Lm/W Warm White	83lm*
CRI	Ra 80
CCT	4000K 3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C

* Please note that Lm/W rating reduces for eyelid versions



	Code	Lamp	Description
Standard	AVILED/CCT/GR	LED	17W - Graphite - Cool White/Warm White
	AVILED/CCT/SG	LED	17W - Silver Grey - Cool White/Warm White
	AVILED/CCT/W	LED	17W - White - Cool White/Warm White
PIR	AVILED/CCT/GR/PIR	LED	17W - Graphite - Cool White/Warm White - PIR
	AVILED/CCT/SG/PIR	LED	17W - Silver Grey - Cool White/Warm White - PIR
	AVILED/CCT/W/PIR	LED	17W - White - Cool White/Warm White - PIR
Options	/PC	Electronic Photocell	
	/M3	Emergency	
	/DD	Digital Dimming (DD1/DD2/DD3/DD4)	
	/MWS	Integral Microwave Sensor	

Vision 3 HP LED

Supplied c/w Integral Driver and 3 Trim Designs

- IP65 polycarbonate 3-In-1 LED luminaire for external applications
- Each fitting supplied with plain, louvred eyelid and plain eyelid covers
- Exceeds performance of CFL equivalents
- Four conduit entry points
- Integral die-cast aluminium heatsink provides thermally managed high performance
- 31W LED lifespan L70 36,000 hours




285



Removable conduit entry cap for ease of installation



Powered by
TRIDONIC
▼ enlightening your ideas



Fitted with Solid Eyelid



Fitted with Louvred Eyelid

LED Information

Total (Watts)	31W
Lumens Delivered	
31W	2426lm
Lm/W 31W	78lm*
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 50°C

* Please note that Lm/W rating reduces for eyelid versions



Code	Lamp	Description
AVILED/HP/GR	LED	31W - Graphite - Cool White
AVILED/HP/SG	LED	31W - Silver Grey - Cool White
AVILED/HP/W	LED	31W - White - Cool White

Options	/PC	Electronic Photocell
	/M3	Emergency
	/DD	Digital Dimming (DD1/DD2/DD3/DD4)
	/MWS	Integral Microwave Sensor

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Topaz LED

Supplied c/w Integral Driver




ATOPLED/B



ATOPLED/W

- All polycarbonate decorative wall light
- Feature eyelid cover
- Exceeds performance to 18W PLC
- LED lifespan L70 56,000 hours
- Non-dimmable



LED Information

Total (Watts)	8W
Lumens Delivered	439lm
Lm/W	55lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	0°C to 25°C

Code	Lamp	Description
ATOPLED/B	LED	8W - Cool White - Black
ATOPLED/W	LED	8W - Cool White - White

Helder LED Circular Bulkhead

Supplied c/w Integral Driver




287

- All polycarbonate circular bulkhead for external applications
- fast loop-in / loop-out connections
- Comparable performance to 28W TC-DD
- Body options of black or white
- Polycarbonate opal diffuser
- LED lifespan L70 25,000 hours
- Non-dimmable



Max 10 metres
10 seconds to 5 minutes
10 - 2000 LUX



AHELED/CB



AHELED/CW/PIR



AHELED/EB

LED Information

Total (Watts)	14W
Lumens Delivered	
Standard	972lm
Eyelid	529lm
PIR	1011lm
Lm/W	
Standard	70lm
Eyelid	38lm
PIR	72lm
CRI	Ra 80
CCT	4000K
Input	220-240V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C

	Code	Lamp	Description
Standard	AHELED/CB	LED	14W - Black - Cool White
	AHELED/CW	LED	14W - White - Cool White
PIR	AHELED/CB/PIR	LED	14W - Black - Cool White - PIR
	AHELED/CW/PIR	LED	14W - White - Cool White - PIR
Standard Eyelid	AHELED/EB	LED	14W - Black - Cool White
	AHELED/EW	LED	14W - White - Cool White
PIR Eyelid	AHELED/EB/PIR	LED	14W - Black - Cool White - PIR
	AHELED/EW/PIR	LED	14W - White - Cool White - PIR



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Helder LED Oval Bulkhead

Supplied c/w Integral Driver






AHELED/OW/PIR



AHELED/O/B

- All polycarbonate oval bulkhead for external applications
- fast loop-in / loop-out connections
- Comparable performance to 28W TC-DD
- Body options of black or white
- Polycarbonate opal diffuser
- LED lifespan L70 25,000 hours
- Non-dimmable



LED Information


Total (Watts)	14W
Lumens Delivered	
Standard	887lm
PIR	925lm
Lm/W	
Standard	63lm
PIR	66lm
CRI	Ra 80
CCT	4000K
Input	220-240V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C

	Code	Lamp	Description
Standard	AHELED/OB	LED	14W - Black - Cool White
	AHELED/OW	LED	14W - White - Cool White
PIR	AHELED/OB/PIR	LED	14W - Black - Cool White - PIR
	AHELED/OW/PIR	LED	14W - White - Cool White - PIR



Sorrento 2 LED

Supplied c/w Integral Driver, Plain Cover and Eyelid Cover




289

- Shallow depth IP65 polycarbonate 2-In-1 LED bulkhead for external applications
- Supplied with both plain and louvred eyelid covers
- Exceeds performance of 18W PLC
- LED lifespan L70 56,000 hours
- Non-dimmable



ASR2LED/W
(Plain Cover)



ASR2LED/B
(Plain Cover)




ASR2LED/B
(Louvred Eyelid Cover)



ASR2LED/W
(Louvred Eyelid Cover)

LED Information

Total (Watts)	8W
Lumens Delivered	634lm
Lm/W	79lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-0°C to 25°C




Code	Lamp	Description
ASR2LED/B	LED	8W - Cool White - Black
ASR2LED/W	LED	8W - Cool White - White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750




Sleek LED Polycarbonate Bulkhead

Supplied c/w Integral Driver



- All polycarbonate multi-purpose bulkhead
- Exceeds performance of 9W PL
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching
- LED lifespan L70 56,000 hours
- Non-dimmable



LED Information

Total (Watts)	6W
Lumens Delivered	440lm
Lm/W	73lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	0°C to 25°C


Code	Lamp	Description
ASBLED	LED	6W - Cool White

Options		
/PC		Electronic Photocell
/MWS		Integral Microwave Sensor




Sleek LED 110V Polycarbonate Bulkhead

Supplied c/w Integral Driver




291

- All polycarbonate multi-purpose bulkhead
- Exceeds performance of 9W PL
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Suitable for all types of site lighting
- Instant light output and unlimited switching
- Red diffuser accessory available for applications that require warning indication luminaires
- LED lifespan L70 56,000 hours
- Non-dimmable



124



244

76

LED Information

Total (Watts)	5W
Lumens Delivered	424lm
Lm/W	85lm
CRI	Ra 80
CCT	4000K
Input	110V
Hertz	50Hz
Operating Temp	-10°C to 40°C



Sleek 110V fitted with Red polycarbonate Lens accessory


Code	Lamp	Description
ASBLED/110V	LED	5W - Yellow Base
Options	/PC	Electronic Photocell
	/MWS	Integral Microwave Sensor
Accessory	ASBLED/DIFF/RED	Red Polycarbonate Lens

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



E27 Aluminium Bulkhead

Supplied Less Lamp




A100PC



A100GC

- Aluminium alloy body to prevent corrosion
- Option of vandal resistant polycarbonate or glass lens



Code	Lamp	Description
A100PC	E27	100W - Polycarbonate Lens
A100GC	E27	100W - Glass Lens

Options	/PC	Electronic Photocell
----------------	------------	----------------------

E27 Options			
100 W	23W	20W	
	53	53	
	130	130	
Maximum size and wattage			




E27 Polycarbonate Bulkhead

Supplied Less Lamp



293

- Vandal resistant all polycarbonate construction



E27 Options		
100 W	23W	20W
130	53	53
130	130	130
Maximum size and wattage		



Code	Lamp	Description
A100POLY	E27	100W - Black Base
Options	/PC	Electronic Photocell




Camini LED

Supplied c/w Integral Driver



- Compact low level square LED pathway light with downward light spill
- Die-cast aluminium construction with graphite paint finish
- Supplied c/w plastic installation box and pre-wired with 1 metre of rubber insulated cable for ease of installation
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	3W
Lumens Delivered	79lm
Lm/W	22lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
ACSQLEDWL	LED	3W - Cool White




Parona LED

Supplied c/w Integral Driver



295

- Compact low level circular LED pathway light with downward light spill
- Die-cast aluminium construction with graphite paint finish
- Supplied c/w plastic installation box and pre-wired with 1 metre of rubber insulated cable for ease of installation
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	3W
Lumens Delivered	178lm
Lm/W	45lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C



Code	Lamp	Description
APCLEDWL	LED	3W - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750






Project - Private Residential
Liverpool, UK

Libretto LED Bricklight

Supplied c/w Integral Driver



297


- Stainless steel front cover with clear polycarbonate front lens and recessed housing
- Integral driver with loop-in, loop-out connections
- LED lifespan L70 40,000 hours
- Non-dimmable



ALIBLED/BLU



ALIBLED/WHI



LED Information

Total (Watts)	2W
Lumens Delivered	
Daylight	126lm
Blue	48lm
Lm/W	63lm
Lm/W Blue	24lm
CRI	Ra 65
CCT	6000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 25°C



Code	Lamp	Description
ALIBLED/WHI	LED	2W - Daylight
ALIBLED/BLU	LED	2W - Blue

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750




Fidenza LED Bricklight

Supplied c/w Integral Driver



AFBLLED




AFBL/GRILL Cover Fitted



AFBL/EYE Cover Fitted

- Die-cast aluminium housing and front cover
- Toughened front frosted glass
- Metal back box with cable entries for ease of installation
- Optional grill and hood front covers
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	2.2W
Lumens Delivered	145lm
Lm/W	66lm
CRI	Ra 65
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C

Code	Lamp	Description
AFBLLED	LED	2.2W - Cool White

Accessories AFBL/GRILL	Front Grill Cover
AFBL/EYE	Front Eyelid Cover





Project - Private Residential
Warrington, UK

LED Inox Stainless Steel Bricklight

Supplied c/w Integral Driver




300






Stainless Steel **AISI 316L**

- Die-cast aluminium bricklight with AISI316L stainless steel front cover
- Comparable performance to 18W PLC
- Tempered and frosted 4mm glass diffuser
- Supplied c/w polyethelyne back box for recessing
- LED lifespan L70 50,000 hours
- Non-dimmable



Box Dimensions



LED Information



Total (Watts)	12W
Lumens Delivered	270lm
Lm/W	23lm
CRI	Ra 70
CCT	3000K
Input	230V
Hertz	50Hz
Operating Temp	-25°C to 35°C

Code	Lamp	Description
ABLFLED/SS	LED	12W - Warm White





- Modern low level surface brick light/wall light
- General illumination ideal for pathway/walkway illumination
- Die-cast aluminium housing graphite powder coated anodized finish
- Tempered frosted glass
- LED lifespan L70 30,000 hours
- Non-dimmable



Wall Mounted



Low Level Mounted

LED Information

Total (Watts)	7W
Lumens Delivered	302lm
Lm/W	43lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50Hz
Operating Temp	-10°C to 50°C






Code	Lamp	Description
AVOLEDSWL	LED	7W - Cool White



Project - Private Residential
Congleton, UK



- Ultra modern exterior wall light
- Die-cast frame with tempered glass enclosure
- Textured powder coated anthracite finish
- Ideal for use with LED Filament lamps



Code	Lamp	Description
ACAL/E27	E27	40W - Sandy Anthracite

Latina LED Half Lantern

Supplied c/w Integral Driver




ALHLLLED/BL



ALHLLLED/PIR/W

- Contemporary IP65 half lantern and resistant to corrosion
- Textured polycarbonate finish and tinted lens
- LED light bar for uniform light output
- PIR option for convenience and security. Incorporates manual override option
- Colour matching PIR lens cover ensures discreet appearance
- LED lifespan L70 56,000 hours
- Non-dimmable



Max 8 metres
5 seconds to 5 minutes
3 LUX - Photocell Off

LED Information



Total (Watts)	8W
Lumens Delivered	400lm
Lm/W	53lm
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C

	Code	Lamp	Description
Standard	ALHLLLED/BL	LED	8W - Warm White - Black
	ALHLLLED/WH	LED	8W - Warm White - White
Photocell	ALHLLLED/PC/BL	LED	8W Photocell - Warm White - Black
	ALHLLLED/PC/WH	LED	8W Photocell - Warm White - White
PIR	ALHLLLED/PIR/BL	LED	8W PIR - Warm White - Black
	ALHLLLED/PIR/WH	LED	8W PIR - Warm White - White





Latina Polycarbonate Half Lantern

Supplied Less Lamp



305

- Contemporary IP65 half lantern and resistant to corrosion
- Textured polycarbonate finish and tinted lens
- PIR option for convenience and security. Incorporates manual override option
- Colour matching PIR lens cover ensures discreet appearance



ALHL/BL



ALHL/PIR/WH

	Code	Lamp	Description
Standard	ALHL/BL	E27	42W - Black
	ALHL/WH	E27	42W - White
Photocell	ALHL/PC/BL	E27	42W Photocell - Black
	ALHL/PC/WH	E27	42W Photocell - White
PIR	ALHL/PIR/BL	E27	42W PIR - Black
	ALHL/PIR/WH	E27	42W PIR - White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Latina LED Wall Lantern

Supplied c/w Integral Driver



ALWLLED/PIR/BL



ALWLLED/WH




ALWL/CBB



ALWL/CBW

- Contemporary IP65 polycarbonate lantern range and resistant to corrosion
- LED light bar for uniform light output
- Unique design provides installer with option of top arm or bottom arm mounting, without the need of additional wiring (PIR version bottom arm mounting only)
- Textured polycarbonate finish and tinted lens
- PIR option for convenience and security. Incorporates manual override option
- Colour matching PIR lens ensures discreet appearance
- LED lifespan L70 56,000 hours
- Non-dimmable



Max 8 metres
5 seconds to 5 minutes
3 LUX - Photocell Off

LED Information

Total (Watts)	8W
Lumens Delivered	546lm
Lm/W	68lm
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50/60Hz
Operating Temp	-10°C to 40°C

	Code	Lamp	Description
Standard	ALWLLED/BL	LED	8W - Warm White - Black
	ALWLLED/WH	LED	8W - Warm White - White
PIR	ALWLLED/PIR/BL	LED	8W PIR - Warm White - Black
	ALWLLED/PIR/WH	LED	8W PIR - Warm White - White



Accessories	ALWL/CBB	Wall Lantern Corner Bracket Black
	ALWL/CBW	Wall Lantern Corner Bracket White



Latina Polycarbonate Wall Lantern

Supplied Less Lamp

- Contemporary IP65 polycarbonate lantern range and resistant to corrosion
- Unique design provides installer with option of top arm or bottom arm mounting, without the need of additional wiring (PIR version bottom arm mounting only)
- Textured polycarbonate finish and tinted lens
- PIR option for convenience and security. Incorporates manual override option
- Colour matching PIR lens ensures discreet appearance



307



ALWL/WH




ALWL/PIR/BL



ALWL/CBB




ALWL/CBW



PIR



4 to 8 metres
5 seconds to 5 minutes
30 LUX



	Code	Lamp	Description
Standard	ALWL/BL	E27	42W - Black
	ALWL/WH	E27	42W - White
PIR	ALWL/PIR/BL	E27	42W PIR - Black
	ALWL/PIR/WH	E27	42W PIR - White
Accessories	ALWL/CBB		Wall Lantern Corner Bracket Black
	ALWL/CBW		Wall Lantern Corner Bracket White



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Roma

Supplied Less Lamp



Transparent Lens
for E27 versions
(excluding
PIR versions)




Opal Lens
for PIR versions



ARE27/HL/BL

- Die-cast aluminium half-lantern in black
- Clear polycarbonate diffuser for E27 versions
- Opal polycarbonate diffuser for PIR versions



E27 Options		
100 W	23W 53	20W 53
Maximum size and wattage		

Code	Lamp	Description
ARE27/HL/BL	E27	100W - Black
ARE27/PIR/HL/BL	E27	100W - PIR - Black






Lampara Inox Stainless Steel

Supplied Less Lamp



309

- Body manufactured from AISI 316L grade stainless steel
- Transparent polycarbonate diffuser



E27 Options		
100W	23W 53	20W 53
130	130	130
Maximum size and wattage		



Code	Lamp	Description
ALE27/WL/SS	E27	100W

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750




Lampara

Supplied Less Lamp



- Die-cast aluminium construction with transparent polycarbonate diffuser
- Black paint finish




E27 Options		
100 W	23W	20W
	53	53
165	165	165
Maximum size and wattage		

Code	Lamp	Description
ALE27/WL/BL	E27	100W - Black






- Die-cast aluminium four sided lantern
- Black paint finish
- Smoked glass diffuser
- Full size post lanterns incorporate hinged door for easy wiring access




ANE27/WLBA/BL



ANE27/WLTA/B

ANE27/PIL/BL






ANE27/PIL/BL



ANE27/WLBA/BL



E27 Options		
60W to 100W	23W 53	20W 53
		
Maximum size and wattage		




	Code	Lamp	Description
Wall Lantern	ANE27/WLTA/BL	E27	60W Top Arm - Black
	ANE27/WLBA/BL	E27	60W Bottom Arm - Black
Pillar Lantern	ANE27/PIL/BL	E27	60W - Black
Mini Post Lantern	ANE27/MPTL/BL	E27	100W - Black



Project - Private Residential
Bangor, Ireland



- High Grade AISI 316L stainless steel bollard
- Slim profile provides additional suitability for patio lighting
- Suitable for commercial and domestic applications






AUE27040/SS



AUE27070/SS



E27 Options		
60W	23W	20W
		
130	53	53
Maximum size and wattage		



Code	Lamp	Description
AUE27040/SS	E27	60W 400mm
AUE27070/SS	E27	60W 700mm

Urano Inox Country

Supplied Less Lamp




AUE27040/WE



AUE27070/WE

- Stunning combination of country wood effect with stainless steel head
- Slim profile provides additional suitability for patio lighting
- Decorative AISI 316L stainless steel head
- Suitable for commercial and domestic applications



Code	Lamp	Description
AUE27040/WE	E27	60W 400mm
AUE27070/WE	E27	60W 700mm

E27 Options		
60W	23W 53	20W 53
Maximum size and wattage		





Project - Private Residential
County Antrim, Ireland



Project - Private Residential
Southport, UK


Pavia Solar LED

Supplied c/w Integral Driver

- Ultra modern die-cast solar powered aluminium LED bollard
- PIR motion sensor as standard
- Automatic day/night mode switching
- 2 operation modes:-
1) 15% output after sunset, motion detected 100% output, no motion 15% for 20 hours
2) Motion detected 100% output, no motion off
- Graphite textured powder coat paint finish
- LED lifespan
L70 36,000 hours



317



LED Information

Lumens Delivered	230lm
CRI	Ra 80
CCT	4000K
Operating Temp	-20°C to 45°C

Code	Lamp	Description
APAVLEDB/60	LED	Cool White
Accessories ASBP/17	7.4V 1500mAh Replacement Li-ION Battery	



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Talana Solar LED


Supplied c/w Integral Driver



- Ultra modern die-cast solar powered aluminium LED bollard
- PIR motion sensor as standard
- 2 operation modes:-
1) 11% output after sunset, motion detected 100% output, no motion 11% for 20 hours
2) Motion detected 100% output, no motion off
- Graphite textured powder coat paint finish
- LED lifespan L70 36,000 hours



Matching
Talana Solar LED Wall Light
see p241



6 to 10 metres
1 minute
10 to 45 LUX

Code	Lamp	Description
ATASLEDB/60	LED	Cool White

Accessories ASBP/17 7.4V 1500mAh Replacement Li-ION Battery

LED Information

Lumens Delivered	210lm
CRI	Ra 80
CCT	4000K
Operating Temp	-20°C to 45°C






Project - Private Residential
Belfast, UK





- Contemporary die-cast aluminium LED bollard
- Standard and PIR options
- Graphite textured powder coat paint finish
- Flange mounted base for surface fixing
- LED lifespan
L70 36,000 hours
- Non-dimmable



PIR



6 to 9 metres
5 seconds to 8 minutes
10 to 2000 LUX

LED Information

Total (Watts)	6.5W
Lumens Delivered	366lm
Lm/W	52lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C



ASELEDB/060/PIR

ASELEDB/100

	Code	Lamp	Description
Standard	ASELEDB/060	LED	6.5W - Cool White 600mm
	ASELEDB/100	LED	6.5W - Cool White 1000mm
PIR	ASELEDB/060/PIR	LED	6.5W - PIR - Cool White 600mm
	ASELEDB/100/PIR	LED	6.5W - PIR - Cool White 1000mm

Arco LED

Supplied c/w Integral Driver



Light distribution from head of bollard



AARLEDB/060




AARLEDB/100

- Ultra modern LED bollard
- Graphite textured powder coated paint finish
- Flange mounted base for surface mounting
- LED lifespan L70 36,000 hours
- Non-dimmable



Matching
Arco LED Wall Light
see p236



LED Information

Total (Watts)	11W
Lumens Delivered	643lm
Lm/W	58lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C




Code	Lamp	Description
AARLEDB/060	LED	11W - Cool White 600mm
AARLEDB/100	LED	11W - Cool White 1000mm



Project - Private Residential
York, UK



- Modern bollard with die-cast aluminium body
- Innovative bi-directional light distribution
- Equivalent performance to 26W PLC
- Powder coated anodized graphite paint finish for enhanced durability
- Flange mounted base for surface fixing
- IP66 loop-in, loop-out connection joint for ease of installation
- LED lifespan L70 30,000 hours
- Non-dimmable



LED Information

Total (Watts)	11W
Lumens Delivered	202lm
Lm/W	18lm
CRI	Ra 90
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C



Code	Lamp	Description
AGLEDB/700	LED	11W - Cool White 700mm

Brock LED Bollard


Supplied c/w Integral Driver and Root mounting kit



- Modern bi-directional bollard providing vivid angled light distribution
- Die-cast aluminium body with a graphite powder coated anodized paint finish for enhanced durability
- Supplied c/w root mounting kit
- LED lifespan L70 50,000 hours
- Non-dimmable



**Matching
Brock LED Wall light**
see p256



LED Information

Total (Watts)	7.7W
Lumens Delivered	
Cool White	452lm
Warm White	447lm
Lm/W	
Cool White	57lm
Warm White	56lm
CRI	Ra 80
CCT	4000K 3000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
ABRLEDB/650/CW	LED	7.7W - Cool White 650mm
ABRLEDB/650/WW	LED	7.7W - Warm White 650mm





Duet LED

Supplied c/w Integral Driver



Light distribution from the rear of the bollard



Light distribution from the front of the bollard




ADULEDB/080



ADULEDB/080/PIR

- Ultra modern bollard with die-cast aluminium body
- Powder coated anodized graphite paint finish for enhanced durability
- Flange mounted base for surface fixing
- LED lifespan L70 36,000 hours
- Non-dimmable



max 12 metres
8 seconds to 8 minutes
5 to 200 LUX

LED Information

Total (Watts)	17W
Lumens Delivered	1536lm
Lm/W	90lm
CRI	Ra 80
CCT	4000K
Input	100V-240V
Hertz	50/60Hz
Operating Temp	-20°C to 45°C

Code	Lamp	Description
ADULEDB/080	LED	17W - Cool White 800mm
ADULEDB/080/PIR	LED	17W - PIR - Cool White 800mm





Project - Private Residential
Bath, UK



Project - Public Walkway
Essex, UK



Taurus LED

Supplied c/w Integral Driver



331

- Robust die-cast aluminium bollard with a textured graphite finish
- Die-cast aluminium head with polycarbonate lens
- Comparable performance to 70W HQI
- Integral emergency option
- Supplied c/w root mounting kit
- LED lifespan L70 50,000 hours
- Non-dimmable



Emergency Operation

LED Information

Total (Watts)	26W
Lumens Delivered	1379lm
Lm/W	53lm
CRI	Ra 70
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-25°C to 50°C



Code	Lamp	Description
ATALEDB/1000	LED	26W - Cool White 1000mm

Option	/M3	Emergency
--------	-----	-----------

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Leo CCT LED Polycarbonate Bollard

Supplied c/w Integral Driver



Powered by
TRIDONIC
▼ enlightening your ideas

- Modern styled bollard with polycarbonate construction
- White reflector with clear polycarbonate diffuser
- Polycarbonate construction is ideal for coastal applications
- Suitable for domestic and commercial applications
- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- CCT selectable between 3000K and 4000K
- LED lifespan L70 61,000 hours
- Non-dimmable




ALEOLED/CCT/045/GR



ALEOLED/CCT/075/GR



ALEOLED/CCT/100/GR



LED Information

Total (Watts)	8W	
	13W	
	13W	
Lumens Delivered	4000K	3000K
8W	592lm	533lm
13W	922lm	880lm
13W	922lm	880lm
Lm/W		
8W	74lm	67lm
13W	77lm	73lm
13W	77lm	73lm
CRI	Ra 80	
CCT	3000K	
	4000K	
Input	230V	
Hertz	50/60Hz	
Operating Temp	-10°C to 40°C	

Code	Lamp	Description
ALEOLED/CCT/045/GR	LED	8W - Warm White/Cool White 450mm
ALEOLED/CCT/075/GR	LED	13W - Warm White/Cool White 750mm
ALEOLED/CCT/100/GR	LED	13W - Warm White/Cool White 1000mm



Monza

Supplied Less Lamp



AME27045/BL




AME27075/BL



AME27100/BL


- Die-cast extruded aluminium bollard with external louvred head
- Textured black powder coat finish
- Suitable for commercial and domestic applications



Code	Lamp	Description
AME27045/BL	E27	100W 450mm
AME27075/BL	E27	100W 750mm
AME27100/BL	E27	100W 1000mm



Accessories ARMK3

Root Mounting Kit





- High Grade AISI 316L stainless steel bollard
- External louvred head and opal polycarbonate diffuser
- Suitable for commercial and domestic applications



AME27045/SS



AME27075/SS



AME27100/SS



Code	Lamp	Description
AME27045/SS	E27	75W 450mm
AME27075/SS	E27	75W 750mm
AME27100/SS	E27	75W 1000mm

Accessories ARMK3 Root Mounting Kit



Aquila

Supplied Less Lamp



336



AAE27045/BL




AAE27075/BL



AAE27100/BL

- Die-cast aluminium bollard with four pillars and opal polycarbonate diffuser
- Textured black powder coat finish
- Suitable for commercial and domestic applications



Code	Lamp	Description
AAE27045/BL	E27	75W 450mm
AAE27075/BL	E27	75W 750mm
AAE27100/BL	E27	75W 1000mm

Accessories ARMK3


Root Mounting Kit

E27 Options		
100W	23W 53	20W 53
165	165	165
Maximum size and wattage		





- Die-cast aluminium bollard with polycarbonate diffuser
- Internal stainless steel louvre
- Detachable head for easy access to lamp housing
- Suitable for surface mounting
- Supplied with root mounting kit



E27 Options		
100 W	23W	20W
130	53	53
130	130	130
Maximum size and wattage		



Code	Lamp	Description
ALIB/100E27	E27	100W 1000mm

Orno LED Portable Lantern

Supplied c/w DC Adaptor




AORNLed/PL1
White LED




AORNLed/PL2

- Modern portable lantern range suitable for domestic applications
- Anodised powder coated die-cast frame construction, c/w polycarbonate enclosure for enhanced durability
- Chargeable USB battery power ensures no installation or maintenance is required
- Integrated bluetooth speaker allows pairing with smart device for audio playback (AORNLED/PL2 Only)
- A selection of light outputs can be selectable via an external touch pad (AORNLED/PL1 Only)
- USB 2.0 output allows a smartphone to be charged from the fitting
- Up to 6 hours of battery life
- LED lifespan L70 36,000 hours



AORNLed/PL1



AORNLed/PL2

LED Information

Total (Watts)	5W
Lumens Delivered	353lm
Lm/W	71lm
CRI	Ra 80
CCT	4000K
Input	3.7VDC
Operating Temp	-20°C to 45°C

Code	Lamp	Description
AORNLed/PL1	LED	5W - Small/Cool White
AORNLed/PL2	LED	6W - Large/Cool White




Project - Private Residential
Congleton, UK




Rondo HP AC LED Surface/Spike Light

No Driver Required



341

- High performance LED feature light
- Suitable for surface or spike mounting (spike accessory included)
- No driver required
- 60° beam angle
- Die-cast aluminium construction with textured graphite paint finish
- Pre-wired with 2 metres of H07RN-F cable
- LED lifespan L70 30,000 hours
- Non-dimmable



Wall Mounting



Spike Mounting



Surface Mounting

LED Information

Total (Watts)	20W
Lumens Delivered	1200lm
Lm/W	60lm
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 40°C



Code	Lamp	Description
AROLEDSSS	LED	20W - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750






Project - Southport Flower Show
Southport, UK


Meteor LED Submersible

Supplied Less Driver



343

- Surface or submersible spot for external applications
- 316L stainless steel construction housing with adjustable head
- Pre-wired with 3 metres of rubber insulated cable
- Submersible to a depth of up to 3 metres
- LED lifespan
L70 50,000 hours



LED Information

Total (Watts)	6W
Lumens Delivered	547lm
Lm/W	91lm
CRI	Ra 75
CCT	4000K
Input	350mA
Operating Temp	-20°C to 40°C



	Code	Lamp	Description
	AMETLED	LED	6W - Cool White
Accessories	AD9W/350	9W 350mA LED Driver	
	ADK20W/350	20W 350mA LED Driver	
	AMCD25W	0-15W Multicurrent Driver	
	AMCD50W	0-20W Multicurrent Driver	

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Flora GU10 LED



Supplied Less Lamp



Wall Mounting

Spike Fixing

- Dual purpose garden spotlight supplied with wall mounting bracket and spike
- Manufactured from 100% recyclable materials
- Pre-wired with 2 metres of rubber insulated cable
- Suitable for GU10 LED lamps only as detailed




Code	Lamp	Description
AFGS/GU10LED	LED	5W LED GU10




Subra LED Inground Uplight

Supplied Less Driver



345

- Small recessed LED marker ground light for a variety of internal and external applications
- 316L stainless steel bezel and housing
- Pre-wired with 2 metres of rubber insulated cable
- Submersible to a depth of up to 2 metres
- LED lifespan
L70 56,000 hours lifetime



LED Information

Total (Watts)	1W
Lumens Delivered	
Cool White	35lm
Warm White	35lm
Lm/W Cool White	35lm
Lm/W Warm White	35lm
CRI Cool White	Ra 75
CRI Warm White	Ra 80
CCT Cool White	6000K
CCT Warm White	3000K
Input	12V/24V
Operating Temp	-20°C to 45°C



ASUWOLED/CW



ASUWOLED/WW

Code	Lamp	Description
ASUWOLED/CW	LED	1W - Cool White
ASUWOLED/WW	LED	1W - Warm White

Accessories	ADK15W/24V	15W 24V LED Driver
	ADK60W/24V	60W 24V LED Driver
	AMCD25W	10 - 20W Multicurrent LED Driver



Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Turlock LED Inground Uplight


Supplied c/w Integral Driver



Powered by



- Powerful compact LED inground uplight
- Exceeds performance of 50W Halogen
- Die-cast aluminium construction with 316L stainless steel top frame
- Static load test to 2000kg
- Supplied c/w installation housing for additional protection and ease of installation
- Pre-wired with 1 metre of rubber insulated cable
- LED lifespan L70 50,000 hours



LED Information

Total (Watts)	3W
Lumens Delivered	135lm
Lm/W	45lm
Beam Angle	23°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
ATURWOLED/70	LED	3W - Cool White





Project - Private Residential
Abersoch, UK

Turlock LED Inground Uplight



Supplied c/w Integral Driver



Powered by



- Powerful compact LED inground uplight
- Exceeds performance of 35W CDM-T
- Static load test to 2000kg
- Supplied c/w installation housing for additional protection and ease of installation
- Die-cast aluminium construction with 316L stainless steel top frame
- Pre-wired with 1 metre of rubber insulated cable
- LED lifespan L70 50,000 hours



LED Information


Total (Watts)	4W
Lumens Delivered	390lm
Lm/W	97lm
Beam Angle	21°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
ATURWOLED/95	LED	4W - Cool White



Turlock LED Inground Uplight

Supplied c/w Integral Driver




349

- High performance LED inground uplight
- Exceeds performance of 70W CDM-T
- Static load test to 2000kg
- Supplied c/w installation housing for additional protection and ease of installation
- Die-cast aluminium construction with 316L stainless steel top frame
- Pre-wired with 1 metre of rubber insulated cable
- LED lifespan L70 50,000 hours

Powered by

HEP



LED Information

Total (Watts)	8W
Lumens Delivered	884lm
Lm/W	110lm
Beam Angle	18°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C



Code	Lamp	Description
ATURWOLED/175	LED	8W - Cool White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750



Turlock LED Inground Uplight

Supplied c/w Integral Driver





Powered by

HEP



- High performance inground uplight
- Exceeds performance of 70W CDM-T
- Static load test to 2000kg
- Supplied c/w installation housing for additional protection and ease of installation
- Die-cast aluminium construction with 316L stainless steel top frame
- Pre-wired with 1 metre of rubber insulated cable
- LED lifespan L70 50,000 hours



LED Information

Total (Watts)	19W
Lumens Delivered	2214lm
Lm/W	116lm
Beam Angle	20°
CRI	Ra 80
CCT	4000K
Input	230V
Hertz	50/60Hz
Operating Temp	-20°C to 25°C

Code	Lamp	Description
ATURWOLED/230	LED	19W - Cool White





Fresno LED Adjustable Inground Uplight

Supplied c/w Integral Driver



351

- High performance LED adjustable inground uplight
- Exceeds performance of 35W CDM-T
- 304L stainless steel bezel and powder coated aluminium housing
- Supplied c/w installation housing for additional protection and ease of installation
- Integral driver and pre-wired with 2 metres of rubber insulated cable
- Static load test to 2000kg and therefore suitable for vehicular and pedestrian traffic
- LED lifespan L70 50,000 hours
- Non-dimmable



LED Information

Total (Watts)	19W
Lumens Delivered	998lm
Lm/W	53lm
Beam Angle	11°
CRI	Ra 80
CCT	3000K
Input	230V
Hertz	50Hz
Operating Temp	-20°C to 40°C



Code	Lamp	Description
AFRWOLED/220	LED	19W - Warm White

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750






GU10/MR16 Inground Uplight


Supplied Less Lamp



- Supplied with both MR16 and GU10 lampholders
- Compact inground uplight which accepts 12V and mains halogen, CFL and LED lamps
- Housing in die-cast aluminium with clear toughened glass diffuser of 10mm thickness
- 316 stainless steel top ring and stainless steel allen key screws
- Suitable for light vehicular traffic with a static impact resistance of up to 2000kgs
- Supplied with recessed sleeve in high resistant thermoplastic




With Sleeve



Without Sleeve

Caution: surface glass temperature will get very hot under normal halogen operation. It is recommended to use GU10 LED lamps for cooler operation.

Code	Lamp	Description
AWO50	GU10/MR16	50W




GU10 Adjustable Inground Uplight

Supplied Less Lamp



353

- Die-cast aluminium housing with a clear toughened glass diffuser of 8mm thickness
- 304 stainless steel top ring and stainless steel allen key screws
- Adjustable lampholder to allow up to 15° vertical inclination of lamp
- Suitable for pedestrian traffic with a static impact resistance of up to 1000kgs



Caution: surface glass temperature will get very hot under normal halogen operation. It is recommended to use GU10 LED lamps for cooler operation.



Code	Lamp	Description
AWO/GU10	GU10	50W

Warrington: +44 (0) 1942 433333
Belfast: +44 (0) 2890 773750

