




COLLINGWOOD  
LIGHTING



NEW

## FEATURES & BENEFITS

- ±20° adjustable 5W downlight to adjust direction of light
- 110lm/W+
- Slimline twist & lock bezels (sold separately)
- Shallow depth of 50mm
- Life of LED: 70,000hrs (L70, B10)
- Insulation coverable
- Uses single point source technology to replicate traditional halogen look
- Flexible driver position for easy installation



## H4 Pro 550 SPS

±20° adjustable, single point source, dimmable, fire-rated LED downlight



Suitable for use in bathrooms



Push-fit terminal connector included



Insulation coverable



High efficacy



7-year extended warranty available



\* IP65 (front) / IP20 (back) | \* Ceiling only | Patent information: [collingwoodlighting.com/patent](http://collingwoodlighting.com/patent)

ZONE

L70, B10

3SDCM

### PHOTOMETRICS @ 25°C

Colour	Product code	CRI	lm	lm/W	lx at 1m
4000K 55°	DLT4365540	>80Ra	560	112	516
3000K 55°	DLT4365530	>80Ra	550	110	506

### EMERGENCY PACK SERVICE OPTION

Approx. 25% light output compared to normal running. Refer to LEDEP06 specification sheet for more information.

For 3hr emergency pack service option suffix partcode with **EM**. eg. DLT4365540 becomes DLT4365540**EM**

### GENERAL

Building regulations	Part B (fire protection), C (moisture protection), E (acoustic protection), P (electrical safety) and L (conservation of energy - 2014 regulations)
Construction material	Mild steel / PC V0 Rated
Flicker free	Yes
Inrush current	1.2A 0.03ms
Maximum ceiling thickness	40mm

### WIRING


Cable / flying lead	0.15m (Class II)
Cable required for 'T' connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm <sup>2</sup> ) or 3-core cable (R02V 3x1.5mm <sup>2</sup> )
Type of wiring required	Parallel (mains) 220-240V AC 50/60Hz

### LED DRIVERS

Product code	Input voltage	Input current	Power factor	Dimming	Bathroom zone
N/A (integrated SELV driver)	220-240V	25mA	>0.86	Yes (mains)	1 (ceiling only)

### ACCESSORIES

Product code	Description	
H4 Pro range bezels	Round H4 Pro bezel options	73
DLCONVERT70	Converter plate	81
DM298GRID	LED mains grid dimmer	82
DM298FP	Faceplate dimmer	82



### 4000K 55°

Additional diagrams available at [collingwoodlighting.com](http://collingwoodlighting.com)

