



COLLINGWOOD LIGHTING

FEATURES & BENEFITS

- > Easy to install compared to halogen
- > Runs cool no need for a fan







FIBRE LED LIGHT Fibre optic LED light injector























L70. B10

Patent information: collingwoodlighting.com/patent	
DUOTON AFTENOC 8 25°C	

PHOTOMETRICS						
Colour	\triangle	Product code	CRI	lm	lm/W	lx at 1m
4000K	-	FIBRE LED LIGHT NW	>80Ra	-	-	-

GENERAL	
Construction material	Aluminium

WIRING	
Cable / flying lead	1m (0.205mm² red & black PTFE)
Type of wiring required	Series

LED DRIVERS Bathroom zone applicable to fitting only						
Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	350	Yes	No	2	1	9
PLR/350 1-5	350	Yes	No	1	1	5
PLD UNI-DRIVE 350MA	350	Yes	Yes (1-10V)	2	1	10

		For LED driver bathroom zone & additional LED drivers see page 288
ACCESSORIES		
Product code	Description	
FIBRE LED 1/30	Fibre optic strands	93
FIBRE LED 2/30	Fibre optic strands	93
UY2 CONNECTOR	Quick waterproof connector	280
DM298GRID	LED mains grid dimmer	82
DM298FP	Faceplate dimmer	82



