



COLLINGWOOD
LIGHTING

GL063



GL064



FEATURES & BENEFITS

- › Cast stainless steel for aged effect
- › Raised profile sending light in three or four directions



GL063 | GL064

3-way LED marker light | 4-way LED marker light

IP67

Protected against temporary immersion

7

7-year extended warranty available

4W

GL063

5W

GL064

Ø55

Patent information: collingwoodlighting.com/patent

37°C

IK10

1/35°C

1.1kg

1

ZONE

70,000h

L70, B10

35DCM

PHOTOMETRICS @ 25°C

Colour		Product code	CRI	lm	lm/W	lx at 1m
3000K	-	GL063	>80Ra	45	11	9
-	-	GL064	>80Ra	65	13	9

GENERAL

Construction material: Cast stainless steel (316)

Drive over / walk over: No

WIRING

Cable / flying lead: 1m (H05RN-F) rubberised cable (outside diameter: 6mm)

Type of wiring required: Series

LED DRIVERS


Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	350	Yes	No	1	1	3 / 2
PLR/350 1-5	350	Yes	No	1	1	1
PLD UNI-DRIVE 350MA	350	Yes	Yes (1-10V)	2	1	3 / 2

For LED driver bathroom zone & additional LED drivers see page 264

ACCESSORIES

Product code	Description	
JB2 / JB4 / JB6	IP68 waterproof connectors	280-281
TUBE/68	Installation tube	124
WCR 275 BLACK	2-core rubber cable	281



GL063 3000K C0/C180 / 3000K C90/C270
Additional diagrams available at collingwoodlighting.com

