



COLLINGWOOD  
LIGHTING



## FEATURES & BENEFITS

- Robust cable for outdoor use
- Shallow depth for easy installation

## GL016 F | GL016 SQ

1W LED ground light | Square 1W LED ground light



Submersible  
to 9m



7-year extended  
warranty available



Also available in RGBW (GL016)  
See page 247



Patent information: [collingwoodlighting.com/patent](http://collingwoodlighting.com/patent)

ZONE

L70, B10

3SDCM

### PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
4000K	26°	GL016 F NW	>70Ra	95	95	267
	26°	GL016 SQ NW	>70Ra	95	95	267
3000K	26°	GL016 F WW	>80Ra	75	75	210
	26°	GL016 SQ WW	>80Ra	75	75	210
Amber	26°	GL016 F AMBER	-	-	-	-
Blue	26°	GL016 F BLUE	-	-	-	-
	26°	GL016 SQ BLUE	-	-	-	-
Green	26°	GL016 F GREEN	-	-	-	-
Red	26°	GL016 F RED	-	-	-	-

### GENERAL

Construction material	Stainless steel (316)
Drive over / walk over	Walk over (5mm toughened glass)

### WIRING

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

### LED DRIVERS


Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	350	Yes	No	1	1	9
PLR/350 1-5	350	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	350	Yes	Yes (1-10V)	2	1	10

For LED driver bathroom zone & additional LED drivers see page 264

### ACCESSORIES

Product code	Description	
JB2 / JB4 / JB6	IP68 waterproof connectors	280-281
TUBE/50	Installation tube	124
WCR 275 BLACK	2-core rubber cable	281
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	280



4000K 26°

Additional diagrams available at [collingwoodlighting.com](http://collingwoodlighting.com)

