



COLLINGWOOD
LIGHTING

GL021

GL022



GL021 | GL022

30° slotted LED ground light | Square 30° slotted LED ground light

IP68

Submersible
to 9m

7-year extended
warranty available

7-year extended
warranty available

30°

1W

Ø50

37°C

IK07

≤35°C

400g

0

70,000h

3SDCM

Patent information: collingwoodlighting.com/patent

ZONE

L70, B10

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
4000K	30°	GL021 NW	>70Ra	10	10	10
	30°	GL022 NW	>70Ra	10	10	10
3000K	30°	GL021 WW	>80Ra	8	8	8
	30°	GL022 WW	>80Ra	8	8	8
Blue	30°	GL021 BLUE	-	-	-	-
	30°	GL022 BLUE	-	-	-	-

GENERAL

Construction material Stainless steel [316]

Drive over / walk over Walk over

WIRING

Cable / flying lead 1m (H05RN-F) rubberised cable (outside diameter: 6mm)

Type of wiring required Series

LED DRIVERS

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	350	Yes	No	1	1	9
PLR/350 1-5	350	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	350	Yes	Yes (1-10V)	2	1	10


For LED driver bathroom zone & additional LED drivers see page 264

ACCESSORIES

Product code	Description	
JB2 / JB4 / JB6	IP68 waterproof connectors	280-281
TUBE/50	Installation tube	124
WCR 275 BLACK	2-core rubber cable	281
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	280

FEATURES & BENEFITS

- › Angled light ideal for use as a step light
- › Cast Stainless steel for aged effect (GL022)
- › Robust cable for outdoor use



3000K C0/C180 / 3000K C90/C270

Additional diagrams available at collingwoodlighting.com

