



## GL018 T

Small panel mount LED marker light

IP68

Submersible  
to 9m

1 yr

1-year guarantee



Patent information: [collingwoodlighting.com/patent](http://collingwoodlighting.com/patent)

ZONE

35DCM

### PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
4000K	120°	GL018 T NW	>70Ra	3	6	1
Blue	120°	GL018 T BLUE	-	-	-	-

### GENERAL

Construction material	Stainless steel (316)
Drive over / walk over	Walk over (5mm toughened glass)

### WIRING

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Parallel

### LED DRIVERS

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PS1524	-	Yes	Yes (PDCINT1-10V)	0 (1 when dimming)	1	30
PS5024	-	Yes	Yes (PDCINT1-10V)	0 (1 when dimming)	1	100
PSDIP10024	-	Yes	Yes (1-10V)	0 (1 when dimming)	1	200


For LED driver bathroom zone & additional LED drivers see page 264

### ACCESSORIES

Product code	Description	
JB1 / JB5 / JB6	IP68 waterproof connectors	280-281
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	280
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers	272

## FEATURES & BENEFITS

- › Frosted effect for softer tone of light
- › Incorporated thread and nut for secure fitting into panels, walls or ceilings
- › Robust cable for outdoor use



### 4000K 120°

Additional diagrams available at [collingwoodlighting.com](http://collingwoodlighting.com)

