



COLLINGWOOD
LIGHTING



FEATURES & BENEFITS

- › Bespoke wall plug for easy installation
- › Quality brushed aluminium finish
- › Requires 20mm drill

MC020 S

Up / down mini cuboid LED wall light



Suitable for use outdoors



7-year extended warranty available



2W



1/35°C



ZONE



L70, B10



350CM

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
4000K	12°	MC020 S NW	>70Ra	140	70	1485
3000K	12°	MC020 S WW	>80Ra	110	55	1466
Amber	12°	MC020 S AMBER	-	-	-	-
Blue	12°	MC020 S BLUE	-	-	-	-
Green	12°	MC020 S GREEN	-	-	-	-
Red	12°	MC020 S RED	-	-	-	-

GENERAL

Construction material Anodised aluminium

WIRING

Cable / flying lead 0.15m (0.205mm² red & black PTFE)

Type of wiring required Series

LED DRIVERS


Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	350	Yes	No	1	1	4
PLR/350 1-5	350	Yes	No	1	1	2
PLD UNI-DRIVE 350MA	350	Yes	Yes (1-10V)	2	1	5

For LED driver bathroom zone & additional LED drivers see page 264

ACCESSORIES

Product code	Description	
CR135	PTFE cable	281
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	280
UY2 CONNECTOR	Quick waterproof connector	280



4000K 12°

Additional diagrams available at collingwoodlighting.com

