



ML03

Mini halo LED wall light

IP65

Suitable for use outdoors

7-year extended warranty available

1W

Ø26

36°C

30°C

50g

1

70,000h

Patent information: collingwoodlighting.com/patent

ZONE

L70, B10

3SDCM

PHOTOMETRICS @ 25°C

Colour		Product code	CRI	lm	lm/W	lx at 1m
4000K	-	ML03 NW	>70Ra	40	40	4
3000K	-	ML03 WW	>80Ra	28	28	3
Amber	-	ML03 AMBER	-	-	-	-
Blue	-	ML03 BLUE	-	-	-	-
Green	-	ML03 GREEN	-	-	-	-
Red	-	ML03 RED	-	-	-	-

GENERAL

Construction material Anodised aluminium

WIRING

Cable / flying lead 1m (0,205mm² red & black PTFE)

Type of wiring required Series

LED DRIVERS

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	350	Yes	No	1	1	9
PLR/350 1-5	350	Yes	No	1	1	5
PLD UNI-DRIVE 350MA	350	Yes	Yes (1-10V)	2	1	10


For LED driver bathroom zone & additional LED drivers see page 264

ACCESSORIES

Product code	Description	
CR135	PTFE cable	281
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	280
UY2 CONNECTOR	Quick waterproof connector	280

FEATURES & BENEFITS

- Low glare, suitable for stair lighting
- Small & discreet for decorative effect



4000K

Additional diagrams available at collingwoodlighting.com

