



BOL255

585mm straight to mains anodised aluminium LED bollard

IP65

Ideal for use outdoors

7-year

extended warranty available

55°

16.5W

240V

35°C

IK10

1.40°C

6.1kg

70,000h

L70, B50

35DCM

FEATURES & BENEFITS

- › Modular design for simple installation
- › Low glare
- › Root-mount or surface-mount
- › 360° illumination, ideal for pathways, boundary marking, or general illumination of public spaces
- › Surface-mount bracket and fixtures are included

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
3000K	55°	BOL255WW	>85Ra	750	45	53

GENERAL

Building regulations	Part P (electrical safety)
Construction material	Anodised aluminium / polycarbonate
Inrush current	38.8A 0.002ms

WIRING


Cable / flying lead	1.5m H05RN-F 3G 0.75mm² 7mm outside
Type of wiring required	Parallel (mains) 220 - 240V AC 50/60Hz

LED DRIVERS

Product code	mA	Dimming	Bathroom zone	Min	Max
N/A (Integrated SELV driver)	-	No	-	-	-

ACCESSORIES

Product code	Description	
BOL255RM	Root mounting kit	231
JB5	Gel filled junction box	281



3000K 55°

Additional diagrams available at collingwoodlighting.com

