



GL007RGBW

Drive over, colour change LED ground light with white LED (12W max.)



Protected against temporary immersion



3-year extended warranty available



Patent information: collingwoodlighting.com/patent

ZONE

L50, B50

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	W	CRI	lm	lm/W	lx at 1m
4000K	36°	GL007RGBW	3.3	>80Ra	180	55	782
Red	36°		2.4	-	131	55	539
Green	36°		3.3	-	208	63	944
Blue	36°		3.3	-	34	10	15

GENERAL

Construction material	Stainless steel 304 (cover ring only) / aluminium (body)
Drive over / walk over	Drive over, 10mm tempered glass (15mph max), static load 2000kg / 20KN

WIRING

Cable / flying lead	2x 3m CR575RGBW (outside diameter: 7.4mm)
Type of wiring required	Series

LED DRIVERS (power repeaters)

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PR3011	350	-	Yes	1	1	2

For LED driver bathroom zone & additional LED drivers see page 264


ACCESSORIES

For complete range of colour change controllers see page 236-241

Product code	Description	
Installation tube included		
JB7	5-pole IP68 inline connector	281
CR575RGBW	5-core PVC cable	263

FEATURES & BENEFITS

- Adjustable LED fitting to $\pm 20^\circ$
- Installation tube included
- 10mm toughened glass, ideal for use in driveways
- Full RGBW colour range
- Separate white LED for permanent use
- Compatible with a large range of controllers



4000K 36°

Additional diagrams available at collingwoodlighting.com

