



FEATURES & **BENEFITS**

- > Complete with wall fixings for easy installation
- > Full RGB colour range
- > Anodised aluminium for use in outdoor and indoor environments















Patent	informatio	n. colling	woodlightir	an com	/nato	m

PHOTOMETRICS	S @ 25°C	LED RGB units a	LED RGB units are designed for colour change. They are not suitable for running on permanent white for long periods of time				
Colour	A	Product code	W	CRI	lm	lm/W	lx at 1m
Red	45°	1	2.4	-	65	27	41
Green	45°	- WL075CARGB	3.7	-	99	27	137
DI	/ = 0		2.7		21	0	1/

GENERAL						
Construction material	Anodise	d aluminium				
WIRING						
Cable / flying lead	2x 1m 4	-core ribbon o	able			
Type of wiring required	Series (Plug & Play)					
	NB: Remov	al of plugs will rend	er this product non-return	nable		
LED DRIVERS (power repeaters)				Ba	throom zone app	licable to fitting only
LED DRIVERS (power repeaters) Product code	mA	SELV	Dimming	Bathroom zone	throom zone app	licable to fitting only
	mA 350	SELV -	Dimming Yes			
Product code		SELV -			Min 1	Max 2
Product code		SELV -		Bathroom zone	Min 1 additional LED o	Max 2 Irivers see page 264
Product code PR3011		-		Bathroom zone 1 For LED driver bathroom zone &	Min 1 additional LED o	Max 2 Irivers see page 264







