



UL345CARGB110° colour change LED wall washing light bar (12W max.)

(110°)

GENERAL













Z	0	N	E

PHOTOMETRICS	S @ 25°C	LED RGB units a	are designed for colour o	hange. They are n	not suitable for running	on permanent white	for long periods of time
Colour	A	Product code	W	CRI	lm	lm/W	lx at 1m
Red	110°	1	4	-	96	24	20
Green	110°	- UL345CARGB	4.1	-	161	39	58
Blue	110°		4.3	-	51	12	0

Colour	A	Product code	W	CRI	lm	lm/W	lx at 1m
Red	110°	1	4	-	96	24	20
Green	110°	- UL345CARGB	4.1	-	161	39	58
Blue	110°		4.3	-	51	12	0

Construction material	Anodised aluminium
WIRING	
Cable / flying lead	1x 3m LED RGB 0.75mm² cable (outside diameter: 6mm)
Type of wiring required	N/A (1 per power repeater)

LED DRIVERS (power repeaters) Bathroom zone applicable to fitting					icable to fitting only	
Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PR3011	350	-	Yes	1	1	1

ACCESSORIES	For complete range of colour chang	ge controllers see page 236-241
Product code	Description	
JB3	Colour change extension lead for RGB products	280
LED RGB 0.75 CABLE	4-core PVC cable	263
ULBRACKET	2 piece black anodised aluminium bracket	215

FEATURES & BENEFITS

- > Surface mount in multiple applications
- > Full RGB colour range
- > Compatible with a large range of controllers
- > Anodised aluminium for use in outdoor and indoor environments
- > Removable feet can be used anywhere along the base or sides. Allen key included







