



UL010RGBW

Colour change LED light with white LED (5W max.)



RGBW



Protected against temporary immersion



5-year extended warranty available



Patent information: collingwoodlighting.com/patent

PHOTOMETRICS @ 25°C

Colour	Beam angle	Product code	W	CRI	lm	lm/W	lx at 1m
4000K	40°	UL010RGBW	1.1	>80Ra	50	45	101
Red	40°		1	-	38	38	75
Green	40°		1.1	-	63	57	124
Blue	40°		1.1	-	11	8	17

GENERAL

Construction material Stainless steel (316)

WIRING

Cable / flying lead 2x 1m CR575RGBW (outside diameter: 7.4mm)

Type of wiring required Series

LED DRIVERS (power repeaters)

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PR3011	350	-	Yes	1	1	6

For LED driver bathroom zone & additional LED drivers see page 264


ACCESSORIES

For complete range of colour change controllers see page 236-241

Product code	Description	
JB7	5-pole IP68 inline connector	281
CR575RGBW	5-core PVC cable	263

FEATURES & BENEFITS

- Complete with wall fixings for easy installation
- Can rotate and be angled to direct light
- Separate white LED for permanent use
- Full RGBW colour range
- Compatible with a large range of controllers
- Marine grade stainless steel for use in outdoor and indoor environments



4000K 40°

Additional diagrams available at collingwoodlighting.com

