





FEATURES & BENEFITS

- > MR16 for retrofit into existing housings
- > Plug & Play connectors for quick
- > Short heatsink for shallow housings
- > Full RGB colour range
- > Compatible with a large range of controllers









LL030CARGBColour change LED unit (4W max.)



(18°)















HOLICING DEDENDANT	

HOUSING DEPENDANT	

PHOTOMETRICS @ 25°C LED RGB units are designed for colour change. They are not suitable for running on						g on permanent white t	for long periods of time
Colour	\triangle	Product code	W	CRI	lm	lm/W	lx at 1m
Red	18°	1	1	-	38	38	319
Green	18°	- LL030CARGB	1.2	-	75	63	774
Blue	18°		1.2	-	11	9	9

GENERAL						
Construction material	Alumin	ium				
WIRING						
Cable / flying lead	2x 1m Plug & Play 4-core ribbon cable					
Type of wiring required	Series (Plug & Play)					
	NB: Remo	val of plugs will ren	der this product non-retu	mable		
LED DRIVERS (power repeaters)						
Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PR3011	350	-	Yes	-	1	6
				For LED driver bathroom zone &	k additional LED o	drivers see page 20
ACCESSORIES				For complete range of colour	change controlle	rs see page 236-2 4
Product code	Description					
LED 3 RGB EXT	Colour	Colour change Plug & Play 1m extension lead 262				



