

Rhapsody LED 500 x 500

Designed, Developed & Manufactured in the UK



Colour Finish



White
R5/W

LED Types

- LED 3000.
- LED 4500.

Materials


- Body: Steel in white RAL9016.
- Diffuser: Premium opal polycarbonate.

Installation

- Suitable for draw up and lay-in applications making it versatile for a number of ceiling systems including:
 - Exposed 'T'.
 - Concealed fix.
 - Some metal pan ceilings.
- Plug & Play options.

Standards


- IP20.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.
- TPA Rated.



Size

Length	497mm
Width	497mm
Depth	110mm

R5/WL4LED3000



Code	Colour	Diffuser	Colour Temp.	System Power	Delivered Lumens	Efficacy
R5/WL4LED3000	White	Premium Opal	4000 K	29.6 W	2407 lm	81 lm/W
R5/WL4LED4500	White	Premium Opal	4000 K	34 W	2980 lm	88 lm/W

Code options (add suffix to code)



3 Hour Maintained Emergency
M (270 lm)



DALI / DSI Dim
-DDD



e-Motion™ Microwave Slave Dim
-CF



Analogue Dim
-DA



Self-Test Emergency
Prefix R5ST/ Suffix M