

# Rhapsody PLUS

Designed, Developed & Manufactured in the UK



## Colour Finish



White  
R6M/W

## LED Types

- LED 3000.
- LED 4500.
- LED 6000.

## Materials


- Body: 100% moulded polycarbonate in RAL 9016.
  - Seamless edges.
  - Perfect corners.
- Gear tray: Steel.
- Diffuser: Premium opal diffuser for visual comfort.
  - Building Reg Compliant Part B.

## Installation

- Suitable for lay-in applications making it versatile for a number of ceiling systems including T 15 / 24.
- Prepared aperture cut to size.
- Plug & Play options.

## Standards


- IP20.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.




## Size

Length	595mm
Width	595mm
Depth	118mm


R6M/WL4LED3000



R6M/WL4LED4500



R6M/WL4LED6000



Code	Colour	Diffuser	Colour Temp.	System Power	Delivered Lumens	Efficacy
R6M/WL4LED3000	White	Premium Opal	4000 K	28.5 W	2772 lm	97 lm/W
R6M/WL4LED4500	White	Premium Opal	4000 K	41 W	3984 lm	97 lm/W
R6M/WL4LED6000	White	Premium Opal	4000 K	50 W	5354 lm	107 lm/W

Code options (add suffix to code)

3 Hour Maintained Emergency  
**M** (265 - 310 lm)

DALI / DSI Dim  
**-DDD**

e-Motion™ Microwave Slave Dim  
**-CF**

Analogue Dim  
**-DA**

Self-Test Emergency  
Prefix **R6MST/** Suffix **M**

Microwave On/Off  
**-9**

e-Motion™ Microwave Master Dim  
**-CFP**

Wireless Control  
**-BT**