

# ZIP LED Downlight

Designed, Developed &  
Manufactured in the UK



### Colour Finish



White  
ZIPM/**W**

### LED Types

- LED 1000.
- LED 2000.
- LED 3000.

### Materials


- Housing material - polycarbonate.

### Installation

- Recessed mounted down light, with ZIP adjustable fixing clip suitable for ceiling systems.
- Fast Fit - Push & Twist.

### Standards


- IP44.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.




### Size

|                |       |
|----------------|-------|
| Diameter       | 236mm |
| Depth          | 91mm  |
| Ø210mm cut out |       |


ZIPM/WL4LED1000



ZIPM/WL4LED2000



ZIPM/WL4LED3000



| Code            | Colour | Diffuser     | Colour Temp. | System Power | Delivered Lumens | Efficacy  |
|-----------------|--------|--------------|--------------|--------------|------------------|-----------|
| ZIPM/WL4LED1000 | White  | Premium Opal | 4000 K       | 16.2 W       | 1389 lm          | 85.7 lm/W |
| ZIPM/WL4LED2000 | White  | Premium Opal | 4000 K       | 21.3 W       | 1886 lm          | 88.5 lm/W |
| ZIPM/WL4LED3000 | White  | Premium Opal | 4000 K       | 28.7 W       | 2495 lm          | 86.9 lm/W |

Code options (add suffix to code)



3 Hour Maintained Emergency  
**M** (255 lm)



e-Motion™ Microwave Master Dim  
**-CFP**  
Subject to compatible ceiling type.



DALI / DSI Dim  
**-DDD**



Self-Test Emergency  
Prefix **ZIPMST**/ Suffix **M**



Switch Dim  
**-DD**



e-Motion™ Microwave Slave Dim  
**-CFS**