

ZIP LED Downlight Drop Ring

Designed, Developed &
Manufactured in the UK



Colour Finish



White
ZIPM/**W**

LED Types

- LED 1000.
- LED 2000.
- LED 3000.

Materials


- Housing material - polycarbonate.

Installation

- Recessed mounted down light, with ZIP adjustable fixing clip suitable for ceiling systems.
- Fast Fit - Push & Twist.

Standards

- IP44.
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.




Size

Diameter 239mm


Depth 109mm

Ø210mm cut out


ZIPM/WLD4LED1000



ZIPM/WLD4LED2000



ZIPM/WLD4LED3000



Code	Colour	Diffuser	Colour Temp.	System Power	Delivered Lumens	Efficacy
ZIPM/WLD4LED1000	White	Premium Opal / Drop Ring	4000 K	16.3 W	1348 lm	82.6 lm/W
ZIPM/WLD4LED2000	White	Premium Opal / Drop Ring	4000 K	19.8 W	1746 lm	88.1 lm/W
ZIPM/WLD4LED3000	White	Premium Opal / Drop Ring	4000 K	28.1 W	2396 lm	85.2 lm/W

Code options (add suffix to code)



3 Hour Maintained Emergency
M (235 lm)



e-Motion™ Microwave Master Dim
-CFP
Subject to compatible ceiling type.



DALI / DSI Dim
-DDD



Self-Test Emergency
Prefix **ZIPMST** / Suffix **M**



Switch Dim
-DD



e-Motion™ Microwave Slave Dim
-CFS