

Dome

Designed, Developed & Manufactured in the UK



Colour Finish



White
AD/**W**



Chrome
AD/**H**



Brass
AD/**Z**

LED Types

- LED 1800.

Materials


- Body: vandal resistant polycarbonate self-extinguishing fire properties in white / brass / chrome.
- Diffuser: snap fit vandal resistant polycarbonate with self-extinguishing fire properties.

Installation

- Ceiling mount.
- BESA fixing and rear cable entry. 3 way mains terminal block. 4 way block for emergency version.
- Quick fit clip on diffuser.

Standards


- IP20 (IP44 available as an option, add to code: B1).
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.



Size

Diameter	388mm
Depth	120mm

AD/WL4LED1800



Code	Colour	Diffuser	Colour Temp.	System Power	Delivered Lumens	Efficacy
AD/WL4LED1800	White	Premium Opal	4000 K	16.7 W	1749 lm	104 lm/W

Code options (add suffix to code)



3 Hour Maintained Emergency
M (91 lm)



e-Motion™ Microwave Master Dim
-CFP



DALI / DSI Dim
-DDD



Switch Dim
-DD



Microwave On/Off
-9



e-Motion™ Microwave Slave Dim
-CFS



Analogue Dim
-DA