

Stealth Elite Opal Diffuser

Designed, Developed &
Manufactured in the UK



Colour Finish



Black
SEL/B



Titanium
SEL/X

LED Types

- LED 2000.
- LED 3000.
- LED 4000.

Materials


- Body: Die cast aluminium (powder coated).
- Diffuser: Vandal resistant polycarbonate.

Installation

- Wall mount.
- BESA fixing and rear cable entry. 3 way mains terminal block. 4 way terminal block for photocell versions.

Standards

- IP65.
- 20 Joules of impact resistance (IK10).
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.
- 60,000 Hours LED.



Size

Width	330mm
Height	343mm
Depth	176mm

Code	Colour	Diffuser	Colour Temp.	System Power	Delivered Lumens	Efficacy
SEL/BL4LED2000	Black	Premium Opal	4000 K	21 W	1805 lm	86 lm/W
SEL/BL4LED3000	Black	Premium Opal	4000 K	29.3 W	2495 lm	85 lm/W
SEL/BL4LED4000	Black	Premium Opal	4000 K	41.2 W	3384 lm	82 lm/W

Code options (add suffix to code)



3 Hour Maintained Emergency
M (275 lm)



Photocell
C



PIR
P



Self-Test Emergency
Prefix SELST/ Suffix M