

# Horizon Eyelid

Designed, Developed & Manufactured in the UK



### Colour Finish



Black  
HR\_**/B**




White  
HR\_**/W**



Titanium  
HR\_**/X**



Satin Aluminium  
HR\_**/F**



| Size     | HR2   | HR3   |
|----------|-------|-------|
| Diameter | 283mm | 353mm |
| Depth    | 107mm | 112mm |

### LED Types

- LED 600 (HR2 only).
- LED 1800 (HR3 only).

### Materials

- Body: 283mm/353mm vandal resistant polycarbonate with self-extinguishing fire properties.
- Diffuser/Fascia Ring: Vandal resistant polycarbonate in opal with self-extinguishing fire properties.
- Diffuser 2: (353mm circular) Vandal resistant polycarbonate clear lens with self-extinguishing fire properties.
- Die cast aluminium option available (HR3 only).


### Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry. 3 way mains terminal block. 4 way terminal block for emergency versions & photocell.
- Screw down lid.
- Photocell version - external use only.
- HI-LO PIR - 100% light output, dims to 10% during periods of inactivity.
- 2 x Conduit entry points (mini version only).


### Standards

- IP65.
- 20 Joules of impact resistance (IK10).
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.

HR2/BLE4LED600



HR3/BLE4LED1800



| Code            | Size  | Colour | Diffuser     | Colour Temp. | System Power | Delivered Lumens | Efficacy  |
|-----------------|-------|--------|--------------|--------------|--------------|------------------|-----------|
| HR2/BLE4LED600  | 283mm | Black  | Premium Opal | 4000 K       | 8.2 W        | 2818 lm          | 34 lm/W   |
| HR3/BLE4LED1800 | 353mm | Black  | Premium Opal | 4000 K       | 17.8 W       | 664 lm           | 37.3 lm/W |

Code options (add suffix to code)



3 Hour Maintained Emergency  
**M**  
Excludes - HR2/BLE4LED600



Photocell  
**C**



PIR  
**P**



HI-LO PIR  
**HILO**



Anti-Tamper Screws  
**T**

Metal Base Option  
HR3**M**/