

Horizon Cage

Designed, Developed & Manufactured in the UK



Colour Finish



Black
HR3/**B**



White
HR3/**W**



Titanium
HR3/**X**



Satin Aluminium
HR3/**F**

LED Types

- LED 1800.

Materials


- Body: 353mm vandal resistant polycarbonate with self-extinguishing fire properties.
- Diffuser/Fascia Ring: Vandal resistant polycarbonate in opal with self-extinguishing fire properties.
- Diffuser 2: (353mm circular) Vandal resistant polycarbonate clear lens with self-extinguishing fire properties.
- Die cast aluminium option available (HR3 only).

Installation

- Wall or ceiling mount.
- BESA fixing and rear cable entry. 3 way mains terminal block. 4 way terminal block for emergency versions & photocell.
- Screw down lid.
- Photocell version - external use only.
- HI-LO PIR - 100% light output, dims to 10% during periods of inactivity.

Standards


- IP65.
- 20 Joules of impact resistance (IK10).
- 'F' Mark.
- CE.
- BS EN 60598.
- Class I.



Size

Diameter	353mm
Depth	116mm

HR3/BLC4LED1800



Code	Size	Colour	Diffuser	Colour Temp.	System Power	Delivered Lumens	Efficacy
HR3/BLC4LED1800	353mm	Black	Premium Opal	4000 K	179 W	10356 lm	578 lm/W

Code options (add suffix to code)



3 Hour Maintained Emergency
M



Photocell
C



PIR
P



HI-LO PIR
HILO



Anti-Tamper Screws
T

Metal Base Option
HR3**M**/