

Bourne IP20 Surface Mount EM Escape Route 2.2W

130lm




Features

- Battery and Gear all in one unit
- Maintained or non-maintained Emergency



Spacing Data

Mounting Height (m)	Spacing (m) min 0.5Lux open area	Spacing (m) min 1Lux escape
2	11.4	9.4
2.5	12.8	10.2
3	13.7	10.9
3.5	14.5	11.4
4	15.1	11.4
6	16.2	11.1



All units are in mm

KEY DATA

Power	2.2W
Luminous Flux	130lm
Colour Temperature	6500K
IP Rating	IP20
Dimensions	180 x 110 x 50mm
Warranty	3 Years

Part Number

NET-44-10-66

TECHNICAL SPECIFICATIONS

Input Voltage AC	220-240V
Power Factor	>0.8
No. of LEDs	1
Driver Manufacturer	DPPUL
Total Circuit Power (W)	2.2 +/- 0.2W
Electrical Class	1
Operating Temp.	0°C to +40°C
Lamp Viewing Angle	70°
Lifespan _{LM80}	50,000 Hours
Battery Pack	Ni-Cd C3.6V 3000 mAh
Charge Time	24H
Discharge Time	>3H
Self Test	No
Maintained	No
Housing Material	Polycarbonate
Housing/Frame Colour	White
Weight	0.5Kg
Manufacturer	DPPUL