

Newton Aluminium Bulkhead 16W | Photocell

1550lm



Features

- IP65 rated housing - protected against dust and water
- Shatterproof polycarbonate diffuser
- Maintained or non-maintained Emergency operation
- Rear or side entry
- Side conduit entry




Compatible Accessories

Half Moon Cover

NET-33-06-69

Page 122



All units are in mm

KEY DATA

Power	16W
Luminous Flux	1300lm/1550lm/1400lm
Colour Temperature	3000K/4000K/5500K
IP Rating	IP65
IK Rating	IK10
Dimensions	Ø323 x 101mm
Warranty	3 Years

Part Number PHO

NET-33-06-74

Part Number PHO EM

NET-33-06-75

TECHNICAL SPECIFICATIONS

Input Voltage AC	220-240V
Power Factor	>0.9
Luminaire Efficacy	90lm/W
LED Manufacturer	Honglitronic
LED Type	SMD 2835
No. of LEDs	52
Driver Manufacturer	Tridonic
Driver Output Voltage DC	36-42V
Total Circuit Power (W)	16W +/- 1.5W
Electrical Class	1
Colour Rendering	>80 CRI
Lamp Viewing Angle	115°
Dimmable	No
Operating Temp.	-15°C to +45°C
Lifespan <small>LM80</small>	35,000 Hours
Fire Rating	V0
UGR Rating	More than 19
Diffuser Material	Polycarbonate
Housing Material	Aluminium
Housing Colour	Black
Weight	3.4Kg
Manufacturer	NET LED Lighting

EMERGENCY SPECIFICATIONS

Emergency Operation	>3H
Battery Pack	Li-on 3.7V
Emergency Pack	Streamer
Emergency Kit	1 Year Warranty
Operating Temp.	0°C to +45°C
Luminous Flux Factor	5%

Typically Replaces

- 1 x 28W fluorescent 2D Standard or Emergency Bulkhead