

## FXBX LED EMERGENCY EXIT BOX

### LED Emergency Exit Box

Fox Lux Emergency Exit Boxes are ICEL Endorsed and manufactured to provide full compliance to current standards, including BS 60598-2-22 and ISO 7010.

*5 year warranty including battery\**



The luminaire can be wired for either maintained or non-maintained operations and have IP20 protection, meaning that it can be used for indoor applications.

Self-test versions can be remote controlled to enable functional and duration tests on demand, check the status of the battery, and programme the automated self-test at the time required.

### KEY FEATURES

- ✂ Self-contained emergency LED exit box
- ✂ Viewing distance 34m.
- ✂ Low stand-by power consumption < 0.5W (NM mode)
- ✂ Self-test versions available
- ✂ Li-ion battery with 5 year warranty
- ✂ Maintained or non-maintained configurations as standard
- ✂ Ceiling or recessed mounting
- ✂ Suitable for indoor applications
- ✂ Optional remote control available (REM10)

### Self Test Function

- ✂ 30 second functional test carried out automatically once a week
- ✂ 3hr duration test every 52 weeks.
- ✂ First full duration within the first 4 weeks of the luminaire being connected to power

### Technical data

Input voltage/frequency	220-240V AC 50Hz
Power consumption	M = 3W, NM = 0.5W
LEDs Lifetime (L-70)	50,000h
Viewing distance	34m
Discharge duration	3hr
Charge duration	< 24hrs
Battery type	Li-Ion 3.6V 2.5Ah
IP rating	IP20
IK rating	IK07
Insulation class	I
Operation temp.	0-40°C
Storage temp.	0-50°C
Housing	Steel
Legend panel	Polycarbonate
Finish	Matt white
Dimensions (L x W x D)	392 x 41 x 196mm
Net weight	1.08kg



### Ordering information

Ref.	Description
FXBX/M/3	LED Exit Box 3hr
FXBX-S/M/3	LED Exit Box 3hr – self-test
FXBX-U	UP arrow legend
FXBX-D	DOWN arrow legend
FXBX-R	RIGHT arrow legend
FXBX-L	LEFT arrow legend