





FXB EMERGENCY BULKHEAD

IP65 LED Emergency Luminaire

Fox Lux Emergency Bulkheads are ICEL Endorsed and manufactured to provide full compliance to current standards, including BS 60598-2-22 and ISO 7010.

5 year warranty including battery*



The luminaire can be wired for either maintained or non-maintained operations and has IP65 protection, meaning that it can be used for in indoor or outdoor applications.

All models can be remote controlled (see REM10) to enable functional and duration tests on demand, check the status of the battery, and pre-programme a duration test to be carried out after battery charging.

KEY FEATURES

- VIP65 self-contained emergency luminaire
- VIK10 impact rating
- Low stand-by power consumption < 0.5W (NM mode)</p>
- Self-test versions and remote controls available
- 😽 Lithium battery
- Maintained or non-maintained configurations as standard
- 😻 Ceiling or recessed mounting
- 😻 Suitable for indoor or outdoor applications
- 😽 Adhesive legends included

Self Test Function

- S0 second functional test carried out automatically once a week
- ✤ 3hr duration test every 52 weeks.
- 😻 First full duration within the first 4 weeks of the luminaire being connected to power
- Optional remote control available (REM10)

NET LED Limited | 300 Anderson Road | Buckingway Business Park | Cambridge | CB24 4UQ Tel: 01223 851505 Email: sales@netled.co.uk



| Technical data | |
|------------------------------|-------------------|
| Input voltage/frequency | 220-240V AC 50Hz |
| Power consumption | M = 3W, NM = 0.5W |
| LEDs Lifetime (L-70) | 50,000h |
| Lumen output (M and NM) | FXB01 - 170lm |
| | FXB02 – 320lm |
| Discharge duration | 3hr |
| Charge duration | < 24hrs |
| Battery type | Li-ion 3.6V 2.5Ah |
| IP rating | IP65 |
| IK rating | IK10 |
| Insulation class | |
| Operation temp. | 0-40°C |
| Storage temp. | 0-50°C |
| | |
| Housing | Polycarbonate |
| Diffuser | Polycorbonate |
| Finish | Matt white body |
| | |
| Dimensions (L x W x D) | 341 x 247 x 46 mm |
| Net weight (kg) | 0.5 |
| Box dimensions (L x W x D)mm | 355 x 109 x 60mm |



Ordering information

| Part no. | Description |
|------------|--------------------------------------------|
| FXB01/M/3 | LED EM bulkhead IP65 170lm 3hr |
| FXB01S/M/3 | LED EM bulkhead IP65 3hr 170lm – self-test |
| FXB02/M/3 | LED EM bulkhead IP65 3hr 320lm |
| FXB02S/M/3 | LED EM bulkhead IP65 3hr 320lm – self-test |
| | |

©2019 Fox Lux Ltd. E&OE. Product specification may vary without prior notice. *Terms apply. See website for details.

NET LED Limited | 300 Anderson Road | Buckingway Business Park | Cambridge | CB24 4UQ Tel: 01223 851505 Email: sales@netled.co.uk