



Quarto



Specification Text

The luminaire shall be manufactured from high pressure die-cast aluminium. It shall have an LED efficacy of up to 114.2 luminaire lm/W and will be capable of producing up to 1,542 luminaire lumens at 4000K with a CRI >70. It shall have an asymmetric forward throw optic and is rated at IP65 and IK10.

Specification

Weight: 4.26kg Max.

Windage: 0.05m² Max.

Material: Die-cast Aluminium


Paint Finish: Anthracite Grey

Key Features

- 7.5W & 14.2W
- 857 - 1542 Luminaire Lumens
- Efficacy up to 114.2 lm/W
- 2700K, 3000K & 4000K
- Lifetime >100,000hr L80
- Asymmetrical
- Dali Dimmable options





Dimensions





Optics


STREET



CYCLE



FLOOD



Code	Power	Light Source	Luminaire Lumens	Optic	CCT(K)	IP	IK	Weight (kg)	Paint Finish	
QUAFL08D	7.5W	LED	857	Asymmetrical Flood Light Optic (FL)	4000	IP65	IK10	3.95	Anthracite Grey	
QUAFL08DEM	7.5W	LED	857		4000	IP65	IK10	4.21	Anthracite Grey	
QUAFL08DEMPEEC	7.5W	LED	857		4000	IP65	IK10	4.26	Anthracite Grey	
QUAF08DPEEC	7.5W	LED	857		4000	IP65	IK10	4.00	Anthracite Grey	
QUAFL15D	13.5W	LED	1542		4000	IP65	IK10	3.95	Anthracite Grey	
QUAFL15DEM	13.5W	LED	1542		4000	IP65	IK10	4.21	Anthracite Grey	
QUAFL15DEMPEEC	13.5W	LED	1542		4000	IP65	IK10	4.26	Anthracite Grey	
QUAF15DPEEC	13.5W	LED	1542		4000	IP65	IK10	4.00	Anthracite Grey	
QUAOC08D	7.5W	LED	825		Asymmetrical Street Optic (ST)	4000	IP65	IK10	3.95	Anthracite Grey
QUAOC08DEM	7.5W	LED	825			4000	IP65	IK10	4.21	Anthracite Grey
QUAOC08DEMPEEC	7.5W	LED	825	4000		IP65	IK10	4.26	Anthracite Grey	
QUAOC08DPEEC	7.5W	LED	825	4000		IP65	IK10	4.00	Anthracite Grey	
QUAOC15D	13.5W	LED	1485	4000		IP65	IK10	3.95	Anthracite Grey	
QUAOC15DEM	13.5W	LED	1485	4000		IP65	IK10	4.21	Anthracite Grey	
QUAOC15DEMPEEC	13.5W	LED	1485	4000		IP65	IK10	4.26	Anthracite Grey	
QUAOC15DPEEC	13.5W	LED	1485	4000	IP65	IK10	4.00	Anthracite Grey		
QUAST08D	7.5W	LED	806	Asymmetrical Cycle optic (OC)	4000	IP65	IK10	3.95	Anthracite Grey	
QUAST08DEM	7.5W	LED	806		4000	IP65	IK10	4.21	Anthracite Grey	
QUAST08DEMPEEC	7.5W	LED	806		4000	IP65	IK10	4.26	Anthracite Grey	
QUAST08DPEEC	7.5W	LED	806		4000	IP65	IK10	4.00	Anthracite Grey	
QUAST15D	13.5W	LED	1453		4000	IP65	IK10	3.95	Anthracite Grey	
QUAST15DEM	13.5W	LED	1453		4000	IP65	IK10	4.21	Anthracite Grey	
QUAST15DEMPEEC	13.5W	LED	1453		4000	IP65	IK10	4.26	Anthracite Grey	
QUAST15DPEEC	13.5W	LED	1453		4000	IP65	IK10	4.00	Anthracite Grey	

Accessories / Options

- Control options available
- Colour temperature options
- Remote driver options

Mounting Options

- Optional pattress

