

NET-23-20-09

Histon Street Light 4000K 150W



Features

- Slip-fitter included for use on 60 or 76mm pole
- Maintenance cover allows for fast and easy installation
- Slim and compact profile for minimum wind resistance
- Extremely energy efficient
- Standard 10KV surge protection
- Head adjustable by -15° to +15°
- IP65 and IK08 rated housing

Key Data

Power	150W
--------------	------

Luminous Flux	20000lm
Colour Temperature	4000K
IP Rating	IP65
Dimensions	608 x 300 x 105mm
Warranty	5 Years (Registration Required)
IK Rating	IK08

Technical Specifications

Input Voltage AC	100-270V
Power Factor	>0.90
Luminaire Efficacy	133lm/W
LED Manufacturer	Philips
LED Type	EMC 3030
No. of LEDs	224
Driver Manufacturer	Tomcarline
Total Circuit Power (W)	150W +/- 5W
Electrical Class	1
Colour Rendering	>70 CRI
Lamp Viewing Angle	140° x 70°
Dimmable	No
Operating Temp.	-15°C to +40°C
Lifespan LM80	50,000 Hours
Housing Material	Aluminium
Weight	8.4Kg



Driver Output Voltage DC	42V
Housing Colour	Grey
Diffuser Material	Glass
Photocell Compatible	Yes (NET-23-20-08)
Manufacturer	FYTLED



NET LED Limited Buckingway Business Park
300 Anderson Road Cambridge CB24 4UQ

T 01223 851505
F 01223 851506
sales@netled.co.uk
www.netled.co.uk

Slip fitter included
for use on 60
or 76mm pole

