

# 55000-017APO

AlarmSense Open Area Sounder/Visual Indicator



## Overview

A powerful wall-mounting open-area Sounder/Visual Indicator suitable for use with C-TEC's CFP AlarmSense range of 2-8 Zone Two-Wire Fire Panels.

IP65 rated.

Up to 99dB(A) sound output at 1m.

Ultra-bright red LED.

Device locking facility.

Max. five Open-Area Alarm Devices per AlarmSense zone.

## Technical Specifications

<b>Flash rate &amp; colour</b>	1Hz / red.
<b>Supply wiring</b>	2-wire monitored, polarity insensitive.
<b>Supply/operating voltage</b>	18-33VDC (sounders active); Less than 15VDC (sounders off).
<b>Quiescent current</b>	100µA @ 12VDC. (Max. surge current 200µA).



<b>Nominal SPL (Sound Pressure Level)</b>	Up to 99dB(A) @ 1m. Note the tone frequency incorporated into this device is the Apollo Evacuate tone (840Hz for 0.5s and 546Hz for 0.5s).
<b>Alarm current</b>	19mA @ 24VDC (nominal).
<b>Product dimensions (mm)</b>	97.5mm diameter x 104mm deep.
<b>Construction &amp; finish</b>	TBC.
<b>IP Rating</b>	IP65
<b>Weight</b>	260g.
<b>Operating conditions/temperature</b>	TBC.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom