

Dual 1000m2 Hearing Loop Amplifier for Phased Array Loops

Part No. **DLR9**



Overview

A dual induction loop amplifier designed to simplify the installation of a 'phased array' induction loop system in areas up to 1000m2.

Includes two PDA Pro-Range induction loop amplifiers, an APPS Phase Shifter and two outreach plates providing one XLR mic and one dual phono line input.

Supplied in a 4U enclosure

Ideal for use in high-profile professional AFILS applications where minimal overspill and consistent loop coverage (i.e. no dead spots) is essential.

Adjustable level controls for all inputs.

Metal compensation.

Technical Specifications

Type	Free-standing. Plugtop IEC mains lead supplied.
Coverage	1000m2 approx.
Mains supply	Plugtop IEC mains lead supplied.
Max battery size and type	n/a.
Auxiliary inputs	1 x XLR mic (via APXM plate); 1 x dual phono (via APL plate).
Indicators	See DLR short form setup guide in Documentation section.
Controls	See DLR short form setup guide in Documentation section.
Product dimensions (mm)	W 600 x H 270 x D 400 mm.
Construction & finish	Mild steel, black; blue/black label.
IP Rating	IP20.
Weight	22kg.
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom