

# Accessible Toilet Reset Point c/w Sounder

Part No. **NC809DBBT**



## Overview

A remote reset point c/w sounder specifically designed for use in Accessible Toilet Alarm systems.

Allows calls generated by an NC807C ceiling pull unit to be cancelled at source, i.e. inside the WC.

On-board reassurance LED and sounder provide audible and visual indication of an acknowledged call to reassure users that help is on the way (calls are acknowledged/accepted at an NC943B Single Zone Call Controller or an NC910/20 Range 10 to 20 Zone Call Controller).

Mounts on a standard UK 25mm single gang flush or surface back box.

Also available as part of the NC951 Accessible Toilet Alarm kit.

## Technical Specifications

Quiescent current	0mA (none).
Alarm current	Determined by the type of control equipment and number / type of field devices connected to the system.
Indicators	Red Reassurance LED and Sounder.
Controls	Reset button.
Connections	SIG (Signal); -Ve (Negative); +Ve (Positive).
Product dimensions (mm)	87 W x 87 H x 24 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.
Weight	55g.
Operating conditions/temperature	-5°C to +40°C. Max. relative humidity 95% non-condensing.
Notes	Connect to an NC943B Call Controller or an NC910 or NC920 10-20 Zone Call Controller to utilise the 800 Series Call System's 'Call Accept' functionality.



T 01942 322744    E sales@c-tec.co.uk  
F 01942 829867    W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom