

Addressable Overdoor Light c/w Sounder

Part No. **QT606A**



Overview

An addressable overdoor light & sounder designed to increase call indication levels in large Quantec sites.

Can be programmed to illuminate and sound when certain groups of call points are calling.

Ideal for providing area indication or 'follow me' lights at the ends of corridors, etc

Flash and sound rates change/intensify to reflect the urgency of incoming calls.

Adjustable volume control.

Dual red and green LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Finished in tough, durable ABS plastic.

Technical Specifications

Power requirements	Nominal 24V DC (from Quantec Controller/Network).
Quiescent current	Less than 15mA.
Alarm current	40mA.
Indicators	Dual ultra-bright red and green Alarm LEDs (Flash rate and colour sequence changes/intensifies to reflect the urgency of the incoming call).
Controls	Adjust volume; Disable sounder.
Connections	R (Red); G (Green); Net +; Net -
Onboard Sounder	Yes. (Sound sequence changes and intensifies to reflect the urgency of the incoming call).
Onboard Infrared Receiver	No.
Product dimensions (mm)	86 W x 86 H x 48 D mm. Mounts on a UK 25mm single gang back box.
Construction & finish	Plastic.
IP Rating	IP41.



Weight 58g.
Operating conditions/temperature -5°C to +40°C. Max. relative humidity 95% non-condensing.



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom