

Slave Overdoor Light

Part No. **QT606**



Overview

Provides visual indication of calls made from a Quantec call point outside bedrooms, WCs, etc.

Flash and colour sequence changes/intensifies to reflect the urgency of the incoming call.

Dual red and green LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Finished in tough, durable ABS plastic.

Technical Specifications

| | |
|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| Quiescent current | 0mA (none). |
| Alarm current | 40mA. |
| Indicators | Dual ultra-bright red and green Alarm LEDs (Flash rate and colour sequence changes/intensifies to reflect the urgency of the incoming call). |
| Connections | R (Red); G (Green); Net +; Net -. Wire as a slave to a Quantec Addressable Call Point or Accessible Toilet Reset Point. See instructions for details. |
| Onboard Sounder | No. |
| Onboard Infrared Receiver | No. |
| Product dimensions (mm) | 87 W x 87 H x 68 D mm. Mounts on a UK 25mm single gang back box. |
| Construction & finish | Plastic. |
| IP Rating | IP41 |
| Weight | 48g. |
| Operating conditions/temperature | -5°C to +40°C. Max. relative humidity 95% non-condensing. |



T 01942 322744 E sales@c-tec.co.uk
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom