



## AADRINA5

Adrina Suspended Linear CCT LO 1500mm



## Features

High specification linear luminaire suitable for education, commercial and large retail applications

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

Supplied bi-directional light output as standard (directional only option can be selected if required)

CCT selectable between 3000K and 4000K

Suitable for individual or continuous surface or suspension mounting

Dimmable and OCTO options available

Powered by Tridonic

## General Information

|                                       |                                      |
|---------------------------------------|--------------------------------------|
| <b>Lamp Type</b>                      | LED                                  |
| <b>OCTO Smart Control</b>             | No                                   |
| <b>IP Rating</b>                      | IP20                                 |
| <b>Class Protection</b>               | 1                                    |
| <b>Internal / External</b>            | Internal                             |
| <b>Surface / Recessed / Suspended</b> | Surface,Suspended                    |
| <b>Lifetime (Hrs)</b>                 | L70 B50 50,000h                      |
| <b>Warranty (Years)</b>               | 5                                    |
| <b>CE Mark</b>                        | Yes                                  |
| <b>Length (mm)</b>                    | 1,528 mm                             |
| <b>Width (mm)</b>                     | 304 mm                               |
| <b>Height (mm)</b>                    | 63 mm                                |
| <b>Accessories</b>                    | AADRINA/SK, AADRINA/SMK, AADRINA/600 |

# Technical Information

---

|                         |                |
|-------------------------|----------------|
| <b>Wattage</b>          | 27W            |
| <b>Lumens Delivered</b> | 3600lm (4000K) |
| <b>Lm/W</b>             | 130lm (4000K)  |
| <b>Beam Angle</b>       | 90             |
| <b>CRI</b>              | 80             |
| <b>CCT</b>              | 3000/4000K     |
| <b>Input</b>            | 220/240V       |
| <b>Hertz</b>            | 50/60Hz        |
| <b>Operating Temp</b>   | -20°C to 45°C  |
| <b>SDCM</b>             | 3              |
| <b>UGR</b>              | 19             |

---

Datasheet generated from <https://onetimepim.com> last updated Friday, November 4, 2022 11:00:37 PM



