ACELED/3M/ST

Centurion LED Bulkhead Maintained / Non-Maintained 7W White

Features

High lumen performance LED polycarbonate bulkhead for increased spacings.

Supplied with self-adhesive legend.

Self-test as standard.

Outperforms 8W T5 and exceeds performance of Guardian by 56%.

20mm conduit entry positions and rear terminal box entry.

Hinged screwless gear tray for ease of installation.

Viewing distance 18 metres.

50,000 hours average lifetime.

General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP65
Class Protection	1
Internal / External	Internal/External
Surface / Recessed / Suspended	Surface
Warranty (Years)	3
CE Mark	Yes
Width (mm)	352
Height (mm)	110
Depth (mm)	64
Accessories	ASBP/2

Technical Information

Wattage	7W
Lumens Delivered	151lm (Emergency), 254lm (Standard)
CCT	6500K
Input	230V
Hertz	50/60Hz
Operating Temp	0C° to 40C°

Technical Data - ETIM - Emergency luminaire (EC001957)

Mounting method	Wall surface mounted / ceiling surface mounting
Function	Escape route lighting
Labelling type	Sticker
Monitoring equipment	Automatic self test
With light source	Yes
Material housing	Plastic
Colour housing	White
Nominal voltage	230-230 V
Degree of protection (IP)	IP65
Protection class	I
Max. system power	7 W
Rated luminous flux acc. IEC 62722-2-1	254 lm
Colour temperature	6500-6500 K
Recognition distance	18 m
Width	110 mm
Height/depth	64 mm
Length	352 mm

Datasheet generated from https://onetimepim.com last updated Friday, March 27, 2020 1:43:35 PM


352
64
110