AENLED/LI/3M/ST

EndLED Lithium Exit Sign 2.5W Maintained / Non-Maintained White

Features

Low profile compact and modern polycarbonate LED exit sign

LiFePO4 Lithium battery provides improved energy consumption, product reliability and lifetime

Self-test emergency as standard

Supplied with all legend options - arrow down, arrow up and arrow left/right

20mm top and rear cable entries

Viewing distance 30 metres

General Information

Lamp Type	LED
Colour / Finish	White
Self Test	Yes
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface
Warranty (Years)	5
CE Mark	Yes
Width (mm)	316
Height (mm)	180
Depth (mm)	33
Accessories	ASBP/18

Technical Information

Wattage	2.5W
Lumens Delivered	18lm (Emergency)
CCT	6000K
Input	220-240V
Hertz	50Hz
Operating Temp	5C° to 40C°

Technical Data - ETIM - Emergency luminaire (EC001957)

Mounting method	Wall surface mounted
Function	Escape route signage
Monitoring equipment	Automatic self test
With light source	Yes
Material housing	Plastic
Colour housing	White
Nominal voltage	220-240 V
Degree of protection (IP)	IP20
Protection class	II
Max. system power	2.5 W
Colour temperature	6000-6000 K
Recognition distance	30 m
Width	33 mm
Height/depth	180 mm
Length	316 mm

Datasheet generated from https://onetimepim.com last updated Monday, September 28, 2020 12:01:55 PM


180
316
33