AERMLED3/60/LO/CW

Endurance LED Recessed Panel - 600 x 600 Cool White 23W

Features

Backlit LED panel suitable for education, commercial and ancillary area applications

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

TPa as standard

Surface mounting frame option

Powered by Tridonic

General Information

Lamp Type	LED
Colour / Finish	White
IP Rating	IP20
Class Protection	2
Internal / External	Internal
Surface / Recessed / Suspended	Surface/Recessed/Suspended
Lifetime (Hrs)	L80 50,000
Warranty (Years)	5
CE Mark	Yes
Length (mm)	595
Width (mm)	595
Depth (mm)	10
Accessories	AERMLED/SK, AERMLED/60/SMF, AERMLED/60/CGCB/KIT, APRK/60

Technical Information

Wattage	23W
Lumens Delivered	2520lm
Lm/W	110lm
CRI	Ra 80
CCT	4000K
Input	220-240V
Hertz	50-60Hz
Operating Temp	-20°C to 40°C
SDCM	6
UGR	17



Datasheet generated from https://onetimepim.com last updated Tuesday, July 5, 2022 2:23:27 PM