



## **AERMLED3/60/WW/OCTO**

Endurance LED Recessed Panel - OCTO Smart Control - 600 x 600 Warm White 30W



### **Features**

Backlit LED panel suitable for education, commercial and ancillary area applications

UGR<19 (unified glare rating) compliant luminaire assisting to eliminate glare for visual comfort

Cool white, warm white and daylight options

White anodised aluminium frame for visual compatibility with ceiling grid

Low glare and even light distribution for multiple applications

TPa as standard

Surface mounting frame option

Powered by Tridonic

## General Information

<b>Lamp Type</b>	LED
<b>Colour / Finish</b>	White
<b>OCTO Smart Control</b>	Yes
<b>IP Rating</b>	IP20
<b>Class Protection</b>	2
<b>Internal / External</b>	Internal
<b>Surface / Recessed / Suspended</b>	Surface/Recessed/Suspended
<b>Diffuser Rating</b>	Tp(a)
<b>Lifetime (Hrs)</b>	L80 50,000
<b>Warranty (Years)</b>	5
<b>CE Mark</b>	Yes
<b>Length (mm)</b>	595
<b>Width (mm)</b>	595
<b>Depth (mm)</b>	10
<b>Accessories</b>	AERMLD/SK, AERMLD/60/SMF, AERMLD/60/CGCB/KIT, APRK/60

# Technical Information

<b>Wattage</b>	30W
<b>Lumens Delivered</b>	2900lm
<b>Lm/W</b>	96lm
<b>CRI</b>	Ra 80
<b>CCT</b>	3000K
<b>Input</b>	220-240V
<b>Hertz</b>	50-60Hz
<b>Operating Temp</b>	-20°C to 40°C
<b>SDCM</b>	6
<b>UGR</b>	17

Datasheet generated from <https://onetimepim.com> last updated Wednesday, June 15, 2022 8:56:18 AM



